

Input/Output Functions

Slide Courtesy: Selim Aksoy, Bilkent University

MATLAB Basics: Data Files

- **save** *filename var1 var2 ...*
 - save homework.mat x y → binary
 - save x.dat x -ascii → ascii
- **load** *filename*
 - load filename.mat → binary
 - load x.dat -ascii → ascii

The textread Function

- It is designed to read ASCII files that are formatted into columns of data
- Each column can be of a different type
- It is useful for importing tables of data printed out by other applications

The textread Function

- `[a,b,c,...] = textread(filename,format,n)`
 - filename: a string that is the name of the file to be read
 - format: a string containing the format primitives (just like in `fprintf`)
 - n: number of lines to read (if not specified, the file is read until the end)

The textread Function

- Example: Assume that you have a file called phones.txt

Varol Akman Prof 1538

Selim Aksoy AsstProf 3405

Erol Arkun Prof 2249

Cevdet Aykanat Prof 1625

Mehmet Baray Prof 1208

Cengiz Çelik Instructor 2613

Ilyas Çiçekli AsstProf 1589

David Davenport AsstProf 1248

...

The textread Function

- `[fname,lname,rank,phone] = textread('phones.txt', '%s %s %s %d')`

- `fname =`

'Varol '
'Selim '
'Erol '
'Cevdet '
'Mehmet '
'Cengiz '

...

cell array

- `phone =`

1537
3405
2249
1625
1208
2613

...

double array

The textread Function

- The textread function skips the columns that have an asterisk (*) in the format descriptor
 - [fname, phone] =
textread('phones.txt', '%s %*s %*s %d')
- The load command (with ASCII option) assumes all of the data is of a single type but textread is more flexible

The textread Function

- Example: Searching for telephone numbers

```
name = 'Selim';  
for ii = 1:length(fname),  
    if ( strcmp( fname(ii), name ) ),  
        disp( phone(ii) );  
    end  
end
```

**be careful about the
usage of cell arrays**

File Processing

- File types:
 - Binary files
 - Data is stored in program readable format
 - Processing is fast
 - ASCII (text) files ← what we will use
 - Data is stored in human readable format
 - Processing is slower
 - Can be used to export/import data that can be used in programs other than MATLAB

Opening Files

- `fid = fopen(filename, permission)`
opens the file *filename* in the mode specified by permission
 - `fid` is the file id (a positive integer) that is assigned to the file by MATLAB
 - `fid` is used for all reading, writing and control operations on that file
 - file id 1 is the standard output device and file id 2 is the standard error device
 - `fid` will contain -1 if the file could not be opened

Opening Files

- Permission can be:
 - 'r' : open file for reading (default)
 - 'w' : open file, or create a new file, for writing; discard existing contents, if any
 - 'a' : open file, or create a new file, for writing; append data to the end of the file
 - 'r+' : open file for reading and writing
 - 'w+' : open file, or create a new file, for reading and writing; discard existing contents, if any
 - 'a+' : open file, or create a new file, for reading and writing; append data to the end of the file
- Add 't' to the permission string for an ASCII (text) file

Opening Files

- Examples:

- `fid = fopen('example.dat', 'r')`
opens a binary file for input
- `fid = fopen('example.dat', 'wt')`
opens a text (ASCII) file for output (if `example.dat` already exists, it will be deleted)
- `fid = fopen('example.dat', 'at')`
opens a text file for output (if `example.dat` already exists, new data will be appended to the end)

Closing Files

- `status = fclose(fid)`
closes the file with file id `fid`
 - If the closing operation is successful, `status` will be 0
 - If the closing operation is unsuccessful, `status` will be -1
- `status = fclose('all')`
closes all open files (except for standard output and standard error)

Writing Formatted ASCII Data

- `count = fprintf(fid,format,val1,val2,...)`
writes formatted ASCII data in a user-specified format
 - `fid`: file id (if `fid` is missing, data is written to the standard output device (command window))
 - `format`: same as what we have been using (combination of format specifiers that start with `%`)
 - `count`: number of characters written

Writing Formatted ASCII Data

- Make sure there is a one-to-one correspondence between format specifiers and types of data in variables
- Format strings are scanned from left to right
- Program goes back to the beginning of the format string if there are still values to write (format string is recycled) (not recommended)
- If you want to print the actual % character, you can use %% in the format string

Reading Formatted ASCII Data

- `line = fgetl(fid)`
reads the next line excluding the end-of-line characters from a file as a character string
 - `line`: character array that receives the data
 - `line` is set to -1 if `fgetl` encounters the end of a file

Formatted ASCII I/O Examples

```
% Script file: table.m
% Purpose: To create a table of square roots, squares, and cubes.

% Open the file.
fid = fopen('table.dat', 'wt');

% Print the title of the table.
fprintf(fid, ' Table of Square Roots, Squares, and Cubes\n\n');

% Print column headings
fprintf(fid, ' Number   Square Root      Square      Cube\n');
fprintf(fid, ' =====   =====      =====      ===\n');

% Generate the required data
ii = 1:10;
square_root = sqrt(ii);
square = ii.^2;
cube = ii.^3;

% Print the data
for ii = 1:10
    fprintf (fid, ' %2d   %11.4f   %6d   %8d\n', ...
        ii, square_root(ii), square(ii), cube(ii));
end

% Close the file.
status = fclose(fid);
```

Formatted ASCII I/O Examples

```
%Updates the phone number of a person
```

```
%Get the name and new phone number
```

```
name = input( 'Enter the last name of the person: ', 's' );
```

```
new_phone = input( 'Enter the new phone number: ' );
```

```
%Read the phone numbers
```

```
[fname,lname,rank,phone] = textread( 'phones.txt', '%s %s %s %d' );
```

```
%Find the person and update the phone number
```

```
for i = 1:length(lname),  
    if ( strcmp( lname(i), name ) ),  
        phone(i) = new_phone;
```

```
    end
```

```
end
```

```
%Write the updated phone numbers
```

```
fid = fopen( 'phones2.txt', 'wt' );
```

```
for i = 1:length(fname),  
    fprintf( fid, '%s %s %s %d\n', fname{i}, lname{i}, rank{i},  
        phone(i) );
```

```
end
```

```
fclose( fid );
```

Formatted ASCII I/O Examples

```
%Updates the name of a person

%Get the old and new names
old_name = input( 'Enter the old name: ', 's' );
new_name = input( 'Enter the new name: ', 's' );

%Open the input file
fid1 = fopen( 'phones.txt', 'rt' );
%Open the output file
fid2 = fopen( 'phones3.txt', 'wt' );

%Read lines one by one
line = fgetl( fid1 );
while ( line > 0 ),
    %Replace the old name with the new name
    line2 = strrep( line, old_name, new_name );
    %Write to the new file
    fprintf( fid2, '%s\n', line2 );
    %Read the next line
    line = fgetl( fid1 );
end

%Close the file
status = fclose( 'all' );
```