Fixed-threshold accuracy in development worlds

Qwen3-32B · pooled polarity-balanced axis · extraction indices 0–49; development indices 50–99

All four layers and seven positions retained; axis sign and classification threshold are unchanged from extraction.

Objects · New-information question

Layer index	Record	Prompt end	Token 32	Token 128	Token 512	Think end	Answer boundary
15	0.770 n=50/50	0.680 n=50/50	0.540 n=50/50	0.520 n=49/50	NA no axis n=0/50	0.770 n=50/50	0.640 n=50/50
31	0.615 n=50/50	0.500 n=50/50	0.575 n=50/50	0.561 n=49/50	NA no axis n=0/50	0.710 n=50/50	0.670 n=50/50
47	0.975 n=50/50	0.500 n=50/50	0.575 n=50/50	0.561 n=49/50	NA no axis n=0/50	0.645 n=50/50	0.705 n=50/50
57	0.995 n=50/50	0.500 n=50/50	0.540 n=50/50	0.571 n=49/50	NA no axis n=0/50	0.700 n=50/50	1.000 n=50/50

Objects · Already-known question

Layer index	Record	Prompt end	Token 32	Token 128	Token 512	Think end	Answer boundary
15	0.785 n=50/50	0.595 n=50/50	0.545 n=50/50	0.635 n=50/50	NA no axis n=0/50	0.725 n=50/50	0.675 n=50/50
31	0.605 n=50/50	0.535 n=50/50	0.580 n=50/50	0.635 n=50/50	NA no axis n=0/50	0.725 n=50/50	0.720 n=50/50
47	0.990 n=50/50	0.560 n=50/50	0.565 n=50/50	0.650 n=50/50	NA no axis n=0/50	0.635 n=50/50	0.735 n=50/50
57	1.000 n=50/50	0.560 n=50/50	0.570 n=50/50	0.615 n=50/50	NA no axis n=0/50	0.770 n=50/50	1.000 n=50/50

Machines · New-information question

Layer index	Record	Prompt end	Token 32	Token 128	Token 512	Think end	Answer boundary
15	0.685 n=50/50	0.575 n=50/50	0.675 n=50/50	0.620 n=50/50	NA no axis n=0/50	0.815 n=50/50	0.750 n=50/50
31	0.760 n=50/50	0.510 n=50/50	0.680 n=50/50	0.680 n=50/50	NA no axis n=0/50	0.835 n=50/50	0.835 n=50/50
47	0.980 n=50/50	0.540 n=50/50	0.550 n=50/50	0.695 n=50/50	NA no axis n=0/50	0.730 n=50/50	0.850 n=50/50
57	0.930 n=50/50	0.545 n=50/50	0.660 n=50/50	0.695 n=50/50	NA no axis n=0/50	0.825 n=50/50	1.000 n=50/50

Machines · Already-known question

Layer index	Record	Prompt end	Token 32	Token 128	Token 512	Think end	Answer boundary
15	0.665 n=50/50	0.550 n=50/50	0.600 n=50/50	0.540 n=50/50	NA no axis n=0/50	0.795 n=50/50	0.675 n=50/50
31	0.765 n=50/50	0.500 n=50/50	0.670 n=50/50	0.605 n=50/50	NA no axis n=0/50	0.830 n=50/50	0.850 n=50/50
47	0.985 n=50/50	0.500 n=50/50	0.660 n=50/50	0.620 n=50/50	NA no axis n=0/50	0.700 n=50/50	0.820 n=50/50
57	0.955 n=50/50	0.500 n=50/50	0.670 n=50/50	0.610 n=50/50	NA no axis n=0/50	0.830 n=50/50	1.000 n=50/50



Development only. Original whole-instrument gate: not met (count validity). Semantic-world overlap: objects 19; machines 0.

There are 82 exact-prompt overlaps between extraction and development. This is not a fresh confirmation sample.

Record precedes the question: its context is identical across task kinds, so cross-kind decoding is not independent replication.

n = complete scored four-cell worlds / 50 assigned. No axis = no complete paired extraction worlds. Available world sets can differ by position.

These are descriptive projections. They establish no causal mechanism, motivational state, or subjective experience.