

Software Security

COSC 466/566

Spring 2023

Dr. Doowon Kim




THE UNIVERSITY OF
TENNESSEE

Today's class

Function

What's function?

- Assigns to each element of X exactly one element of Y
- A group of statements that together perform a task.
- Every C program has at least one function, which is `main()`, and all the most trivial programs can define additional functions.



Function

```
int x = 100;
int main()
{
    // data stored on stack
    int a=2;
    float b=2.5;
    static int y;

    // allocate memory on heap
    int *ptr = (int *) malloc(2*sizeof(int));

    // values 5 and 6 stored on heap
    ptr[0]=5;
    ptr[1]=6;

    // deallocate memory on heap
    free(ptr);

    return 1;
}
```


- Function name
 - Main
- Arguments
 - none
- Local variables
 - E.g., a, b
- Return address
 - Invisible
 - this parameter is passed automatically when the function is called
 - the function needs to be able to get back to wherever it was called from
- Return value
 - 1

Function call/return

```
foo(...) {  
    ...  
    bar();  
    ...  
}
```


```
bar(...) {  
    ...  
    ...  
}
```

```
main(...) {  
    ...  
    foo(...);  
    ...  
}
```




Memory Layout

All programs are stored in memory



All programs are stored in memory




Wait!

- How would it be possible for two programs to run at the same time on your Windows or MacOS?
- May conflict your program with other programs
- You have a limited memory like 4GB, your program needs more memory space than 4GB.
- How can we overcome this challenge?


Virtual Memory

- Freeing applications from having to manage a shared memory space. You don't worry about managing memory when programming. ➔ Process isolation, Simplifying application writing, Simplifying compilation, linking, loading
- Able to conceptually use more memory than might be physically available


Virtual Memory




All programs are stored in memory




The instructions are stored in memory




The instructions are stored in memory




Data are stored in memory




Data are stored in memory




Data are stored in memory




Stack (Local variables)




Heap (Dynamic memory)



Heap (Dynamic memory)



Stack & Heap grow in opposite directions



Program Memory Stack


```
int x = 100;
int main()
{
    // data stored on stack
    int a=2;
    float b=2.5;
    static int y;

    // allocate memory on heap
    int *ptr = (int *) malloc(2*sizeof(int));

    // values 5 and 6 stored on heap
    ptr[0]=5;
    ptr[1]=6;


    // deallocate memory on heap
    free(ptr);

    return 1;
}
```



x86-64 Memory Layout


- Text
 - Executable machine instructions for the currently running program
 - Read-only
- Shared libraries
 - Executable machine instructions from libraries
 - Shared by all processes
 - Read-only
- Data
 - Statically allocated data
 - Global variables, static variables, string constants
- Stack
 - Stores stack frames and associated data
 - 8MB by default size limit
- Heap
 - Dynamically allocated objects
 - `malloc()`, `calloc()`, `new`



Stack Management


Stack

- Managed programmatically
 - Compiler outputs all necessary management functionality
- Grows towards lower addresses
- `%rsp` points to the lowest stack address
 - Points to the "top" element



Push Instruction


- **push src**
 - Decrement `%rsp` by 4
 - Write operand `src` to memory address stored in `%esp`



Pop Instruction

- **pop dst**


- Read value at the memory address stored in %rsp
 - Put that value into dst
- Increment %esp by 4



Calling Procedures


Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```




Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```




Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```



Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```




EBP (Base Pointer)

What's the addr. of loc2?

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) Where is loc2?
What's the specific address?




What's the addr. of loc2?

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) Where is loc2?

What's the specific address?

A) We don't know before running
since undecidable at compile time




What's the addr. of loc2?

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) Where is loc2?

What's the specific address?

A) But we can know loc2 is always
8bytes before “???”s → addr of ??? - 8B




EBP (Base Pointer)

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) Where is loc2?

What's the specific address?

A) But we can know loc2 is always
8bytes before “???”s → addr of ??? - 8B



EBP (Base Pointer): Notation

- `%ebp`: A memory address
- `(%ebp)`: The value at memory address `%ebp` (like dereferencing a pointer)

EBP (Base Pointer)


```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) where is loc2?

What's the specific address?

Quiz: 8 (%ebp) or -8 (%ebp)

A) -8 (%ebp)




Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) What are “???”?

First, we need \$ebp




Stack layout when calling function

```
void func(char *arg1, int arg2, int arg3)
{
    char loc1[4]
    int  loc2;
    int  loc3;
    ...
}
```

Q) What are “???” ?


First, we need \$ebp

Second, we need a return address



Function Call Stack

```
void f(int a, int b)
{
    int x;
}
void main()
{
    f(1,2);
    printf("hello world");
}
```




Order of the function arguments in stack

```
void func(int a, int b)
{
    int x, y;

    x = a + b;
    y = a - b;
}
```

```
movl    12(%ebp), %eax    ; b is stored in %ebp + 12
movl    8(%ebp), %edx     ; a is stored in %ebp + 8
addl    %edx, %eax
movl    %eax, -8(%ebp)    ; x is stored in %ebp - 8
```

Stack Layout for Function Call Chain



Heap

```
int x = 100; // In Data segment
int main() {
    int a = 2; // In Stack
    float b = 2.5; // In Stack
    static int y; // In BSS

    // Allocate memory on Heap
    int *ptr = (int *) malloc(2*sizeof(int));
    // values 5 and 6 stored on heap
    ptr[0] = 5; // In Heap
    ptr[1] = 6; // In Heap
    free(ptr);
    return 1;
}
```


Returning from functions

In C

```
return;
```

In compiled assembly

```
leave: → mov  %ebp %esp  
       pop  %ebp  
ret:    pop  %eip
```



Returning from functions

In C

```
return;
```

In compiled assembly

```
leave: → mov  %ebp %esp  
       pop  %ebp  
ret:   pop  %eip
```

\$esp




\$ebp



0xffffffff

0x00000000





Returning from functions

In C

```
return;
```

In compiled assembly

```
leave:  mov  %ebp %esp  
         pop  %ebp  
ret:    pop  %eip
```





Returning from functions

In C

```
return;
```

In compiled assembly

```
leave:  mov  %ebp %esp  
         pop  %ebp  
ret:    pop  %eip
```




Returning from functions


In C

```
return;
```

In compiled assembly

```
leave:  mov  %ebp %esp  
        pop  %ebp  
ret:     pop  %eip
```

1. The next instruction is to “remove” the arguments off the stack
2. And now we’re back where we started



Stack & functions: Summary

Calling function (before calling):

1. **Push arguments** onto the stack (in reverse)
2. **Push the return address**, i.e., the address of the instruction you want run after control returns to you: e.g., `%eip + 2`
3. **Jump to the function's address**

Stack & functions: Summary

Calling function (before calling):

1. **Push arguments** onto the stack (in reverse)
2. **Push the return address**, i.e., the address of the instruction you want run after control returns to you: e.g., `%eip + 2`
3. **Jump to the function's address**

Called function (when called):

1. **Push the old frame pointer** onto the stack: `push %ebp`
2. **Set frame pointer** `%ebp` to where the end of the stack is right now: `%ebp=%esp`
3. **Push local variables** onto the stack; access them as offsets from `%ebp`

Stack & functions: Summary

Calling function (before calling):

1. **Push arguments** onto the stack (in reverse)
2. **Push the return address**, i.e., the address of the instruction you want run after control returns to you: e.g., `%eip + 2`
3. **Jump to the function's address**

Called function (when called):

1. **Push the old frame pointer** onto the stack: `push %ebp`
2. **Set frame pointer** `%ebp` to where the end of the stack is right now: `%ebp=%esp`
3. **Push local variables** onto the stack; access them as offsets from `%ebp`

Called function (when returning)

1. **Reset the previous stack frame:** `%esp = %ebp; pop %ebp`
2. **Jump back to return address:** `pop %eip`