

Namespace CodiceFiscale

Classes

[CodiceFiscaleExtensions](#)

Provides extension methods for working with Italian Codice Fiscale strings and data objects.

[CodiceFiscaleGenerator](#)

Provides methods to generate an Italian Codice Fiscale.

[CodiceFiscaleMatcher](#)

Provides methods to match and compare Italian Codice Fiscale strings against personal data.

[CodiceFiscaleNormalizer](#)

Provides normalization utilities for Italian Codice Fiscale strings.

[CodiceFiscaleParser](#)

Provides methods to parse an Italian Codice Fiscale into its constituent data.

[CodiceFiscaleValidator](#)

Provides methods to validate Italian Codice Fiscale codes.

[IBANValidator](#)

Provides methods to validate IBAN (International Bank Account Number) strings. Only SEPA countries are supported (EU27 + UK, Switzerland, Norway, Iceland, Liechtenstein, Monaco, San Marino, Andorra, Vatican City).

[ItalianVatCodeValidator](#)

Provides validation for Italian VAT codes (Partita IVA) and fiscal codes used in a VAT context.

Class CodiceFiscaleExtensions

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides extension methods for working with Italian Codice Fiscale strings and data objects.

```
public static class CodiceFiscaleExtensions
```

Inheritance

[object](#)  ← CodiceFiscaleExtensions

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

GetAge(CodiceFiscaleData)

Gets the current age (in full years) of the person represented by this [CodiceFiscaleData](#).

```
public static int GetAge(this CodiceFiscaleData data)
```

Parameters

data [CodiceFiscaleData](#)

The parsed Codice Fiscale data.

Returns

[int](#) 

The age in full years as of today.

IsAdult(CodiceFiscaleData)

Determines whether the person represented by this [CodiceFiscaleData](#) is 18 or older.

```
public static bool IsAdult(this CodiceFiscaleData data)
```

Parameters

data [CodiceFiscaleData](#)

The parsed Codice Fiscale data.

Returns

[bool](#)

true if the person is at least 18 years old; otherwise, **false**.

IsValidCodiceFiscale(string)

Determines whether this string is a valid Italian Codice Fiscale.

```
public static bool IsValidCodiceFiscale(this string cf)
```

Parameters

cf [string](#)

The string to validate.

Returns

[bool](#)

true if valid; otherwise, **false**.

NormalizeOmocodia(string)

Normalizes any omocodia letter substitutions in this Codice Fiscale back to digits.

```
public static string NormalizeOmocodia(this string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale string (may contain omocodia substitutions).

Returns

[string](#) 

The normalized Codice Fiscale with digits restored at numeric positions.

ParseCodiceFiscale(string)

Parses this string as an Italian Codice Fiscale.

```
public static CodiceFiscaleData ParseCodiceFiscale(this string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale string to parse.

Returns

[CodiceFiscaleData](#)

The decoded [CodiceFiscaleData](#).

Exceptions

[InvalidCodiceFiscaleException](#)

Thrown when the string is not valid.

TryParseCodiceFiscale(string, out CodiceFiscaleData?)

Attempts to parse this string as an Italian Codice Fiscale without throwing.

```
public static bool TryParseCodiceFiscale(this string cf, out CodiceFiscaleData? data)
```

Parameters

cf [string](#) 

The Codice Fiscale string to parse.

data [CodiceFiscaleData](#)

The parsed data, or **null** if invalid.

Returns

[bool](#) 

true if parsing succeeded; otherwise, **false**.

Class CodiceFiscaleGenerator

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides methods to generate an Italian Codice Fiscale.

```
public class CodiceFiscaleGenerator
```

Inheritance

[object](#) ← CodiceFiscaleGenerator

Inherited Members

[object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#), [object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Methods

Generate(string, string, DateOnly, Gender, string)

Generates a Codice Fiscale based on the provided personal information.

```
public static string Generate(string name, string surname, DateOnly dateOfBirth, Gender gender, string belfioreCode)
```

Parameters

name [string](#)

The person's first name.

surname [string](#)

The person's surname.

dateOfBirth [DateOnly](#)

The person's date of birth.

gender [Gender](#)

The person's gender.

belfioreCode [string](#) 

The Belfiore (cadastral) code of the person's place of birth.

Returns

[string](#) 

The generated 16-character Codice Fiscale string.

Exceptions

[InvalidCodiceFiscaleDataException](#)

Thrown when **name**, **surname**, or **belfioreCode** is not valid.

Class CodiceFiscaleMatcher

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides methods to match and compare Italian Codice Fiscale strings against personal data.

```
public class CodiceFiscaleMatcher
```

Inheritance

[object](#)  ← CodiceFiscaleMatcher

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

Matches(string, string, string, DateOnly, Gender, string)

Determines whether the specified Codice Fiscale matches the provided personal data. The comparison is case-insensitive. Omocodia variants of the CF are normalized before comparison.

```
public static bool Matches(string cf, string name, string surname, DateOnly dateOfBirth,  
    Gender gender, string belfioreCode)
```

Parameters

cf [string](#) 

The Codice Fiscale to check.

name [string](#) 

The person's first name (minimum 3 characters).

surname [string](#) 

The person's surname (minimum 3 characters).

`dateOfBirth` [DateOnly](#)

The person's date of birth.

`gender` [Gender](#)

The person's gender.

`belfioreCode` [string](#)

The 4-character Belfiore code of the person's place of birth.

Returns

[bool](#)

`true` if the Codice Fiscale is valid and matches the generated CF for the provided personal data; otherwise, `false`.

Class CodiceFiscaleNormalizer

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides normalization utilities for Italian Codice Fiscale strings.

```
public static class CodiceFiscaleNormalizer
```

Inheritance

[object](#)  ← CodiceFiscaleNormalizer

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

IsOmocodia(string)

Determines whether a Codice Fiscale contains omocodia letter substitutions at any numeric position.

```
public static bool IsOmocodia(string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale to inspect.

Returns

[bool](#) 

true if any omocodia substitution is present; otherwise, **false**.

NormalizeOmocodia(string)

Normalizes a Codice Fiscale by converting any omocodia letter substitutions at numeric positions (6, 7, 9, 10, 12, 13, 14) back to their original digit values. Position 15 (check character) is never modified.

```
public static string NormalizeOmocodia(string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale string (may or may not contain omocodia substitutions).

Returns

[string](#) 

The normalized Codice Fiscale with digits restored. Returns the input unchanged if it is null, empty, or not exactly 16 characters.

Class CodiceFiscaleParser

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides methods to parse an Italian Codice Fiscale into its constituent data.

```
public class CodiceFiscaleParser
```

Inheritance

[object](#)  ← CodiceFiscaleParser

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

Parse(string)

Parses the specified Codice Fiscale and returns the decoded personal data.

```
public static CodiceFiscaleData Parse(string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale string to parse. Case-insensitive.

Returns

[CodiceFiscaleData](#)

A [CodiceFiscaleData](#) instance containing the gender, date of birth, and Belfiore code extracted from the Codice Fiscale.

Exceptions

[InvalidCodiceFiscaleException](#)

Thrown when `cf` is not a valid Codice Fiscale.

TryParse(string, out CodiceFiscaleData?)

Attempts to parse the specified Codice Fiscale without throwing an exception.

```
public static bool TryParse(string cf, out CodiceFiscaleData? data)
```

Parameters

`cf` [string](#)

The Codice Fiscale string to parse. Case-insensitive.

`data` [CodiceFiscaleData](#)

When this method returns [true](#), contains a [CodiceFiscaleData](#) instance with the gender, date of birth, and Belfiore code extracted from the Codice Fiscale; otherwise, [null](#).

Returns

[bool](#)

[true](#) if `cf` was parsed successfully; otherwise, [false](#).

Examples

```
if (CodiceFiscaleParser.TryParse("RSSMRA85T10A562S", out CodiceFiscaleData? data))
{
    Console.WriteLine($"Gender: {data.Gender}, Born: {data.DateOfBirth}");
}
```

Class CodiceFiscaleValidator

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides methods to validate Italian Codice Fiscale codes.

```
public class CodiceFiscaleValidator
```

Inheritance

[object](#)  ← CodiceFiscaleValidator

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

IsValid(string)

Determines whether the specified Codice Fiscale is valid.

```
public static bool IsValid(string cf)
```

Parameters

cf [string](#) 

The Codice Fiscale string to validate.

Returns

[bool](#) 

true if the Codice Fiscale is valid; otherwise, **false**.

Class IBANValidator

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides methods to validate IBAN (International Bank Account Number) strings. Only SEPA countries are supported (EU27 + UK, Switzerland, Norway, Iceland, Liechtenstein, Monaco, San Marino, Andorra, Vatican City).

```
public class IBANValidator
```

Inheritance

[object](#)  ← IBANValidator

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

IsValid(string)

Determines whether the specified IBAN string is valid. Spaces are ignored. Only SEPA country codes are accepted.

```
public static bool IsValid(string iban)
```

Parameters

iban [string](#) 

The IBAN string to validate. Spaces are allowed and will be stripped.

Returns

[bool](#) 

true if the IBAN is valid and belongs to a SEPA country; otherwise, **false**.

Class ItalianVatCodeValidator

Namespace: [CodiceFiscale](#)

Assembly: CodiceFiscale.dll

Provides validation for Italian VAT codes (Partita IVA) and fiscal codes used in a VAT context.

```
public class ItalianVatCodeValidator
```

Inheritance

[object](#)  ← ItalianVatCodeValidator

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) , [object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Methods

IsValid(string, bool, bool)

Validates the specified Italian VAT or fiscal code string.

```
public static bool IsValid(string vat, bool isConsumer, bool isFiscal)
```

Parameters

vat [string](#) 

The code to validate. Can be an 11-digit Partita IVA or, if **isFiscal** is **true**, a 16-character Codice Fiscale.

isConsumer [bool](#) 

true if the code belongs to a natural person (consumer); the first digit must be 8 or 9. **false** for standard company VAT codes (first digit 0–7).

isFiscal [bool](#) 

`true` to also accept a 16-character Codice Fiscale as valid input in addition to an 11-digit VAT code.
`false` to accept only the 11-digit Partita IVA format.

Returns

`bool`[↗](#)

`true` if the code is valid according to the specified rules; otherwise, `false`.

Namespace CodiceFiscale.Entities

Classes

[CodiceFiscaleData](#)

Represents the personal data extracted from or used to generate an Italian Codice Fiscale.

[Coordinates](#)

Represents a geographical coordinate with latitude and longitude.

[ForeignCountry](#)

Represents a foreign country as encoded in the Italian Codice Fiscale dataset.

[Municipality](#)

Represents an Italian municipality with related administrative and contact information.

[Province](#)

Represents an Italian province with its name, acronym, code, and region.

[ValidationResult](#)

Represents the result of a Codice Fiscale validation, including whether it is valid and a list of human-readable error messages for each failed check.

Class CodiceFiscaleData

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents the personal data extracted from or used to generate an Italian Codice Fiscale.

```
public record CodiceFiscaleData : IEquatable<CodiceFiscaleData>
```

Inheritance

[object](#)  ← CodiceFiscaleData

Implements

[IEquatable](#)  <[CodiceFiscaleData](#)>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  ,
[object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Extension Methods

[CodiceFiscaleExtensions.GetAge\(CodiceFiscaleData\)](#) , [CodiceFiscaleExtensions.IsAdult\(CodiceFiscaleData\)](#)

Constructors

CodiceFiscaleData(Gender, DateOnly, string)

Represents the personal data extracted from or used to generate an Italian Codice Fiscale.

```
public CodiceFiscaleData(Gender Gender, DateOnly DateOfBirth, string BelfioreCode)
```

Parameters

Gender [Gender](#)

The gender of the individual.

DateOfBirth [DateOnly](#) 

The date of birth of the individual.

BelfioreCode [string](#)

The 4-character Belfiore (cadastral) code representing the place of birth.

Properties

BelfioreCode

The 4-character Belfiore (cadastral) code representing the place of birth.

```
public string BelfioreCode { get; init; }
```

Property Value

[string](#)

DateOfBirth

The date of birth of the individual.

```
public DateOnly DateOfBirth { get; init; }
```

Property Value

[DateOnly](#)

Gender

The gender of the individual.

```
public Gender Gender { get; init; }
```

Property Value

[Gender](#)

Class Coordinates

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents a geographical coordinate with latitude and longitude.

```
public record Coordinates : IEquatable<Coordinates>
```

Inheritance

[object](#)  ← Coordinates

Implements

[IEquatable](#)  <[Coordinates](#)>

Inherited Members

[object.Equals\(object\)](#)  , [object.Equals\(object, object\)](#)  , [object.GetHashCode\(\)](#)  , [object.GetType\(\)](#)  ,
[object.MemberwiseClone\(\)](#)  , [object.ReferenceEquals\(object, object\)](#)  , [object.ToString\(\)](#) 

Constructors

Coordinates(double, double)

Represents a geographical coordinate with latitude and longitude.

```
public Coordinates(double Lat, double Lng)
```

Parameters

Lat [double](#) 

Gets the latitude component of the coordinate.

Lng [double](#) 

Gets the longitude component of the coordinate.

Properties

Lat

Gets the latitude component of the coordinate.

```
[JsonProperty("lat")]  
public double Lat { get; init; }
```

Property Value

[double](#)

Lng

Gets the longitude component of the coordinate.

```
[JsonProperty("lng")]  
public double Lng { get; init; }
```

Property Value

[double](#)

Class ForeignCountry

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents a foreign country as encoded in the Italian Codice Fiscale dataset.

```
public record ForeignCountry : IEquatable<ForeignCountry>
```

Inheritance

[object](#)  ← ForeignCountry

Implements

[IEquatable](#)  <[ForeignCountry](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Constructors

ForeignCountry(string, string, string, bool)

Represents a foreign country as encoded in the Italian Codice Fiscale dataset.

```
public ForeignCountry(string CatastalCode, string Name, string Continent, bool Deleted)
```

Parameters

CatastalCode [string](#) 

The Belfiore catastal code assigned to the country (e.g. **Z614** for Venezuela). All foreign country codes start with the letter **Z**.

Name [string](#) 

The Italian name of the country (e.g. **Venezuela**).

Continent [string](#) 

The continent to which the country belongs (e.g. **America**).

Deleted [bool](#)

true if the country code has been abolished (e.g. former states such as Czechoslovakia); **false** for currently active countries.

Properties

CatastalCode

The Belfiore catastal code assigned to the country (e.g. **Z614** for Venezuela). All foreign country codes start with the letter **Z**.

```
[JsonProperty("codiceCatastale")]  
public string CatastalCode { get; init; }
```

Property Value

[string](#)

Continent

The continent to which the country belongs (e.g. **America**).

```
[JsonProperty("continente")]  
public string Continent { get; init; }
```

Property Value

[string](#)

Deleted

true if the country code has been abolished (e.g. former states such as Czechoslovakia); **false** for currently active countries.


```
[JsonProperty("soppresso")]  
public bool Deleted { get; init; }
```

Property Value

[bool](#)

Name

The Italian name of the country (e.g. *Venezuela*).

```
[JsonProperty("nome")]  
public string Name { get; init; }
```

Property Value

[string](#)

Class Municipality

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents an Italian municipality with related administrative and contact information.

```
public record Municipality : IEquatable<Municipality>
```

Inheritance

[object](#)  ← Municipality

Implements

[IEquatable](#)  <[Municipality](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Properties

CatastalCode

Gets the catastal code of the municipality.

```
[JsonProperty("codiceCatastale")]  
public required string CatastalCode { get; init; }
```

Property Value

[string](#) 

Code

Gets the unique code of the municipality.

```
[JsonProperty("codice")]  
public string? Code { get; init; }
```

Property Value

[string](#) 

Coordinates

Gets the geographical coordinates of the municipality.

```
[JsonProperty("coordinate")]  
public Coordinates? Coordinates { get; init; }
```

Property Value

[Coordinates](#)

Email

Gets the email address of the municipality.

```
[JsonProperty("email")]  
public string? Email { get; init; }
```

Property Value

[string](#) 

FAX

Gets the fax number of the municipality.

```
[JsonProperty("fax")]  
public string? FAX { get; init; }
```

Property Value

[string](#)

ForeignName

Gets the foreign name of the municipality, if available.

```
[JsonProperty("nomeStraniero")]  
public string? ForeignName { get; init; }
```

Property Value

[string](#)

Name

Gets the name of the municipality.

```
[JsonProperty("nome")]  
public string? Name { get; init; }
```

Property Value

[string](#)

PEC

Gets the certified email (PEC) address of the municipality.

```
[JsonProperty("pec")]  
public string? PEC { get; init; }
```

Property Value

[string](#)

Prefix

Gets the telephone prefix of the municipality.

```
[JsonProperty("prefisso")]  
public string? Prefix { get; init; }
```

Property Value

[string](#)[↗]

Province

Gets the province to which the municipality belongs.

```
[JsonProperty("provincia")]  
public Province? Province { get; init; }
```

Property Value

[Province](#)

Telephone

Gets the telephone number of the municipality.

```
[JsonProperty("telefono")]  
public string? Telephone { get; init; }
```

Property Value

[string](#)[↗]

ZipCode

Gets the ZIP code of the municipality.

```
[JsonProperty("cap")]  
public string? ZipCode { get; init; }
```

Property Value

[string](#) 

Class Province

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents an Italian province with its name, acronym, code, and region.

```
public record Province : IEquatable<Province>
```

Inheritance

[object](#)  ← Province

Implements

[IEquatable](#)  <[Province](#)>

Inherited Members

[object.Equals\(object\)](#) , [object.Equals\(object, object\)](#) , [object.GetHashCode\(\)](#) , [object.GetType\(\)](#) ,
[object.MemberwiseClone\(\)](#) , [object.ReferenceEquals\(object, object\)](#) , [object.ToString\(\)](#) 

Constructors

Province(string, string, string, string)

Represents an Italian province with its name, acronym, code, and region.

```
public Province(string Name, string Acronym, string Code, string Region)
```

Parameters

Name [string](#) 

The name of the province.

Acronym [string](#) 

The acronym (sigla) of the province.

Code [string](#) 

The code of the province.

Region [string](#)

The region to which the province belongs.

Properties

Acronym

The acronym (sigla) of the province.

```
[JsonProperty("sigla")]  
public string Acronym { get; init; }
```

Property Value

[string](#)

Code

The code of the province.

```
[JsonProperty("codice")]  
public string Code { get; init; }
```

Property Value

[string](#)

Name

The name of the province.

```
[JsonProperty("nome")]  
public string Name { get; init; }
```

Property Value

[string](#) 

Region

The region to which the province belongs.

```
[JsonProperty("regione")]  
public string Region { get; init; }
```

Property Value

[string](#) 

Class ValidationResult

Namespace: [CodiceFiscale.Entities](#)

Assembly: CodiceFiscale.dll

Represents the result of a Codice Fiscale validation, including whether it is valid and a list of human-readable error messages for each failed check.

```
public record ValidationResult : IEquatable<ValidationResult>
```

Inheritance

[object](#) ← ValidationResult

Implements

[IEquatable](#) <[ValidationResult](#)>

Inherited Members

[object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.GetType\(\)](#), [object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#), [object.ToString\(\)](#)

Constructors

ValidationResult(bool, IReadOnlyList<string>)

Represents the result of a Codice Fiscale validation, including whether it is valid and a list of human-readable error messages for each failed check.

```
public ValidationResult(bool IsValid, IReadOnlyList<string> Errors)
```

Parameters

IsValid [bool](#)

true if all validation checks passed; otherwise, **false**.

Errors [IReadOnlyList](#) <[string](#)>

A read-only list of error messages describing each failed validation step. Empty when [IsValid](#) is **true**.

Fields

Valid

Gets a [ValidationResult](#) representing a fully valid Codice Fiscale.

```
public static readonly ValidationResult Valid
```

Field Value

[ValidationResult](#)

Properties

Errors

A read-only list of error messages describing each failed validation step. Empty when [IsValid](#) is **true**.

```
public IReadOnlyList<string> Errors { get; init; }
```

Property Value

[IReadOnlyList](#) <[string](#)>

IsValid

true if all validation checks passed; otherwise, **false**.

```
public bool IsValid { get; init; }
```

Property Value

[bool](#)

Namespace CodiceFiscale.Enums

Enums

[Gender](#)

Specifies the biological gender of an individual, as encoded in the Italian Codice Fiscale.

Enum Gender

Namespace: [CodiceFiscale.Enums](#)

Assembly: CodiceFiscale.dll

Specifies the biological gender of an individual, as encoded in the Italian Codice Fiscale.

```
public enum Gender : byte
```

Fields

Female = 2

Represents a female individual. The day-of-birth field in the Codice Fiscale ranges from 41 to 71 (actual day + 40).

Male = 1

Represents a male individual. The day-of-birth field in the Codice Fiscale ranges from 1 to 31.

Namespace CodiceFiscale.Exceptions

Classes

[InvalidCodiceFiscaleDataException](#)

The exception that is thrown when some of the data that compones the Italian Codice Fiscale string are not valid.

[InvalidCodiceFiscaleException](#)

The exception that is thrown when an Italian Codice Fiscale string fails validation.

Class InvalidCodiceFiscaleDataException

Namespace: [CodiceFiscale.Exceptions](#)

Assembly: CodiceFiscale.dll

The exception that is thrown when some of the data that compones the Italian Codice Fiscale string are not valid.

[Serializable]

```
public class InvalidCodiceFiscaleDataException : Exception, ISerializable
```

Inheritance

[object](#) ← [Exception](#) ← InvalidCodiceFiscaleDataException

Implements

[ISerializable](#)

Inherited Members

[Exception.GetBaseException\(\)](#), [Exception.GetType\(\)](#), [Exception.ToString\(\)](#), [Exception.Data](#), [Exception.HelpLink](#), [Exception.HResult](#), [Exception.InnerException](#), [Exception.Message](#), [Exception.Source](#), [Exception.StackTrace](#), [Exception.TargetSite](#), [Exception.SerializeObjectState](#), [object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#)

Constructors

InvalidCodiceFiscaleDataException()

Initializes a new instance of [InvalidCodiceFiscaleDataException](#) with no message.

```
public InvalidCodiceFiscaleDataException()
```

InvalidCodiceFiscaleDataException(string)

Initializes a new instance of [InvalidCodiceFiscaleDataException](#) with a descriptive message.

```
public InvalidCodiceFiscaleDataException(string message)
```

Parameters

message [string](#)

A human-readable message that describes the validation failure.

InvalidCodiceFiscaleDataException(string, Exception)

Initializes a new instance of [InvalidCodiceFiscaleDataException](#) with a descriptive message and a reference to the inner exception that caused this exception.

```
public InvalidCodiceFiscaleDataException(string message, Exception innerException)
```

Parameters

message [string](#)

A human-readable message that describes the validation failure.

innerException [Exception](#)

The exception that is the cause of the current exception.

Class InvalidCodiceFiscaleException

Namespace: [CodiceFiscale.Exceptions](#)

Assembly: CodiceFiscale.dll

The exception that is thrown when an Italian Codice Fiscale string fails validation.

[Serializable]

```
public class InvalidCodiceFiscaleException : Exception, ISerializable
```

Inheritance

[object](#) ← [Exception](#) ← InvalidCodiceFiscaleException

Implements

[ISerializable](#)

Inherited Members

[Exception.GetBaseException\(\)](#), [Exception.GetType\(\)](#), [Exception.ToString\(\)](#), [Exception.Data](#), [Exception.HelpLink](#), [Exception.HResult](#), [Exception.InnerException](#), [Exception.Message](#), [Exception.Source](#), [Exception.StackTrace](#), [Exception.TargetSite](#), [Exception.SerializeObjectState](#), [object.Equals\(object\)](#), [object.Equals\(object, object\)](#), [object.GetHashCode\(\)](#), [object.MemberwiseClone\(\)](#), [object.ReferenceEquals\(object, object\)](#)

Constructors

InvalidCodiceFiscaleException()

Initializes a new instance of [InvalidCodiceFiscaleException](#) with no message.

```
public InvalidCodiceFiscaleException()
```

InvalidCodiceFiscaleException(string)

Initializes a new instance of [InvalidCodiceFiscaleException](#) with a descriptive message.

```
public InvalidCodiceFiscaleException(string message)
```

Parameters

message [string](#)

A human-readable message that describes the validation failure.

InvalidCodiceFiscaleException(string, Exception)

Initializes a new instance of [InvalidCodiceFiscaleException](#) with a descriptive message and a reference to the inner exception that caused this exception.

```
public InvalidCodiceFiscaleException(string message, Exception innerException)
```

Parameters

message [string](#)

A human-readable message that describes the validation failure.

innerException [Exception](#)

The exception that is the cause of the current exception.