

Hydra Field Mixer

Daisy Field performance mixer for Hydra Explorer + Edge

A4 landscape quick reference

Common mix to OUT L, OUT R, and headphones

Connections + Knobs

- Hydra Explorer -> Field IN L. Edge -> Field IN R.
- OUT L, OUT R, and headphones carry the same protected common mix.
- Start with K8 low, raise K1/K2, then set K8 master.

Main bank - no switch held

K1	Hydra level
K2	Edge level
K3	Hydra tone: warm - neutral - bright
K4	Edge tone: warm - neutral - bright
K5	Hydra delay send
K6	Edge delay send
K7	Delay return
K8	Master level

Alt bank - hold SW1

K1	Hydra input trim
K2	Edge input trim
K3	Hydra high-pass
K4	Edge high-pass
K5	Delay time, approx. 60-850 ms
K6	Delay feedback, clamped safe
K7	Delay tone
K8	Ducking amount

Utility layer - hold SW2

K1	Hydra mute fade time
K2	Edge mute fade time
K3	Delay throw amount
K4	Delay freeze feedback
K5	Limiter threshold
K6	Output saturation amount
K7	Input gate threshold
K8	Output safety ceiling

Keys + Performance

A row

A1	Hydra mute
A2	Edge mute
A3	Delay mute
A4	Master mute
A5	Hydra solo
A6	Edge solo
A7	Bypass modifiers, keep mixer live
A8	Panic: clear mutes, solos, freeze, throw

B row

B1	Delay freeze
B2	Delay throw
B3	Edge ducking on/off
B4	Soft saturation on/off
B5	Scene 1: clean mix
B6	Scene 2: Hydra lead
B7	Scene 3: Edge lead
B8	Scene 4: delay performance

Scenes

B5	Balanced, dry-safe startup sound
B6	Hydra louder, Edge support, modest delay
B7	Edge louder, Hydra support, Edge delay
B8	Higher sends, return, and feedback

OLED + LEDs

- Overview shows active bank, source status, and meters.
- Edit zoom appears after parameter changes.
- Knob LEDs show stored values; dim means not captured yet.
- Mute keys stay on; solo and panic keys blink.

Startup + Troubleshooting

Startup defaults

Hydra	Level 75%, send 10%, tone neutral
Edge	Level 70%, send 15%, tone slightly warm
Delay	Return 20%, feedback 25%
Cleanup	Hydra HPF 133 Hz, Edge HPF 158 Hz
Safety	Input gate 45%, limiter on, master 80%
Mods	Ducking off, saturation off

No-input tone / hum

- Unplugged Field line inputs can float and sound like hum.
- Raise SW2+K7 for stronger input gate.
- Raise SW1+K3/K4 for more Hydra/Edge high-pass.
- Turn K1/K2 down when sources are disconnected.

Signal flow

Hydra IN L

Trim/HPF/Tone/Gate

Mix + Delay

Limiter

OUT L/R + HP

Edge IN R uses the same cleanup path, then ducks under Hydra when B3 is on.

Live-use order

- 1. Set K8 low; connect Hydra and Edge.
- 2. Bring up K1/K2, then K8 master.
- 3. Shape with K3/K4; send with K5/K6.
- 4. Use B1/B2 for delay gestures, A8 for panic.