

Software Requirements Specifications

for QueueLab (fictional sample)

SYNTHETIC NON-STUDENT BENCHMARK. Fictional QueueLab requirements; not actual student work or operational evidence.

Change History

Version 0.1 - Generated fictional evaluation fixture.

Table of Contents

- 1. Introduction
 - 1.1. Purpose
 - 1.2. Scope
 - 1.3. Definitions, Acronyms and Abbreviations
 - 1.4. References
- 2. Overall Description
 - 2.1. Product perspective
 - 2.2. User characteristics
 - 2.4. Constraints
 - 2.5. Assumptions and dependencies
- 3. Specific Requirements
 - 3.1. External interface requirements
 - 3.1.1. Hardware interfaces
 - 3.1.2. Software interfaces
 - 3.1.3. Communications interfaces
 - 3.2. Functional requirements
- Module 1: Reservation queue
 - 1.1. Request a queue slot
- Use Case Description
- Activity Diagram
- Wireframe
- 3.4 Non-functional requirements
 - Performance
 - Security
 - Reliability

1. Introduction

This specification describes the fictional QueueLab demonstration application and its controlled acceptance boundaries.

1.1. Purpose

Document the QueueLab appointment queue functions, user roles, interfaces, and testable acceptance criteria for a fictional example.

1.2. Scope

QueueLab lets an example guest request a queue slot and lets an example clerk close it. No real organization or user data is involved.

1.3. Definitions, Acronyms and Abbreviations

Guest: an anonymous synthetic queue requester. Clerk: a fictional person allowed to close queue slots. Slot: one queued appointment.

1.4. References

No external project documents are needed by this standalone fictional benchmark.

2. Overall Description

QueueLab is a small demonstration web page with a fictional queue backend and a single synthetic data set.

2.1. Product perspective

A browser makes requests to a local example API; an in-memory queue stores a request identifier and state.

2.2. User characteristics

Guests request a slot. Clerks may close an existing slot. Both are hypothetical roles in this specification.

2.4. Constraints

PLACEHOLDER: This section still needs substantive project-specific requirements.

2.5. Assumptions and dependencies

The local example API is available during demonstrations; there is no production deployment or external service dependency.

3. Specific Requirements

Each statement below is an illustrative requirement for QueueLab only, not a mandate for other submitted SRS documents.

3.1. External interface requirements

The illustrative interface requirements below describe local browser and API behavior.

3.1.1. Hardware interfaces

A standard desktop or mobile browser is sufficient; no specialized hardware is required.

3.1.2. Software interfaces

A local JSON API returns queue slot records to the sample browser UI.

3.1.3. Communications interfaces

The browser sends a JSON request to the local API over HTTP in this isolated demonstration.

3.2. Functional requirements

PLACEHOLDER: This section still needs substantive project-specific requirements.

Module 1: Reservation queue

The reservation module manages creation and closure of fictional slots.

1.1. Request a queue slot

Create queue slot: guest sends a label; the system assigns a synthetic slot identifier and OPEN status.

Use Case Description

Actor: guest. Preconditions: the local API is available. Main flow: enter a label, submit, receive a slot ID. Alternate flow: reject an empty label. Postcondition: one OPEN record exists.

Activity Diagram

Synthetic flow description: Start > validate input > create open slot > display acknowledgement > End.

Wireframe

Text-only wireframe description: display-label field, Request Slot button, slot-status feedback region.

3.4 Non-functional requirements

The following illustrative quality requirements apply to QueueLab only.

Performance

NFR-01: The local demo acknowledges a valid queue request within two seconds under a single-user synthetic test.

Security

NFR-02: Only the clerk role can close a slot; a guest closure request shall be rejected.

Reliability

NFR-03: A rejected empty-label request shall not create a queue record.