

Software Test Document

QueueBoard | STD-06

FICTIONAL SYNTHETIC BENCHMARK ONLY. Expected/actual text below is scripted illustration, NOT observed software execution or student evidence.

Table of Contents

1. Introduction	2
1.1. System Overview	2
1.2. Test Approach	2
1.3. Definitions and Acronyms	2
2. Test Plan	2
2.1 Features to be Tested	2
2.2 Features not to be Tested	2
3.3 Testing Tools and Environment	2
3. Test Cases	2
3.1.1 Purpose	2
3.1.2 Inputs	2
3.1.3 Expected Outputs & Pass/Fail Criteria	2
3.1.4 Test Procedure	2
Appendix (Test Logs)	2
A.1 Log for Test 1	2
A.2 Test Results	2
A.3 Incident Report	2

1. Introduction

QueueBoard is a fictional local workshop queue example with no real users or deployed code.

1.1. System Overview

An imaginary guest requests one queue slot and an imaginary coordinator can close a slot. No real student, organization, or course data is involved.

1.2. Test Approach

Illustrative plans cover valid, empty, duplicate, boundary, unauthorized and unavailable-storage inputs. These are only hypothetical steps, not proof any test ran.

1.3. Definitions and Acronyms

Guest: imaginary requester. Coordinator: imaginary queue manager. Slot: invented queue record.

2. Test Plan

The fictional queue case is scoped to simple request creation and closure; there is no actual application under test.

2.1 Features to be Tested

QR-01 valid request; QR-02 empty label rejection; QR-03 duplicate rejection; QR-04 unauthorized closure rejection; QR-05 capacity-30 boundary rejection.

2.2 Features not to be Tested

Real authentication, payment, production deployment and user records are not part of this fictional fixture.

3.3 Testing Tools and Environment

Hypothetical local JSON endpoint, simulated queue records and a manual example worksheet; no software was executed to author this PDF.

3. Test Cases

The following are synthetic illustrative test-case descriptions, not recorded student tests.

3.1.1 Purpose

QR-To1 compares a hypothetical accepted label with a hypothetical invalid empty-label request.

3.1.2 Inputs

Synthetic request label DEMO-A; blank label; a mocked queue with zero or thirty open slots; guest and coordinator roles.

3.1.3 Expected Outputs & Pass/Fail Criteria

For valid DEMO-A, expected output is OPEN slot S-001. For blank label, expected validation failure without a slot. For 30 occupied slots, expected capacity rejection.

3.1.4 Test Procedure

Prepare imaginary queue state, apply DEMO-A then empty label to the fictional endpoint and compare scripted responses to predetermined expected outputs.

Appendix (Test Logs)

Example logs below are entirely fictional records and do not authenticate execution evidence.

A.1 Log for Test 1

SIMULATED ONLY: scripted example QR-To1 produced OPEN S-001; sample QR-To2 produced invalid-label response. This is not an actual run.

A.2 Test Results

SIMULATED ONLY: expected OPEN versus invented actual OPEN for QR-To1; expected invalid-label versus invented actual invalid-label for QR-To2. No real testing is claimed.

A.3 Incident Report

No mismatch is scripted in this fictional positive control; no conclusion about actual application incidents is justified.