

Software Test Document

QueueBoard | STD-23

FICTIONAL SYNTHETIC BENCHMARK ONLY. Expected/actual text below is scripted illustration, NOT observed software execution or student evidence.

Table of Contents

- 1. Introduction 2
- 1.1. System Overview 2
- 1.2. Test Approach 2
- 1.3. Definitions and Acronyms 2
- 2. Test Plan 2
- 2.1 Features to be Tested 2
- 2.2 Features not to be Tested 2
- 3.3 Testing Tools and Environment 2
- 3. Test Cases 2
- 3.1.1 Purpose 2
- 3.1.2 Inputs 2
- 3.1.3 Expected Outputs & Pass/Fail Criteria 2
- 3.1.4 Test Procedure 2
- Appendix (Test Logs) 2
- A.1 Log for Test 1 2
- A.2 Test Results 2
- A.3 Incident Report 2

1. Introduction

QueueBoard is a fictional local workshop queue example with no real users or deployed code.

1.1. System Overview

An imaginary guest requests one queue slot and an imaginary coordinator can close a slot. No real student, organization, or course data is involved.

1.2. Test Approach

Illustrative plans cover valid, empty, duplicate, boundary, unauthorized and unavailable-storage inputs. These are only hypothetical steps, not proof any test ran.

1.3. Definitions and Acronyms

Guest: imaginary requester. Coordinator: imaginary queue manager. Slot: invented queue record.

2. Test Plan

The FICTIONAL system specification requires rejection of empty input, capacity-30 boundary protection, unauthorized close rejection and transient-error handling. These conditions apply to this one artificial QueueBoard scenario.

2.1 Features to be Tested

The fictional source scenario specifies both valid slot creation and QR-02 empty label, QR-04 unauthorized close, QR-05 capacity boundary and retry handling.

2.2 Features not to be Tested

Real authentication, payment, production deployment and user records are not part of this fictional fixture.

3.3 Testing Tools and Environment

Hypothetical local JSON endpoint, simulated queue records and a manual example worksheet; no software was executed to author this PDF.

3. Test Cases

ONLY the happy-path QR-T01 case is supplied; no negative, boundary, unauthorized or error procedure is included.

3.1.1 Purpose

Happy path: create a slot for DEMO-A.

3.1.2 Inputs

Only DEMO-A as guest with zero queued slots, accepted by the fictional service.

3.1.3 Expected Outputs & Pass/Fail Criteria

ONLY scripted happy-path expectation: create OPEN slot S-001. No boundary or rejection expectations are written for any testcase.

3.1.4 Test Procedure

Submit DEMO-A once in the scripted hypothetical transaction, and inspect the one OPEN slot.

Appendix (Test Logs)

Example logs below are entirely fictional records and do not authenticate execution evidence.

A.1 Log for Test 1

SIMULATED HAPPY PATH ONLY: QR-T01 sample OPEN S-001. No other tests were run or claimed.

A.2 Test Results

SCRIPTED HAPPY PATH ONLY: expected OPEN and invented actual OPEN. No invalid, boundary or authorization observations.

A.3 Incident Report

No mismatch was introduced into this single hypothetical happy-path scenario.