

Wind Turbine Mechanics


B. Wind Turbine Loads

2. Sources of Load

c. Aerodynamic Loading

TURBULENCE IN WIND INFLOW

- PRODUCES VARYING LOADS AT FREQUENCIES AND LENGTH SCALES OF THE ATMOSPHERIC BOUNDARY LAYER



$\cos \theta$
 $-\cos$

NOTE THAT
TURBULENCE
MOTIONS
CAN AFFECT
ENTIRE
ROTOR OR
JUST A
PORTION

NOTE: YAW CAN PRODUCE
LARGE CHANGES IN U
→ LEAD TO α EXCEEDS $\frac{1}{3}$
SMALL EVENY V_t
ROTATION

↓
DYNAMIC &
STALL
RESTART ALIGNMENT

$$V_t = V \sin \theta_{yaw}$$

$$V_n = V \cos \theta_{yaw}$$

f IS THAT OF
TURBINE ROTATION

CHANGE IN U DEPENDENT
ON ROTOR ANGLE

IF THE ROTOR PLANE IS YAWED
TO INCOMING WIND

- RELATIVE ROTATION SPEED IS ALTERNATING INCREASE & DECREASED DUE TO COMPONENT V_t IN THE ROTOR PLANE

$$\Omega r (1 + a') = V \sin \theta_{yaw} \cos \theta_b$$

Wind Turbine Mechanics

B. Wind Turbine Loads

2. Sources of Load

c. Aerodynamic Loading

FOR EXTREME EVENTS ASSUME THAT THE
BLADES HAVE BEEN PARKED

$$F_{ext}(r) = g C_f C(r)$$

$$g = \frac{1}{2} \rho V^2$$

$C_f \rightarrow$ REPRESENTATIVE
OF WORST

UNDISTURBED
WIND SPEED


LIFT/DRAG CASE ~ 1.5

CONSIDER 60 m/s COMPARED A HIGH
OPERATING WIND SPEED 20 m/s

$$\frac{F_{60}}{F_{20}} = \frac{\frac{1}{2} \rho V_{60}^2 C_f C(r)}{\frac{1}{2} \rho V_{20}^2 C_f C(r)} = \frac{(60 \frac{\text{m}}{\text{s}})^2}{(20 \frac{\text{m}}{\text{s}})^2} = 9$$



Extreme Events




Wind Turbine Mechanics

B. Wind Turbine Loads

3. Cyclic Loads and Fatigue

AS DISCUSSED, WIND TURBINES ARE SUBJECT TO CYCLIC LOADING FROM VARIOUS SOURCES



Wind Turbine Mechanics

B. Wind Turbine Loads

3. Cyclic Loads and Fatigue

FATIGUE - INCREASING INABILITY TO WITHSTAND LOADS APPLIED MULTIPLE TIMES

FATIGUE IS PHYSICALLY REALIZED AS CRACKS THAT GROW SLOWLY IN TIME
THE LOWER ^{THE} MAGNITUDE ^{OF THE} CYCLIC LOADS, THE LONGER THE COMPONENT CAN SURVIVE

IMPORTANT TO WIND TURBINES IS THE NUMBER OF CYCLES THEY EXPERIENCE

$$\text{TOTAL CYCLES} = n_{\text{rotor}} \left(\frac{\text{rev}}{\text{min}} \right) T (\text{years}) \frac{60 \times 24 \times 365 \text{ min}}{1 \text{ year}} K$$

$K \equiv \text{EVENTS/REV}$

$$n_{\text{rotor}} = 20 \text{ rpm}$$

$$T = 20 \text{ YEARS}$$

TOTAL CYCLES	$K=1$	$K=5$	$K=10$
	2×10^8	1×10^9	2×10^9