

Ica_algebraic

Bringing *symbolic calculus* to **Brightway2**

Raphaël Jolivet - Research Engineer / IT
Observation Impact Energy - MINES ParisTech



INCER-ACV project




INCER-ACV project


INCER-ACV project

Parameterized
inventory


INCER-ACV project




INCER-ACV project



INCER-ACV project



INCER-ACV project



lca_algebraic

Ica_algebraic

Open Source library based on ***Brightway2*** & ***Sympy***

Ica_algebraic

Open Source library based on *Brightway2* & *Sympy*

Helper functions for **compact** & **declarative** definition of **parametric inventories**

Ica_algebraic

Open Source library based on *Brightway2* & *Sympy*

Helper functions for **compact** & **declarative** definition of **parametric inventories**

Symbolic calculus (Sympy) brings:

Ica_algebraic

Open Source library based on *Brightway2* & *Sympy*

Helper functions for **compact** & **declarative** definition of **parametric inventories**

Symbolic calculus (Sympy) brings:

- Parametric amounts in **pure Python** (vs strings)

Ica_algebraic

Open Source library based on *Brightway2* & *Sympy*

Helper functions for **compact** & **declarative** definition of **parametric inventories**

Symbolic calculus (Sympy) brings:

- Parametric amounts in **pure Python** (vs strings)
- **Factorize** background activities
 - ➔ super fast Monte Carlo (~ **1 million** / sec vs **100**)
 - ➔ **GSA** (*Sobol* indices)

Ica_algebraic

Open Source library based on *Brightway2* & *Sympy*


Helper functions for **compact** & **declarative** definition of **parametric inventories**

Symbolic calculus (Sympy) brings:

- Parametric amounts in **pure Python** (vs strings)
- **Factorize** background activities
 - ➔ super fast Monte Carlo (~ **1 million** / sec vs **100**)
 - ➔ **GSA** (*Sobol* indices)
- Automatic generation of **simplified models**

Ica_algebraic

Internals




A_i Foreground activities

B_i Background activities

P_i Parameters

Ica_algebraic

Internals



to **Sympy** expression :

$$A_1 = f(B_i, P_i)$$


A_i Foreground activities

B_i Background activities

P_i Parameters

Ica_algebraic

Internals



LCIA once, replace **B_i** by values :

$$A_1 = f(P_i)$$


A_i Foreground activities

B_i Background activities

P_i Parameters

Ica_algebraic

Internals



Compiles to **fast numpy** function

$$A_1 = f(P_i) \text{ ⚡}$$

- A_i Foreground activities
- B_i Background activities
- P_i Parameters

Demo time !