

How to write a good backend

if you have technical questions, feel free to open a issue in [biletado/biletado.gitlab.io](https://biletado.com/biletado/gitlab.io)

API v1

- select your API to start with, either `assets` or `reservation`
- each API has at least one request to the other one
- each API needs to check for authentication on some methods
- authorization will not be checked
- feel free when choosing programming languages or frameworks
- you may check the authentication via middleware, this includes maybe traefik
- you are not forced to use the equipped postgres-database as long as the API reacts like demanded
 - include your db-engine in the compose-environment

what to pay attention

containers

15%

- Pack your software inside a container so others can easily start your software in their own environments.
- adjust your copy of [biletado/compose/compose.yaml](#) by your needs.
- [keep your containers simple, stupid](#). The smaller your runtime container is the smaller is the amount of potential security issues (i. e. use a build-container to create the runtime-image)
- choose good base-images
 - good choices are e. g. [official docker-images](#), the ones built by [bitnami](#) or official images of your softwaredeveloper like [bazelbuild](#) for [Bazel](#)

script everything

5%

- create scripts for automated creation of your images, best is to use CI-integration like gitlab-ci or GitHub Actions

- `docker build` is not always the way to go, some frameworks like quarkus have their own way to build container-images

choose your framework wisely

15%

- use established web-frameworks which are designed for creating APIs
- probably some good ones are
 - [Symfony](#) (PHP)
 - [Laminas](#) (PHP)
 - [Quarkus](#) (Java/Kotlin)
 - [Spring Boot](#) (Java/Kotlin)
 - [Golang stdlib](#) (Go)
 - [Gin Web Framework](#) (Go)
 - [Rust-Frameworks](#)
 - [django](#) (Python)
 - [Ruby on Rails](#) (Ruby)
 - [Dart-Frameworks](#)
 - [Typescript-Frameworks](#)
- not so good ones are
 - PHP StdLib
 - Perl oneliners
 - javascript in general (IMHO)

secure your Queries

5%

- use always prepared statements to prevent SQL-Injection
- use an ORM or ODM for faster development

clean code

5%

- you are writing the legacy code of tomorrow, write it careful

- in half a year your own code is as far away from yourself like to any co-worker
- write self-documenting code
 - small classes and methods
 - good method- and variable-names
- use consistent code-style
- this means sadly, you should not use assembler, [Brainfuck](#), [2k16](#) (😞) or most other [esoteric languages](#)

validate the JWT

10%

- load the public-key from the id-provider and check if the JWT is applicable and has a valid signature

tracing

5%

- respect the tracing-header and reuse it for further requests so that the spans can be followed when requesting through traefik
- have a look at how to implement tracing inside your application

configurability

5%

- make your software and container-images configurable so that they can run in different environments
 - this can be by environment-variables or config-files which can be mounted into the container
 - e. g. the database-connection parameters or the HTTP-endpoints where requests are getting send to

licensing

1% (bonus)

- choose a appropriate license for your software to make it easy for others to reuse your code
 - e. g. MIT or BSD-2-clause

version-control

1% (bonus)

- use the version-control-system of your choice to make it easy to collaborate
- if you choose the right one, you get a container-registry and CI/CD for free

write documentation

5%

- document your project, especially your configuration-parametes and how to use your container
- a readme-file inside the code-repository is always a good choice

testautomation

5%

- include some tests inside your CI/CD-process, e. g. unit-tests, linting and/or automated API-Tests
- test your project before or after building and don't deliver it if the tests fail

logging

5%

- write useful logs to stdout and stderr with different, configurable loglevels to help yourself and other developers when debugging
- worth to have a look at: [Elastic Common Schema](#)

ah, and implement the API

20%

- CRUD-Operations
- Do good input-validation *before* communicate with other APIs or Databases
- use always descriptive return values, i. e. choose the right HTTP-Status and return meaningful errormessages if necessary