

mockito




Agenda

- What is Mockito?
- How does Mockito work?
- How to use Mockito?
- Demonstration and Examples
- Best Practice

What is Mockito?

- A mocking framework for unit tests
- Top 3 Java library
- Fork of EasyMock
- First use in 2008
- Currently at version 5
- License under MIT

How does Mockito work?



<https://stablediffusionweb.com/>: Black Magic culture Pentagram

Black Magic

How to use Mockito?

Maven

```
<dependency>  
  <groupId>org.mockito</groupId>  
  <artifactId>mockito-core</artifactId>  
  <version>5.2.0</version>  
  <scope>test</scope>  
</dependency>
```

Gradle

```
repositories { mavenCentral() }  
dependencies { testImplementation "org.mockito:mockito-core:5.2.0" }
```

How to use Mockito?

```
import static org.mockito.Mockito.*;
```

Importend Methods:

- `T mockObject = mock();`
- `when(mockObject.<methodCall>).thenReturn(<value>)`
- `doReturn(<value>).when(mockObject).<methodCall>`
- `verify(mockObject).<methodCall>`

How to use Mockito?

```
T mockObject = mock()
```

- Creates a mock of given type
- Returns nice values by default
- Default can be change via an Answer

```
T mockObject = mock(invocation -> {  
    throw new AssertionError("Unexpected Method call");  
})
```

How to use Mockito?

`when(mockObject.<methodCall>).thenReturn(<value>)` (Standard)

`doReturn(<value>).when(mockObject).<methodCall>` (When other is not working)

- Stubs the given method call
- Arguments in Method calls are respected

`when(listMock.indexOf("value")).thenReturn(0)`

- Use argument matcher for more control

`when(listMock.indexOf(anyString())).thenReturn(0)`

- Note: All values need an argument matcher if used

Wrong: `when(listMock.subList(anyInt(), 6)).thenReturn(new ArrayList())`

Correct: `when(listMock.subList(anyInt(), eq(6))).thenReturn(new ArrayList())`

How to use Mockito?

```
verify(mockObject).<methodCall>
```

- Check if a method was called once
- Arguments in Method calls are respected
- Use VerificationMode for more control

```
verify(listMock, times(2)).size()
```

```
verify(listMock, atLeast(3)).clear()
```

```
verify(listMock, atMost(4)).isEmpty()
```

Best Practice

- Only one of many tools for testing
- Only mock your own types
- Don't mock value objects
- Don't return a mock from a mock from a mock etc.

Links

- <https://site.mockito.org/>
- <https://github.com/mockito/mockito>
- <https://github.com/mockito/mockito/wiki/Mockito-Popularity-and-User-Base>
- <https://stackoverflow.com/questions/2665812/what-is-mocking>
- <https://stackoverflow.com/questions/14440270/how-does-mockito-when-invocation-work>
- <https://stackoverflow.com/questions/15693283/mockito-internals>
- <https://stackoverflow.com/questions/42496911/how-does-mockito-when-work-under-the-hood>