IBMI9I5O4I5
Derek Stanley Kannathe

```c
#include <stdio.h>
#include <string.h>
typedef struct student
{ char name[20];
  int ele;
} student;

void Enter(int n, student s[])
{ printf("The electives are : \n1. IOT\n2.JAVA\n3.DS \n");
  printf(" Enter the student details ( Name, Elective )");
  for(int i=0; i<n; i++)
    { printf("\n Student %d\n", i+1);
      scanf(" %s %d", s[i].name, &s[i].ele);
    }
}

void Same(int n, student s[])
{ int x;
  printf("\n Enter your elective number : ");
  scanf(" %d", &x);
  printf(" Same elective students are : \n");
  if(n>0)
    { for(int a=0; a<n; a++)
        { if(x == s[a].ele)
            printf("%s \n", s[a].name);
        }
    }
  else { printf("\n No students entered "); }
}

void count(int n, student s[])
{ int i=0, j=0, d=0;
  for(int x=0; x<n; x++)
    { if(s[x].ele == 1)
        i++;
      else if(s[x].ele == 2)
        j++;
      else if(s[x].ele == 3)
        d++;
    }
  printf(" IOT : %d \n JAVA : %d\n DS : %d", i, j, d);
}
```

1

```c
void check (int n, student s[])
{ int x, c=0;
  char nm[20];
  printf(" Enter your selective : ");
  scanf("%d",&x);
  for(int i=0;i<n; i++);
  { if(x == s[i].ele)
     c++; }
  if(c<30)
  { printf("\n Reselect your elective \n");
    printf(" Enter your name : \n");
    scanf("%s",nm);
    for(int p=0; p<n; p++)
    { if(! strcmp(nm, s[p].name))
      { printf("Enter new elective : \n");
        scanf("%d", &s[p].ele);
        count(n, s);
        break;
      }
    }
  }
}

void display(int n, student s[])
{ for(int e=1; e<=3; e++)
  { printf("\n Elective %d \n", e);
    for(int i=0; i<n; i++)
    { if(e == s[i].ele)
       printf("%s \t", s[i].name);
    }
  }
}

int main(void)
{ int n,ch;
  printf(" \n Enter the no of students to enter: ");
  scanf("%d",&n);
  student s[n];
  Enter(n, s);
  do
  { printf("\n1. CHECK SAME ELECTIVE \n2. COUNT ALL \n3. CHECK \n4.
    DISPLAY \n 5. EXIT \n");
    printf(" Enter choice : ");
```

```
switch (ch);
{ case 1: Same (n, s);
          break ;
  case 2: count (n, s);
          break;
  case 3: check (n, s);
          break;
  case 4: display (n, s);
          break;
  default: if (ch! = 5)
           printf (" Enter valid option : ");
  }
} while (ch! = 5)
return 0;
}
```

3