

Project Smart Trigger for ECE/CS 3992

Andrew Koebbe *Student ID: u1450645*, Stephen Hofmann *Student ID: u1028605*,
Thomas Stay *Student ID: u1249316*, Derek Jenkins *Student ID: u1506428*

Abstract—This project proposes a smart trigger for firearms that uses RFID technology to authenticate the user and ensure that only authorized users can fire the gun. This would help to prevent accidental shootings and unauthorized use of firearms, ultimately improving public safety. This paper will discuss solutions already in the market, the proposed solution, and the ethical considerations that need to be taken into account when designing and implementing such a system. It will also explore the project and outline the tasks that need to be completed in order to successfully implement the smart trigger and demonstrate its functionality at Demo Day. The risks associated with the project will also be assessed and strategies for mitigating those risks will be discussed.

Index Terms—IEEE, IEEEtran, journal, L^AT_EX, paper, template.

I. PROBLEM STATEMENT

A huge problem with firearms is that they are dangerous and can cause serious harm or death if not handled properly. This is especially true when it comes to children getting ahold of firearms or unauthorized users who may not know how to handle a firearm safely. Police officers can lose their firearms in the line of duty and if they are not recovered they can be used in crime. The proposed system, a smart trigger, would help to address this problem by preventing the gun from firing unless it is used by the owner. It would use RFID technology to authenticate the user and ensure that only authorized users can fire the gun. This would help to prevent accidental shootings and unauthorized use of firearms, ultimately improving public safety.

II. SOLUTION SPACE

Efforts to improve firearm safety through access control have evolved through several distinct technological approaches. At the most basic level, traditional solutions rely on purely mechanical safeguards such as trigger locks or integrated key-based locking mechanisms. These systems are inexpensive and highly reliable because they do not depend on electronics or power, but they fundamentally lack user-specific authentication.

Anyone with access to the key or combination can operate the firearm, which causes concern toward illegitimate use. In time-sensitive or high-stress situations, the need to manually unlock a device with a key can render the safety ineffective in practice, leading many police and military personnel to avoid using such systems altogether. This creates a gap between theoretical safety and real-world adoption, motivating the development of systems that can enforce access control without requiring manual, non-instantaneous intervention.

Electronic authentication methods represent the next step in this progression. Systems based on PIN entry, external key fobs, or smartphone connectivity attempt to introduce user-specific control while maintaining relatively simple hardware implementations. While these approaches improve upon mechanical systems by enabling programmable access, they still require explicit interaction from the user, such as entering a code or activating a device. This introduces latency and cognitive load that can be unacceptable in defensive scenarios. Additionally, wireless-based systems may be vulnerable to interception or spoofing, depending on their implementation. As a result, these approaches highlight the need for authentication mechanisms that are both secure and implicit, allowing the system to verify the user seamlessly without requiring conscious action.

Biometric authentication has emerged as the most prominent alternative in this space, particularly in commercial “smart gun” designs. By leveraging physiological traits such as fingerprints, palm vein patterns, or even grip characteristics, biometric systems aim to bind firearm operation directly to the identity of the user. This approach is compelling because it eliminates the need for external tokens and ensures that only authorized individuals can operate the weapon. However, when examined in the context of real-world firearm use, biometrics introduce a number of critical challenges. Sensors such as fingerprint scanners are highly sensitive to environmental conditions. Metrics like dirt, sweat, gloves, or moisture can significantly degrade performance. Firearms are often used in unpredictable and harsh environments, where such conditions are common, leading to an increased

likelihood of authentication failure.

Latency is another major concern. Biometric systems require time to capture, process, and match data against stored templates. Even small delays can be unacceptable in scenarios where immediate response is necessary. Equally important is the issue of reliability in terms of false negatives and false positives. A false negative, where an authorized user is denied access, represents a potentially dangerous failure in a defensive situation. Conversely, a false positive undermines the entire purpose of the system. These risks are compounded by the long-term degradation of sensors and the variability of human biological signals. In addition to these technical concerns, biometric systems tend to be significantly more expensive and power-intensive than alternative solutions. Commercial implementations often cost on the order of \$1000 to \$1500, reflecting the complexity of most biometric devices. This cost and power burden conflicts directly with the constraints of a small, battery-powered module designed to fit within the firing control group of an AR-15.

RFID-based authentication offers a different point in the design space by prioritizing simplicity, robustness, and low power consumption. In a passive near-field RFID system, authentication occurs when a tag enters the electromagnetic field generated by a reader, allowing the tag to transmit its unique identifier without requiring its own power source. This enables extremely low-latency operation and reduces the system's overall energy requirements. RFID systems are also less sensitive to environmental contaminants compared to optical or capacitive biometric sensors, making them more reliable in varied conditions. The primary tradeoff is that RFID relies on possession rather than inherent identity. A user must carry an external token, such as a ring or card, which introduces the possibility of loss or unauthorized use if the token is compromised.

More complex hybrid systems attempt to combine multiple authentication methods, such as pairing RFID with biometrics or behavioral sensing, in order to improve security. While these approaches can reduce certain vulnerabilities, they significantly increase system complexity, cost, and power consumption. For a compact, retrofittable module operating under strict physical and electrical constraints, this hybrid complexity is impractical. As a result, the solution space reflects a series of tradeoffs between security, reliability, usability, and feasibility. Biometric systems offer strong identity assurance but struggle with robustness and cost, while RFID systems sacrifice some degree of identity binding in exchange for speed, reliability, and practicality. This balance makes RFID a compelling candidate for a system

intended to be compact, cost-effective, and deployable in real-world conditions.

III. RELATED WORK

Radio frequency identification (RFID) has been widely studied as part of the broader class of automatic identification technologies. Kaur et al. provides a comprehensive overview of its principles, capabilities, and limitations. RFID systems enable the wireless transmission of identification using radio waves, allowing individuals or objects to be identified without requiring line-of-sight interaction, in contrast to traditional barcode systems [1]. This capability significantly improves automation and reduces the need for human action within lock systems, making RFID useful for embedded and access control applications that require high speed and reliability.

A major focus of prior work is the distinction between passive and active RFID systems, as well as the physical mechanisms that enable their operation. Passive RFID operates by harvesting energy from the electromagnetic field generated by a reader. In near-field systems, this process is governed by magnetic induction, where an alternating magnetic field induces a voltage across a tag's coil, which provides enough energy for the tag to transmit its stored ID [1]. This eliminates the need for an onboard power source. These characteristics make passive RFID well-suited for compact, power-constrained embedded systems, such as our intended implementation within a firearm's firing control group.

Despite these advantages, Kaur et al. also identifies several important limitations of RFID systems that must be addressed. One key constraint is the relationship between operating frequency and read range. In near-field systems, the effective communication range is limited and decreases rapidly due to the inverse cubic decay of the magnetic field [1]. While this restricts long-range communication, it can be advantageous for security sensitive applications by ensuring that the authenticated user is within close proximity. Other challenges include signal collision when multiple tags are present, environmental interference caused by conductive materials or electromagnetic noise, and the lack of universal standardization across RFID systems [1]. Security and privacy concerns are also significant, as unauthorized cloning of tags can compromise system integrity if appropriate safeguards are not implemented.

Taken together, the existing literature establishes RFID as a mature and well-understood technology for identification and access control. It has demonstrated advantages in automation, robustness, and low power operation. At

the same time, it highlights key technical and security challenges that must be carefully addressed in our implementation. This paper provides a strong foundation for the proposed system, informing both the design choices and the tradeoffs involved in applying RFID to firearm safety.

IV. SOLUTION / CONTRIBUTION

To truly understand our project and our approach, an overview of the firing control group of an AR-15 rifle is necessary. The firing control group operates through a precise mechanical interaction between the trigger, sear, and hammer. As seen in Figure 1,

the hammer is held back under spring tension by the sear. When the trigger is pulled, it disengages the sear, releasing the hammer and allowing it to rotate forward where it would eventually hit the firing pin. Our proposed solution is to block the firing control group by applying an additional force against the hammer, ensuring that it can never strike the firing pin. Our idea is to use a linear actuator to provide this force against the hammer. A linear actuator paired with a microcontroller would allow for low-voltage operation of our access control. The gun would then only be able to fire when a validated RFID tag is present in close proximity to our implemented system on the firing control group.

The primary contribution of this project is the integration of RFID-based access control into this already operating, small mechanical system. A passive RFID reader embedded near the control group continuously scans for a valid tag worn by the user, particularly in a ring worn on their finger. When an authorized tag is detected, the system signals the actuator to disengage, allowing normal operation of the firing mechanism. If no valid tag is present, the actuator blocks the hammer from hitting the firing pin. This way the firearm would never fire even if the trigger is pressed. This approach enables fast and implicit authentication without requiring user interaction, while also remaining low-power and cost-effective compared to biometrics alternatives. By combining a simple mechanical intervention with proximity-based RFID authentication, the system provides a practical solution for enhancing firearm safety.

V. SAFETY, GLOBAL, SOCIETAL, ETHICAL CONSIDERATIONS

What are the public health, safety and welfare, global, cultural, societal, environmental, and economic factors related to the problem and solution space? What power does the proposed system provide, and to whom? What are the relevant professional ethical obligations to consider in the design of the system?

A. Factors Related to the Problem and Solution

1) *Public Health, Safety, and Welfare:* The main issue the proposed system addresses is the potential for negligent discharge of a firearm. This is because of the nature of guns in that they are designed to inflict harm on a target. The smart trigger would help to protect the public safety in a couple of ways. First the system would be designed to prevent the gun from firing unless it is used by the owner. This would help to prevent accidental shootings by children or others that are not licensed to shoot a firearm. Secondly, if the gun was lost unless the module was removed the gun wouldn't be able to fire. This would help to prevent the gun from being used in crime or from being used in a negligent way. Lastly, the system is module meaning that if at any point it has a malfunction the module can be removed and the gun can be used as normal. This would help to prevent situations where a gun is rendered unusable due to malfunctions of the system. In the past since the mid 1990s, there have been numerous starts to create something similar to the smart trigger. These safety devices are known as Firearm Safety Devices (FSDs) and are most of the time mechanical as they are reliable and don't require a power source as shown in fig ??.

They also have some characteristics and features that are mentioned in [?]

- the option of integrating and combining mechanical devices with various authorization processes (token, password, biometric);
- hierarchical authorization;
- traceability and logging functions;
- networking and remote availability.



Fig. 1. Trigger and Cable Lock

2) *Global, and Cultural:* Because our project is focused on firearms it is important to consider the global and cultural factors that may affect the implementation and use of the smart trigger. For example, different countries have different laws and regulations regarding firearms, and the cultural attitudes towards guns can

vary significantly. It is important to ensure that the system is designed in a way that is compliant with these regulations and respectful of these cultural differences. For the scope of the project we will be focusing on the United States, but it is also important to consider its implications in other countries. The United States has a deep history with firearms and the Second Amendment to the Constitution guarantees the right of citizens to keep and bear arms. This doesn't mean that no regulations have been put in place regarding firearms. Some laws that may affect the system include.

- Maryland (SB 334/HB 1339) This law requires that all firearms be equipped with a safety device before being sold or transferred. In order for our system to be approved in Maryland it would need to be approved by the Handgun Roster Board, which is responsible for evaluating and approving firearms and firearm safety devices for sale in the state.
- 1) New Jersey's "Display Mandate": This law requires that all firearms be displayed in a visible manner when being sold or transferred. This would require the entire state to adopt the smart trigger as the standard to use in New Jersey.
- 2) Because our system uses RFID technology its legally and intentional radiator. This means that if we ever wanted to sell the system in the United States we would need to get approval from the Federal Communications Commission (FCC) to ensure that it complies with regulations regarding radio frequency emissions.

3) *Societal and Economic*: Part of the reason why the RFID authentication would be beneficial is that it would be a more affordable and reliable solution compared to other biometric authentication methods. This would make it more accessible to a wider range of gun owners, which could help to increase the adoption of the system and ultimately improve public safety. At gun ranges unless the user was wearing the RFID tag they wouldn't be able to use the gun. This would make shooting ranges safer for everyone because it would prevent unauthorized users from using the guns. This would also help to prevent accidents and injuries at shooting ranges, which could have a positive impact on public health and safety. Another way in which the system would increase safety is if a gun was lost or stolen from the police department. If the gun was equipped with the smart trigger it would be rendered useless to any thief.

For each of the

Microcontroller	\$15 or free
RFID Scanner	9prototypeboard,3-5 per chip
AR-15 Lower	Free (thanks Stephen)
3D Printed Parts	\$20 maximum
Custom PCB	\$50 in prototyping, ~25 per order
Various electronic parts for the PCBs	\$20-50
Linear Actuator	\$20
RFID Tags	10forprototypes,10 for the ring
RFID Programmer	\$30
Battery	10forbattery,5 for charger parts
Total	\$190-235

4) *Environmental*: The use of RFID technology in our system also has some environmental considerations. The production and disposal of the RFID tags and other electronic components can have an impact on the environment. However, we will strive to use sustainable materials and practices wherever possible to minimize this impact.

B. Power

Understanding how the system could be used and how power is shifting is important to ensure that the system is designed in a way that is ethical and responsible. The smart trigger would provide power to the gun owner by allowing them to have more control over who can use their firearm. This would help to prevent unauthorized use of the gun, which could improve public safety and reduce the risk of accidents and injuries. This would also give power to law enforcement by making it more difficult for stolen guns to be used in crimes and against police officers in shoot outs. The system would also provide power to the general public by helping to prevent accidents and injuries caused by negligent discharge of firearms. If the system were to have any bugs or issues it could potentially be exploited by moving power to the criminals.

VI. PROPOSED WORK

A project includes some things and excludes others you know you won't work on. Define more explicitly what is included and not included here. What will be demonstrated at project completion at Demo Day?

For our project, we will include parts of the gun that are necessary to demo the smart trigger functionality. Items Included:

- Lower receiver: This is the part of the gun that contains the trigger mechanism and is necessary for demonstrating the smart trigger functionality.
- RFID reader: This is the component that will be used to authenticate the user and ensure that only authorized users can fire the gun.

- RFID tag: This is the component that will be attached to the user's ID and will be read by the RFID reader to authenticate the user.
- Microcontroller: This is the brain of the smart trigger system and will be responsible for processing the RFID data and controlling the trigger mechanism.
- Custom PCB: This will be used to connect all the components together and ensure that they work together seamlessly.

Items Excluded:

- Upper receiver: This is the part of the gun that contains the barrel and is not necessary for demonstrating the smart trigger functionality.
- Stock: This is the part of the gun that provides support and is not necessary for demonstrating the smart trigger functionality.
- Grip: This is the part of the gun that is held by the user and is not necessary for demonstrating the smart trigger functionality.

VII. PROJECT TASKS

Describe each task.

A. Major Milestones

- Planning:
 - Full bill of materials made
 - Major research complete
 - Safety precautions addressed
 - Due:
- Functional RFID reader:
 - Able to read and log tags
 - Exportable log
 - Due:
- Application for updating authorized tags:
 - User able to update authorized tags without reflashing
 - Due:
- Successful blocking of fire control:
 - Method of blocking the firing of the AR-15 solidified and location confirmed
 - Due:
- Part fitting:
 - Adapting all components into the small form factor required by constraints
 - Due:
- Assembly:
 - All components fit together and operate in basic expected function

– Due:

- Endurance testing:

- Full system able to withstand operation of firearm
- Due:

B. Stretch goals

things that you are planning to include, but the project will succeed even without them (and why)

C. Purchase, build, borrow

What components will be purchased and what will be built? What resources are needed to complete the tasks? These may be your own, or in a lab, or may be people who will help you.

D. Task interfaces

What are the important inputs and outputs of each individual component? Define them.

E. Testing

How will each task be tested

F. Design approach

For each component, how will it be designed? What tools will be used (software, hardware, measurement, etc.)

G. Current status

What tasks have been finished? What is left to be done?

H. Parts

Complete parts list with vendor name and information

VIII. INTEGRATION STRATEGY

Our project has a constraint to fit within a very small space. We will utilize a partially distributed integration strategy in order to mesh all of the components together. The primary electronics are an RFID module, a microcontroller unit (MCU), a power supply, and a linear actuating solenoid. All components except the solenoid will be housed in the plastic grip for an AR-15. The plastic grip has the benefit of not interfering with the RFID signal thus reducing the complexity of a faraday cage effect that could block any electromagnetic signal from being identified.

The solenoid will be housed inside the actual receiver of the AR-15. This separate location allows for the direct blocking of the fire control group. The actuation will be triggered via fine gauge wire passing through one of the holes where the grip physically attaches to the receiver.

Power management is one of the most challenging parts of this entire project. The RFID module can consume up to 60mA during its operation and the solenoid up to 200mA. To compensate for these power requirements we will employ an interrupt driven state machine. A low power timer will periodically activate the RFID module to check for a tag, if one is detected it will activate hardware interrupt on the MCU to check if the tag is authorized. If the tag is in the authorized list the MCU will then actuate the solenoid to remove the block of the fire control group, ultimately allowing the firing of the AR-15.

IX. RISK ASSESSMENT

To ensure project success and the safety of all personnel, we have identified and mitigated key risks associated with the development of a smart trigger. Each risk was initially categorized as Red (high), Yellow (moderate), or Green (low). Through a proactive de-risking process, all identified hazards have been moved to the Green category.

- **Safety/Legal (Initially Red):** Bringing a firearm to campus; potential regulatory non-compliance; negligent discharges.
- **Operational (Initially Yellow):** Inadequate real-world testing; mechanical component failure; pinch injuries from moving parts.
- **Design (Initially Green):** Spatial constraints within the fire control group.

Campus Safety and Legal Compliance: The most critical risk involved the presence of a firearm on school grounds. We have fully de-risked this by utilizing a modular design: only the smart trigger assembly is brought to campus for testing, while the firearm remains off-site. To address legal concerns, we are consulting with university police and safety officers to ensure all protocols meet local regulations. These measures transition these risks to **Green**.

Safe Handling and Negligent Discharge: To mitigate risks of improper handling or accidental discharge, all team members have undergone a safety orientation focused on the four primary laws of firearm safety. Furthermore, all initial functionality testing of the smart trigger is performed in a lab environment without a firearm present. These strict protocols ensure a **Green** safety rating.

Testing and Mechanical Reliability: To address the risk of component failure or inadequate testing, we will implement a rigorous, multi-stage validation process. This includes individual component stress testing (e.g., solenoid durability) followed by integrated field testing in varied environments. This ensures the system is robust and functions as intended, moving these concerns to **Green**.

Physical Hazards and Spatial Design: Potential for minor injuries from moving parts is mitigated through the mandatory use of personal protective equipment (PPE) and ergonomic housing designs. Regarding spatial constraints, we will utilize precise measurements of the fire control group and detailed prototypes during the design phase to ensure a proper fit. Both risks are confirmed **Green**.

With these mitigation strategies finalized, the project is fully de-risked and prepared for safe demonstration.

X. CONCLUSION

ACKNOWLEDGMENT

REFERENCES

- [1] E. S. Devices, "Personalized firearms and electronic safety devices," 2013.
- [2] S. M. Alamouti, "A simple transmit diversity technique for wireless communications," *IEEE J. Select Areas in Communications*, vol. 16, no. 8, pp. 1451–1458, Oct. 1998.
- [3] Special Committee 239 of the RTCA, "Assessment of C-band mobile telecommunications interference impact on low range radar altimeter operations," Oct 2020, RTCA Paper No. 274-20/PMC-2073. [Online]. Available: https://www.rtca.org/wpcontent/uploads/2020/10/SC-239-5G-Interference-Assessment-Report_274-20-PMC2073_accepted_changes.pdf
- [4] L. Yin and A. Sankin, "Dollars to megabits, you may be paying 400 times as much as your neighbor for internet service," *The Markup*, Oct. 2022. [Online]. Available: <https://themarkup.org/still-loading/2022/10/19/dollars-to-megabits-you-may-be-paying-400-times-as-much-as-your-neighbor-for-internet-service>
- [5] J. D. O'Sullivan, G. R. Daniels, T. M. Percival, D. I. Ostry, and J. F. Deane, "Wireless LAN," Jan 1996, u.S. Patent 5,487,069.
- [6] D. Maas, M. H. Firooz, J. Zhang, N. Patwari, and S. K. Kasper, "Channel sounding for the masses: Low complexity GNU 802.11b channel impulse response estimation," *IEEE Transactions on Wireless Communications*, vol. 11, no. 1, pp. 1–8, 2012.
- [7] D. Halperin, W. Hu, A. Sheth, and D. Wetherall, "802.11 with multiple antennas for dummies," *ACM SIGCOMM Computer Communication Review*, vol. 40, no. 1, pp. 19–25, 2010.
- [8] D. Halperin, B. Greenstein, A. Sheth, and D. Wetherall, "Demystifying 802.11n power consumption," in *Proc. 2010 Intl. Conf. on Power-Aware Computing and Systems*, 2010.
- [9] J. G. Proakis and M. Salehi, *Communication systems engineering*, 2nd ed. Prentice Hall, 2002.
- [10] R. V. Hartley, "Transmission of information," *The Bell System Technical Journal*, vol. 7, no. 3, pp. 535–563, 1928.
- [11] W. Shakespeare, *Romeo and Juliet*, 1597. [Online]. Available: http://shakespeare.mit.edu/romeo_juliet/full.html
- [12] J. Breen, A. Buffmire, J. Duerig, K. Dutt, E. Eide, M. Hibler, D. Johnson, S. K. Kasper, E. Lewis, D. M. A. Orange, N. Patwari, D. Reading, R. Ricci, D. Schurig, L. B. Stoller, J. Van der Merwe, K. Webb, and G. Wong, "Powder: Platform for open wireless data-driven experimental research," in *in Proc. 14th Intl. Workshop on Wireless Network Testbeds, Experimental Evaluation and Characterization (WiNTECH)*, Sep. 2020.
- [13] C. E. Shannon, "A mathematical theory of communication," *The Bell System Technical Journal*, vol. 27, no. 3, pp. 379–423, 1948. [Online]. Available: <http://math.harvard.edu/~ctm/home/text/others/shannon/entropy/entropy.pdf>
- [14] A. Papoulis and S. U. Pillai, *Probability, random variables, and stochastic processes*. Tata McGraw-Hill Education, 2002.
- [15] T. S. Rappaport, *Wireless communications: principles and practice*. Cambridge University Press, 2024.
- [16] G. D. Durgin, T. S. Rappaport, and D. A. De Wolf, "New analytical models and probability density functions for fading in wireless communications," *IEEE Transactions on Communications*, vol. 50, no. 6, pp. 1005–1015, 2002.
- [17] R. Malik, "Spread spectrum - secret military technology to 3G," in *IEEE Conference on the History of Telecommunications*, 2001, pp. 1–5.
- [18] V. Tarokh, H. Jafarkhani, and A. R. Calderbank, "Space-time block codes from orthogonal designs," *IEEE Transactions on Information Theory*, vol. 45, no. 5, pp. 1456–1467, 1999.
- [19] P. W. Wolniansky, G. J. Foschini, G. D. Golden, and R. A. Valenzuela, "V-BLAST: An architecture for realizing very high data rates over the rich-scattering wireless channel," in *1998 URSI International Symposium on Signals, Systems, and Electronics*, 1998, pp. 295–300.
- [20] P. Lundrigan, N. Patwari, and S. K. Kasper, "On-off noise power communication," in *Proc. of the ACM Intl. Conf. on Mobile Computing and Networking (MobiCom 2019)*, Oct. 2019, <https://span.engineering.wustl.edu/pub/lundrigan2019onoff.pdf>.
- [21] L. W. Couch, *Digital and Analog Communication Systems*, 7th ed. Pearson, 2007.
- [22] S. Kay, *Fundamentals of Statistical Signal Processing, Volume II: Detection Theory*, 1st ed. Pearson, 1998.
- [23] N. Patwari, A. O. Hero, M. Perkins, N. S. Correal, and R. J. O'Dea, "Relative location estimation in wireless sensor networks," *IEEE Transactions on Signal Processing*, vol. 51, no. 8, pp. 2137–2148, 2003.
- [24] M. Rice, *Digital Communications: a Discrete-Time Approach*. Pearson Prentice Hall, 2009.
- [25] S. O. Haykin and M. Moher, *Modern Wireless Communications*, 1st ed. Pearson, 2005.
- [26] B. P. Lathi and Z. Ding, *Modern Digital and Analog Communication Systems*, 4th ed. Oxford University Press, 2008.
- [27] C. Chang and T. Pham, "DSN telecommunications link design handbook," 2019. [Online]. Available: <http://deepspace.jpl.nasa.gov/dsndocs/810-005/>
- [28] S. Gordon, "Talking to Martians: Communications with Mars Curiosity rover," 2012, web page. [Online]. Available: <https://sandilands.info/sgordon/communications-with-mars-curiosity>
- [29] D. Dobrijevic, "Distance to Mars: How far away is the red planet?" Feb 2022. [Online]. Available: <https://www.space.com/14729-spacekids-distance-earth-mars.html>
- [30] R. Ludwig and J. Taylor, *Voyager telecommunications*. John Wiley and Sons, Inc., 2016. [Online]. Available: https://voyager.gsfc.nasa.gov/Library/DeepCommo_Chapter3--141029.pdf
- [31] H. T. Friis, "A note on a simple transmission formula," *Proceedings of the IRE*, vol. 34, no. 5, pp. 254–256, 1946.
- [32] H. Hashemi, "The indoor radio propagation channel," *Proceedings of the IEEE*, vol. 81, no. 7, pp. 943–968, 1993.
- [33] adlughmin, "This 3d printed spirograph allows you to draw fascinating geometric designs," <https://3dprint.com/79095/3d-printed-spirograph/>, July 2015.
- [34] L. Camhi, "Hedy Lamarr's forgotten, frustrated career as a wartime inventor," *The New Yorker*, 2017. [Online]. Available: <https://www.newyorker.com/tech/annals-of-technology/hedy-lamarrs-forgotten-frustrated-career-as-a-wartime-inventor>
- [35] G. Bianchi, "Performance analysis of the IEEE 802.11 distributed coordination function," *IEEE Journal on Selected Areas in Communications*, vol. 18, no. 3, pp. 535–547, 2000.
- [36] H. Kopka and P. W. Daly, *Guide to L^AT_EX*. Pearson Education, 2003.
- [37] P. Piniés, J. D. Tardós, and J. Neira, "Localization of avalanche victims using robocentric SLAM," in *2006 IEEE/RSJ International Conference on Intelligent Robots and Systems*. IEEE, 2006, pp. 3074–3079.