

Project Smart Trigger for ECE/CS 3992

Andrew Koebbe Student ID: u1450645, Stephen Hofmann Student ID: u11111111,
Thomas Stay Student ID: u22222222, Derek Jenkins Student ID: u1506428

Abstract—Some people will read this and nothing else. What should they know about your proposal?

Index Terms—IEEE, IEEEtran, journal, L^AT_EX, paper, template.

I. PROBLEM STATEMENT

What is the problem the project is trying to solve?

II. SOLUTION SPACE

Efforts to improve firearm safety through access control have evolved through several distinct technological approaches. At the most basic level, traditional solutions rely on purely mechanical safeguards such as trigger locks or integrated key-based locking mechanisms. These systems are inexpensive and highly reliable because they do not depend on electronics or power, but they fundamentally lack user-specific authentication. Anyone with access to the key or combination can operate the firearm, which causes concern toward illegitimate use. In time-sensitive or high-stress situations, the need to manually unlock a device with a key can render the safety ineffective in practice, leading many police and military personnel to avoid using such systems altogether. This creates a gap between theoretical safety and real-world adoption, motivating the development of systems that can enforce access control without requiring manual, non-instantaneous intervention.

Electronic authentication methods represent the next step in this progression. Systems based on PIN entry, external key fobs, or smartphone connectivity attempt to introduce user-specific control while maintaining relatively simple hardware implementations. While these approaches improve upon mechanical systems by enabling programmable access, they still require explicit interaction from the user, such as entering a code or activating a device. This introduces latency and cognitive load that can be unacceptable in defensive scenarios. Additionally, wireless-based systems may be vulnerable to interception or spoofing, depending on their implementation. As a result, these approaches highlight the need for authentication mechanisms that are both secure

and implicit, allowing the system to verify the user seamlessly without requiring conscious action.

Biometric authentication has emerged as the most prominent alternative in this space, particularly in commercial “smart gun” designs. By leveraging physiological traits such as fingerprints, palm vein patterns, or even grip characteristics, biometric systems aim to bind firearm operation directly to the identity of the user. This approach is compelling because it eliminates the need for external tokens and ensures that only authorized individuals can operate the weapon. However, when examined in the context of real-world firearm use, biometrics introduce a number of critical challenges. Sensors such as fingerprint scanners are highly sensitive to environmental conditions. Metrics like dirt, sweat, gloves, or moisture can significantly degrade performance. Firearms are often used in unpredictable and harsh environments, where such conditions are common, leading to an increased likelihood of authentication failure.

Latency is another major concern. Biometric systems require time to capture, process, and match data against stored templates. Even small delays can be unacceptable in scenarios where immediate response is necessary. Equally important is the issue of reliability in terms of false negatives and false positives. A false negative, where an authorized user is denied access, represents a potentially dangerous failure in a defensive situation. Conversely, a false positive undermines the entire purpose of the system. These risks are compounded by the long-term degradation of sensors and the variability of human biological signals. In addition to these technical concerns, biometric systems tend to be significantly more expensive and power-intensive than alternative solutions. Commercial implementations often cost on the order of \$1000 to \$1500, reflecting the complexity of most biometric devices. This cost and power burden conflicts directly with the constraints of a small, battery-powered module designed to fit within the firing control group of an AR-15.

RFID-based authentication offers a different point in the design space by prioritizing simplicity, robustness, and low power consumption. In a passive near-field

RFID system, authentication occurs when a tag enters the electromagnetic field generated by a reader, allowing the tag to transmit its unique identifier without requiring its own power source. This enables extremely low-latency operation and reduces the system's overall energy requirements. RFID systems are also less sensitive to environmental contaminants compared to optical or capacitive biometric sensors, making them more reliable in varied conditions. The primary tradeoff is that RFID relies on possession rather than inherent identity. A user must carry an external token, such as a ring or card, which introduces the possibility of loss or unauthorized use if the token is compromised.

More complex hybrid systems attempt to combine multiple authentication methods, such as pairing RFID with biometrics or behavioral sensing, in order to improve security. While these approaches can reduce certain vulnerabilities, they significantly increase system complexity, cost, and power consumption. For a compact, retrofittable module operating under strict physical and electrical constraints, this hybrid complexity is impractical. As a result, the solution space reflects a series of tradeoffs between security, reliability, usability, and feasibility. Biometric systems offer strong identity assurance but struggle with robustness and cost, while RFID systems sacrifice some degree of identity binding in exchange for speed, reliability, and practicality. This balance makes RFID a compelling candidate for a system intended to be compact, cost-effective, and deployable in real-world conditions.

III. RELATED WORK

A more in-depth, formal exploration of the research and product development related to the problem space.

IV. SOLUTION / CONTRIBUTION

1-2 paragraphs summarizing your approach, what's exciting about it, why it will succeed

V. SAFETY, GLOBAL, SOCIETAL, ETHICAL CONSIDERATIONS

What are the public health, safety and welfare, global, cultural, societal, environmental, and economic factors related to the problem and solution space? What power does the proposed system provide, and to whom? What are the relevant professional ethical obligations to consider in the design of the system?

A. Factors Related to the Problem and Solution

1) Public Health:

2) Safety and Welfare:

3) Global:

4) Cultural:

5) Societal:

6) Environmental:

7) Economic:

B. Power

VI. PROPOSED WORK

A project includes some things and excludes others you know you won't work on. Define more explicitly what is included and not included here. What will be demonstrated at project completion at Demo Day?

VII. PROJECT TASKS

Describe each task.

- "baseline deliverables" – things you will deliver
- "stretch goals" – things that you are planning to include, but the project will succeed even without them (and why)
- What components will be purchased and what will be built?
- What resources are needed to complete the tasks? These may be your own, or in a lab, or may be people who will help you.
- Task Interfaces: What are the important inputs and outputs of each individual component? Define them.
- Testing: How will each task be tested?
- Design approach: For each component, how will it be designed? What tools will be used (software, hardware, measurement, etc.)
- Current status: What tasks have been finished? What is left to be done?
- Schedule: A date when each task will be completed.
- Parts: Complete parts list with vendor name and information

VIII. INTEGRATION STRATEGY

How will the individual tasks/components be integrated? How will the integration be tested?

IX. RISK ASSESSMENT

What are the largest risks to successful demonstration of the project? Describe each risk as green, yellow, or red. At proposal stage, your goal is to have all risks in the "green" category, that is, you have de-risked any major risks to the project. Describe the de-risking process.

X. CONCLUSION

ACKNOWLEDGMENT

REFERENCES

- [1] M. Shell. (2008) IEEEtran homepage. [Online]. Available: <http://www.michaelshell.org/tex/ieeetran/>
- [2] —. (2008) IEEEtran webpage on CTAN. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/IEEEtran/>
- [3] (2008) The IEEE website. [Online]. Available: <http://www.ieee.org/>
- [4] O. Patashnik. (1988, Feb.) ing. btxdoc.pdf. [Online]. Available: <http://www.ctan.org/tex-archive/biblio/bibtex/contrib/doc/>
- [5] —. (1988, Feb.) Designing styles. btxhak.pdf. [Online]. Available: <http://www.ctan.org/tex-archive/biblio/bibtex/contrib/doc/>
- [6] N. Markey. (2005, Oct.) Tame the beast — the b to x of . [Online]. Available: <http://tug.ctan.org/tex-archive/info/bibtex/tamethebeast/>
- [7] D. Hoadley and M. Shell. (2007, Jan.) tips and FAQ. btxFAQ.pdf. [Online]. Available: <http://www.ctan.org/tex-archive/biblio/bibtex/contrib/doc/>
- [8] R. Fairbairns. (2008, Jun.) The T_EX FAQ. [Online]. Available: <http://www.tex.ac.uk/cgi-bin/texfaq2html/>
- [9] K.-J. Kim. (2004, Apr.) A guide via examples. bibtex_guide.pdf. [Online]. Available: <http://www.geocities.com/kijoo2000/>
- [10] N. H. F. Beebe. (2008, Jul.) T_EX user group bibliography archive. [Online]. Available: <http://www.math.utah.edu/pub/tex/bib/index-table.html>
- [11] P. W. Daly. (2007, Oct.) The natbib.sty package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/natbib/>
- [12] D. Arseneau. (2006, Apr.) The url.sty package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/misc/>
- [13] S. Rahtz and H. Oberdiek. (2008, Sep.) The hyperref.sty package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/hyperref/>
- [14] V. C. Neto. (2008, Jul.) The breakurl.sty package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/breakurl/>
- [15] J. Braams. (2008, Jul.) The babel package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/required/babel/>
- [16] T. Hansen. (2004, Jan.) The multibib.sty package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/contrib/multibib/>
- [17] P. Lehman. (2008, Apr.) The biblatex package. [Online]. Available: <http://www.ctan.org/tex-archive/macros/latex/exptl/biblatex/>
- [18] S. Zhang, C. Zhu, J. K. O. Sin, and P. K. T. Mok, “A novel ultrathin elevated channel low-temperature poly-Si TFT,” vol. 20, pp. 569–571, Nov. 1999.
- [19] F. Delorme *et al.*, “Butt-jointed DBR laser with 15 nm tunability grown in three MOVPE steps,” *Electron. Lett.*, vol. 31, no. 15, pp. 1244–1245, 1995.
- [20] R. K. Gupta and S. D. Senturia, “Pull-in time dynamics as a measure of absolute pressure,” in *Proc. IEEE International Workshop on Microelectromechanical Systems (MEMS’97)*, Nagoya, Japan, Jan. 1997, pp. 290–294.
- [21] B. D. Cullity, *Introduction to Magnetic Materials*. Reading, MA: Addison-Wesley, 1972.
- [22] A. Castaldini, A. Cavallini, B. Fraboni, P. Fernandez, and J. Piqueras, “Midgap traps related to compensation processes in CdTe alloys,” *Phys. Rev. B.*, vol. 56, no. 23, pp. 14 897–14 900, 1997.
- [23] Y. Okada, K. Dejima, and T. Ohishi, “Analysis and comparison of PM synchronous motor and induction motor type magnetic bearings,” vol. 31, pp. 1047–1053, Sep./Oct. 1995.
- [24] M. Coates, A. Hero, R. Nowak, and B. Yu, “Internet tomography,” May 2002, to be published.
- [25] N. Kahale and R. Urbanke, “On the minimum distance of parallel and serially concatenated codes,” submitted for publication.
- [26] J. C. Candy and G. C. Temes, Eds., *Oversampling Delta-Sigma Data Converters Theory, Design and Simulation*. New York: IEEE Press., 1992.
- [27] S. M. Metev and V. P. Veiko, *Laser Assisted Microtechnology*, 2nd ed., R. M. Osgood, Jr., Ed. Berlin, Germany: Springer-Verlag, 1998.
- [28] J. Breckling, Ed., *The Analysis of Directional Time Series: Applications to Wind Speed and Direction*, ser. Lecture Notes in Statistics. Berlin, Germany: Springer, 1989, vol. 61.
- [29] H. E. Rose, *A Course in Number Theory*. New York, NY: Oxford Univ. Press, 1988, ch. 3.
- [30] B. K. Bul, *Theory Principles and Design of Magnetic Circuits*. Moscow: Energia Press, 1964, p. 464, (in Russian).
- [31] W. V. Sorin, “Optical reflectometry for component characterization,” in *Fiber Optic Test and Measurement*, D. Derickson, Ed. Englewood Cliffs, NJ: Prentice-Hall, 1998.
- [32] J. B. Anderson and K. Tepe, “Properties of the tailbiting BCJR decoder,” in *Codes, Systems and Graphical Models*, ser. IMA Volumes in Mathematics and Its Applications. New York: Springer-Verlag, 2000.
- [33] P. Hedelin, P. Knagenhjelm, and M. Skoglund, “Theory for transmission of vector quantization data,” in *Speech Coding and Synthesis*, W. B. Kleijn and K. K. Paliwal, Eds. Amsterdam, The Netherlands: Elsevier Science, 1995, ch. 10, pp. 347–396.
- [34] R. M. A. Dawson, Z. Shen, D. A. Furst, S. Connor, J. Hsu, M. G. Kane, R. G. Stewart, A. Ipri, C. N. King, P. J. Green, R. T. Flegal, S. Pearson, W. A. Barrow, E. Dickey, K. Ping, C. W. Tang, S. V. Slyke, F. Chen, J. Shi, J. C. Sturm, and M. H. Lu, “Design of an improved pixel for a polysilicon active-matrix organic LED display,” in *SID Tech. Dig.*, 1998, vol. 29, pp. 11–14.
- [35] *FLEXChip Signal Processor (MC68175/D)*, Motorola, 1996.
- [36] *FLEXChip Signal Processor, MC68175/D*, Motorola, 1996.
- [37] M. S. Yee and L. Hanzo, “Radial basis function decision feedback equaliser assisted burst-by-burst adaptive modulation,” in *Proc. IEEE Globecom ’99*, Rio de Janeiro, Brazil, Dec. 5–9, 1999, pp. 2183–2187.
- [38] M. Yajnik, S. B. Moon, J. Kurose, and D. Towsley, “Measurement and modeling of the temporal dependence in packet loss,” in *Proc. IEEE INFOCOM’99*, vol. 1, New York, NY, Mar. 1999, pp. 345–352.
- [39] M. Wegmuller, J. P. von der Weid, P. Oberson, and N. Gisin, “High resolution fiber distributed measurements with coherent OFDR,” in *Proc. ECOC’00*, 2000, paper 11.3.4, p. 109.

- [40] B. Mikkelsen, G. Raybon, R.-J. Essiambre, K. Dreyer, Y. Su., L. E. Nelson, J. E. Johnson, G. Shtengel, A. Bond, D. G. Moodie, and A. D. Ellis, "160 Gbit/s single-channel transmission over 300 km nonzero-dispersion fiber with semiconductor based transmitter and demultiplexer," in *Proc. ECOC'99*, 1999, postdeadline paper 2-3, pp. 28–29.
- [41] S. G. Finn, M. Médard, and R. A. Barry, "A novel approach to automatic protection switching using trees," presented at the Proc. Int. Conf. Commun., 1997.
- [42] N. C. Loh, "High-resolution micromachined interferometric accelerometer," Master's thesis, Massachusetts Institute of Technology, Cambridge, 1992.
- [43] A. Karnik, "Performance of TCP congestion control with rate feedback: TCP/ABR and rate adaptive TCP/IP," M. Eng. thesis, Indian Institute of Science, Bangalore, India, Jan. 1999.
- [44] Q. Li, "Delay characterization and performance control of wide-area networks," Ph.D. dissertation, Univ. of Delaware, Newark, May 2000. [Online]. Available: <http://www.ece.udel.edu/~qli>
- [45] R. Jain, K. K. Ramakrishnan, and D. M. Chiu, "Congestion avoidance in computer networks with a connectionless network layer," Digital Equipment Corporation, MA, Tech. Rep. DEC-TR-506, Aug. 1987.
- [46] J. Padhye, V. Firoiu, and D. Towsley, "A stochastic model of TCP Reno congestion avoidance and control," Univ. of Massachusetts, Amherst, MA, CMPSCI Tech. Rep. 99-02, 1999.
- [47] D. Middleton and A. D. Spaulding, "A tutorial review of elements of weak signal detection in non-Gaussian EMI environments," National Telecommunications and Information Administration (NTIA), U.S. Dept. of Commerce, NTIA Report 86-194, May 1986.
- [48] S. Kandala, "Changes to Annex D," IEEE 802.11 TGe, Tech. Rep. 02/680r0, Oct. 2002.
- [49] T. J. Ott and N. Aggarwal, "TCP over ATM: ABR or UBR," unpublished.
- [50] V. Jacobson. (1990, Apr.) Modified TCP congestion avoidance algorithm. end2end-interest mailing list. [Online]. Available: <ftp://ftp.isi.edu/end2end/end2end-interest-1990.mail>
- [51] V. Valloppillil and K. W. Ross. (1998) Cache array routing protocol v1.1. Internet draft. [Online]. Available: <http://ds1.internic.net/internet-drafts/draft-vinod-carp-v1-03.txt>
- [52] D. H. Lorenz and A. Orda. (1998, Jul.) Optimal partition of QoS requirements on unicast paths and multicast trees. Dept. Elect. Eng., Technion. Haifa, Israel. [Online]. Available: <ftp://ftp.technion.ac.il/pub/supported/ee/Network/lor.mopq98.ps>
- [53] R. E. Sorace, V. S. Reinhardt, and S. A. Vaughn, "High-speed digital-to-RF converter," U.S. Patent 5 668 842, Sep. 16, 1997.
- [54] U. Hideki, "Quadrature modulation circuit," Japanese Patent 152 932/92, May 20, 1992.
- [55] F. Kowalik and M. Isard, "Estimateur d'un défaut de fonctionnement d'un modulateur en quadrature et étage de modulation l'utilisant," French Patent Request 9 500 261, Jan. 11, 1995.
- [56] , *Special Issue on Wireless ATM*, vol. 3, Aug. 1996.
- [57] *Wireless LAN Medium Access Control (MAC) and Physical Layer (PHY) Specification*, IEEE Std. 802.11, 1997.
- [58] *Fiber Channel Physical Interface (FC-PI)*, NCITS Working Draft Proposed Standard, Rev. 5.2, 1999.
- [59] I. Widjaja and A. Elwalid, "MATE: MPLS adaptive traffic engineering," IETF Draft, 1999.
- [60] L. Roberts, "Enhanced proportional rate control algorithm PRCA," ATM Forum Contribution 94-0735R1, Aug. 1994.
- [61] "Advanced QoS services for the intelligent internet," White Paper, Cisco, May 1997.
- [62] "PDCA12-70 data sheet," Opto Speed SA, Mezzovico, Switzerland.
- [63] S. Konyagin, private communication, 1998.
- [64] K. K. Ramakrishnan and S. Floyd, "A proposal to add explicit congestion notification (ECN) to IP," RFC 2481, Jan. 1999.
- [65] *Saber Designer Reference Manual*, Analogy, Inc., Beaverton, OR, 1998, release 4.3.
- [66] Ucb/lbnl/vint network simulator—ns (version 2). [Online]. Available: <http://www-mash.cs.berkeley.edu/ns/>
- [67] "Messung von Störfeldern an Anlagen und Leitungen der Telekommunikation im Frequenzbereich 9 kHz bis 3 GHz," Meßvorschrift Reg TP MV 05, Regulierungsbehörde für Telekommunikation und Post (Reg TP).
- [68] Consultative Committee for Space Data Systems (CCSDS), "Telemetry channel coding," *Blue Book*, no. 4, 1999. [Online]. Available: <http://www.ccsds.org/documents/pdf/CCSDS-101.0-B-4.pdf>
- [69] —, *Telemetry Channel Coding*, ser. Blue Book. Newport Beach, CA: CCSDS, 1999, no. 4. [Online]. Available: <http://www.ccsds.org/documents/pdf/CCSDS-101.0-B-4.pdf>
- [70] *Telemetry Channel Coding*, ser. Blue Book, No. 4, Consultative Committee for Space Data Systems (CCSDS), Newport Beach, CA, 1999. [Online]. Available: <http://www.ccsds.org/documents/pdf/CCSDS-101.0-B-4.pdf>
- [71] *Telemetry Channel Coding*, ser. Blue Book, No. 4, Consultative Committee for Space Data Systems (CCSDS) Recommendation for Space Data System Standard 101.0-B-4, May 1999. [Online]. Available: <http://www.ccsds.org/documents/pdf/CCSDS-101.0-B-4.pdf>
- [72] S. M. Alamouti, "A simple transmit diversity technique for wireless communications," *IEEE J. Select Areas in Communications*, vol. 16, no. 8, pp. 1451–1458, Oct. 1998.
- [73] Special Committee 239 of the RTCA, "Assessment of C-band mobile telecommunications interference impact on low range radar altimeter operations," Oct 2020, RTCA Paper No. 274-20/PMC-2073. [Online]. Available: https://www.rtca.org/wpcontent/uploads/2020/10/SC-239-5G-Interference-Assessment-Report_274-20-PMC2073_accepted_changes.pdf
- [74] L. Yin and A. Sankin, "Dollars to megabits, you may be paying 400 times as much as your neighbor for internet service," *The Markup*, Oct. 2022. [Online]. Available: <https://themarkup.org/still-loading/2022/10/19/dollars-to-megabits-you-may-be-paying-400-times-as-much-as-your-neighbor-for-internet-service/>
- [75] J. D. O'Sullivan, G. R. Daniels, T. M. Percival, D. I. Ostry, and J. F. Deane, "Wireless LAN," Jan 1996, u.S. Patent 5,487,069.
- [76] D. Maas, M. H. Firooz, J. Zhang, N. Patwari, and S. K. Kasera, "Channel sounding for the masses: Low complexity GNU 802.11b channel impulse response estimation," *IEEE Transactions on Wireless Communications*, vol. 11, no. 1, pp. 1–8, 2012.
- [77] D. Halperin, W. Hu, A. Sheth, and D. Wetherall, "802.11 with multiple antennas for dummies," *ACM SIGCOMM*

- Computer Communication Review*, vol. 40, no. 1, pp. 19–25, 2010.
- [78] D. Halperin, B. Greenstein, A. Sheth, and D. Wetherall, “Demystifying 802.11n power consumption,” in *Proc. 2010 Intl. Conf. on Power-Aware Computing and Systems*, 2010.
- [79] J. G. Proakis and M. Salehi, *Communication systems engineering*, 2nd ed. Prentice Hall, 2002.
- [80] R. V. Hartley, “Transmission of information,” *The Bell System Technical Journal*, vol. 7, no. 3, pp. 535–563, 1928.
- [81] W. Shakespeare, *Romeo and Juliet*, 1597. [Online]. Available: http://shakespeare.mit.edu/romeo_juliet/full.html
- [82] J. Breen, A. Buffmire, J. Duerig, K. Dutt, E. Eide, M. Hibler, D. Johnson, S. K. Kasera, E. Lewis, D. M. A. Orange, N. Patwari, D. Reading, R. Ricci, D. Schurig, L. B. Stoller, J. Van der Merwe, K. Webb, and G. Wong, “Powder: Platform for open wireless data-driven experimental research,” in *Proc. 14th Intl. Workshop on Wireless Network Testbeds, Experimental Evaluation and Characterization (WiNTECH)*, Sep. 2020.
- [83] C. E. Shannon, “A mathematical theory of communication,” *The Bell System Technical Journal*, vol. 27, no. 3, pp. 379–423, 1948. [Online]. Available: <http://math.harvard.edu/~ctm/home/text/others/shannon/entropy/entropy.pdf>
- [84] A. Papoulis and S. U. Pillai, *Probability, random variables, and stochastic processes*. Tata McGraw-Hill Education, 2002.
- [85] T. S. Rappaport, *Wireless communications: principles and practice*. Cambridge University Press, 2024.
- [86] G. D. Durgin, T. S. Rappaport, and D. A. De Wolf, “New analytical models and probability density functions for fading in wireless communications,” *IEEE Transactions on Communications*, vol. 50, no. 6, pp. 1005–1015, 2002.
- [87] R. Malik, “Spread spectrum - secret military technology to 3G,” in *IEEE Conference on the History of Telecommunications*, 2001, pp. 1–5.
- [88] V. Tarokh, H. Jafarkhani, and A. R. Calderbank, “Space-time block codes from orthogonal designs,” *IEEE Transactions on Information Theory*, vol. 45, no. 5, pp. 1456–1467, 1999.
- [89] P. W. Wolniansky, G. J. Foschini, G. D. Golden, and R. A. Valenzuela, “V-BLAST: An architecture for realizing very high data rates over the rich-scattering wireless channel,” in *1998 URSI International Symposium on Signals, Systems, and Electronics*, 1998, pp. 295–300.
- [90] P. Lundrigan, N. Patwari, and S. K. Kasera, “On-off noise power communication,” in *Proc. of the ACM Intl. Conf. on Mobile Computing and Networking (MobiCom 2019)*, Oct. 2019, <https://span.engineering.wustl.edu/pub/lundrigan2019onoff.pdf>.
- [91] L. W. Couch, *Digital and Analog Communication Systems*, 7th ed. Pearson, 2007.
- [92] S. Kay, *Fundamentals of Statistical Signal Processing, Volume II: Detection Theory*, 1st ed. Pearson, 1998.
- [93] N. Patwari, A. O. Hero, M. Perkins, N. S. Correal, and R. J. O’Dea, “Relative location estimation in wireless sensor networks,” *IEEE Transactions on Signal Processing*, vol. 51, no. 8, pp. 2137–2148, 2003.
- [94] M. Rice, *Digital Communications: a Discrete-Time Approach*. Pearson Prentice Hall, 2009.
- [95] S. O. Haykin and M. Moher, *Modern Wireless Communications*, 1st ed. Pearson, 2005.
- [96] B. P. Lathi and Z. Ding, *Modern Digital and Analog Communication Systems*, 4th ed. Oxford University Press, 2008.
- [97] C. Chang and T. Pham, “DSN telecommunications link design handbook,” 2019. [Online]. Available: <http://deepspace.jpl.nasa.gov/dsndocs/810-005/>
- [98] S. Gordon, “Talking to Martians: Communications with Mars Curiosity rover,” 2012, web page. [Online]. Available: <https://sandilands.info/sgordon/communications-with-mars-curiosity>
- [99] D. Dobrijevic, “Distance to Mars: How far away is the red planet?” Feb 2022. [Online]. Available: <https://www.space.com/14729-spacekids-distance-earth-mars.html>
- [100] R. Ludwig and J. Taylor, *Voyager telecommunications*. John Wiley and Sons, Inc., 2016. [Online]. Available: https://voyager.gsfc.nasa.gov/Library/DeepCommo_Chapter3--141029.pdf
- [101] H. T. Friis, “A note on a simple transmission formula,” *Proceedings of the IRE*, vol. 34, no. 5, pp. 254–256, 1946.
- [102] H. Hashemi, “The indoor radio propagation channel,” *Proceedings of the IEEE*, vol. 81, no. 7, pp. 943–968, 1993.
- [103] adlughmin, “This 3d printed spirograph allows you to draw fascinating geometric designs,” <https://3dprint.com/79095/3d-printed-spirograph/>, July 2015.
- [104] L. Camhi, “Hedy Lamarr’s forgotten, frustrated career as a wartime inventor,” *The New Yorker*, 2017. [Online]. Available: <https://www.newyorker.com/tech/annals-of-technology/hedy-lamarrs-forgotten-frustrated-career-as-a-wartime-inventor>
- [105] G. Bianchi, “Performance analysis of the IEEE 802.11 distributed coordination function,” *IEEE Journal on Selected Areas in Communications*, vol. 18, no. 3, pp. 535–547, 2000.
- [106] H. Kopka and P. W. Daly, *Guide to L^AT_EX*. Pearson Education, 2003.
- [107] P. Pinies, J. D. Tardos, and J. Neira, “Localization of avalanche victims using robocentric slam,” in *2006 IEEE/RSJ International Conference on Intelligent Robots and Systems*, 2006, pp. 3074–3079.