Learning a Codebase

Derek Somerville

June 15, 2026

Contents

1 Glossary - Summary **3**

2 Repository Summary Table **4**

3 Sample scatter touched against commit - **6**

4 Total commits by developer - Developer Commits **8**

5 Histogram components touched by developer - For components with total **10**
5.1 Time series components touched - For packages touched for first five commits 19
5.2 Time series components touched - For packages touched for first ten commits 24
5.3 Time series components touched - For packages touched for first twenty commits 29
5.4 Time series components touched - For packages touched for commit 33
5.5 Time series components touched - For packages touched for each week commit 38

6 Normality and homoscedasticity - For all components touched for all commits **43**

7 Statistical significance test - For all components touched for all commits **46**

8 Generated standard anova - For all components touched for all commits **51**
8.1 Generated standard anova - For all components touched for a all commits excluding tranient 52

9 Tukey hsd - For all components touched for all commits **54**

10 Strategy logistic regression - For all components touched for all commits **58**

11 Repository **61**
11.1 Repository: 14 61
11.1.1 Time series sustained components touched by developer - 14 For developer commits and components touched. 61
11.1.2 Time series sustained components touched by developer - 14 For developer day and components touched. 64
11.2 Repository: 21 66
11.2.1 Time series sustained components touched by developer - 21 For developer commits and components touched. 66
11.2.2 Time series sustained components touched by developer - 21 For developer day and components touched. 69

1 Glossary - Summary


- The founder developer starts in the first six months of a project.
- Later joiner developers start after six months.
- Transient developers have less than nine (9) commits.
- Moderate developers have more than nine (9) commits but fewer than 50 commits or commits for less than 250 days.
- Sustained developers make 50 or more commits and commit for 250 days or more.

2 Repository Summary Table

Table 1: Summary of thirty-nine open-source repositories identified from GitHub zero or more sustained late joiner developers. Sustained later joiner developers who joined the project after six months and contributed at least 50 commits over a period of 250 days or more. Please note that five developers each worked on two repositories.


ID	Repo Name	Transient Founder	Moderate Founder	Sustained Founder	Transient Later Joiner	Moderate Later Joiner	Sustained Later Joiner	Commit	Start	End
1	acs-aem-commons	3	0	0	189	0	0	1191	17-07-2013	Ongoing
2	acs-packaging	1	0	0	52	0	0	115	10-10-2014	23-11-2023
3	activiti	6	7	6	210	22	5	9836	18-06-2010	Ongoing
4	aem-core-wcm-components	1	0	0	100	0	0	366	06-01-2016	Ongoing
5	airbyte-platform	16	2	1	454	35	6	7002	04-08-2020	27-09-2023
6	alluxio	2	0	0	11	0	0	318	10-02-2013	01-12-2013
7	ambari	0	3	0	127	34	15	4357	22-09-2011	Ongoing
8	antlr4	3	0	0	293	0	0	3847	05-09-2011	Ongoing
9	refactoring-toy-example	1	0	0	0	0	0	60	20-10-2014	10-06-2015
10	automq	4	0	0	300	11	3	1889	10-08-2011	21-04-2017
11	avro	1	0	0	333	0	0	3339	15-04-2009	Ongoing
12	azure-sdk-for-java	8	0	0	11	0	0	1147	13-10-2011	08-01-2014
13	beam	57	0	0	38	0	0	6561	11-07-2014	20-05-2016
14	buck	17	6	6	524	92	21	15889	21-03-2013	05-05-2022
15	camel	1	4	1	1133	76	13	37463	19-03-2007	Ongoing
16	camel-spring-boot	0	0	0	5	0	0	9401	13-01-2020	Ongoing
17	cas	2	0	0	305	0	0	46401	01-11-2010	Ongoing
18	checkstyle	0	0	1	359	45	9	17497	22-06-2001	Ongoing
19	commons-lang	4	0	0	202	0	0	3389	19-07-2002	Ongoing
20	cxf	6	6	3	201	17	3	8781	29-04-2008	Ongoing
21	intellij-community	0	3	7	334	103	84	104964	11-11-2004	18-04-2018
22	assertj	5	0	0	39	0	0	431	07-09-2010	09-04-2014
23	calcite	2	0	0	13	0	0	6211	20-04-2012	24-02-2014
24	dolphinscheduler	15	0	0	464	0	0	13029	29-03-2019	Ongoing
25	dubbo	4	0	0	176	0	0	4180	20-10-2011	07-04-2019
26	guava	0	1	0	400	10	3	9708	15-09-2009	Ongoing
27	hibernate-orm	4	0	0	15	0	0	531	29-06-2007	07-07-2010
28	jenkins	5	1	1	831	45	4	31546	05-11-2006	Ongoing
29	keycloak	3	0	0	1186	0	0	22954	02-07-2013	Ongoing
30	kubernetes-client	7	0	0	290	0	0	23224	09-07-2015	Ongoing
31	minecraftforge	2	0	0	493	0	0	20436	14-07-2011	Ongoing
32	openapi-generator	2	0	0	2646	0	0	30837	19-07-2011	Ongoing
33	openmrs-core	0	1	0	385	29	3	15769	03-05-2006	Ongoing
34	opensearch	1	0	0	0	0	0	1872	08-02-2010	25-08-2010
35	plugin-hub	18	0	0	347	0	0	8395	20-12-2019	Ongoing
36	presto	0	1	3	685	78	18	31858	09-08-2012	Ongoing
37	quarkus	2	3	5	820	29	8	82652	14-06-2018	Ongoing
38	runelite	0	0	0	673	0	0	60188	01-12-2014	Ongoing
39	selenium	5	3	0	709	20	8	23522	03-11-2004	Ongoing
	Total	208	41	34	15353	646	203	671156		

3 Sample scatter touched against commit -



(a) Packages


(b) Classes




(c) Methods

Figure 1: Scatter plots of the log total number of components touched (y-axis) against the number of commits (x-axis) made by samples of developers capped at 203 sustained later joiners from six (6) categories: Transient Founder (Blue, 203), Moderate Founder (Purple, 41), Sustained Founder (Green, 34), Transient Later Joiner (Orange, 203), Moderate Later Joiner (Cyan, 203), Sustained Later Joiner (Red, 203).


4 Total commits by developer - Developer Commits




(a) Transient founder (n=208, max=83.7).




(b) Transient later joiner (n=15309, max=86.1).




(c) Moderate founder (n=41, max=14.6).



(d) Moderate later joiner (n=646, max=17.8).




(e) Sustained founder (n=34, max=5.9).



(f) Sustained later joiner (n=203, max=7.4).

Figure 2: Histogram of percentage of developers (y-axis) against total commits made (x-axis) in six (6) categories. This is from 39 repositories sampled from GitHub.


5 Histogram components touched by developer - For components with total




(a) By Day (max=77.3).

(b) By Commit (max=82.3).


Figure 3: Histogram of percentage of all developers (y-axis) against the average packages touched by day and commit (x-axis) from all 16412 developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=84.6).




(b) Transient later joiner (n=15309, max=81.7).




(c) Moderate founder (n=41, max=63.4).



(d) Moderate later joiner (n=646, max=70.3).




(e) Sustained founder (n=34, max=55.9).




(f) Sustained later joiner (n=203, max=59.1).


Figure 4: Histogram of percentage of developers (y-axis) against the average packages touched by day (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=88.0).




(b) Transient later joiner (n=15309, max=85.1).




(c) Moderate founder (n=41, max=14.6).



(d) Moderate later joiner (n=646, max=9.3).




(e) Sustained founder (n=34, max=47.1).



(f) Sustained later joiner (n=203, max=25.6).


Figure 5: Histogram of percentage of developers (y-axis) against the average packages touched by commit (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.




(a) By Day (max=85.3).

(b) By Commit (max=85.4).


Figure 6: Histogram of percentage of all developers (y-axis) against the average classes touched by day and commit (x-axis) from all 16412 developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=98.1).




(b) Transient later joiner (n=15309, max=97.8).




(c) Moderate founder (n=41, max=80.5).



(d) Moderate later joiner (n=646, max=95.5).




(e) Sustained founder (n=34, max=55.9).




(f) Sustained later joiner (n=203, max=87.7).


Figure 7: Histogram of percentage of developers (y-axis) against the average classes touched by day (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=93.7).




(b) Transient later joiner (n=15309, max=93.8).




(c) Moderate founder (n=41, max=31.7).



(d) Moderate later joiner (n=646, max=36.5).




(e) Sustained founder (n=34, max=52.9).



(f) Sustained later joiner (n=203, max=42.4).


Figure 8: Histogram of percentage of developers (y-axis) against the average classes touched by commit (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.




(a) By Day (max=86.2).

(b) By Commit (max=82.2).


Figure 9: Histogram of percentage of all developers (y-axis) against the average methods touched by day and commit (x-axis) from all 16412 developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=98.6).




(b) Transient later joiner (n=15309, max=99.0).




(c) Moderate founder (n=41, max=63.4).



(d) Moderate later joiner (n=646, max=92.0).




(e) Sustained founder (n=34, max=38.2).




(f) Sustained later joiner (n=203, max=69.5).


Figure 10: Histogram of percentage of developers (y-axis) against the average methods touched by day (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.




(a) Transient founder (n=208, max=97.1).




(b) Transient later joiner (n=15309, max=96.8).




(c) Moderate founder (n=41, max=22.0).



(d) Moderate later joiner (n=646, max=26.5).




(e) Sustained founder (n=34, max=41.2).




(f) Sustained later joiner (n=203, max=37.4).

Figure 11: Histogram of percentage of developers (y-axis) against the average methods touched by commit (x-axis) from six (6) categories of developers from 39 repositories sampled from GitHub.


5.1 Time series components touched - For packages touched for first five commits




(a) Packages for All founders (n=84, μ=5.02, median=3.0 & std=3.57)




(b) Packages for All joiners (n=1277, μ=6.09, median=3.0 & std=4.66)




(c) Classes for All founders (n=84, μ=36.31, median=7.0 & std=51.51)



(d) Classes for All joiners (n=1277, μ=22.77, median=6.0 & std=28.25)




(e) Methods for All founders (n=84, μ=151.17, median=18.5 & std=294.09)




(f) Methods for All joiners (n=1277, μ=80.35, median=12.0 & std=138.17)


Figure 12: A time series for the five (5) commits, excluding transient, with the average mean (blue line), all components touched (y-axis) against the number of commits (x-axis) for six (6) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Transient founder (n=9, μ=4.56, median=3.0 & std=1.99)




(b) Transient later joiner (n=429, μ=5.62, median=3.0 & std=3.96)




(c) Moderate founder (n=41, μ=5.37, median=3.0 & std=4.31)



(d) Moderate later joiner (n=646, μ=6.4, median=3.0 & std=4.82)




(e) Sustained founder (n=34, μ=4.74, median=2.0 & std=2.79)




(f) Sustained later joiner (n=203, μ=6.13, median=3.0 & std=5.36)


Figure 13: A time series for the five (5) commits, excluding transient, with the average mean (blue line), packages touched (y-axis) against the number of commits (x-axis) for six (6) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Transient founder (n=9, μ=16.22, median=6.0 & std=9.9)




(b) Transient later joiner (n=429, μ=19.05, median=5.0 & std=19.33)




(c) Moderate founder (n=41, μ=40.71, median=9.0 & std=48.68)



(d) Moderate later joiner (n=646, μ=22.96, median=6.0 & std=21.93)




(e) Sustained founder (n=34, μ=36.32, median=7.0 & std=60.21)




(f) Sustained later joiner (n=203, μ=30.01, median=6.0 & std=51.67)


Figure 14: A time series for the five (5) commits, excluding transient, with the average mean (blue line), classes touched (y-axis) against the number of commits (x-axis) for six (6) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Transient founder (n=9, μ=51.0, median=16.0 & std=30.34)




(b) Transient later joiner (n=429, μ=63.11, median=10.0 & std=79.44)




(c) Moderate founder (n=41, μ=183.63, median=23.0 & std=308.64)



(d) Moderate later joiner (n=646, μ=80.93, median=14.5 & std=100.84)




(e) Sustained founder (n=34, μ=138.53, median=15.0 & std=311.7)




(f) Sustained later joiner (n=203, μ=114.77, median=13.0 & std=271.55)

Figure 15: A time series for the five (5) commits, excluding transient, with the average mean (blue line), methods touched (y-axis) against the number of commits (x-axis) for six (6) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.


5.2 Time series components touched - For packages touched for first ten commits




(a) Packages for All founders (n=75, μ=7.39, median=4.0 & std=5.2)




(b) Packages for All joiners (n=849, μ=9.4, median=5.0 & std=6.27)




(c) Classes for All founders (n=75, μ=64.4, median=17.0 & std=70.95)



(d) Classes for All joiners (n=849, μ=43.67, median=14.0 & std=40.97)




(e) Methods for All founders (n=75, μ=261.01, median=46.0 & std=414.75)




(f) Methods for All joiners (n=849, μ=155.65, median=37.0 & std=199.82)


Figure 16: A time series for the ten (10) commits, excluding transient, with the average mean (blue line), all components touched (y-axis) against the number of commits (x-axis) for four (4) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Moderate founder (n=41, μ=8.02, median=4.0 & std=5.85)



(b) Moderate later joiner (n=646, μ=9.64, median=5.0 & std=6.16)




(c) Sustained founder (n=34, μ=6.62, median=3.0 & std=4.25)




(d) Sustained later joiner (n=203, μ=8.65, median=4.0 & std=6.6)


Figure 17: A time series for the ten (10) commits, excluding transient, with the average mean (blue line), packages touched (y-axis) against the number of commits (x-axis) for four (4) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Moderate founder (n=41, μ=60.93, median=19.0 & std=69.12)



(b) Moderate later joiner (n=646, μ=42.32, median=14.0 & std=31.27)




(c) Sustained founder (n=34, μ=68.59, median=15.0 & std=73.09)




(d) Sustained later joiner (n=203, μ=47.98, median=13.0 & std=62.35)


Figure 18: A time series for the ten (10) commits, excluding transient, with the average mean (blue line), classes touched (y-axis) against the number of commits (x-axis) for four (4) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Moderate founder (n=41, μ=267.12, median=59.0 & std=460.61)



(b) Moderate later joiner (n=646, μ=147.78, median=38.0 & std=146.66)




(c) Sustained founder (n=34, μ=253.65, median=42.5 & std=351.3)



(d) Sustained later joiner (n=203, μ=180.7, median=34.0 & std=313.08)

Figure 19: A time series for the ten (10) commits, excluding transient, with the average mean (blue line), methods touched (y-axis) against the number of commits (x-axis) for four (4) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.


5.3 Time series components touched - For packages touched for first twenty commits



(a) Sustained founder (n=34, μ=9.32, median=4.0 & std=6.14)

(b) Sustained later joiner (n=203, μ=13.06, median=6.0 & std=9.14)


Figure 20: A time series for the twenty (20) commits, sustained developers, with the average mean (blue line), packages touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=107.5, median=30.0 & std=91.26)

(b) Sustained later joiner (n=203, μ=81.91, median=27.0 & std=72.01)

Figure 21: A time series for the twenty (20) commits, sustained developers, with the average mean (blue line), classes touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Sustained founder (n=34, μ=401.24, median=85.5 & std=426.09)


(b) Sustained later joiner (n=203, μ=295.1, median=79.0 & std=349.63)

Figure 22: A time series for the twenty (20) commits, sustained developers, with the average mean (blue line), methods touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.


5.4 Time series components touched - For packages touched for commit




(a) Packages for All founders (n=34, μ=36.62, median=18.0 & std=28.13)




(b) Packages for All joiners (n=203, μ=37.08, median=22.0 & std=36.82)




(c) Classes for All founders (n=34, μ=746.59, median=426.0 & std=403.07)



(d) Classes for All joiners (n=203, μ=442.33, median=239.0 & std=426.23)




(e) Methods for All founders (n=34, μ=3095.18, median=1645.5 & std=2043.47)



(f) Methods for All joiners (n=203, μ=1672.84, median=838.0 & std=1909.9)


Figure 23: A time series for the all commits, excluding transient, with the average mean (blue line), all components touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=36.62, median=18.0 & std=28.13)

(b) Sustained later joiner (n=203, μ=37.08, median=22.0 & std=36.82)


Figure 24: A time series for the all commits, excluding transient, with the average mean (blue line), packages touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=746.59, median=426.0 & std=403.07)

(b) Sustained later joiner (n=203, μ=442.33, median=239.0 & std=426.23)

Figure 25: A time series for the all commits, excluding transient, with the average mean (blue line), classes touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.




(a) Sustained founder (n=34, μ=3095.18, median=1645.5 & std=2043.47)


(b) Sustained later joiner (n=203, μ=1672.84, median=838.0 & std=1909.9)

Figure 26: A time series for the all commits, excluding transient, with the average mean (blue line), methods touched (y-axis) against the number of commits (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.


5.5 Time series components touched - For packages touched for each week commit




(a) Packages for All founders (n=34, μ=35.38, median=14.0 & std=23.11)




(b) Packages for All joiners (n=203, μ=35.84, median=13.0 & std=33.4)




(c) Classes for All founders (n=34, μ=746.15, median=321.28 & std=515.17)



(d) Classes for All joiners (n=203, μ=408.05, median=125.0 & std=440.63)




(e) Methods for All founders (n=34, μ=3129.0, median=1296.71 & std=2539.1)



(f) Methods for All joiners (n=203, μ=1545.61, median=435.2 & std=1709.56)


Figure 27: A time series for the all commits, excluding transient, with the average mean (blue line), all components touched (y-axis) against the number of week (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=35.38, median=14.0 & std=23.11)

(b) Sustained later joiner (n=203, μ=35.84, median=13.0 & std=33.4)


Figure 28: A time series for the all commits, excluding transient, with the average mean (blue line), packages touched (y-axis) against the number of week (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=746.15, median=321.28 & std=515.17)

(b) Sustained later joiner (n=203, μ=408.05, median=125.0 & std=440.63)

Figure 29: A time series for the all commits, excluding transient, with the average mean (blue line), classes touched (y-axis) against the number of week (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.



(a) Sustained founder (n=34, μ=3129.0, median=1296.71 & std=2539.1)

(b) Sustained later joiner (n=203, μ=1545.61, median=435.2 & std=1709.56)

Figure 30: A time series for the all commits, excluding transient, with the average mean (blue line), methods touched (y-axis) against the number of week (x-axis) for two (2) developer categories. Green is the standard deviation above the mean, and pink is the standard deviation below the mean.

6 Normality and homoscedasticity - For all components touched for all commits

Certain statistical methods require normality of each sample or the equality of variance. A Shapiro-Wilk Test evaluates whether a sample distribution significantly differs from the normal distribution. A Levene's test evaluates if the independent samples have equal variance.

Table 2: Diagnostic P-Value Thresholds Required for Statistical Method Selection

Statistical Method	**Shapiro-Wilk A (P)**	**Shapiro-Wilk B (P)**	**Levene's Test (P)**
Student's t-test	≥ 0.05 (Normal)	≥ 0.05 (Normal)	≥ 0.05 (Equal Variance)
Standard ANOVA	≥ 0.05 (Normal)	≥ 0.05 (Normal)	≥ 0.05 (Equal Variance)
Welch's t-test	≥ 0.05 (Normal)	≥ 0.05 (Normal)	< 0.05 (Unequal Variance)
Mann-Whitney U test	< 0.05 (Skewed)	< 0.05 (Skewed)	≥ 0.05 (Equal Variance)
Brunner-Münzel test	< 0.05 (Skewed)	< 0.05 (Skewed)	< 0.05 (Unequal Variance)
ART Anova test	< 0.05 (Skewed)	< 0.05 (Skewed)	< 0.05 (Unequal Variance)

Columns below:

- **Component** - Packages, classes or methods touched.
- **First *n* commits** - A sample of the first x number of commits for developers.
- **Contributor Category** Transient, Moderate or Sustained. "vs." equals versus.
- **Sample A** μ - The mean average of the first sample A.
- **Sample A NUmber** - The number of developers the first sample A.
- **Sample B** μ - The mean average of the second sample B.
- **Sample B Number** - The number of developers the first sample B.
- **Percentage Difference in** μ - The percentage difference in means between samples.
- **Sample A Normality** P - Shapiro normality P value of sample A.
- **Sample B Normality** P - Shapiro normality P value of sample B.
- **Variance Equality** P - The Levene variance equality p-value between sample A and B.
- **Statistical Model** - A recommended statistical model of Welch t test; Mann-Whitney; Brunner Münzel
- **Model** P - The P value of the recommended test Welch t test; Mann-Whitney; Brunner Münzel

Table 3: A Shapiro-Wilk test of different categories of founder versus different categories of late joiner sample normality and a Levene's variance test between samples

Component	First n commits	Contributory Category	Founder		Joiner		Percentage Difference in μ	Founder Normality P	Joiner Normality P	Variance Equality P	Statistical Models	Model P
			μ	number	μ	number						
Packages	1	All	1.52	283	1.22	16158	80.56	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Packages	1	Moderate	2.59	41	2.59	646	100.35	<0.001	<0.001	0.8110	Mann-Whitney	0.7564
Packages	1	Sustained	2.21	34	2.40	203	108.98	<0.001	<0.001	0.6501	Mann-Whitney	0.8805
Packages	5	Transient with five or more; moderate & sustained	22.65	84	15.94	1278	70.35	<0.001	<0.001	0.0318	Brunner-Münzel	0.0054
Packages	5	Moderate	15.00	41	15.54	646	103.58	<0.001	<0.001	0.9528	Mann-Whitney	0.6067
Packages	5	Sustained	36.62	34	37.08	203	101.26	<0.001	<0.001	0.9187	Mann-Whitney	0.9397
Packages	10	Moderate & sustained	7.39	75	9.40	849	127.28	<0.001	<0.001	0.3972	Mann-Whitney	0.0031
Packages	10	Moderate	8.02	41	9.64	646	120.11	<0.001	<0.001	0.7772	Mann-Whitney	0.0394
Packages	10	Sustained	6.62	34	8.65	203	130.71	<0.001	<0.001	0.4753	Mann-Whitney	0.1076
Packages	20	Sustained	9.32	34	13.06	203	140.12	<0.001	<0.001	0.3136	Mann-Whitney	0.0435
Classes	1	All	2.74	283	1.27	16158	46.38	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	1	Moderate	7.88	41	2.95	646	37.41	<0.001	<0.001	<0.001	Brunner-Münzel	0.4372
Classes	1	Sustained	3.44	34	5.49	203	159.47	<0.001	<0.001	0.7146	Mann-Whitney	0.1429
Classes	5	Transient with five or more; moderate & sustained	374.23	84	120.59	1278	32.22	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	5	Moderate	143.59	41	82.88	646	57.72	<0.001	<0.001	<0.001	Brunner-Münzel	0.0324
Classes	5	Sustained	746.59	34	442.33	203	59.25	0.0035	<0.001	0.1161	Mann-Whitney	0.0001
Classes	10	Moderate & sustained	64.40	75	43.67	849	67.82	<0.001	<0.001	0.0012	Brunner-Münzel	0.0798
Classes	10	Moderate	60.93	41	42.32	646	69.46	<0.001	<0.001	0.0092	Brunner-Münzel	0.1571
Classes	10	Sustained	68.59	34	47.98	203	69.95	<0.001	<0.001	0.1446	Mann-Whitney	0.2478
Classes	20	Sustained	107.50	34	81.91	203	76.20	<0.001	<0.001	0.0906	Mann-Whitney	0.2857
Methods	1	All	6.86	283	2.00	16158	29.14	<0.001	<0.001	0.0046	Brunner-Münzel	0.0000
Methods	1	Moderate	24.27	41	7.92	646	32.65	<0.001	<0.001	0.0026	Brunner-Münzel	0.5050
Methods	1	Sustained	10.59	34	24.08	203	227.41	<0.001	<0.001	0.7393	Mann-Whitney	0.2351
Methods	5	Transient with five or more; moderate & sustained	1554.73	84	443.83	1278	28.55	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Methods	5	Moderate	605.73	41	297.26	646	49.07	<0.001	<0.001	<0.001	Brunner-Münzel	0.0061
Methods	5	Sustained	3095.18	34	1672.84	203	54.05	<0.001	<0.001	0.0871	Mann-Whitney	0.0000
Methods	10	Moderate & sustained	261.01	75	155.65	849	59.63	<0.001	<0.001	0.0020	Brunner-Münzel	0.0597
Methods	10	Moderate	267.12	41	147.78	646	55.32	<0.001	<0.001	0.0023	Brunner-Münzel	0.1446
Methods	10	Sustained	253.65	34	180.70	203	71.24	<0.001	<0.001	0.3267	Mann-Whitney	0.2291
Methods	20	Sustained	401.24	34	295.10	203	73.55	<0.001	<0.001	0.1120	Mann-Whitney	0.5131

Table 4: A Shapiro-Wilk test of sample A category versus sample B category sample normality and a Levene's variance test between samples

Component	First n commits	Contributory Category	Sample		Sample		Percentage Difference in μ	Sample		Variance Equality P	Statistical Models	Model P
			A μ	A number	B μ	B number		A Normality P	B Normality P			
Packages	1	Transient vs. moderate	1.15	15517	2.59	687	225.92	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Packages	1	Transient vs. sustained	1.15	15517	2.38	237	206.90	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Packages	1	Transient vs. moderate & sustained	1.15	15517	2.54	924	221.04	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Packages	1	Moderate vs. sustained	2.59	687	2.38	237	91.58	<0.001	<0.001	0.5986	Mann-Whitney	0.1002
Packages	5	Moderate vs. sustained	15.51	687	37.01	237	238.71	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Packages	10	Moderate vs. sustained	9.54	687	8.36	237	87.60	<0.001	<0.001	0.4602	Mann-Whitney	0.0010
Classes	1	Transient vs. moderate	1.15	15517	3.24	687	281.94	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	1	Transient vs. sustained	1.15	15517	5.19	237	451.75	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	1	Transient vs. moderate & sustained	1.15	15517	3.74	924	325.49	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	1	Moderate vs. sustained	3.24	687	5.19	237	160.23	<0.001	<0.001	0.1255	Mann-Whitney	0.2576
Classes	5	Moderate vs. sustained	86.51	687	485.98	237	561.79	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Classes	10	Moderate vs. sustained	43.43	687	50.94	237	117.28	<0.001	<0.001	0.0223	Brunner-Münzel	0.6723
Methods	1	Transient vs. moderate	1.47	15517	8.90	687	603.74	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Methods	1	Transient vs. sustained	1.47	15517	22.14	237	1502.21	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Methods	1	Transient vs. moderate & sustained	1.47	15517	12.30	924	834.19	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Methods	1	Moderate vs. sustained	8.90	687	22.14	237	248.82	<0.001	<0.001	0.1237	Mann-Whitney	0.1344
Methods	5	Moderate vs. sustained	315.67	687	1876.89	237	594.58	<0.001	<0.001	<0.001	Brunner-Münzel	0.0000
Methods	10	Moderate vs. sustained	154.90	687	191.16	237	123.41	<0.001	<0.001	0.0503	Mann-Whitney	0.9692

7 Statistical significance test - For all components touched for all commits

A Welch t-test was employed to determine if the mean contributions of Group A differ significantly from Group B. This test is appropriate for continuous data and is robust to unequal variances.

Complementarily, the Mann-Whitney U (MWU) test was used to assess stochastic dominance by ranking data points. This non-parametric approach does not require a normal distribution and is highly resistant to outliers.

The Brunner-Münzel test was employed as a robust non-parametric method to determine if the relative treatment effects of Group A differ significantly from Group B. This test is highly appropriate for skewed count data and is completely robust to unequal variances and large group size imbalances. Complementarily, Cliff's δ and the Probability of Superiority (PS) are provided as robust non-parametric effect sizes to quantify the directional dominance magnitude between the samples.

Columns below:

- **Component** - Packages, classes or method touched.
- **First *n* commits** - A sample of the first x number of commits for developers.
- **Contributor Category** Transient, Moderate or Sustained. "vs." equals versus.
- **Sample A** μ - The mean average of the first sample A. In brackets the number of developers for sample A.
- **Sample B** μ - The mean average of the second sample B. In brackets the number of developers for sample b.
- **Welch Statistic** - This is the magnitude of the change, greater than 2.0 generally indicates a significant change.
- **Welch** P - A significance test of the difference between sample A and sample B. A $p < 0.05$ indicates a significant difference between samples.
- **MWU** P - The Mann-Whitney p-value. A significance test of the difference between sample A and sample B. A $p < 0.05$ indicates a significant difference between samples.
- **BM** P - The Brunner-Münzel asymptotic p-value. A $p < 0.05$ indicates a significant difference in relative effects.
- **Brunner-Münzel W** - The robust test statistic. Large absolute values indicate a significant structural shift.
- **Cliff's** δ - Non-parametric effect size bound between -1 and +1, evaluating directional dominance.
- **Prob. of Superiority (PS)** - The empirical probability (0 to 1) that a randomly selected developer from Sample A outranked a developer from Sample B.

Table 5: Statistical significance tests of different categories of founder versus different categories of late joiner touches of different granularities of component (package, class, method) after 1, 5, 10 and 20 commits for contributors. The significance has been calculated for the following statistical tests: Welch t-test, Mann-Whitney and Brunner Münzel.

Component	First n commits	Contributory Category	Founder		Joiner		Percentage Difference in μ	Welch		MWU P	BM P	Brunner-Münzel W	Cliff's δ	Prob. Sup. (PS)
			μ	Number	μ	Number		Statistic	P					
Packages	1	All	1.52	283	1.22	16158	80.56	3.59	0.0004	0.0000	0.0000	-5.11	0.127	0.564
Packages	1	Moderate	2.59	41	2.59	646	100.35	-0.02	0.9817	0.7564	0.7537	-0.32	0.028	0.514
Packages	1	Sustained	2.21	34	2.40	203	108.98	-0.55	0.5833	0.8805	0.8804	0.15	-0.015	0.492
Packages	5	Transient with five or more; moderate & sustained	22.65	84	15.94	1278	70.35	2.33	0.0219	0.0041	0.0054	-2.85	0.187	0.593
Packages	5	Moderate	15.00	41	15.54	646	103.58	-0.24	0.8080	0.6067	0.6227	0.50	-0.048	0.476
Packages	5	Sustained	36.62	34	37.08	203	101.26	-0.07	0.9420	0.9397	0.9395	-0.08	0.008	0.504
Packages	10	Moderate & sustained	7.39	75	9.40	849	127.28	-2.42	0.0177	0.0031	0.0046	2.91	-0.206	0.397
Packages	10	Moderate	8.02	41	9.64	646	120.11	-1.29	0.2053	0.0394	0.0504	2.01	-0.191	0.404
Packages	10	Sustained	6.62	34	8.65	203	130.71	-1.85	0.0694	0.1076	0.1319	1.54	-0.172	0.414
Packages	20	Sustained	9.32	34	13.06	203	140.12	-2.31	0.0243	0.0435	0.0572	1.96	-0.216	0.392
Classes	1	All	2.74	283	1.27	16158	46.38	2.61	0.0095	0.0000	0.0000	-5.06	0.107	0.553
Classes	1	Moderate	7.88	41	2.95	646	37.41	1.43	0.1605	0.3900	0.4372	-0.78	0.063	0.531
Classes	1	Sustained	3.44	34	5.49	203	159.47	-0.80	0.4241	0.1429	0.1814	-1.36	0.117	0.559
Classes	5	Transient with five or more; moderate & sustained	374.23	84	120.59	1278	32.22	4.70	0.0000	0.0000	0.0000	-6.46	0.416	0.708
Classes	5	Moderate	143.59	41	82.88	646	57.72	1.97	0.0557	0.0180	0.0324	-2.21	0.220	0.610
Classes	5	Sustained	746.59	34	442.33	203	59.25	2.95	0.0051	0.0001	0.0001	-4.36	0.434	0.717
Classes	10	Moderate & sustained	64.40	75	43.67	849	67.82	2.04	0.0446	0.0557	0.0798	-1.77	0.133	0.567
Classes	10	Moderate	60.93	41	42.32	646	69.46	1.36	0.1807	0.1158	0.1571	-1.44	0.146	0.573
Classes	10	Sustained	68.59	34	47.98	203	69.95	1.30	0.2003	0.2478	0.2786	-1.10	0.124	0.562
Classes	20	Sustained	107.50	34	81.91	203	76.20	1.34	0.1863	0.2857	0.3224	-1.00	0.115	0.557
Methods	1	All	6.86	283	2.00	16158	29.14	2.35	0.0194	0.0000	0.0000	-5.28	0.116	0.558
Methods	1	Moderate	24.27	41	7.92	646	32.65	1.30	0.2026	0.4647	0.5050	-0.67	0.056	0.528
Methods	1	Sustained	10.59	34	24.08	203	227.41	-0.78	0.4382	0.2351	0.2715	-1.11	0.098	0.549
Methods	5	Transient with five or more; moderate & sustained	1554.73	84	443.83	1278	28.55	4.45	0.0000	0.0000	0.0000	-7.01	0.442	0.721
Methods	5	Moderate	605.73	41	297.26	646	49.07	2.01	0.0511	0.0027	0.0061	-2.88	0.279	0.640
Methods	5	Sustained	3095.18	34	1672.84	203	54.05	2.86	0.0067	0.0000	0.0000	-4.69	0.458	0.729
Methods	10	Moderate & sustained	261.01	75	155.65	849	59.63	1.73	0.0884	0.0384	0.0597	-1.91	0.144	0.572
Methods	10	Moderate	267.12	41	147.78	646	55.32	1.24	0.2205	0.1041	0.1446	-1.49	0.151	0.576
Methods	10	Sustained	253.65	34	180.70	203	71.24	1.00	0.3240	0.2291	0.2666	-1.13	0.129	0.565
Methods	20	Sustained	401.24	34	295.10	203	73.55	1.16	0.2533	0.5131	0.5561	-0.59	0.070	0.535

Table 6: Statistical significance tests of sample A category versus sample B category touches of different granularities of component (package, class, method) after 1, 5 and 10 commits for contributors. The significance has been calculated for the following statistical tests: Welch t-test, Mann-Whitney and Brunner Münzel.

Component	First n commits	Contributory Category	Sample A μ	Sample A Number	Sample B μ	Sample B Number	Percentage Difference in μ	Welch Statistic	Welch P	MWU P	BM P	Brunner-Münzel W	Cliff's δ	Prob. Sup. (PS)
Packages	1	Transient vs. moderate	1.15	15517	2.59	687	225.92	-12.35	0.0000	0.0000	0.0000	27.60	-0.526	0.237
Packages	1	Transient vs. sustained	1.15	15517	2.38	237	206.90	-7.23	0.0000	0.0000	0.0000	14.29	-0.468	0.266
Packages	1	Transient vs. moderate & sustained	1.15	15517	2.54	924	221.04	-14.27	0.0000	0.0000	0.0000	30.91	-0.511	0.244
Packages	1	Moderate vs. sustained	2.59	687	2.38	237	91.58	1.06	0.2896	0.1002	0.0995	-1.65	0.068	0.534
Packages	5	Moderate vs. sustained	15.51	687	37.01	237	238.71	-8.40	0.0000	0.0000	0.0000	11.65	-0.463	0.268
Packages	10	Moderate vs. sustained	9.54	687	8.36	237	87.60	2.06	0.0397	0.0010	0.0012	-3.27	0.142	0.571
Classes	1	Transient vs. moderate	1.15	15517	3.24	687	281.94	-6.44	0.0000	0.0000	0.0000	14.31	-0.245	0.378
Classes	1	Transient vs. sustained	1.15	15517	5.19	237	451.75	-2.07	0.0397	0.0000	0.0000	7.55	-0.210	0.395
Classes	1	Transient vs. moderate & sustained	1.15	15517	3.74	924	325.49	-4.66	0.0000	0.0000	0.0000	16.15	-0.236	0.382
Classes	1	Moderate vs. sustained	3.24	687	5.19	237	160.23	-0.99	0.3256	0.2576	0.2451	-1.16	0.038	0.519
Classes	5	Moderate vs. sustained	86.51	687	485.98	237	561.79	-11.13	0.0000	0.0000	0.0000	42.42	-0.834	0.083
Classes	10	Moderate vs. sustained	43.43	687	50.94	237	117.28	-1.48	0.1409	0.6684	0.6723	-0.42	0.019	0.509
Methods	1	Transient vs. moderate	1.47	15517	8.90	687	603.74	-5.75	0.0000	0.0000	0.0000	15.70	-0.279	0.360
Methods	1	Transient vs. sustained	1.47	15517	22.14	237	1502.21	-1.46	0.1458	0.0000	0.0000	7.95	-0.228	0.386
Methods	1	Transient vs. moderate & sustained	1.47	15517	12.30	924	834.19	-2.88	0.0041	0.0000	0.0000	17.55	-0.266	0.367
Methods	1	Moderate vs. sustained	8.90	687	22.14	237	248.82	-0.93	0.3527	0.1344	0.1240	-1.54	0.053	0.526
Methods	5	Moderate vs. sustained	315.67	687	1876.89	237	594.58	-10.46	0.0000	0.0000	0.0000	41.88	-0.823	0.088
Methods	10	Moderate vs. sustained	154.90	687	191.16	237	123.41	-1.44	0.1497	0.9692	0.9696	0.04	-0.002	0.499

Statistical Models

Welch's t-test To specifically compare the two primary roles (**Sample A** vs. **Sample B**) without assuming equal variances or sample sizes, Welch's t-test is employed. The t-statistic is defined as:

$$t = \frac{\bar{X}_1 - \bar{X}_2}{\sqrt{\frac{s_1^2}{N_1} + \frac{s_2^2}{N_2}}} \tag{1}$$

Where:

- $\bar{X}_1, \bar{X}_2$ are the sample means of Sample A and Sample B.
- s_1^2, s_2^2 are the sample variances.
- N_1, N_2 are the sample sizes.

The degrees of freedom (ν) for this test are calculated using the Welch-Satterthwaite equation:

$$\nu \approx \frac{\left(\frac{s_1^2}{N_1} + \frac{s_2^2}{N_2}\right)^2}{\frac{(s_1^2/N_1)^2}{N_1 - 1} + \frac{(s_2^2/N_2)^2}{N_2 - 1}} \tag{2}$$

Mann-Whitney U Test To evaluate the differences in the stochastic dominance of architectural component exploration between primary roles (**Sample A** vs. **Sample B**) without assuming a normal distribution, the non-parametric Mann-Whitney U test (Wilcoxon rank-sum test) is employed.

The data from both independent groups are combined and ranked globally from lowest (1) to highest ($N_1 + N_2$), resolving ties by assigning the average rank. The U statistic for Sample A (U_1) is calculated as:

$$U_1 = R_1 - \frac{N_1(N_1 + 1)}{2} \tag{3}$$

Where:

- N_1 is the sample size of Sample A.
- R_1 is the sum of the ranks assigned to Sample A.
- The total number of pairwise comparisons (maximum possible pairs) is defined by $N_1 \times N_2$.

Normal Approximation for Large Samples Given the substantial sample sizes present in repository participant metrics, the distribution of the U statistic rapidly approaches a normal distribution. The asymptotic significance is determined using a standard normal Z-score approximation:

$$Z = \frac{U_1 - \mu_U}{\sigma_U} \tag{4}$$

Where the expected mean (μ_U) and standard deviation (σ_U) under the null hypothesis of identical distributions are defined as:

$$\mu_U = \frac{N_1 N_2}{2}, \quad \sigma_U = \sqrt{\frac{N_1 N_2 (N_1 + N_2 + 1)}{12}} \tag{5}$$

A calculated p-value lower than the alpha threshold ($p < 0.05$) indicates a statistically significant difference in the rank-order distributions of the two groups, demonstrating that one developer role systematically outranks the other in codebase exploration.

Brunner-Münzel Test To test for differences in the stochastic distributions of primary roles (**Sample A** vs. **Sample B**) without assuming normal distribution or variance homogeneity, the Brunner-Münzel test is applied. The test statistic W is defined as:

$$W = \sqrt{\frac{N_1 N_2}{N_1 + N_2}} \cdot \frac{\hat{p} - \frac{1}{2}}{\sqrt{\hat{\sigma}^2}} \tag{6}$$

Where $\hat{p}$ represents the relative treatment effect (Probability of Superiority), reflecting the probability that a random observation from Sample A is larger than one from Sample B plus half the probability that they are equal.

Cliff's δ Effect Size To complement hypothesis significance testing with a distribution-free magnitude metric, Cliff's δ is tracked to express the degree of dominance of one sample over the other:

$$\delta = \frac{\sum_{i=1}^{N_1} \sum_{j=1}^{N_2} \text{sign}(X_{1i} - X_{2j})}{N_1 N_2} \tag{7}$$

Where the sign function yields $+1$ when an element of Sample A is larger than Sample B, 0 if equal, and -1 if smaller. Effect sizes are interpreted using standard empirical thresholds ($|\delta| < 0.147$ is negligible, ≥ 0.147 is small, ≥ 0.330 is medium, and ≥ 0.474 is large).

8 Generated standard anova - For all components touched for all commits

An Anova table for all components touched on average.

The Two-Way ANOVA evaluates the influence of two independent categorical variables—*Role* (Founder vs. Late Joiner) and *Tenure* (Moderate vs. Sustained)—on the number of unique architectural components touched. The analysis excludes and includes Transient developers to isolate the behaviors of contributors with established project engagement.

Explanation of Table Columns:

- **Sum Sq (Sum of Squares):** Represents the total variation explained by that specific factor. A higher Sum Sq relative to the Residual indicates that the factor has a strong influence on the outcome.
- **df (Degrees of Freedom):** The number of independent values that can vary in the calculation. For categorical variables, this is typically $N - 1$ levels.
- **F (F-statistic):** The ratio of the variance explained by the factor to the variance unexplained (Residual). A larger F-value suggests the factor is more likely to be significant.
- **p-Value ($PR(> F)$):** The probability that the observed differences occurred by chance. Using a significance threshold of $\alpha = 0.05$, values above this indicate no statistically significant effect.
- **ETA Sq** The effect size, quantifies the proportion of the total variance in your dependent variable.

Explanation of Table Rows:

- **Intercept:** Represents the baseline value of the dependent variable when all categorical factors are at their reference levels.
- **Role(F/L):** Tests the *Main Role Effect* of being a Founder versus a Late Joiner. The p-Value above 0.05 indicates that the timing of project entry does not significantly change the breadth of early-stage component exploration.
- **Category(M/S):** Tests the *Main Category Effect* of the eventual contributor catregory (Transient vs Moderate vs. Sustained).
- **Interaction:** Tests the *Interaction Effect*. It evaluates if the effect of being a Founder is different for the different categories.
- **Residual:** Represents the "noise" or variance within the groups that cannot be explained by Role or Tenure.

8.1 Generated standard anova - For all components touched for a all commits excluding tranient

Table 7: Anova results for all components, number of commits and 16441 developers excluding transient

Component	Number of First Commits	Factor	Sum Squared	df	F-Stat	P Value	ETA Sq
packages	1	Role (F/LJ)	0.00	1	0.00	0.9606	0.0000
packages	1	Category (T/M/S)	84.86	2	32.75	0.0000	0.0039
packages	1	Interaction	1.52	2	0.59	0.5557	0.0001
packages	1	Residual	21290.10	16435	-	-	
packages	5	Role (F/LJ)	11.12	1	0.03	0.8640	0.0000
packages	5	Category (M/S)	11907.40	2	15.71	0.0000	0.0222
packages	5	Interaction	12.31	2	0.02	0.9839	0.0000
packages	5	Residual	514037.69	1356	-	-	
packages	10	Role (F/LJ)	100.35	1	1.79	0.1809	0.0018
packages	10	Category (M/S)	36.78	1	0.66	0.4177	0.0007
packages	10	Interaction	2.92	1	0.05	0.8195	0.0001
packages	10	Residual	51484.41	920	-	-	
classes	1	Role (F/LJ)	937.29	1	47.90	0.0000	0.0029
classes	1	Category (T/M/S)	1364.42	2	34.86	0.0000	0.0042
classes	1	Interaction	916.29	2	23.41	0.0000	0.0028
classes	1	Residual	321604.87	16435	-	-	
classes	5	Role (F/LJ)	142055.48	1	2.54	0.1109	0.0017
classes	5	Category (M/S)	8035870.96	2	71.98	0.0000	0.0935
classes	5	Interaction	1215900.38	2	10.89	0.0000	0.0142
classes	5	Residual	75688676.66	1356	-	-	
classes	10	Role (F/LJ)	13347.02	1	4.68	0.0308	0.0048
classes	10	Category (M/S)	1090.98	1	0.38	0.5365	0.0004
classes	10	Interaction	66.46	1	0.02	0.8787	0.0000
classes	10	Residual	2625443.61	920	-	-	
methods	1	Role (F/LJ)	10298.74	1	12.70	0.0004	0.0008
methods	1	Category (T/M/S)	16297.00	2	10.05	0.0000	0.0012
methods	1	Interaction	15001.18	2	9.25	0.0001	0.0011
methods	1	Residual	13328286.72	16435	-	-	
methods	5	Role (F/LJ)	3668624.09	1	3.78	0.0519	0.0025
methods	5	Category (M/S)	137755503.49	2	71.05	0.0000	0.0920
methods	5	Interaction	25729945.47	2	13.27	0.0000	0.0172
methods	5	Residual	1314541598.99	1356	-	-	
methods	10	Role (F/LJ)	549077.04	1	7.22	0.0073	0.0075
methods	10	Category (M/S)	3374.83	1	0.04	0.8332	0.0000
methods	10	Interaction	35707.01	1	0.47	0.4934	0.0005
methods	10	Residual	69978889.05	920	-	-	

Statistical Model

The differences between developer categories are assessed using a Two-Way ANOVA with interaction. The value for any individual developer metric (Y_{ijk}) is modeled as:

$$Y_{ijk} = \mu + \alpha_i + \beta_j + (\alpha\beta)_{ij} + \epsilon_{ijk} \tag{8}$$

Where:

- μ is the grand mean of the touched components.
- α_i represents the effect of the **Role** (Founder vs. Late Joiner).
- β_j represents the effect of the **Tenure** (Transient, Moderate, Sustained).
- $(\alpha\beta)_{ij}$ is the interaction effect between Role and Tenure.
- ϵ_{ijk} is the residual error.

The F-statistic for each factor is calculated by:

$$F = \frac{SS_{factor}/df_{factor}}{SS_{residual}/df_{residual}} \tag{9}$$

9 Tukey hsd - For all components touched for all commits

A Tukey Honestly Significant Difference table for all components touched on average.

Post-hoc Analysis (Tukey HSD): Following the ANOVA, a Tukey Honestly Significant Difference (HSD) test was performed. While ANOVA identifies if at least one group differs, Tukey HSD performs pairwise comparisons to identify specific differences between developer roles and tenure categories while controlling for Type I error rates across multiple comparisons.

Table 8: Significant Tukey HSD results for classes and number of commits, for 16441 developers

Component	Commits	Group		Mean Diff	Adj P Value
		A	B		
classes	1	Founder Moderate	Founder Sustained	-4.44	0.0002
classes	1	Founder Moderate	Founder Transient	-6.27	0.0000
classes	1	Founder Moderate	Later Joiner Moderate	-4.93	0.0000
classes	1	Founder Moderate	Later Joiner Sustained	-2.39	0.0199
classes	1	Founder Moderate	Later Joiner Transient	-6.73	0.0000
classes	1	Founder Sustained	Later Joiner Transient	-2.30	0.0299
classes	1	Founder Transient	Later Joiner Moderate	1.34	0.0021
classes	1	Founder Transient	Later Joiner Sustained	3.88	0.0000
classes	1	Later Joiner Moderate	Later Joiner Sustained	2.54	0.0000
classes	1	Later Joiner Moderate	Later Joiner Transient	-1.80	0.0000
classes	1	Later Joiner Sustained	Later Joiner Transient	-4.34	0.0000
classes	5	Founder Moderate	Founder Sustained	603.00	0.0000
classes	5	Founder Moderate	Later Joiner Sustained	298.75	0.0000
classes	5	Founder Moderate	Later Joiner Transient	-118.47	0.0267
classes	5	Founder Sustained	Founder Transient	-728.37	0.0000
classes	5	Founder Sustained	Later Joiner Moderate	-663.70	0.0000
classes	5	Founder Sustained	Later Joiner Sustained	-304.25	0.0000
classes	5	Founder Sustained	Later Joiner Transient	-721.47	0.0000
classes	5	Founder Transient	Later Joiner Sustained	424.11	0.0000
classes	5	Later Joiner Moderate	Later Joiner Sustained	359.45	0.0000
classes	5	Later Joiner Moderate	Later Joiner Transient	-57.77	0.0013
classes	5	Later Joiner Sustained	Later Joiner Transient	-417.22	0.0000
classes	10	Founder Sustained	Later Joiner Moderate	-26.27	0.0272
methods	1	Founder Moderate	Founder Transient	-21.45	0.0002
methods	1	Founder Moderate	Later Joiner Moderate	-16.34	0.0049
methods	1	Founder Moderate	Later Joiner Transient	-22.81	0.0000
methods	1	Founder Transient	Later Joiner Sustained	21.26	0.0000
methods	1	Later Joiner Moderate	Later Joiner Sustained	16.15	0.0000
methods	1	Later Joiner Moderate	Later Joiner Transient	-6.47	0.0000
methods	1	Later Joiner Sustained	Later Joiner Transient	-22.62	0.0000
methods	5	Founder Moderate	Founder Sustained	2489.44	0.0000
methods	5	Founder Moderate	Later Joiner Sustained	1067.11	0.0000
methods	5	Founder Moderate	Later Joiner Transient	-522.74	0.0151
methods	5	Founder Sustained	Founder Transient	-3036.73	0.0000
methods	5	Founder Sustained	Later Joiner Moderate	-2797.92	0.0000
methods	5	Founder Sustained	Later Joiner Sustained	-1422.33	0.0000
methods	5	Founder Sustained	Later Joiner Transient	-3012.19	0.0000
methods	5	Founder Transient	Later Joiner Sustained	1614.40	0.0000
methods	5	Later Joiner Moderate	Later Joiner Sustained	1375.59	0.0000
methods	5	Later Joiner Moderate	Later Joiner Transient	-214.26	0.0065
methods	5	Later Joiner Sustained	Later Joiner Transient	-1589.85	0.0000
methods	10	Founder Moderate	Later Joiner Moderate	-119.34	0.0368

Table 9: Not Significant Tukey HSD results for classes and number of commits, for 16441 developers

Component	Commits	Group		Mean Diff	Adj P Value
		A	B		
classes	1	Founder Sustained	Founder Transient	-1.83	0.2208
classes	1	Founder Sustained	Later Joiner Moderate	-0.49	0.9885
classes	1	Founder Sustained	Later Joiner Sustained	2.05	0.1250
classes	1	Founder Transient	Later Joiner Transient	-0.47	0.6562
classes	5	Founder Moderate	Founder Transient	-125.36	0.7015
classes	5	Founder Moderate	Later Joiner Moderate	-60.70	0.6018
classes	5	Founder Transient	Later Joiner Moderate	64.66	0.9648
classes	5	Founder Transient	Later Joiner Transient	6.89	1.0000
classes	10	Founder Moderate	Founder Sustained	7.66	0.9262
classes	10	Founder Moderate	Later Joiner Moderate	-18.61	0.1346
classes	10	Founder Moderate	Later Joiner Sustained	-12.95	0.4899
classes	10	Founder Sustained	Later Joiner Sustained	-20.61	0.1598
classes	10	Later Joiner Moderate	Later Joiner Sustained	5.66	0.5524
classes	20	Founder Sustained	Later Joiner Sustained	-25.59	0.1034
methods	1	Founder Moderate	Founder Sustained	-13.68	0.3026
methods	1	Founder Moderate	Later Joiner Sustained	-0.19	1.0000
methods	1	Founder Sustained	Founder Transient	-7.77	0.6803
methods	1	Founder Sustained	Later Joiner Moderate	-2.66	0.9949
methods	1	Founder Sustained	Later Joiner Sustained	13.49	0.1083
methods	1	Founder Sustained	Later Joiner Transient	-9.13	0.4222
methods	1	Founder Transient	Later Joiner Moderate	5.11	0.2153
methods	1	Founder Transient	Later Joiner Transient	-1.36	0.9837
methods	5	Founder Moderate	Founder Transient	-547.29	0.6579
methods	5	Founder Moderate	Later Joiner Moderate	-308.48	0.3749
methods	5	Founder Transient	Later Joiner Moderate	238.81	0.9792
methods	5	Founder Transient	Later Joiner Transient	24.55	1.0000
methods	10	Founder Moderate	Founder Sustained	-13.47	0.9967
methods	10	Founder Moderate	Later Joiner Sustained	-86.42	0.2598
methods	10	Founder Sustained	Later Joiner Moderate	-105.87	0.1291
methods	10	Founder Sustained	Later Joiner Sustained	-72.95	0.4825
methods	10	Later Joiner Moderate	Later Joiner Sustained	32.92	0.4480
methods	20	Founder Sustained	Later Joiner Sustained	-106.14	0.1554

Post-hoc Analysis: Tukey HSD

Following the Two-Way ANOVA, a Tukey Honestly Significant Difference (HSD) test is used to conduct pairwise comparisons. This test determines which specific group means differ significantly while maintaining a constant family-wise error rate.

The studentized range statistic (q) for comparing two group means is defined as:

$$q = \frac{\bar{Y}_{max} - \bar{Y}_{min}}{\sqrt{\frac{MS_{residual}}{n}}} \tag{10}$$

Where:

- $\bar{Y}_{max}$ and $\bar{Y}_{min}$ are the larger and smaller means of the two groups being compared.
- $MS_{residual}$ is the Mean Square Error derived from the ANOVA residual.
- n is the number of observations in each group (adjusted for unequal sample sizes via the harmonic mean).

A pair of groups is considered significantly different if the absolute difference between their means exceeds the Honestly Significant Difference (HSD):

$$HSD = q_{\alpha,k,df}\sqrt{\frac{MS_{residual}}{n}} \tag{11}$$

Where $q_{\alpha,k,df}$ is the critical value from the studentized range distribution based on the significance level ($\alpha = 0.05$), the number of groups (k), and the degrees of freedom (df) from the ANOVA residual.

10 Strategy logistic regression - For all components touched for all commits

To identify early indicators of long-term developer engagement, a Logistic Regression model was employed. The model treats the developer category (Sustained vs. Non-Sustained) as a binary dependent variable. The following metrics are reported:

- **Coefficient (β):** This value represents the change in the log-odds of a developer becoming 'Sustained' for every unit increase in the component count. A positive coefficient indicates that higher activity in that component increases the likelihood of long-term retention.
- **Odds Ratio (e^{β}):** Perhaps the most interpretable metric, the Odds Ratio quantifies the relative increase in the likelihood of being a Sustained developer. For example, an Odds Ratio of 1.05 implies a 5% increase in the odds of becoming sustained for each additional component touched.
- **Std. Err (Standard Error):** Measures the accuracy of the coefficient estimate. A lower standard error relative to the coefficient indicates a more precise estimate.
- **p-Value ($P > |z|$):** Indicates the statistical significance of the predictor. In this study, a p-Value < 0.05 suggests that the specific component count is a significant predictor of whether a developer will transition into a sustained role.
- **50% Threshold:** The threshold number of components to touch to have a 50
- **Moderate Met Threshold:** The moderate number of developers to have met the threshold, the percentage of developers in brackets.
- **Sustained Met Threshold:** The sustained number of developers to have met the threshold, the percentage of developers in brackets.

Interpretation of Intercept vs. Component Count:

- **Intercept:** Represents the baseline log-odds of the dependent variable (Sustained Status) when the independent variable (e.g., Package Count) is zero. In this study, the consistently negative intercepts indicate that the probability of a developer becoming 'Sustained' is statistically low without active engagement in the codebase.
- **Component Count (Slope):** Represents the effect size of architectural engagement. The positive coefficients and Odds Ratios greater than 1.0 demonstrate that every additional unique component touched by a developer significantly increases their likelihood of transitioning into a sustained contributor.

Table 10: Strategy Logistic Regression for all components against number of commits for 16441 developers excluding transient

Component	Number of First Commits	Type	Moderate μ	Sustained μ	Coefficient	Odds Ratio	Std. Err	p-Value	30% Threshold	Moderate Met Threshold	Sustained Met Threshold
packages	1	Intercept	0.48	5.76	-4.6275	0.0098	0.0785	0.0000	-	-	-
packages	1	Packages Count	0.48	5.76	0.2433	1.2755	0.0136	0.0000	**15.5347**	38 (0.2%)	15 (6.3%)
packages	5	Intercept	11.26	35.24	-2.7036	0.0670	0.1256	0.0000	-	-	-
packages	5	Packages Count	11.26	35.24	0.0618	1.0638	0.0049	0.0000	**30.0232**	71 (6.3%)	100 (42.2%)
packages	10	Intercept	13.85	32.42	-1.9820	0.1378	0.1286	0.0000	-	-	-
packages	10	Packages Count	13.85	32.42	0.0463	1.0474	0.0050	0.0000	**24.5148**	104 (15.1%)	106 (44.7%)
classes	1	Classes Count	1.43	36.49	0.0514	1.0528	0.0028	0.0000	**73.2123**	45 (0.3%)	28 (11.8%)
classes	5	Intercept	57.53	447.83	-3.3919	0.0336	0.1557	0.0000	-	-	-
classes	5	Classes Count	57.53	447.83	0.0130	1.0131	0.0009	0.0000	**195.0338**	56 (5.0%)	156 (65.8%)
classes	10	Intercept	75.67	407.66	-2.7164	0.0661	0.1544	0.0000	-	-	-
classes	10	Classes Count	75.67	407.66	0.0111	1.0112	0.0009	0.0000	**167.9633**	64 (9.3%)	158 (66.7%)
methods	1	Methods Count	4.78	133.11	0.0103	1.0104	0.0007	0.0000	**353.2009**	34 (0.2%)	16 (6.8%)
methods	5	Intercept	207.57	1737.49	-3.0246	0.0486	0.1351	0.0000	-	-	-
methods	5	Methods Count	207.57	1737.49	0.0028	1.0028	0.0002	0.0000	**778.7300**	47 (4.2%)	144 (60.8%)
methods	10	Intercept	275.76	1574.80	-2.3681	0.0937	0.1350	0.0000	-	-	-
methods	10	Methods Count	275.76	1574.80	0.0023	1.0023	0.0002	0.0000	**651.2866**	61 (8.9%)	143 (60.3%)

Predictive Identification Model

To determine if early-stage developer behavior can identify future sustained contributors, we employ a Logistic Regression model. The probability P of a developer becoming a **Sustained Contributor** is modeled using the log-odds (logit) function:

$$\ln\left(\frac{P}{1-P}\right) = \beta_0 + \beta_1 X_1 + \beta_2 X_2 + \ldots + \beta_n X_n + \epsilon \tag{12}$$

Where:

- P is the probability that the developer's tenure is "Sustained".
- β_0 is the intercept.
- X_n represents early-stage metrics (e.g., methods or classes touched in the first 10, 20, or 50 commits).
- β_n are the coefficients representing the weight of each predictor.

The impact of each behavior is quantified using the **Odds Ratio (OR)**, calculated as:

$$OR = e^{\beta_n} \tag{13}$$

An $OR > 1$ indicates that an increase in the metric (e.g., touching more classes) increases the likelihood of long-term retention.

Model Evaluation The predictive power is evaluated using the Area Under the Receiver Operating Characteristic Curve (AUC-ROC). An AUC of 0.5 represents random chance, while an AUC closer to 1.0 indicates high predictive accuracy.

11 Repository

11.1 Repository: 14


11.1.1 Time series sustained components touched by developer - 14 For developer commits and components touched.

Table 11: Table of first 6 sustained founder developers in the Scatter Developer graphs.

Developer ID	Colour
2930	Maroon
2932	Sienna
2934	LightCoral
2935	DarkCyan
2946	DarkOrange
2959	MediumPurple

Table 12: Table of first 21 sustained later joiner developers in the Scatter Developer graphs.

Developer ID	Colour
1774	Maroon
2986	Sienna
3000	LightCoral
3020	DarkCyan
3037	DarkOrange
3050	MediumPurple
3071	LightSkyBlue
3072	HotPink
3141	ForestGreen
3143	FireBrick
3163	DodgerBlue
3172	Tomato
3178	SeaGreen
3216	SlateGray
3217	Ivory
3272	Orchid
3339	Chocolate
3354	SteelBlue
3456	RosyBrown
3473	Azure
3485	Tan



(a) Packages for sustained founder

(b) Packages for sustained later joiner

(c) Classes for sustained founder


(d) Classes for sustained later joiner

(e) Methods for sustained founder


(f) Methods for sustained later joiner

Figure 31: Repo: 14. First six (6) sustained founder and first twenty-one (21) sustained later joiner developers. The number of components touched (y-axis) against the number of commits (x-axis). Sustained founder developers with colours are shown in Table 11. Sustained later joiner developers with colours are shown in Table 12.


11.1.2 Time series sustained components touched by developer - 14 For developer day and components touched.




(a) Packages for sustained founder




(b) Packages for sustained later joiner




(c) Classes for sustained founder



(d) Classes for sustained later joiner



(e) Methods for sustained founder



(f) Methods for sustained later joiner

Figure 32: Repo: 14. First six (6) sustained founder and first twenty-one (21) sustained later joiner developers. The number of components touched (y-axis) against the number of day (x-axis). Sustained founder developers with colours are shown in Table 11. Sustained later joiner developers with colours are shown in Table 12.

11.2 Repository: 21


11.2.1 Time series sustained components touched by developer - 21 For developer commits and components touched.

Table 13: Table of first 7 sustained founder developers in the Scatter Developer graphs.

Developer ID	Colour
6245	Maroon
6246	Sienna
6247	LightCoral
6249	DarkCyan
6250	DarkOrange
6251	MediumPurple
6257	LightSkyBlue

Table 14: Table of first 50 sustained later joiner developers in the Scatter Developer graphs.

Developer ID	Colour
199	Maroon
6252	Sienna
6253	LightCoral
6259	DarkCyan
6260	DarkOrange
6262	MediumPurple
6263	LightSkyBlue
6264	HotPink
6267	ForestGreen
6271	FireBrick
6272	DodgerBlue
6276	Tomato
6278	SeaGreen
6280	SlateGray
6282	Ivory
6284	Orchid
6288	Chocolate
6295	SteelBlue
6297	RosyBrown
6298	Azure
6302	Tan
6306	Plum
6309	Crimson
6312	Khaki
6313	Lavender
6314	Indigo
6315	Turquoise
6326	Beige
6329	Silver
6333	Gold
6338	Coral
6342	Lime
6343	Maroon
6349	Navy
6352	Teal
6355	Olive
6363	Violet
6368	Gray
6369	Pink
6370	Brown
6373	Black
6374	Yellow
6375	Magenta
6379	Cyan
6391	Salmon
6410	Orange
6411	Red
6417	Green
6418	Blue
6420	Purple



(a) Packages for sustained founder

(b) Packages for sustained later joiner

(c) Classes for sustained founder


(d) Classes for sustained later joiner

(e) Methods for sustained founder

(f) Methods for sustained later joiner

Figure 33: Repo: 21. First seven (7) sustained founder and first fifty (50) sustained later joiner developers. The number of components touched (y-axis) against the number of commits (x-axis). Sustained founder developers with colours are shown in Table 13. Sustained later joiner developers with colours are shown in Table 14.

11.2.2 Time series sustained components touched by developer - 21 For developer day and components touched.



(a) Packages for sustained founder

(b) Packages for sustained later joiner

(c) Classes for sustained founder

(d) Classes for sustained later joiner

(e) Methods for sustained founder

(f) Methods for sustained later joiner

Figure 34: Repo: 21. First seven (7) sustained founder and first fifty (50) sustained later joiner developers. The number of components touched (y-axis) against the number of day (x-axis). Sustained founder developers with colours are shown in Table 13. Sustained later joiner developers with colours are shown in Table 14.