SHATTERPROOF POLYCARBONATE DIFFUSER

Prevents the fitting from breaking into multiple small pieces

IP65 RATED HOUSING

Protect your bulkhead from water and dust







SELECTABLE COLOUR TEMPERATURE

Choose your colour temperature 3000K, 4000K or 5500K



BRITAIN

MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

NOT on Microwave Sensor options

INTEGRAL MICROWAVE SENSOR

Featuring a O or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only



Multi-Wattage Tri-Colour and Single Colour 4000K IP65 Polycarbonate Bulkheads

Available in

Emergency/Self Test Emergency

✓ Microwave Sensor



NEW

MANUAL OR SELF TEST

EMERGENCY

SELECTABLE

of installation

Choose between manual emergency or self test emergency at the time

Emergency options only

DUSK TO DAWN

Detects ambient light levels

and adjusts the light accordingly

Photocell options only

Reduce installation time with easy-to-use push fit terminals

FUNCTION

PUSH

CONNECTOR

SUITABLE FOR

INSTALLATION

BESA BOX



Part Number	Description	Dimensions	Power	Lumens	Colour Temp.
NET-33-06-20	Standard		12W/14W/ 16W/18W	1200lm/1400lm/ 1600lm/1800lm	3000K/4000K/5500K
NET-33-06-30	Emergency/Self Test				
NET-33-06-24	Microwave Sensor		16W	1600lm	
NET-33-06-34	Microwave Sensor Emergency/Self Test				
NET-33-06-70	Photocell	Ø325 x 110mm	12W/14W/ 16W/18W	1200lm/1400lm/ 1600lm/1800lm	
NET-33-06-71	Photocell Emergency/Self Test				
NET-33-06-48	Photocell Microwave Sensor		16W	1600lm	
NET-33-06-49	Photocell Microwave Sensor Emergency/Self Test				

NET-33-06-40	Standard	Ø325 x 110mm	12W/14W/ 16W/18W	1200lm/1400lm/ 1600lm/1800lm	4000K
NET-33-06-42	Emergency/Self Test				
NET-33-06-44	Microwave Sensor		16W	1600lm	
NET-33-06-46	Microwave Sensor Emergency/Self Test				

Compatible Accessories






Chrome Ring

NET-33-06-06

NET-33-06-08

Black Ring

Luminous Intensity Distribution



Save time on site with pre-made cable entry points







NEW

of installation

MANUAL OR SELF TEST

EMERGENCY SELECTABLE

Choose between manual emergency

or self test emergency at the time



SELECTABLE COLOUR TEMPERATURE

DUSK TO DAWN FUNCTION

Reduce installation time with easy-to-use push fit terminals

CONNECTOR

Choose your colour temperature 3000K, 4000K or 5500K

Detects ambient light levels and adjusts the light accordingly



Featuring a 0 or 10% Standby Mode, 2-10m detection range and 5sec to 10min hold time

Microwave Sensor options only



Retro fit into existing housings quickly and easily



Emergency options only

MULTI WATTAGE DRIVER

Choose between 12W, 14W, 16W or 18W at the time of installation

NOT on Microwave Sensor options

DUXFORD RANGE

Multi-Wattage Tri-Colour and Single Colour 4000K Retrofit Gear Trays

Available in

Emergency/Self Test Emergency



✓ Microwave Sensor



			- 11
Р	nai	\cap	110

Part Number	Description	Dimensions	Power	Lumens	Colour Temp.
NET-33-06-12	Standard	Ø261 x 23.6mm	12W/14W/ 16W/18W	1200lm/1400lm/ 1600lm/1800lm	3000K/4000K/5500K
NET-33-06-32	Emergency/Self Test				
NET-33-06-16	Microwave Sensor		16W 12W/14W/ 16W/18W	1600lm 1200lm/1400lm/ 1600lm/1800lm	
NET-33-06-36	Microwave Sensor Emergency/Self Test				
NET-33-06-72	Photocell				
NET-33-06-73	Photocell Emergency/Self Test				
NET-33-06-78	Photocell Microwave Sensor		16W	1600lm	
NET-33-06-79	Photocell Microwave Sensor Emergency/Self Test				

NET-33-06-0	Standard	Ø261 x 23.6mm	12W/14W/	1200lm/1400lm/ 1600lm/1800lm	
NET-33-06-0	Emergency/Self Test		16W/18W		
NET-33-06-0	Microwave Sensor		16W	1600lm	
NET-33-06-0	Microwave Sensor Emergency/Self Test				

powered by **TRIDONIC**



Designed to be retrofitted into existing housings







