Report: Exercise 2

Group 9: Øyvin Richardsen, Sandor Zeestraten, Stian Habbestad

Norwegian University of Science and Technology TDT4258 Energy Efficient Computer Design March 12, 2013

Abstract

Contents

1	Introduction	2
2	Description and methodology	2
3	Results	2
4	Tests Results	2
5	Evaluation of assignment	2
6	Conclusion	2
7	Appendix	2

1 Introduction

2 Description and methodology

We started out with implementing the previous exercise that was coded in assembly, in C. This was an easy start for implemting an interrupt routine, as well as the basics we needed for this exercise. Next step

3 Results

4 Tests

Description

Results Below is a table of the different tests we ran, the preconditions and the results.

Name	Preconditions	Description	Expected result	Test result
Steady-state test	Power is on, and the board is con- nected	Upload program to card, push reset switch	The board is powered and LED 7 should be on	Passed
Move LED right test	Program is active, only LED 7 is on	Push switch 6	LED 7 should be turned off and LED 6 should be turned on	Passed
Move LED left test	Program is active, only LED 6 is on	Push switch 7	LED 6 should be turned off and LED 7 should be turned on	Passed
Left LED wrap-around test	Program is active, only LED 7 is on	Push switch 67	LED 7 should be turned off and LED 0 should be turned on	Passed
Right LED wrap-around test	Program is active, only LED 0 is on	Push switch 6	LED 0 should be turned off and LED 7 should be turned on	Passed
Long push test	Program is active, only LED 7 is on	Push and hold switch 6 for a few seconds	LED 7 should be turned off and LED 6 should be turned on as soon as the switch is pushed	Passed

5 Evaluation of assignment

6 Conclusion

7 Appendix

References

 $[1] \quad TDT4258 \ Compendium \ \texttt{http://www.idi.ntnu.no/emner/tdt4258/_media/kompendium.pdf}$

.