

CSC/CPE 138

COMPUTER NETWORK FUNDAMENTALS

Lecture 1_1: Computer Network and the Internet – Part 1

California State University, Sacramento
Fall 2024

About the Course

Instructor: Dr. Syed Badruddoja

Class Time and Location: Tu,Th, 10:30 AM – 11:45 AM, Alpine Hall 156

Office Hours (Online): Tu,Th, 2:30 PM – 4:00 PM

Office Hours Zoom Link: <https://csus.zoom.us/j/82588604485>

Mode of Instruction: In-person

E-mail: badruddoja@csus.edu

Course Objectives

- Explain the basic principles, architecture, layered models, and implementations of computer networks.
- Describe the details of important network protocols on different layers across the protocol stack.
- Apply reliable communication including the various methods for error detection, correction, retransmission, flow control, and congestion control.
- Explain the working mechanisms of routing, forwarding, internet addressing, and switching.
- Identify professional and ethical responsibilities, security issues and countermeasures.

Prerequisite and Materials

Prerequisite

- Introduction to Systems Programming - CSC60,
- Data Structures and Algorithm Analysis - CSC130

Textbook

- Computer Networking: A Top-Down Approach, 7/8th edition, Kurose and Ross, Pearson, ISBN-10: 9780133594140, 1292405465 ISBN-13: 978-0133594140, 978-1292405469

Supplemental Materials


- Slides are adapted from Computer Networking: A Top-Down Approach, 8th edition, J.F Kurose and K.W. Ross
- Coding examples, online resources and Youtube videos

Grading Policy - Assignments

Assignment Categories	Grade Percentage
In-Class Activity	5.0%
Homework & Programming	20.0%
Lab Assignment	15.0%
Project	10.0%
Midterm Exam	25.0%
Final Exam	25.0%
Total	100.0%

Grading Policy - Assignments

- In-Class activities
 - Quiz
 - Self-reflection
 - Think-pair-share
 - Prompt questions
 - Concept-Map
- Homework and Programming Assignments
- Lab Assignments
- Programming Project
- Exams



Submission Policy

- Submission guidelines
 - Submit assignments on due date
 - Pdf files submission for homework
 - Code files submission for programs (zipped folder)
 - Recheck submission
- Late submissions will be penalized by the following rules.
 - 10% deduction for one day late submission.
 - 20% deduction for two days late submission.
 - 30% deduction for three days late submission.
 - 100% deduction from, 4th day onwards

Other Policies in Syllabus

- Check emails and canvas regularly
- Make-up exams are not allowed
 - Exempted from extreme circumstances with evidence
 - Require instructor approval
- Syllabus may be modified in the semester
 - Any changes to the syllabus will be communicated

Tentative Class Schedule

Week	Date	Materials to Cover	Remarks	Textbook Chapters
1	8/26 – 1/30	Computer Networks and The Internet	-	1
2	9/2 – 9/6	Computer Networks and The Internet	ASSIGNMENT 1	
3	9/9 – 9/13	Application Layer	-	2
4	9/16 – 9/20	Application Layer	ASSIGNMENT 2	
5	9/23 – 9/27	Application Layer	-	
6	9/30 – 10/4	Transport Layer	LAB 1	3
7	10/7 – 10/11	Transport Layer	MID-TERM EXAM	
8	10/14 – 10/18	Transport Layer	LAB 2	
9	10/21 – 10/25	Network Layer: Data Plane	ASSIGNMENT 3	4
10	10/28 – 11/1	Network Layer: Data Plane	-	
11	11/4 – 11/8	Network Layer: Control Plane	ASSIGNMENT 4	5
12	11/11 – 11/15	Network Layer: Control Plane	-	
13	11/18 – 11/22	Link Layer	LAB 3	6
14	11/25 – 11/29	Link Layer	PROJECT SUBMISSION	
15	12/2 – 12/6	Network Security	-	8
16	12/9 – 12/13	-	FINAL EXAM	-

Getting Started:

Computer Network and the Internet

Overview

- The computer network
- Protocol and Internet
- Network infrastructure
- Access networks and physical media
- Packet switching versus circuit-switching


Fun Activity: Brainstorm Internet



Parking



Ecommerce



Reservation



Training



Smart Home



TAB



Laptop

Connected-world



IP picture frame
<http://www.ceiva.com/>



Web-enabled toaster +
weather forecaster



Tweet-a-watt:
monitor energy use



Smart
refrigerator



Streaming Services




sensorized,
bed
mattress



Internet phones




Introducing Computer Network



- What's the Internet?
- What's a protocol?
- Network edge; hosts, access network, physical media
- Network core: packet/circuit switching, Internet structure
- Performance: loss, delay, throughput
- Security
- Protocol layers, service models
- History


What's the Internet: “nuts and bolts” view

- billions of connected computing devices:
 - *hosts = end systems*
 - *running network apps*
- *communication links*
 - fiber, copper, radio, satellite
 - transmission rate: *bandwidth*
- *packet switches: forward packets (chunks of data)*
 - *routers and switches*




What's the Internet: “nuts and bolts” view

- **Internet:** “network of networks”
 - Interconnected ISPs
- **protocols** control sending, receiving of messages
 - e.g., TCP, IP, HTTP, Skype, 802.11
- **Internet standards**
 - RFC: Request for comments
 - IETF: Internet Engineering Task Force



What's the Internet: a service view

- *infrastructure that provides services to applications:*
 - Web, VoIP, email, games, e-commerce, social nets, ...
- *provides programming interface to apps*
 - hooks that allow sending and receiving app programs to “connect” to Internet
 - provides service options, analogous to postal service



What's a protocol?

human protocols:

- “what’s the time?”
- “I have a question”
- introductions

... specific messages sent

... specific actions taken
when messages
received, or other
events


network protocols:

- machines rather than humans
- all communication activity in Internet governed by protocols

protocols define format, order of messages sent and received among network entities, and actions taken on message transmission, receipt

What's a protocol?


a human protocol and a computer network protocol:



Q: other human protocols?

Network Infrastructure

- *network edge:*
 - hosts: clients and servers
 - servers often in data centers
- *access networks, physical media:* wired, wireless communication links
- *network core:*
 - interconnected routers
 - network of networks




Access networks and physical media

Q: How to connect end systems to edge router?


- residential access nets
- institutional access networks (school, company)
- mobile access networks

keep in mind:

- bandwidth (bits per second) of access network?
- shared or dedicated?




Access network: digital subscriber line (DSL)




- use *existing* telephone line to central office DSLAM
 - data over DSL phone line goes to Internet
 - voice over DSL phone line goes to telephone net
- < 2.5 Mbps upstream transmission rate (typically < 1 Mbps)
- < 24 Mbps downstream transmission rate (typically < 10 Mbps)

Access network: cable network



frequency division multiplexing: different channels transmitted in different frequency bands


Access network: cable network




■ HFC: hybrid fiber coax

- asymmetric: up to 30Mbps downstream transmission rate, 2 Mbps upstream transmission rate.
- **network** of cable, fiber attaches homes to ISP router
 - homes *share access network* to cable headend
 - unlike DSL, which has dedicated access to central office

Access network: home network



Enterprise access networks (Ethernet)




- typically used in companies, universities, etc.
- 10 Mbps, 100Mbps, 1Gbps, 10Gbps transmission rates
- today, end systems typically connect into Ethernet switch

Wireless access networks

- shared *wireless* access network connects end system to router
 - via base station aka “access point”


wireless LANs:

- within building (100 ft.)
- 802.11b/g/n (WiFi): 11, 54, 450 Mbps transmission rate



wide-area wireless access


- provided by telco (cellular) operator, 10's km
- between 1 and 10 Mbps
- 3G, 4G: LTE



Host: sends *packets* of data

host sending function:

- takes application message
- breaks into smaller chunks, known as *packets*, of length L bits
- transmits packet into access network at *transmission rate R*
 - link transmission rate, aka link *capacity*, aka *link bandwidth*



$$\text{packet transmission delay} = \text{time needed to transmit } L\text{-bit packet into link} = \frac{L \text{ (bits)}}{R \text{ (bits/sec)}}$$

Physical media

- **bit:** propagates between transmitter/receiver pairs
- **physical link:** what lies between transmitter & receiver
- **guided media:**
 - signals propagate in solid media: copper, fiber, coax
- **unguided media:**
 - signals propagate freely, e.g., radio

twisted pair (TP)

- two insulated copper wires
 - Category 5: 100 Mbps, 1 Gbps Ethernet
 - Category 6: 10Gbps



Physical media: coax, fiber

coaxial cable:

- two concentric copper conductors
- bidirectional
- broadband:
 - multiple channels on cable
 - HFC



fiber optic cable:

- glass fiber carrying light pulses, each pulse a bit
- high-speed operation:
 - high-speed point-to-point transmission (e.g., 10's-100's Gbps transmission rate)
- low error rate:
 - repeaters spaced far apart
 - immune to electromagnetic noise



Physical media: radio

- signal carried in electromagnetic spectrum
- no physical “wire”
- bidirectional
- propagation environment effects:
 - reflection
 - obstruction by objects
 - interference

radio link types:


- **Terrestrial microwave**
 - e.g. up to 45 Mbps channels
- **LAN** (e.g., WiFi)
 - 54 Mbps
- **Wide-area** (e.g., cellular)
 - 4G cellular: ~ 10 Mbps
- **Satellite**
 - Kbps to 45Mbps channel (or multiple smaller channels)
 - 270 msec end-end delay
 - geosynchronous versus low altitude

Minute Paper


- Differentiate between Internet and Protocol?
- Identify the elements in hierarchical network infrastructure ?
- Identify types of access networks and their use case in daily lives?

The network core

- Mesh of interconnected routers
- Packet-switching: hosts break application-layer messages into *packets*
 - Forward packets from one router to the next, across links on path from source to destination
 - Each packet transmitted at full link capacity



Packet-switching: store-and-forward




- takes L/R seconds to transmit (push out) L -bit packet into link at R bps
- *store and forward*: entire packet must arrive at router before it can be transmitted on next link
- end-end delay = $2L/R$ (assuming zero propagation delay)

one-hop numerical example:

- $L = 7.5$ Mbits
 - $R = 1.5$ Mbps
 - Delay = $L/R = 7.5/1.5$
 - one-hop transmission delay = 5 sec
- } more on delay shortly ...

Packet Switching: queueing delay, loss



queuing and loss:


- if arrival rate (in bits) to link exceeds transmission rate of link for a period of time:
 - packets will queue, wait to be transmitted on link
 - packets can be dropped (lost) if memory (buffer) fills up

Two key network-core functions

routing: determines source-destination route taken by packets

- *routing algorithms*


forwarding: move packets from router's input to appropriate router output



Alternative core: circuit switching


end-end resources allocated to, reserved for “call” between source & dest:

- in diagram, each link has four circuits.
 - call gets 2nd circuit in top link and 1st circuit in right link.
- dedicated resources: no sharing
 - circuit-like (guaranteed) performance
- circuit segment idle if not used by call (*no sharing*)
- commonly used in traditional telephone networks



Minute Paper

- How many circuits can be active from source computer A to destination computer B simultaneously?
- When can C communicate with B?
- Answers: 8 circuits can be active. C can communicate when one of the 8 circuits from A-B stops transmission




Circuit switching: FDM versus TDM

Example:


4 users



FDM




TDM




A Little more on TDM

Synchronous TDM – Time is divided into periods of slots



Asynchronous TDM – No periods, anyone can send



TDM : Example

Suppose that you have a multiplexer (mux) with 2 different inputs at the following bit-rates: (A) 10 Kbps, (B) 8 Kbps, Using a fixed slot size in the frame, how would you organize a single asynchronous TDM link receiving the output of the mux?

Solution: Common slot size is 2 Kbps



How about the below solution? Is it asynchronous?




Circuit Switching Vs Packet Switching

packet switching allows more users to use network!

example:

- 1 Mb/s link
- each user:
 - 100 kb/s when “active”
 - active 10% of time
- *circuit-switching:*
 - 10 users can be active
- *packet switching:*
 - With 35 users, probability of 10 active at same time is less than .002 *



Q: how did we get value 0.002?

Efficiency of Packet-Switching Method

Measuring probability of users being active

- Given
 - Total number of users = 35
 - The probability of a user being active = 0.1
- Find
 - Probability of 10 users simultaneously active

Solution :

$$\begin{aligned}\text{Binomial probability distribution} &= \binom{n}{x} p^x (1 - p)^{n-x} \\ &= \binom{35}{10} 0.1^{10} (1 - 0.1)^{35-10} \\ &= 0.00131\end{aligned}$$

$$\text{Note: } \binom{n}{x} = \frac{n!}{x!(n-x)!}$$

DIY : Computing Binomial Probability

Now consider a scenario where 20 users are using the packet switched line and users are active 10% of time.

- A. Compute probability of 1 user being active
- B. Compute the summative probability of up to 7 users being active simultaneously
- C. Compute the probability that more than 7 of 20 users are transmitting at the same time.

DIY : Solutions

A. Compute probability of 1 user being active

$$\begin{aligned}\text{Binomial probability distribution} &= \binom{n}{x} p^x (1 - p)^{n-x} \\ &= \binom{20}{1} 0.1^1 (1 - 0.1)^{20-1} \\ &= 0.27017\end{aligned}$$

B. Compute the summative probability of any upto 7 (0,1,2, ...7) users being active

Cumulative Binomial distribution for 0 through 7 users

$$\begin{aligned}&= \binom{20}{0} 0.1^0 (1 - 0.1)^{20-0} + \binom{20}{1} 0.1^1 (1 - 0.1)^{20-1} + \dots \\ &\quad + \binom{20}{7} 0.1^7 (1 - 0.1)^{20-7} \\ &= 0.999584\end{aligned}$$

DIY : Solutions

C. Compute the probability of more than 7 of 20 users are transmitting at the same time.

$$= 1 - (\text{summative probability of 7 users})$$

$$= 1 - 0.999584$$

$$= 0.000416$$

Packet switching versus circuit switching



is packet switching a “slam dunk winner?”

- great for bursty data
 - resource sharing
 - simpler, no call setup
- **excessive congestion possible:** packet delay and loss
 - protocols needed for reliable data transfer, congestion control
- **Q: How to provide circuit-like behavior?**
 - bandwidth guarantees needed for audio/video apps
 - still an unsolved problem (chapter 7)

Q: human analogies of reserved resources (circuit switching) versus on-demand allocation (packet-switching)?

Summary

- The computer network
- Protocol and Internet
- Network infrastructure
- Access networks and physical media
- Packet switching versus circuit-switching

End of Lecture 1_1