

Diage: A Dialogue Generator

Nico Andrew Glas

November 2, 2013

Abstract

When we create games, much of our time goes in to story writing (where applicable), and while this is unavoidable in narrative heavy games, we can automate it for 'non-critical' dialogue. For example, in the Pokémon RPGs the player can speak to every NPC in the game. All of these monologues were written by a story writer, even the singular sentences that hold no value to plot. We believe that with the right tooling we can automate this process and save valuable development time. [1] [2] [3] [4] [9] [6] [5] [7] [8]

Acknowledgements

Contents

1	Introduction	9
1.1	Create-IT	9
1.2	Problem definition	9
1.3	Related work	9
1.4	Proof of concept	9
2	Diage modelling language	11
2.1	Actors	11
3	Usage in Ludoscope	13
4	Further study	15

Chapter 1

Introduction

1.1 Create-IT

1.2 Problem definition

1.3 Related work

1.4 Proof of concept

Chapter 2

Diage modelling language

In this chapter I will cover the Diage Modelling Language (DML) that is used to visualize the flow of information, some are static and others will wait for the interaction of the player to release this information and ensuring plot progression. *Diage* uses the symbols to represent the *Diage* entities as seen in figure 2.1.





Figure 2.1: DML Symbols

2.1 Actors

An actor is the representation of any one object that can, as the noun implies, act. Examples are the store-clerk, a wandering adventurer or the player. The actor is the only entity that can physically interact with the world, and by doing so changing the world's state. By being able to change the world, the actors are the only entities that can ensure plot progression. An actor has two properties; **name** and **type**. The type property is used in predefined actions as seen in figure 2.2a. This defines that the **player** can speak to all actors of type NPC¹.

¹This can be generalized for all entities, I guess.



(a) A standard action for NPC interaction (b) A standard action for plot interaction (c) A standard action for space interaction

Figure 2.2: Predefined actions




Figure 2.3: An example of a Diage diagram using predefined actions




Figure 2.4: An example of a Diage diagram without using predefined actions

Chapter 3

Usage in Ludoscope

Chapter 4

Further study

Bibliography

- [1] Marc Cavazza, Fred Charles, and Steven J. Mead. Character-based interactive storytelling. IEEE Intelligent Systems, 17(4):17–24, July 2002.
- [2] Marvin Katilius-Boydston. The semiotics of A.J. Greimas: An introduction. Lituanian quarterly journal of arts and sciences, 36(3), 1990.
- [3] Brian Magerko, John E. Laird, Mazin Assanie, Alex Kerfoot, and Devvan Stokes. Ai characters and directors for interactive computer games. In Proceedings of the 16th conference on Innovative applications of artificial intelligence, IAAI’04, pages 877–883. AAAI Press, 2004.
- [4] Julie Porteous and Marc Cavazza. Controlling narrative generation with planning trajectories: The role of constraints. In Proceedings of the 2nd Joint International Conference on Interactive Digital Storytelling: Interactive Storytelling, ICIDS ’09, pages 234–245, Berlin, Heidelberg, 2009. Springer-Verlag.
- [5] Mark Owen Riedl, C. J. Saretto, and R. Michael Young. Managing interaction between users and agents in a multi-agent storytelling environment. In Proceedings of the second international joint conference on Autonomous agents and multiagent systems, AAMAS ’03, pages 741–748, New York, NY, USA, 2003. ACM.
- [6] Mark Owen Riedl and R. Michael Young. Character-focused narrative generation for execution in virtual worlds. In Proceedings of the International Conference on Virtual Storytelling, pages 47–56, 2003.
- [7] Mark Owen Riedl and R. Michael Young. An intent-driven planner for multi-agent story generation. In Proceedings of the Third International Joint Conference on Autonomous Agents and Multiagent Systems - Volume 1, AAMAS ’04, pages 186–193, Washington, DC, USA, 2004. IEEE Computer Society.
- [8] Nikitas M. Sgouros. Dynamic generation, management and resolution of interactive plots. Artificial Intelligence, 107(1):29 – 62, 1999.
- [9] Peter William Weyhrauch. Guiding interactive drama. PhD thesis, Carnegie Mellon University, Pittsburgh, PA, USA, 1997. AAI9802566.