

Diage: A Dialogue Generator

Nico Andrew Glas

October 31, 2013

Abstract

When we create games, much of our time goes in to story writing (where applicable), and while this is unavoidable in narrative heavy games, we can automate it for 'non-critical' dialogue. For example, in the Pokémon RPGs the player can speak to every NPC in the game. All of these monologues were written by a story writer, even the singular sentences that hold no value to plot. We believe that with the right tooling we can automate this process and save valuable development time. [1] [2] [3] [4] [9] [6] [5] [7] [8]

Acknowledgements

Contents

| | | |
|----------|------------------------------|----------|
| 1 | Introduction | 2 |
| 1.1 | Create-IT | 2 |
| 1.2 | Problem definition | 2 |
| 1.3 | Related work | 2 |
| 1.4 | Proof of concept | 2 |
| 2 | Defining a story | 2 |
| 3 | Representing a story | 2 |
| 4 | Usage in Ludoscope | 3 |
| 5 | Further study | 3 |

1 Introduction

1.1 Create-IT

1.2 Problem definition

1.3 Related work

1.4 Proof of concept




Figure 1: List of Declarative Symbols

2 Defining a story

In our setting the "story" is a collection of coherent events that move forward in time with definitive starting and ending positions. For example; We define our story to begin with our hero Jack in his house and he wants to go to Jill's house for reasons. We can hereby define our story's initial state as:

S: Jack IN Jack's House

P: Jack IN Jill's House

In this case, the P is the last plot point in our story, thus it will become an Ending (notated as E). We want to be able to exercise a director's role in the system, e.g. being able to make sure some plots will play out, but we do not want to keep filling in on how this should be executed. That should be the actors responsibility.

3 Representing a story

This section will cover the modelling language I use to visualize the flow of information, some static and some waiting for the interaction of the player to release this information and ensuring plot progression.

In figure 1 we see the list of symbols that I use in the diage system¹. An actor can represent anything within the story that can, as the noun implies, act. Be that a store clerk, a brave adventurer or indeed the player himself. These actors have a knowledge pool that immediately conveys what he does and does not know. Spaces represent world spaces such as; rooms, buildings and complete worlds. They are also defined as information containers. This means that spaces have information that will be shared with an actor the moment said actor steps into the space. For example, as the player walks in to a new town, his actor representation will know where the local store is. This information sharing is limited to other spaces within the parent space. So in the aforementioned example the player would know that there is a local store, but he doesn't know what that store sells, as that is a different entity. Plots on the other hand are volatile information containers that release information on completion. Plots are also actions that the player must do to get plot progression. This does not mean that every plot should be mandatory, but without it some information will never become available. Plots, just like spaces, are nestable. When this happens, a plot turns in to a side-story which should - as the main story - have a definitive start and end position for the player. Objects are rather straight-forward. In the local store from previous examples we could have the desk, an apple or a new sword. The only

¹So, diage is becoming a modelling system as well? I really need to work on naming stuff.




Figure 2: A *Diage* Diagram

items that should be represented in *Diage* should be those that have a plot importance. Think of them as Chekov’s guns, if you will ². Actions define what actors can do with something or some one and accessors declare what actors know about a given subject. The latter is commonly used in conjunction with plots, signifying an increase in knowledge the moment that said plot is resolved. When incorporated in a full diagram we get something like figure 3. An other form of notation used is shown in figure 3. This is less verbose and therefore has less detail, but gives more oversight. These diagrams are called swimlanes ³ and should remain static and does not contain any dynamic information. These could be seen as the *status quo* for a given space. More research is needed to make a definitive conclusion on a sensible and readable notation.

4 Usage in Ludoscope

5 Further study

References

- [1] Marc Cavazza, Fred Charles, and Steven J. Mead. Character-based interactive storytelling. *IEEE Intelligent Systems*, 17(4):17–24, July 2002.
- [2] Marvin Katilius-Boydston. The semiotics of A.J. Greimas: An introduction. *Lituanian quarterly journal of arts and sciences*, 36(3), 1990.
- [3] Brian Magerko, John E. Laird, Mazin Assanie, Alex Kerfoot, and Devvan Stokes. Ai characters and directors for interactive computer games. In *Proceedings of the 16th conference on Innovative applications of artificial intelligence*, IAAI’04, pages 877–883. AAAI Press, 2004.
- [4] Julie Porteous and Marc Cavazza. Controlling narrative generation with planning trajectories: The role of constraints. In *Proceedings of the 2nd Joint International Conference on Interactive Digital Storytelling: Interactive Storytelling*, ICIDS ’09, pages 234–245, Berlin, Heidelberg, 2009. Springer-Verlag.

²A trite to smug, mayhaps? But I do like the idea of making diage using a strict literary vernacular

³Aw, hell no. Swimlanes? Come on, you can do better




Figure 3: *Diage* swim lane diagram

- [5] Mark Owen Riedl, C. J. Saretto, and R. Michael Young. Managing interaction between users and agents in a multi-agent storytelling environment. In Proceedings of the second international joint conference on Autonomous agents and multiagent systems, AAMAS '03, pages 741–748, New York, NY, USA, 2003. ACM.
- [6] Mark Owen Riedl and R. Michael Young. Character-focused narrative generation for execution in virtual worlds. In Proceedings of the International Conference on Virtual Storytelling, pages 47–56, 2003.
- [7] Mark Owen Riedl and R. Michael Young. An intent-driven planner for multi-agent story generation. In Proceedings of the Third International Joint Conference on Autonomous Agents and Multiagent Systems - Volume 1, AAMAS '04, pages 186–193, Washington, DC, USA, 2004. IEEE Computer Society.
- [8] Nikitas M. Sgouros. Dynamic generation, management and resolution of interactive plots. Artificial Intelligence, 107(1):29 – 62, 1999.
- [9] Peter William Weyhrauch. Guiding interactive drama. PhD thesis, Carnegie Mellon University, Pittsburgh, PA, USA, 1997. AAI9802566.