

R Markdown Cheatsheet

R Markdown

Header

```
---
title: ""
author: ""
date: ""
output:
  html_document:
    df_print: paged
  theme:
    version: 4
---
```

Keybinds

Strg + Alt + I insert R Codeblock

Alt + - insert left Arrow

Strg + Shift + M insert Pipe

Strg + Enter Run Current Line

Strg + Alt + R Run Everything

Default Settings

```
```{r include=F}
 knitr::opts_chunk$set(echo=T, error=T, warning=F)
 options(scipen=999) #Disable Scientific notation in Inline code
...`
```

!! IMPORTANT !! `error = T` lets KnitR ignore errors and therefore is able to build regardless. Additionally missing dependencies do not crash the build. DO NOT load libraries in the same block as setting the `knitr::opts_chunk`!

### Settings per block

```
```{r, label="", include=T, echo=T, eval= T, results="markup", fig.cap=""}`
```

- `label` - name, for debugging
- `include` - hides code and output in file
- `echo` - hides code in file
- `eval` - determines if code is ran
- `results` - determines the output style
 - `markup` - standard

- asis - plain text
- hidden - not shown
- fig.cap - caption for figure in this block

Settings

Tools → **Global Options...** → **Code** → **Display** to activate *Rainbow Parenthesis*

Force Pagebreak

```
<div style="page-break-after: always;"></div>
```

Export

!! IMPORTANT !! DO NOT KNIT TO PDF!, because a LaTeX installation is required.

- Knit to HTML
- Click “Open in Browser” in the top right corner
- Then Print the Page to PDF (***Strg + P***)