

APPENDIX B. MATCHING SPECIES TABLES WITH DIFFERENT TAXONOMIC RESOLUTION

Trait-based approaches are a promising tool in ecology. Unlike taxonomy-based methods, traits may not be constrained to biogeographic boundaries [27] and have potential to disentangle the effects of multiple stressors [24].

To analyse trait-composition abundance data must be matched with trait databases like [25]. However these two datatables may contain species information on different taxonomic levels and perhaps data must be aggregated to a joint taxonomic level.

taxize can help in this data-cleaning step, providing a reproducible workflow. Here we illustrate this on a small fictitious example.

Suppose we have fuzzy coded trait table with 2 traits with 3 respectively 2 modalities:

```
(traits <- read.table(header = TRUE, sep = ';', stringsAsFactors=FALSE,
  text = 'taxon;T1M1;T1M2;T1M3;T2M1;T2M2
Gammarus sp.;0;0;3;1;3
Potamopyrgus antipodarum;1;0;3;1;3
Coenagrion sp.;3;0;1;3;1
Enallagma cyathigerum;0;3;1;0;3
Erythromma sp.;0;0;3;3;1
Baetis sp.;0;0;0;0;0
'))
```

	taxon	T1M1	T1M2	T1M3	T2M1	T2M2
1	Gammarus sp.	0	0	3	1	3
2	Potamopyrgus antipodarum	1	0	3	1	3
3	Coenagrion sp.	3	0	1	3	1
4	Enallagma cyathigerum	0	3	1	0	3
5	Erythromma sp.	0	0	3	3	1
6	Baetis sp.	0	0	0	0	0

And want to match this to a table with abundances:

```
(abundances <- read.table(header = TRUE, sep = ';', stringsAsFactors=FALSE,
  text = 'taxon;abundance;sample
Gammarus roeseli;5;1
Gammarus roeseli;6;2
Gammarus tigrinus;7;1
Gammarus tigrinus;8;2
Coenagrionidae;10;1
Coenagrionidae;6;2
Potamopyrgus antipodarum;10;1
xxxxx;10;2
'))
```

	taxon	abundance	sample
1	Gammarus roeseli	5	1
2	Gammarus roeseli	6	2
3	Gammarus tigrinus	7	1
4	Gammarus tigrinus	8	2
5	Coenagrionidae	10	1
6	Coenagrionidae	6	2
7	Potamopyrgus antipodarum	10	1
8	xxxxx	10	2

First we do some basic data-cleaning and create a lookup-table, that will link taxa in trait table with the abundance table.

```
# first we remove ' sp.' from out trait table:
traits$taxon_cleaned <- tolower(gsub(" sp.", "", traits$taxon))
```

```
# since abundance tables can be very long with repeating taxa, we look only
# at unique taxon names This will be a lookup-table linking taxon names
# between both tables
lookup <- data.frame(taxon = tolower(unique(abundances$taxon)), stringsAsFactors = FALSE)
```

The we query the taxonomic hierarchy for both tables, this will be the backbone of this procedure:

```
library(taxize)
traits_classi <- classification(get_uid(traits$taxon_cleaned))
lookup_classi <- classification(get_uid(lookup$taxon))
```

First we look if we can find any direct matches between taxon names:

```
# first search for direct matches
direct <- match(lookup$taxon, traits$taxon_cleaned)
# and add the matched name to our lookup table
lookup$traits <- tolower(traits$taxon[direct])
lookup$match <- ifelse(!is.na(direct), "direct", NA)
lookup
```

	taxon	traits	match
1	gammarus roeseli	<NA>	<NA>
2	gammarus tigrinus	<NA>	<NA>
3	coenagrionidae	<NA>	<NA>
4	potamopyrgus antipodarum	potamopyrgus antipodarum	direct
5	xxxxx	<NA>	<NA>

We found a direct match - *potamopyrgus antipodarum* - so nothing to do here.

Next we look for species which are on a higher taxonomic resolution than our trait table. For these species we will take directly the trait-data since no better information is available.

```
# look for cases where taxonomic resolution in abundance data is higher than
# in trait data: here we take the trait-values for the lower resolution
for (i in which(is.na(lookup$traits))) {
  if (is.data.frame(lookup_classi[[i]])) {
    matches <- tolower(lookup_classi[[i]]$ScientificName) %in% traits$taxon_cleaned
    if (any(matches)) {
      lookup$traits[i] <- tolower(lookup_classi[[i]]$ScientificName[matches])
      lookup$match[i] <- lookup_classi[[i]]$Rank[matches]
    }
  }
}
lookup
```

	taxon	traits	match
1	gammarus roeseli	gammarus	genus
2	gammarus tigrinus	gammarus	genus
3	coenagrionidae	<NA>	<NA>
4	potamopyrgus antipodarum	potamopyrgus antipodarum	direct
5	xxxxx	<NA>	<NA>

So our abundance data has two *Gammarus* species, however trait data is only on genus level.

The next step is to search for species where we have to aggregate trait-data, since our abundance data is on a lower taxonomic level. We are walking the taxonomic ladder for the species in our trait-data upwards and search for matches with our abundance data. Since we'll have many taxa in the trait-data belonging to one taxon, we'll take the median modality scores as an approximation. Of course also other methods may be used here, e.g. weighting by genetic distance.

```

# look for cases taxonomic resolution in abundance data is lower than in
# trait data, here we need to aggregate the trait-values (eg. median value
# for modality)
for (i in which(is.na(lookup$traits))) {
  # find matches
  agg <- sapply(traits_classi, function(x) any(tolower(x$ScientificName) %in%
    lookup$taxon[i]))
  if (sum(agg) > 1) {
    # add taxon as aggregate to trait-table
    traits <- rbind(traits, c(paste0(lookup$taxon[i], "-aggregated"), apply(traits[agg,
      2:6], 2, median), paste0(lookup$taxon[i], "-aggregated")))
    # fill lookup table
    lookup$traits[i] <- paste0(lookup$taxon[i], "-aggregated")
    lookup$match[i] <- "aggregated"
  }
}
lookup

#           taxon           traits      match
# 1   gammarus roeseli   gammarus    genus
# 2   gammarus tigrinus   gammarus    genus
# 3   coenagrionidae coenagrionidae-aggregated aggregated
# 4 potamopyrgus antipodarum potamopyrgus antipodarum direct
# 5           xxxxx           <NA>      <NA>

```

Finally we have only one taxon left - clearly an error. We remove this from our dataset:

```

abundances <- abundances[!abundances$taxon == lookup$taxon[is.na(lookup$traits)],
]

```

Now we can create *species x sites* and *traits x species* matrices, which could be plugged into methods to analyse trait responses [28].

```

# species (as matched with trait table) by site matrix
abundances$traits_taxa <- lookup$traits[match(tolower(abundances$taxon), lookup$taxon)]
library(reshape2)
# reshape data to long format and name rows by samples
L <- dcast(abundances, sample ~ traits_taxa, fun.aggregate = sum, value.var = "abundance")
rownames(L) <- L$sample
L$sample <- NULL
L

#   coenagrionidae-aggregated gammarus potamopyrgus antipodarum
# 1                10          12                10
# 2                 6          14                 0

# traits by species matrix
Q <- traits[, 2:7][match(names(L), traits$taxon_cleaned), ]
rownames(Q) <- Q$taxon_cleaned
Q$taxon_cleaned <- NULL
Q

#           T1M1 T1M2 T1M3 T2M1 T2M2
# coenagrionidae-aggregated    0    0    1    3    1
# gammarus                    0    0    3    1    3
# potamopyrgus antipodarum     1    0    3    1    3

# check
all(rownames(Q) == colnames(L))

# [1] TRUE

```

This is just an example how taxonomic APIs (via taxize) could be used to search for matches up- and downwards the taxonomic ladder. We are looking forward to integrate the freshwater ecology.info database www.freshwaterecology.info into taxize, which will facilitate trait-based analyses in R.