DESIGN SYSTEMS

TECHNICAL DATA SHEET RE-COLOR® patented product

ANTIQUING RELEASE AGENT FOR STAMPED FLOORS

DESCRIPTION

The RE-COLOR product, based on high-quality solvents, pigments and additives, is used both as a release agent between the stamping mat and the cementitious surface and as an antiquing agent, for thin-layer stamped floors made with the Masbeton product and for stamped concrete floors.

APPLICATION METHOD

Mix the product carefully. On the coloured, trowelled floor ready to be stamped, spray-apply the RE-COLOR product; it must always be shaken before use. The RE-COLOR product is applied to the stamping mats initially and then only to the floor. During stamping, once the mat has been removed, immediately spray the RE-COLOR product again onto the stamped surface, in sufficient quantity to create the desired mottled and/or antiqued effect.

Average consumption is 110 g per m^2; much depends on the type of antiquing effect to be achieved. When the treated surface is dry, after at least 3 days, protect the floor with DS-CS resin.

Advantages of using RE-COLOR rather than powder release agent:

- Elimination of the washing phase of the stamped floor, with major cost savings and, in the following days, the advantage of producing further m^2 of stamped floor.
- The RE-COLOR product also provides curing: curing, or post-treatment, is the set of protective measures to which "young" concrete must be subjected in order to keep it warm and moist, allowing slower evaporation of the water in the concrete and protecting it from external heat and wind. Retaining heat and moisture has a positive effect on the compressive and tensile strength of the concrete, on its durability, on its permeability and on plastic shrinkage.
- The elimination of dust, both during stamping and during washing, should also not be underestimated.
- The RE-COLOR product also allows, during stamping, the repair of any surface micro-cracks caused by the hardening of the dry-shake colour hardener, which is normally not possible with powder release agents, because they leave streaks of colour on the floor, staining it.
- In some cases, when making the stamped floor, the dry-shake colour hardener cannot be trowelled perfectly, for example along a wall, in a corner, near manholes, grates, drains, etc. Now the hardener can be trowelled even when the RE-COLOR product is already on top of it.
- In case of rain, a floor stamped with powder release agent will remain stained and darker, also creating a difference between one pour and the next. With the RE-COLOR product this will no longer happen.
- Footprints left on the powder release agent by passers-by who are unaware of the problem force the operator to carry out a special treatment to remove them, wasting time: with the RE-COLOR product this problem is eliminated.
- During repairs, for example the removal of a fin of cement that has squeezed out between one mat and the next, the grey of the cement will be visible at that point. With traditional powder release agent, great

care must be taken to recreate the same colour as the joint; with the RE-COLOR product it will be very simple, because it is already pre-dosed in the right shade.

- A wide variety of colours, which you can also mix together to generate other shades.

WARNINGS

Ventilate the work area. During application, wear protective clothing such as gloves, goggles and a mask suitable for the product. Wash the stamping mats with water and detergent at the end of the work.

STORAGE

The product in its original, intact container has a shelf life of 12 months.

PACKAGING

20 litre can

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof, according to Design Systems systems. The methods applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. However, for uses other than those indicated, preliminary tests are recommended. In any case, Design Systems Srl accepts no responsibility for damage or defects caused by the use of its products, since the conditions of use are not under its control. It also advises that its technical service is available to customers for any information concerning the correct use of its products.