DESIGN SYSTEMS

TECHNICAL DATA SHEET COLORSTYLE
CEMENTITIOUS COLOURANT

DESCRIPTION

The STAMPED PLASTER (INTONACO STAMPATO) “Wall System” uses 5 products:

- Starmix, white pre-mixed plaster
- Pemid, which is added to the mix with the Starmix
- Retop, a release agent that prevents the stamping mats from sticking to the Starmix mortar
- Protewall, which protects the surface from atmospheric agents.
- ColorStyle, a colouring product which, with its 7 different shades, gives an antiqued effect and greater strength to the finished product

GENERAL INFORMATION

With the application of the ColorStyle product, the wall is coloured even before it is stamped, choosing the shade from the colour chart or creating it by mixing several colours together. For greater protection of the STAMPED PLASTER, it is advisable to apply the ColorStyle product over the whole surface, so as to protect and strengthen the entire work. Thanks to its composition, ColorStyle has good breathability. It is also resistant to weathering, ultraviolet rays, water and atmospheric agents in general. Because of all these characteristics, it is used to colour, shade and harden the surface of the Stamped Plaster both indoors and outdoors. The product has excellent resistance to UV rays and abrasion.

APPLICATION METHOD

Mix the product with approximately 45% water, stirring the ColorStyle until a homogeneous mix is obtained, with a viscosity suited to the tool used, preferably mixed with a whisk fitted to a drill. The ColorStyle product is applied by roller, with brushes or, better still, by spray, etc.

- The ColorStyle product must be applied wet-on-wet after the application and trowelling of the Starmix (cementitious pre-mix); if a surface crust forms, wet the surface thoroughly by spraying and trowel until the surface layer is completely softened again, then colour with the ColorStyle product.
- Spread a ColorStyle colour mix over the Starmix, uniformly over the surface (to obtain a single shade) or several ColorStyle colour mixes, applying them in areas (to achieve shades of various tones and natural effects); trowel the surface before stamping. It is important to carry out the stamping while both the Starmix and the ColorStyle are still fresh, in order to avoid possible cracks in the applied mixes; if the ColorStyle product has dried excessively, spray a little water on the surface and trowel until the surface layer is completely softened, then stamp immediately afterwards.
- On the following day or after several days (do not exceed two days, depending on the temperatures), further colouring (for example of the joints) or repairs can be carried out with ColorStyle, using brushes or sponges.

- The above indications refer to temperatures of around 20°C; in any case, the working times are dictated by the temperatures.

Stamping

Stamping is carried out using rubber stamping mats previously wetted with the Retop product, which prevents the ColorStyle from sticking to the mat. Wet and trowel the surface with a steel finishing trowel before stamping, completely softening the surface layer; it is important that no surface cracks appear, although these can be repaired immediately after stamping or even on the following day. Once the whole surface has been stamped with the chosen pattern(s), the product is left to dry and, depending on the temperatures, it is finished on the same day or the following day using Design Systems engraving tools. Stamping, by lowering the level of the Starmix mortar, can create micro-cracks, as can wind and/or high temperatures. These micro-cracks do not create structural problems for the product and can be repaired by closing them with the Starmix product or with ColorStyle. The ColorStyle product can also be used for grouting between one stone and another, using the product as is or adding about 2 kg (8%) of ColorStyle to a 25 kg bag of Starmix product.

Protection of the substrate

Once finished, the Stamped Plaster must be protected with the Protewall product applied by spray, brush or roller, taking care to avoid runs.

Field of use

With the application of the ColorStyle product, the wall is coloured even before it is stamped, choosing the shade from the colour chart or creating it by mixing several colours together. For greater protection of the STAMPED PLASTER, it is advisable to apply the ColorStyle product over the whole surface, so as to protect and strengthen the entire work. Thanks to its composition, ColorStyle has good breathability. It is also resistant to weathering, ultraviolet rays, water and atmospheric agents in general; because of all these characteristics it is suitable for both indoor and outdoor environments.

COVERAGE

With 1 kg of product approximately 6 m^2 can be covered, but this consumption can change completely depending on the type of colouring carried out.

STORAGE

Store the product at temperatures above 5°C.

PACKAGING

5 kg bag.

DESIGN SYSTEMS

The information contained in this data sheet is based on the best practical or laboratory experience as at the date shown above. We cannot therefore guarantee that it is exhaustive, since the use of the product is not under our direct control. It is the Customer's responsibility to verify that the product is suitable for its intended use. Design Systems reserves the right to change this information without notice. The user is required to ensure that this information is suitable and complete in relation to the specific use to be made of it. This data sheet cancels and replaces all previous editions. Design Systems recommends always carrying out tests before applying the product, in order to ensure the suitability of the product itself.