DESIGN SYSTEMS

TECHNICAL DATA SHEET PROTEWALL
PROTECTIVE POLYMER RESIN

DESCRIPTION

Protewall consists of an aqueous dispersion of a synthetic copolymer with high stability in alkaline environments, specially modified for the protection of cementitious mixes. The special formulation makes it possible to obtain highly adhesive, elastic films that facilitate and improve bonding to the substrate on all the surfaces to which it is applied.

GENERAL INFORMATION

Protewall comes in the form of a viscous, milky liquid. The hardened films obtained with Protewall have remarkable elasticity and excellent resistance to alkalis, and can no longer be re-emulsified in either cold or hot water. These characteristics guarantee the durability of the bond over time under the most severe conditions. Protewall makes the treated surfaces permeable and breathable, rendering them inert to the action of oils, solvents and many chemical products. Resistant to weathering.

TECHNICAL DATA			
Chemical nature	Styrene resins	Density	min. 1,020 kg/dm^3
Appearance	Viscous liquid	Solubility in water	Fully soluble
Colour	Milky white		

APPLICATION METHOD

Once finished, Stamped Plaster (Intonaco Stampato) must be protected with the Protewall product applied by spray, brush or roller, taking care to avoid runs.

Protewall must be applied on substrates that are perfectly clean, sound and free from loose material, free from oil, grease, wax, lime paint, water films and any other anti-adhesive material.

Polimero 20 and the mixes containing it must be applied at temperatures not below +2°C.

It is important to stir from time to time to restore the homogeneity of the product.

WARNINGS

Protewall is a harmless product on contact with the skin, but it tends to harden quickly, so it must be removed immediately with water; if it has hardened, wash thoroughly with soap and water, avoiding the use of solvents. In case of contact with eyes, wash immediately and thoroughly with fresh water. Do not release the product or its container into the environment. Do not ingest. Keep out of reach of children.

COVERAGE

On smooth or slightly porous substrates, consumption is 100 - 200 g/m^2

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it

STORAGE

Protewall is sensitive to frost and excessively high temperatures, so it must be stored at temperatures between 0°C and 50°C. In the original, tightly closed containers, stored under the stated conditions and protected from strong sunlight, the shelf life is 12 months from the date of the transport document.

Store in a protected, dry place.

PACKAGING

10 kg plastic drum.

The information contained in this data sheet is based on the best practical or laboratory experience as at the date given above. We cannot therefore guarantee that it is exhaustive, since the use of the product is not under our direct control. It is the Customer's responsibility to check that the product is suitable for its intended use. Design Systems reserves the right to change this information without notice. The user is required to ensure the suitability and completeness of this information in relation to the specific use to be made of it. This data sheet cancels and replaces any previous edition. Design Systems recommends always carrying out tests before applying the product, in order to ensure the suitability of the product itself.