DESIGN SYSTEMS

TECHNICAL DATA SHEET CERA MT

DOUBLE CROSS-LINKING PROTECTIVE METALLISED POLISHING WAX – GLOSSY OR MATT

DESCRIPTION

CERA MT, available in glossy and matt versions, is a double cross-linking metallised wax with very high resistance, designed specifically for the protection of resin floors. The double cross-linking binds all the components of the film together, creating an excellent protective layer, particularly flexible and resistant, which reduces the risk of deterioration and soiling of the surface (scratches, smears, shoe marks, etc.). The protection gives very high tolerance to traffic and washing, even with strong detergents and alcohol.

- Double cross-linking: flexible and highly resistant film.
- Reduces scratches, smears and shoe marks; eliminates floor "dusting".
- Film classified as "slip resistant" (compliant with the CSMA/USA standard).
- Suitable for antistatic PVC floors: does not alter their conductivity.

In addition to resin surfaces, CERA MT is also suitable for protecting, reviving and polishing all other types of floors (marble, granite, wood, PVC, rubber, terrazzo, linoleum, single-fired tiles, etc.), on which it makes routine cleaning easier and, where present, eliminates that annoying floor "dusting".

USES

Specifically for resin floors and coatings. For all types of floors in stone, marble, granite (not lead-polished), terracotta, wood, parquet, cementitious surfaces, etc. Synthetic surfaces (linoleum, PVC, rubber), resin surfaces (epoxy, polyurethane, etc.). Antistatic floors. For indoor use.

SUBSTRATE PREPARATION

Wash and degrease the surface thoroughly with detergents that do not contain traces of wax or similar substances, and rinse abundantly. The surface must be perfectly dry, clean and free from any source of detachment (dust, grease, oils, dirt in general).

APPLICATION

CERA MT is ready to use. Pour a small quantity of product onto the floor and spread it evenly using a wax applicator or a normal microfibre flat mop (single cloth). Wait at least 1 hour (2 for marble and granite floors), making sure the product has dried completely, then apply a second coat and, if necessary, a third. Better adhesion on marble and granite surfaces is obtained by applying, two days after the first treatment, a further coat of CERA MT with a high-speed machine fitted with a cream pad.

The final coverage of the product is 40-70 g/m^2 depending on the porosity of the substrate.

PRODUCT DATA

DESCRIPTION	RESULT
Product type	Single-component, ready to use

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it

Appearance	White liquid
Final appearance of the surface	Glossy or matt, depending on the version
pH	8,4 ± 0,2
Specific gravity	1,036 g/l
Dry matter	25%
Active substance	29%
Coefficient of friction (ASTM 2447/75)	0,56
Water solubility	Soluble
Flammability	Non-flammable
Packaging	5 l
Storage	1 year, in a dry place at a temperature between +5°C and +35°C

APPLICATION DATA AND TIMES

DESCRIPTION	RESULT
Drying time	approx. 30-45 min
Overcoating time	approx. 60 min (2 hours for marble and granite)
Minimum application temperature	+5°C
Average final consumption	Depending on the absorption of the substrate, approx. 40-70 g/m^2
Application tools	Wax applicator or single-cloth microfibre flat mop
Tool cleaning	Water

WARNINGS

Sensitive to frost: do not apply at temperatures below +5°C. Store in a dry place at a temperature between +5°C and +35°C. Check adhesion and spreadability beforehand on paraffin-treated PVC floors.

Irritating to the eyes: in case of contact, rinse abundantly with water and, if necessary, seek medical advice. Use latex gloves. Keep out of reach of children. Do not dispose of the container in the environment after use.

SPECIFICATION CLAUSE

Glossy protective treatment based on high cross-linking wax for resin, terracotta, marble, granite, ceramic, PVC, linoleum, wood and stone floors, including those subject to heavy traffic, with CERA MT applied by wax applicator or microfibre flat mop at a rate of 40-70 g/m^2.

DESIGN SYSTEMS

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof, according to Design Systems systems. The methods applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. However, for uses other than those indicated, preliminary tests are recommended. In any case, Design Systems Srl accepts no responsibility for damage or defects caused by the use of its products, since the conditions of use are not under its control. It also advises that its technical service is available to customers for any information concerning the correct use of its products.

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it