DESIGN SYSTEMS

TECHNICAL DATA SHEET COLORPASTA W
PIGMENTED PASTE IN AQUEOUS DISPERSION

DESCRIPTION

COLORPASTA W is a pigmented paste in aqueous dispersion with high compatibility and stability, suitable for various resin systems, including alkaline ones. It can be formulated with reference to the RAL chart or to the main colour coding systems; suitable for use in tinting systems.

COLORPASTA W is available in a complete range of colours with inorganic and organic pigments, highly stable to light and in alkaline environments.

- Concentrated colouring paste with high compatibility.
- Free from solvents and plasticisers, formaldehyde-free, APE-free.
- Inorganic and organic pigments with high stability to light and alkaline environments.

A specific "40 Colori Design Systems" colour chart is available, containing a targeted selection of shades in line with the demands of contemporary design; next to the colour code, the light reflectance value (LRV) is given, which, together with the gloss of the finishing product, can contribute to LEED NC 4.1 credits "EQc6 – Interior Lighting" under the "Indoor Environmental Quality" chapter. For further details, consult the Design Systems LEED Compliance document.

USES

COLORPASTA W is particularly suitable for colouring non-pigmented water-based finishing systems. It is also perfectly compatible with water-based skim coats and self-levelling compounds. It is also used for pigmenting PU-cement systems or for lightening intrinsically dark epoxy-cement base coats.

COLORPASTA W is suitable for the development of highly reliable tinting systems.

APPLICATION

General instructions

Before using COLORPASTA W, it is always necessary to mix thoroughly in order to homogenise any sediment.

Method of use

For the methods of incorporation and the percentages of use, consult the technical data sheets of the specific products. If COLORPASTA W is to be used in systems other than Design Systems ones, careful assessments and preliminary compatibility tests are essential.

For outdoor applications, take care to select suitable shades. In such cases, contact the Design Systems technical service.

PRODUCT DATA

DESCRIPTION	RESULT

Colour	On request according to the RAL chart or the main coding systems (check the feasibility of the colour with the Design Systems technical service). For design purposes, the "40 Colori Design Systems" colour chart is available.
Consumption	Depends on the product and the degree of coverage required
Specific gravity (at 25°C)	1,10 – 1,90 g/ml
Viscosity (at 25°C)	100 – 4.000 mPa · s (Brookfield viscometer)
pH (at 25°C)	Between 7 and 11
Flash point	Not applicable
Tool cleaning	Water
Storage	8 months, in a dry place at a temperature between 5°C and 35°C

WARNINGS

Different production batches of the same colour may show slight differences: where possible, use material from a single production batch. In the case of paint products, yellow, orange and some red shades may require several coats to achieve a good covering effect (in some cases a first coat in white is recommended). Some colours based on organic pigments (reds, blues, greens, intense yellows, etc.) tend to release colour when subjected to abrasion, whether dry or wet: in these cases it is advisable to protect the colour with a coat of transparent finish.

It is advisable to check the colours in daylight and/or under the lighting of the room in which they will be used for a better result and, if necessary, to make the choice on the basis of physical samples.

Product for professional use: the purchaser undertakes to strictly follow the warnings given above when applying the purchased product, as well as the instructions in the safety data sheet.

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof, according to Design Systems systems. The methods applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. However, for uses other than those indicated, preliminary tests are recommended. In any case, Design Systems Srl accepts no responsibility for damage or defects caused by the use of its products, since the conditions of use are not under its control. It also advises that its technical service is available to customers for any information concerning the correct use of its products.

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it