DESIGN SYSTEMS

TECHNICAL DATA SHEET CORPAV
COLOURED DRY-SHAKE HARDENER

DESCRIPTION

Corpav dry-shake colour hardener is a pre-mixed compound ready for professional use, available in various colour shades, and is a product created specifically for the construction of stamped concrete floors, although it is very often used in other applications such as industrial floors.

Corpav dry-shake colour hardener is a blend consisting mainly of three ingredients (certified Portland-type cement, silica-based spheroidal quartz, synthetic-mineral oxide pigments) plus specific additives. This compound has the ability to improve the concrete surface and increase its wear resistance.

GENERAL INFORMATION

Colours: 21 standard, other colours available to order (minimum 10 quintals)

Resistance to UV rays – excellent

Resistance to abrasion – excellent

Store the product at temperatures above 5°C; the product must be used within 6 months. The colours of the Corpav product may show slight colour variations from batch to batch and depending on the concrete and/or the combination of hardener and release agent. In summer, the sun's rays can cause the colour to vary during trowelling.

The best product to use both indoors and outdoors, e.g.: driveways, roads, pavements, terraces, pool surrounds, ramps, squares, shopping and industrial centres, and any other place requiring a floor that is attractive, durable over time, unique and customisable.

REFERENCE TABLE

RECOMMENDED QUANTITIES ACCORDING TO REQUIREMENTS			
Dark colours and light traffic	2,5 – 3 kg/m^2	Light colours and heavy traffic	4,5 – 5 kg/m^2
Medium colours and medium traffic	3,5 – 4 kg/m^2		

In any case, never exceed 6 kg/m^2

APPLICATION METHOD

It is essential to broadcast the dry-shake hardener onto the fresh, damp concrete, trowel it with the special Design Systems tools and repeat the operation until the planned dosage or colouring is achieved. Do not use the product below 5°C. Do not use the product when it is raining, unless there is adequate cover. The quantity of product to be used is governed by two factors: one is the traffic it has to withstand and the other is the colour chosen for the floor. Bear in mind that if several shades of Corpav hardener are applied (known as: shaded stamped floor), the shades and colour intensity will differ according to the size of the floor to be made.

DESIGN SYSTEMS

WARNINGS

The product must be used with suitable masks, taking care to avoid contact with the skin, eyes, mucous membranes, etc.; in such cases, wash the affected part thoroughly with soap and water and seek medical advice. When working in enclosed spaces, provide adequate ventilation. The use of protective gloves and masks is recommended. Keep out of reach of children.

PACKAGING

25 kg bag

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof, according to Design Systems systems. The methods applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. However, for uses other than those indicated, preliminary tests are recommended. In any case, Design Systems Srl accepts no responsibility for damage or defects caused by the use of its products, since the conditions of use are not under its control. It also advises that its technical service is available to customers for any information concerning the correct use of its products.