DESIGN SYSTEMS

TECHNICAL DATA SHEET DS-F
POLYPROPYLENE FIBRES

DESCRIPTION

DS-F fibres are a product used mainly to reduce the plastic shrinkage of concrete, the main cause of micro-cracks. They are also used to reinforce concrete and increase its resistance to wear and impact.

GENERAL INFORMATION

One bag per m^3 of concrete	
Material	Polypropylene
Colour	White
Resistance to acids	Good
Resistance to the chemical agents present in the mixes	
Tensile strength	400 ÷ 500 MPa

APPLICATION METHOD

DS-F fibres are added to the concrete in the truck mixer on arrival at the site. Mix the whole batch for at least 5 minutes.

PACKAGING

0,9 kg bag

Fibre length 18 mm

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof, according to Design Systems systems. The methods applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. However, for uses other than those indicated, preliminary tests are recommended. In any case, Design Systems Srl accepts no responsibility for damage or defects caused by the use of its products, since the conditions of use are not under its control. It also advises that its technical service is available to customers for any information concerning the correct use of its products.

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it