DESIGN SYSTEMS

TECHNICAL DATA SHEET DS-R
POWDER RELEASE AGENT

DESCRIPTION

DS-R release agent is a compound of water-repellent powders, oxides and other additives, created for producing stamped concrete floors. It is used mainly for two purposes: the first is to prevent the rubber stamping mats from sticking to the still-fresh concrete hardened with DS-H product; the other is to give an antiqued effect in a different colour from the hardened concrete, thus recreating a stone effect.

GENERAL INFORMATION

Product available in 15 standard colours. DS-R release agent has excellent resistance to UV rays.

Definitely the best product to use outdoors, for example: driveways, roads, pavements, terraces, pool surrounds, ramps, squares, shopping and industrial centres, and any other place requiring a floor that is attractive, long-lasting, unique and customisable. Store the product at temperatures above 5°C.

APPLICATION METHOD

Mix the product before use. Broadcast the DS-R evenly over the concrete surface previously coloured with DS-H. Clean the floor a few days after pouring, once the pattern has been made, depending on the seasonal temperatures, which may vary from the day after to four days after pouring, washing with a pressure washer and paying attention to cleaning the gaps. Do not apply it to the surface when it is raining or during bleeding (water rising to the surface), or at temperatures below 5°C. Do not trowel the surface with tools after the product has been applied. The DS-R product, applied on a more or less damp dry-shake colour hardener, can create different antiqued effects.

COVERAGE

One pack is sufficient for approximately 100 m^2.

WARNINGS

The product must be used with suitable masks, taking care to avoid contact with the skin, eyes, mucous membranes, etc. In such cases, wash the affected part thoroughly with soap and water and consult a doctor. When working in enclosed spaces, ensure adequate ventilation. The use of gloves and protective masks is recommended. Keep out of the reach of children.

PACKAGING

12,60 kg plastic tub.

Design Systems Srl | Via Dorando Petri,1 | 00011 Tivoli Terme (RM) | Italy | Tel .+39 0774/379782 | Fax +39 0774/378092
www.designsystems.it | info@designsystems.it

DESIGN SYSTEMS

The technical data given in this bulletin were obtained using standardised tests and standards, or modifications thereof according to Design Systems methods. The procedures applied may be requested from our technical service. The contents of this technical bulletin represent the best of our knowledge and experience. For uses other than those indicated, it is nevertheless advisable to carry out preliminary tests. In any case, Design Systems Srl accepts no liability for damage or defects caused by the use of its products, as the conditions of use are beyond its control. It also informs that its technical service is available to customers for any information concerning the correct use of its products.