DESIGN SYSTEMS

TECHNICAL DATA SHEET STAICOLOR
COMPOUND OF WATER AND METALLIC-SALT-BASED SOLUTIONS

DESCRIPTION

The StainColor product is a compound of water and metallic-salt-based solutions created for producing artistic floors. The StainColor product, for professional use, is specifically designed for colouring cured surfaces, old or new, made of concrete or cement-based materials. The StainColor chemical compound creates uneven stains and mottling in colour tones directly influenced by the substrate.

StainColor floors, thanks to their strength, beauty and ease of cleaning, are ideal for shops, offices, homes, shopping centres, etc.

GENERAL INFORMATION

The final appearance of the floor is influenced by many factors (such as the colour of the surface, the porosity, the mix and age of the concrete, the preparation methods, the different techniques of application of the StainColor product, etc.); therefore the result obtained will be unique and unrepeatable, even after sampling on another surface.

IMPORTANT

The use of some light StainColor colours is recommended for indoor use only; moreover, on industrial floors the laying of a polyethylene sheet as a vapour barrier must also be planned for. In the case of an industrial floor without a vapour barrier, DS-TIXCEM or DS-LIVCEM can be applied, which allow the use of light StainColor colours. The product does not eliminate any imperfections in the surface.

The strength of the StainColor floor is provided by the base concrete, by its dry-shake surface hardener, as well as by the protective resin

APPLICATION METHOD

It is essential to apply the product on a concrete surface that has been well cured for about 20 days, or on our DS-TIXCEM or DS-LIVCEM products, in which case the treatment can be carried out on the day after they are laid. In the case of floors with figures or patterns, these must be made before the StainColor is applied. After the treatment with StainColor, clean the surface with water and hydrochloric acid. Then wet the surface thoroughly, remove any standing water and proceed with colouring by spray, brush or other means, repeating the operation according to the colour tone to be achieved. Then wash the surface with water and detergent. Finally, protect the StainColor floor with acrylic or polyurethane resin as required.

MAINTENANCE

Wash the floor again and, once dry, re-protect it with DS-CS transparent resin (Methacrylic Resin) or with DS-P or DS-REPOTEK (Polyurethane Resins). Carry out maintenance after a few years, or many more, depending on the type of traffic the floor has to withstand. The surface can also be maintained with conventional floor

wax, applied periodically. To obtain a long-lasting floor, it is recommended to use only Design Systems products and qualified labour, and good-quality concrete.

WARNINGS

The product must be used taking care to avoid contact with the skin, eyes, mucous membranes, etc.; in such cases, wash the affected part thoroughly with soap and water and consult a doctor. When working in enclosed spaces, ensure adequate ventilation. The use of gloves and protective masks is recommended. Keep out of the reach of children.

STORAGE

Shelf life: approximately one calendar year.

Keep at a temperature below 30°C.

PACKAGING

5 litre canister.

20 litre canister.

The information contained in this data sheet is based on the best practical or laboratory experience as at the date shown above. We cannot therefore guarantee that it is exhaustive, since the use of the product is not under our direct control. It is the Customer's responsibility to verify that the product is suitable for its intended use. Design Systems reserves the right to change this information without notice. The user is required to ensure that this information is suitable and complete in relation to the specific use to be made of it. This data sheet cancels and replaces all previous editions. Design Systems recommends always carrying out tests before applying the product, in order to ensure the suitability of the product itself.