

HTML

```
<h1>Grade Calculator</h1>
<p>Enter number of course: <input type="number" name="num" id="textNum">
<button id="btnSubmit">Submit</button></p>
<div id="listCourse"></div>
<div>
<button id="btnCalculate" style="display:none">Calculate Grade</button>
<span id="totalMarks"></span>
</div>
```

Javascript

```
const btnSubmit = document.querySelector('#btnSubmit');
const btnCalculate = document.querySelector('#btnCalculate');
const textNum = document.querySelector('#textNum');
btnSubmit.addEventListener('click', addCourse);
btnCalculate.addEventListener('click', calculateGrade);

function addCourse() {
    let num = parseInt(textNum.value);
    if (textNum.value == "" || num > 7) {
        alert("Please enter valid number of course");
        return;
    }
    txt = "";
    for (i = 0; i < num; i++) {
        txt += '<p>Course ' + (i + 1) + ': <input type="text" class="name" placeholder="Course name" size="30"> <input type="number" class="marks" placeholder="Marks (%) " min="1" max="100"></p>';
    }
    document.querySelector('#listCourse').innerHTML = txt;
    btnCalculate.style.display = "block";
}

function calculateGrade() {
    let num = parseInt(textNum.value);
    let listMarks = document.querySelectorAll('.marks');
    totalMarks = 0.0;
    avgMarks = 0.0;
    grade = "";
    listMarks.forEach(marks => totalMarks += parseFloat(marks.value));
    if (totalMarks > 0) {
        avgMarks = totalMarks / num;
        if (avgMarks >= 80)
            grade = "A";
        else if (avgMarks < 80 && avgMarks >= 70)
            grade = "B";
        else if (avgMarks < 70 && avgMarks >= 50)
            grade = "C";
        else if (avgMarks < 50)
            grade = "Fail";
        document.querySelector('#totalMarks').innerHTML = "<h2>Total marks: " + avgMarks.toFixed(1) + "</h2><h2>Grade: " + grade + "</h2>";
    }
}
```