

Laboratory Exercise 6

cpe 357 Fall 2022

Due by (or before) 11:59pm, Thursday, November 10th.
The program is to be done individually.

Laboratory Exercises

This is a chance to get some experience with signals and timers.

1. There's one task for this week: Write a program, `timeit`, that acts as a simple count-down timer using the interval timer to keep track of the passage of time.

The timer takes a single command-line argument indicating the number of seconds to count down and counts down to zero in half-second increments printing “Tick...” on odd half-seconds and “Tock\n” on even ones. When time's up it prints “Time's up!\n” and ends. Since an example is worth a whole mess of words, consider the following example:

```
% ./timeit 2
Tick...Tock
Tick...Tock
Time's up!
%
```

Note that the last “Tock” will come immediately before the “Time's up!”

Details

- If the argument is missing, not a number, or less than zero, `timeit` should print a usage message and exit with nonzero status.
- `timeit` must use `setitimer(2)` to generate the `SIGALRMs` for each clock tick. Because the display requires half-second accuracy, the granularity of the timer must be finer than one tick per second. There's really no reason to tick faster than that, though.
- Be a good computing citizen: Don't just spin while waiting for signals. Use `pause(2)` or `sigsuspend(2)`.

Tricks and Tools

You should probably look into the functions and system calls in Figure 1.

Debugging a program with asynchronous events can be very tricky. Remember also that while debugging, you can also generate `SIGALRMs` via `kill(1)` rather than from the timer.

Caution: If you are working remotely you may not see the behavior you expect because remote operation adds another layer of potential buffering. This is particularly true when using `ssh`, because `ssh` uses block-ciphers for its secure link. Plain old-fashioned net-lag can have the same effect, though. If you experience bursty behavior, you may want to go to the lab in person and work at the console to be sure you are seeing what you think you are seeing.

Also, **remember that `stdio` is buffered.** If you write something to the console with `putchar()` or `printf()`, it may not appear immediately. You should either use unbuffered writes, or flush the output stream after writing.

getitimer(2) setitimer(2)	for getting and setting the system interval timer
sigaction(2)	the POSIX reliable interface for signal handling
sigprocmask(2)	for manipulating the blocking or unblocking of particular signals
sigemptyset(3) sigfillset(3) sigaddset(3) sigdelset(3) sigismember(3)	for manipulating signal sets used by <code>sigaction(2)</code> and <code>sigprocmask(2)</code>
strtol(3) sscanf(3)	for converting the command-line arguments
fflush(3)	to flush a stdio stream
pause(2)	Suspend execution until a signal is delivered
sigsuspend(2)	Temporarily replace the procmask and suspend execution until a signal is delivered

Figure 1: Useful system calls and library functions

What to turn in

For the Laboratory Exercises: Submit the program described above to the `lab06` directory of `pn-cs357` via handin.

A makefile (called `Makefile`) that will build your program when given either the target “`timeit`” or just “`all`”.

A README file that contains:

- Your name(s). In addition to your names, please include your Cal Poly login names with it, in parentheses. E.g. (`pnico`)
- Any special instructions for running your program.
- Any other thing you want me to know while I am grading it.

The README file should be **plain text**, i.e, **not a Word document**, and should be named “`README`”, all capitals with no extension.

Sample Runs

Since the execution of the program evolves over time it’s difficult to give the full effect. I’ve included some examples below, but I will also place an executable version on the CSL in `~pn-cs357/demos` so you can run it yourself.

```
% timeit 23skedoo
23skedoo: malformed time.
usage: timeit <seconds>
% timeit one hour
usage: timeit <seconds>
% timeit 3
Tick...Tock
Tick...Tock
```

Tick...Tock
Time's up!
%