


A5013249 **HEAT TREATMENT & FINAL FINISH** PHYSICAL PROPERTIES JUNE 1.1931 Y. P. RED. REVISIONS SCL. HEAT TREAT .003 TO.005 T. S. C. C. 12 5-10-48 BR. TYPE I FINISH, CLASS B EL 2 ROCK DRG. PERTAINS TO .19-30NS-3-144235 30 BMG M1944 (FXD) M1944 (FLEX) M1946 B7132923 .165 INSCRIBE PART NO. DO NOT **→.050 TOLERANCE ON DIMENSIONS** NOT OTHERWISE SPECIFIED DECIMAL ± .005 -.505 FRACTIONAL ± -ANGULAR ± 50 TRACER L'D'G DRAFTSMAN 0.K. CHIEF DRAFTSMAN SCREW, LOCKING, FRONT SIGHT BRACKET
STEEL FS X 1315 5013249 SUBMITTED: FINISH 125/ ORD. DEPT.. U. S. A. APPROVED BY ORDER OF THE CHIEF OF ORDNANCE: WAS A13249 SCALE 4 ORD. DEPT., U. S. A. 5013249 ORDNANCE DEPT., U. S. A.



A 5156881 **HEAT TREATMENT & FINAL FINISH** PHYSICAL PROPERTIES MARCH 10, 1939 **REVISIONS** Y. P. RED. SCL. TYPE II FINISH, CLASS B 6 5-10-48 T. S. EL 2 ROCK NOTE: A .249-.002 DIA HARDENED AND GROUND STEEL BALL MAY DRG. PERTAINS TO BE USED AS AN ALTERNATIVE .30 BMG M19A4 (FXD) M19A4 (FLEX) M19A6 B 144235 METHOD OF MANUFACTURE. B7132923 BREAK CORNER SPHERICAL-INSCRIBE PART NO. DO NOT .312-.005-TOLERANCE ON DIMENSIONS .249-.002 NOT OTHERWISE SPECIFIED DECIMAL ± -FRACTIONAL ±-ANGULAR ±-DRAFTSMAN TRACER L'D'G DRAFTSMAN HOC. O.K. CHIEF DRAFTSMAN Source PLUNGER FRONT SIGHT 5)56881 SUBMITTED: FINISH 63/ ORD. DEPT., U. S. A. APPROVED BY ORDER OF THE CHIEF OF ORDNANCE: WAS A 156881 SCALE 2 ORD. DEPT., U. S. A. A 5156881 ORDNANCE DEPT., U.S. A.

A5156882

							ASISOCOE			
HEAT TREATMENT & FINAL FINISH	PHYSICAL PROPERTIES					_	MARCH 10,1939			
DRAW AT 450°F	Y. P.	SCL.		REVISIONS						
TYPE I FINISH, CLASS OSC	T. S.	BR.	X			8	5-10-46			
BAKE ONE HOUR AT 300-350°F	EL 2	ROCK				1-				
DIAMETER OF WIRE— TOTAL NUMBER OF COILS— OUTSIDE DIAMETER PREE— MAX OUTSIDE DIA AT MIN OPERATING HEIGHT— FREE LENGTH— TYPE OF ENDS— WOUND— MEAN ASSEMBLED HEIGHT— MIN LOAD AT MEAN ASSEMBLED HEIGHT— MINIMUM OPERATING HEIGHT— MIN LOAD AT MINIMUM OPERATING HEIGHT—			-15 224±.004 230 -1.00±.03 - SQ.AND GROUND -R.H. 593 -9.75 LB 527			B7	DRG. PERTAINS TO B 144235 B7132923 INSCRIBE PART NO DO NOT		984 (FXD) 984 (FXD) 984 (FLEX) 986	
LB PER INCH OF SPRING DEFLECTION SPRING FUNCTIONS IN HOLE CALCULATED MAXIMUM SOLID HEIGHT CAUTION: DO NOT COMPRESS SOLID.				24			TOLERANCE ON DIMENSIONS NOT OTHERWISE SPECIFIED DECIMAL ± — FRACTIONAL ± — ANGULAR ± —			
						W.L.M. E.B. CHIEF DRAFTSMAN				
SPRING, FRONT SIG SPRING STEEL WIRE (WDIO85 SPECIAL-CLASS A				(5136682			SUBMITTED: APPROVED BY ORDER OF THE CHIEF			
		_			WAS A156882			OF ORDNANCE: Walter Askersean ORD. DEPT., U. S. A.		
	5156882			ORDNANCE DEPT., U. S. A.						

MADE AT ROCK ISLAND ARSENAL

A5156883 PHYSICAL PROPERTIES MARCH 10,1939 **HEAT TREATMENT & FINAL FINISH REVISIONS** Y. P. RED. TYPE I FINISH, CLASS B T. S. BR. 8 5-10-48 EL. 2 ROCK DRG. PERTAINS TO 144 235 30 BMG M 1944 (FXD) M 1944 (FLEX) B7132923 .035 x 45° M 19A6 INSCRIBE PART NO. DO NOT TOLERANCE ON DIMENSIONS -.050 NOT OTHERWISE SPECIFIED DECIMAL ± .005 FRACTIONAL: -.255-ANGULAR ± 5° DRAFTSMAN TRACER L'D'G DRAFTSMAN HOC. O.K. CHIEF DRAFTSMAN SUBMITTED: STEEL FSX 1315 FINISH 125 ORD. DEPT., U. S. A. APPROVED BY ORDER OF THE CHIEF OF ORDNANCE: WAS A 156883 SCALE 2 5156883 ORDNANCE DEPT., U. S. A.

A5156884 **HEAT TREATMENT & FINAL FINISH** PHYSICAL PROPERTIES MARCH 10,1939 Y. P. RED. SCL. **REVISIONS** TYPE I FINISH, CLASS B T. S. BR. 7 5-10-48 EL 2 ROCK DRG. PERTAINS TO 104-005 144235 30 BMG MI9A4 (FXD) MI9A4 (FLEX) B7132923 MISAG .193-.002-.190-32NF-3 .045 INSCRIBE PART NO. DO NOT .01 +.01 X 45° .310-.005 TOLERANCE ON DIMENSIONS NOT OTHERWISE SPECIFIED DECIMAL ± .005 FRACTIONAL ± -ANGULAR ± 5° DRAFTSMAN TRACER L'D'G DRAFTSMAN H.D.C 0. K. CHIEF DRAFTSMAN SCREW, BEARING, FRONT SIGHT (
STEEL FSX 1315
FINISH 125 OTHER SURFACES, AS SPECIFIED SUBMITTED: APPROVED BY ORDER OF THE CHIEF OF ORDNANCE: WAS A 156884 Walter acker SCALE ? ORD. DEPT.. U. S. A. A 5156884 ORDNANCE DEPT., U. S. A.

A7110440 **HEAT TREATMENT & FINAL FINISH** PHYSICAL PROPERTIES JANUARY 31,1944 Y. P. RED. **REVISIONS** TYPE II FINISH, CLASS B T. S. 3 5-10-48 EL 2 ROCK DRG. PERTAINS TO 144235 M1944 (FXD) M1944 (FLEX) M1946 87132923 INSCRIBE PART NO. DO NOT **TOLERANCE ON DIMENSIONS** NOT OTHERWISE SPECIFIED DECIMAL ± -FRACTIONAL ± -ANGULAR ± -L'D'G DRAFTSMAN O.K. WASHER LOCK CHIEF DRAFTSMAN SHAKEPROOF EXTERNAL TOOTH LOCK WASHER NO. 1114-05 OR EQUAL SUBMITTED: ORD. DEPT.. U. S. A. APPROVED BY ORDER OF THE CHIEF OF ORDNANCE: ORD. DEPT.. U. S. A. 7110440 SUPERSEDES A7110440 WO/C 5-10-48 ORDNANCE DEPT., U. S. A.

