

MUSIKWISSENSCHAFTLICHES SEMINAR
DETMOLD/PADERBORN

DETMOLDER HOFTHEATER PROJEKT

Theatre Tool
Systems Design

For Version TheatreTool_1-Dev

https://github.com/Detmolder-Hoftheater/TheatreTool_1-Dev

Contents

I. Introduction	6
II. User Interface Design	6
1. Toolbar	6
1.1. Simple Search	7
1.2. Extended Search	7
2. Navigation Tree	7
3. Tab View	9
3.1. Repertoire Tab	9
3.1.1. Work Section	11
3.1.2. Source Section	13
3.2. Playschedules Tab	16
3.3. Persons Tab	17
3.4. Expenses Tab	20
3.5. Revenues Tab	22
3.6. Press Tab	23
3.7. Feebooks Tab	24
3.8. Directionbooks Tab	25
3.9. Role- & Costumbooks Tab	26
3.10. Subscriptions Tab	27
3.11. Custom Items Tab	28
3.12. Search Results Tab	28
III. Data Design	30
4. DB-Structure	30
5. Property-Files	31
6. MEI and TEI Subsets	33
6.1. Works	33
6.2. Sources	36
6.3. Persons	42
6.4. Playscedules	46
6.5. Expenses	49
6.6. Revenues	52

7. Relation-Diagram	54
IV. Process Design	55
8. getDBStructure.xql	55
9. getRevenuelItems.xql	55
10.getExpensesslItems.xql	55
11.getScheduleslItems.xql	55
12.getCustomlItems.xql	55
13.getWorks.xql	55
14.getSource.xql	55
15.getMonthsForSelectedYear.xql	55
16.getScheduleTable.xql	55
17.getPersonsForSelection.xql	55
18.getPersonOverview.xql	55
19.getIssueNames.xql	55
20.getIssueTable.xql	55
21.getMonthsByRevenueYear.xql	55
22.getRevenueTable.xql	55
23.searchWorks.xql	55
24.searchPersons.xql	55

List of Figures

1. User Interface Design: Tool Bar	6
2. Navigation Tree	8
3. Repertoire Tab	10
4. Work Section	12
5. Repertoire Tab: Source	14
6. Source Section: Single Sources	15

7.	Playschedules Tab	16
8.	Persons Tab: Navigation	18
9.	Persons Tab: Section	19
10.	Expensess Tab	21
11.	Revenues Tab	22
12.	Revenues Tab	23
13.	Revenues Tab	24
14.	Revenues Tab	25
15.	Revenues Tab	26
16.	Revenues Tab	27
17.	Search Results: Works	28
18.	Search Results: Persons	29
19.	DB-Structure	31
20.	Works: Subsets Overviewer	33
21.	Works: TitleStmt Block	34
22.	Works: Identifier Block	34
23.	Works: Language Block	35
24.	Works: PerfMedium Block	35
25.	Works: History Block	36
26.	Sources: Overview	37
27.	Sources: Attributes Block	37
28.	Sources: TitleStmt Block	38
29.	Sources: PubStmt Block	38
30.	Sources: PhysLoc Block	39
31.	Sources: PhysDesc Block	40
32.	Sources: NotesStmt Block	41
33.	Sources: LangUsage Block	41
34.	Sources: Contents Block	41
35.	Sources: RelationList Block	42
36.	Sources: SIngle Source Block	42
37.	Persons: Overview	43
38.	Persons: Idno Block	43
39.	Persons: Name Block	44
40.	Persons: Birth Block	44
41.	Persons: Death Block	45
42.	Persons: Gender Block	45
43.	Persons: Occupation Block	45
44.	Persons: Residence Block	46
45.	Persons: Note Block	46
46.	Playscedules: Overview	46
47.	Playscedules: Facsimile Block	47
48.	Playscedules: Header Block	47
49.	Playscedules: Text Block	48
50.	Expensess: Overview	49

51.	Expensess: Header Block	49
52.	Expensess: Facsimile Block	50
53.	Expensess: Text Block	51
54.	Revenues: Overview	52
55.	Revenues: Header Block	52
56.	Revenues: Facsimile Block	53
57.	Revenues: Text Block	53
58.	Relation-Diagram	54

Part I.

Introduction

The tool is designed for visualizing, loading and searching archived information e.g for theatre in defined time period. The Informations are encoded in the formats of the Text Encoding Initiative (TEI) and Music Encoding Initiative (MEI) and saved in the XML-Database. Database structure and time period can be defined in the property files.

Part II.

User Interface Design

The User interface contains three parts: toolbar with search functions, navigation tree and tabview.

1. Toolbar

Layout




Figure 1: Tool Bar

Action Paths and Results

1. Select an item in "Order Tabs" combobox —> all opened tabs will be reordered; default: "Stapeln". (disabled)
2. Select an item in "Duplicate Tabs" button —> selected tab will be duplicated. (disabled)
3. Select an item in "History Tabs" combobox —> selected tab will be activated; alternative navigation - with arrows.

4. Select an item in "Filter" combobox and enter search term in search field -> select search icon -> a new tab will be opened with search results.
5. Select "Extended" button -> a window will be opened for enter search filters. (disabled)
6. Select an item in "Help" combobox:
 - a) "Data Relation" —> open a windows with data relations diagram;
 - b) "Documentation" —> open a new browser tab with systems design document.

1.1. Simple Search

Simple search function contains a filter field (work title or person name) and search field with search icon as button.

Action Paths and Results

1. Select an item in "Filter" combobox and search field is empty -> select search icon -> a new tab will be opened with all persons or works.
2. Select an item in "Filter" combobox and enter optionally search term in search field -> select search icon -> a new tab will be opened with search results.
3. An item in "Filter" combobox is not selected and search term in search field is entered or empty -> select search icon -> a information window will be opened: "Please select the searchfilter!"
4. If search field are not empty -> select "x" -> clear search field.

Validation and Constraints

1. "Filter" in combobox should be set;
2. Upper case and lower case are equal;
3. For all person names variants and for all work title variants will be searched.

1.2. Extended Search

This function is disabled.

2. Navigation Tree

The Navigation Tree contains two subtrees preliminary called: "Play Operation" and "Management". The "Play Operation" subtree contains information about the theater and its public relations work. The "Management" tab contains any information about the inside organization of the theater.

Layout




Figure 2: Navigation Tree

Action Paths and Results

1. Click for any end-node —> a new tab will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.
2. Click to arrow in title bar -> navigation tree will be hide.
3. If navigation tree is hidden, click to title bar -> navigation tree will be opened for item selection; select an item and cclick to section field -> navigation tree will be hide again. Click arrow to open the navigation tree.

Validation and Constraints

1. "Projectname" and "Timeslot" will be generated from property file: dbStructure.xml.
2. "Repertoire" tabs: show all works with all title variants in alphabetic order.
3. "Playschedules" end nodes are years generated from property file: dbStructure.xml.
4. "Persons" tabs: show all persons with all name variants in alphabetic order.

5. "Press" end nodes are names generated from folder defined in property file: dbStructure.xml.
6. "Revenues" and "Expensess" end nodes are years generated from property file: dbStructure.xml.
7. "Feebooks" end nodes are names generated from folder defined in property file: dbStructure.xml.
8. "Subscriptions" end nodes are names generated from folder defined in property file: dbStructure.xml.
9. Cutom tabs end nodes are name generated from property file: dbStructure.xml.

Data sources and targets

Sources	getDBStructure.xml getRevenueItems.xml getExpensessItems.xml getSchedulesItems.xml getGagenMenu.xml getAboMenu.xml getJournalMenu.xml getCustomItems.xml
---------	---

3. Tab View

Execution

One click for end node in navigation tree, or cklick link in relation data fields in sections, or cklick in search result table row a new closable tab will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

3.1. Repertoire Tab

Execution

Click for "Repertoire" end-node in navigation tree —> a new tab will be opened. Tab contains a content section and navigation tree.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 3: Repertoire Tab

Widgets description

Table tree contains two columns: works -> sources and presons.

First column

Show works with one or more sources. Sources are optional.

Second column

Show all persons for this work. Persons are optional.

Action Paths and Results

1. Click for one work or source —> a new section will be opened.
2. Select "Incipits" item-> a section with incipit will be shown.
3. Select one "Incipit" item-> a window with selected incipit will be opened..
4. Click to arrow in title bar or right side arrow from tree -> navigation tree will be hide.
5. If navigation tree is hidden, click to title bar -> navigation tree will be opened for item selection; select an item and cklick to section field -> navigation tree will be hide again. Click arrow to open the navigation tree.

Validation and Constraints

Work titles are alphabetical sorted. "The", "Der", "Die", "Das", "Le", "La", "L'" are ignored.

3.1.1. Work Section

Execution

Click for one work in "Repertoire" tab navigation tree —> one section will be opened.

Layout

Work: ...

Show XML

Load XML

Title Types

Uniformtitle (language): ...
Titel (language): ...
Alternativetitle (language): ...
Subtitle (language): ...
...

Persons

Profession/Function: Name
Profession/Function: [Name](#)
...

General Data

[Deutschen Nationalbibliothek Page](#)
[Weber-Gesamtausgabe Page](#)
Language(s):
Instrumentation:
Creation:
Description:

Debut Performances

Event	Date	Place	City

Play Operations and Management

Playschedules

Jahr	Monat
...	Monat

Revenues

Year	Months
...	Month

Expenses

Year	Months
...	Month

Press

Title
...

Figure 4: Work Section

Widgets description

Work section contains following sections: "Title Types", "Persons", "Generally Informations", "Playschedules", "Revenues", "Expensess", "Press".

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link in „Persons“ section a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.
4. Click on extern link in „Generally Information“ section a new browser tab with detailed information will be opened. Extern links are "Deutsche Nationalbibliothek" and "Weber-Gesamtausgabe".
5. Click on link in „Playschedules“, or „Revenues“, or "Expensess" table a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Validation and Constraints Only exists data fields will be show.

Data sources and targets

Sources	getWorks.xql
---------	--------------

3.1.2. Source Section

Execution

Click for source in "Repertoire" tab navigation tree —> one section will be opened.

Layout

Source: ...

Show XMLLoad XML

SignaturSingle Sources

Title: ...

Title Types (Work)

Uniformtitle (language): ...

Titel (language): ...

Alternativetitle (language): ...

Subtitle (language): ...

...

Persons

Profession/Function: Name

Profession/Function: [Name](#)

...

General Data

[Répertoire International des Sources Musicales \(RISM\)](#)

Libraries:

Provenance:

Creation:

Summary:

Debut Performances

Event	Date	Place	City
-------	------	-------	------

Figure 5: Source Section

Source: ...

Show XML

Load XML

Signatur

Single Sources

Title	Signatur
Title_1	...
Title_2	...
...	...

Physical Data

Titlepage(s):

Cover:

Scribe:

Condition:

Inventory Number:

Page Number:

Dimension:

Persons

Name

[Name](#)

...

Generally Information

Contents:

Annotations:

Language(s):

Creation:

Summary

Debut Performance

Event	Date	Place	City
-------	------	-------	------

Figure 6: SIngle Source Section

Widgets description

Source section contains tow tabs: Source and Single Sources.

Source tab contains following sections: "Title Types", "Persons", "Generally Informations", "Playschedules", "Revenues", "Expensess".

Single Sources tab contains following sections: "Physical Data", "Persons" and "General Data".

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link in „Persons“ section a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Source tab Click on extern link in „Generally Information“ section a new browser tab

with detailed information will be opened. Extern links is "Repertoire International des Sources Musicales" (RISM).

Validation and Constraints

Only exists data fields will be show.

Data sources and targets

Sources	getSource.xql getSourceDetails.xql getIncipit.xql getIncipitsXML.xql
---------	---

3.2. Playschedules Tab

Execution

Click for "„Playschedules“" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout

Playschedule ...

Show XML

Load XML

Settlement ...

Date	Performances
...	Title_1, Personname
...	Title_2
...	...

Facsimile(s)

Page < 1 ▾ > of ...

Playschedule ...

...

Figure 7: Playschedules Tab

Widgets description

Name	Mandatory/Optional
Settlementl	O
Date Column	O
Performances Column	O

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Validation and Constraints

Section can contains a facsimile area. Facsimile area show one or more pages.

Data sources and targets

Sources	getMonthsForSelectedYear.xql getScheduleTable.xql
---------	--


3.3. Persons Tab

Execution

Click for "„Persons“" end-node in navigation tree —> a new tab will be opened. Tab contains an detailed information section and navigation tree.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout



Persons ...	
Name/Pseudonym	Name Type
Name_1	...
Name_2	...
...	

Figure 8: Navigation in Person Tab

Person: ...

Show XML

Load XML

Name Types

Regular:
Full:
Alternative:
Pseudonym(s):

Generally Information

[Deutschen Nationalbibliothek Page](#)
[Weber-Gesamtausgabe Page](#)
[Virtual International Authority File](#)

Male/Female
Date of Birth
Date of Death
Summary:

Occupation

Date	Function

Residance(s)

Date	City

Play Operations and Management

Works

Source
Work_1

Sources

Source
Source_1

Expensess

Year	Months
...	Month

Revenues

Year	Months
...	Month

Press

Title
...

Feebooks

Title
...

Figure 9: Person Tab

Widgets description

Navigation tree show persons sorted alphabetical. detailed information section contains "Name Types", "Generally Information", "Works", "Sources", "Expensess", "Press", "Feebooks".

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link in navigation tree -> a section detailed information will be opened.
4. Click on name link in tables -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.
5. Click on extern link in „Generally Information“ section a new browser tab with detailed information will be opened. Extern links are "Deutsche Nationalbibliothek", "Weber-Gesamtausgabe" and "Virtual International Authority File".

Validation and Constraints

Only exists data fields will be show.

Data sources and targets

Sources	getPersonsForSelection.xql getPersonOverview.xql
---------	---

3.4. Expensess Tab

Execution

Click for "„Expensess“" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout

Date	Informations	Measure(s)
...	Title_1
...	... Title_2	...
...	... Personname	...

Page < 1 > of ...

Figure 10: Expensess Tab

Widgets description

Name	Mandatory/Optional
Date Column	O
Information Column	O
Measure Column	O

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getIssueNames.xql getIssueTable.xql
---------	--

3.5. Revenues Tab

Execution

Click for "„Revenues“" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 11: Revenue Tab

Widgets description

Name	Mandatory/Optional	
Date Column	O	
Information Column	O	
Measure Column	O	

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)

3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getMonthsByRevenueYear.xql getRevenueTable.xql
---------	---

3.6. Press Tab

Execution

Click for "„Press“" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 12: Press Tab

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)

3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getJournalContent.xml getJournalXML.xml
---------	--

3.7. Feebooks Tab

Execution

Click for "„Feebooks“" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 13: Feebook Tab

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)

3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getGageContent.xml
	getGageXML.xml

3.8. Directionbooks Tab

Execution

Click for "Directionbooks" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 14: Directionbooks Tab

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getRegieContent.xml getRegieXML.xml
---------	--

3.9. Role- & Costumbooks Tab

Execution

Click for "Role- & Costumbooks" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 15: Role- & Costumbooks Tab

Action Paths and Results

1. Select button "Show XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getRoleCostumContent.xml getRoleCostumXML.xml
---------	--

3.10. Subscriptions Tab

Execution

Click for "Subscriptions" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Layout




Figure 16: Subscription Tab

Action Paths and Results

1. Select button "Schow XML"-> a window will be opened with xml content.
2. Select button "Load XML"-> a window will be opened for save xml content. (disabled)
3. Click on name link for one person or on title for work -> a new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Data sources and targets

Sources	getAboContent.xml getAboXML.xml
---------	------------------------------------

3.11. Custom Items Tab

Execution

Click for "Custom Items" end-node in navigation tree —> a new tab will be opened. For each exists month one closable section will be created. Section can contains a facsimile area. Facsimile area show one or more pages.

If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Widgets description

HTML- or PDF-File will be shown.

Data sources and targets

Get file from DB.

3.12. Search Results Tab

Execution

Select an item in "Filter" combobox and enter optionally search term in search field -> select search icon -> a new tab will be opened with search results. A new item in "History Tabs" combobox will be created.

Layout

Works with ...					
Nr.	Title	Title Type	Language	Persons	Details
1	Title_1	...			
2			
...			

Figure 17: Search Results Tab for Works

Persons with ... △			
Nr.	Name	Name Type	Details
1	Name_1	...	
2	
...	

Figure 18: Search Results Tab for Persons

Widgets description

Name	Mandatory/Optional
Nr Column	M
Name Column	O
Name Type Column	O
Details Column	M

Action Paths and Results

Select icon in details column-> new tab with detailed information will be opened. If one tab for clicked item is opened -> this tab will be activated. For both cases a new item in "History Tabs" combobox will be created.

Validation and Constraints

If searched information will be found in DB, a table with results will be shown.

Data sources and targets

Sources	searchWorks.xml searchPersons.xml
---------	--------------------------------------

Part III.

Data Design

4. DB-Structure

Informations, presented as MEI-, TEI-, Image-, HTM-L or PDf-Files, are saved in database for types (e.g works, persons, sources, ...) . For Facsimiles exists are image order. Images will be shown with a Leaflet library. For this library images must be cut (one Tool, that will be implemented in Detmold: <https://github.com/Edirom/cutImages>). The Figure shows an example for database structure.




Figure 19: DB-Structure

5. Property-Files

A configuration file describe database structure and some project data for show information in GUI. File dbStricture.xml should be saved in xml-database in app/theater-data directory. Informations for key="custom" are saved as PDF or HTML other informations for defined entry-keys are saved as MEI or TEI. For details show an example configuration (https://github.com/Detmolder-Hoftheater/TheatreTool_1-Dev).

DB Structure File

<prefs>

```

<entries>
  <!--language: en = englishm de= deutsch-->
  <entry key="language" value="en"/>

  <!--Types of Navigation: "theatre", "other". For type "theatre"
    two items "Organization" and "Administration"-->
  <entry key="navigation_type" value="theatre"/>
  <entry key="name" value="Detmolder_Hoftheater"/>
  <entry key="startyear" value="1825"/>
  <entry key="endyear" value="1875"/>

  <!--Database paths. For each path one item in navigation tree
    will be generated.-->
  <!--If one item will be not shown in GUI the value is value="".-->
  <!--Key words are not changeable.-->
  <!--For more details please show "Systems Design" in help menu in
    toolbar.-->
  <!--DB paths for repertoire item. For show repertoire work path
    must be exist, other paths are optional.-->
  <entry key="works" value="theater-data-exs/works"/>
  <entry key="sources" value="theater-data-exs/sources"/>

  <!--Schedule paths are optional.-->
  <entry key="playschedule" value="theater-data-exs/spielplaene"/>
  <entry key="leafletimagesSchedule"
    value="theater-data-exs/leafletImages/spielplaene"/>

  <!--DB path for persons.-->
  <entry key="persons" value="theater-data-exs/persons"/>

  <!--DB path for revenue.-->
  <entry key="revenue" value="theater-data-exs/einnahmen"/>
  <entry key="leafletimagesRevenue"
    value="theater-data-exs/leafletImages/einnahmen"/>

  <!--DB path for expenses.-->
  <entry key="expenses" value="theater-data-exs/ausgaben"/>
  <entry key="leafletimagesExpenses"
    value="theater-data-exs/leafletImages/ausgaben"/>

  <!--Definition of one or more custom navigation items. Value is
    name for navigation item.-->
  <entry key="custom" value="Books"
    dbPath="theater-data-exs/info"/>

```


</entries>
</prefs>

6. MEI and TEI Subsets

The GUI shows data that will be coded in MEI- or TEI-Format. Following structure for files will be support. For details show an example configuration (https://github.com/Detmolder-Hoftheater/TheatreTool_1-Dev).

6.1. Works

Works are coded in MEI format.




Figure 20: Subsets for works: overview




Figure 21: TitleStmt Block




Figure 22: Identifier Block




Figure 23: Language Block




Figure 24: PerfMedium Block




Figure 25: History Block

6.2. Sources

Sources are coded in MEI format.




Figure 26: Sources: Overview




Figure 27: Sources: Attributes Block




Figure 28: Sources: TitleStmt Block




Figure 29: Sources: PubStmt Block




Figure 30: Sources: PhysLoc Block




Figure 31: Sources: PhysDesc Block




Figure 32: Sources: NotesStmt Block




Figure 33: Sources: LangUsage Block




Figure 34: Sources: Contents Block




Figure 35: Sources: RelationList Block




Figure 36: Sources: Single Source Block

6.3. Persons

Persons are coded in MEI format.




Figure 37: Persons: Overview




Figure 38: Persons: Idno Block




Figure 39: Persons: Name Block




Figure 40: Persons: Birth Block




Figure 41: Persons: Death Block




Figure 42: Persons: Gender Block




Figure 43: Persons: Occupation Block




Figure 44: Persons: Residence Block




Figure 45: Persons: Note Block

6.4. Playscdules

Playscdules are coded in TEI format.




Figure 46: Playscdules: Overview




Figure 47: Playscdules: Facsimile Block




Figure 48: Playscdules: Header Block




Figure 49: Playscdules: Text Block

6.5. Expenses

Expensess are coded in TEI format.




Figure 50: Playscedules: Overview




Figure 51: Expenses: Header Block




Figure 52: Expenses: Facsimile Block




Figure 53: Expensess: Text Block

6.6. Revenues

Revenues are coded in TEI format.




Figure 54: Revenues: Overview




Figure 55: Revenues: Header Block




Figure 56: Revenues: Facsimile Block




Figure 57: Revenues: Text Block

7. Relation-Diagram

Following diagram shows relations between objects. Objects are linked with id's and have direction only one direction. Exception is directions between works and sources. They have references in both directions. With dotted line are references that to be done.




Figure 58: Relationdiagram

Part IV.

Process Design

8. `getDBStructure.xql`
9. `getRevenueItems.xql`
10. `getExpensesItems.xql`
11. `getSchedulesItems.xql`
12. `getCustomItems.xql`
13. `getWorks.xql`
14. `getSource.xql`
15. `getMonthsForSelectedYear.xql`
16. `getScheduleTable.xql`
17. `getPersonsForSelection.xql`
18. `getPersonOverview.xql`
19. `getIssueNames.xql`
20. `getIssueTable.xql`
21. `getMonthsByRevenueYear.xql`
22. `getRevenueTable.xql`
23. `searchWorks.xql`
24. `searchPersons.xql`