



printf (- - -)


Socket Appl. Deng


- a Client msq server
 - Server msg All clients.
- a Client registration server
- 6 Client termination (Server
 - Connect ()
- · disconnect()
 - . send ()
 - · receive [)











What transport service does an app need?

data integrity

- some apps (e.g., file transfer, web transactions) require 100% reliable data transfer
- other apps (e.g., audio) can tolerate some loss

timing

some apps (e.g., Internet ∠ 150 M telephony, interactive games) require low delay to be "effective"

delay all uses & Same

throughput

- some apps (e.g., multimedia) require minimum amount of throughput to be "effective"
- other apps ("elastic apps") make use of whatever throughput they get

security

encryption, data integrity, Financial Trans


Transport service requirements: common apps

application	data loss	throughput	time sensitive
en			
file transfer	no loss	elastic	no
e-mail	no loss	elastic	no
V <mark>Veb documents</mark>	no loss	elastic	no
real-time audio/video	loss-tolerant	audio: 5kbps-1Mbps	yes, 100's
		video:10kbps-5Mbps	smsec
stored audio/video	loss-tolerant	same as above	
interactive games	loss-tolerant	few kbps up	yes, few secs
text messaging	no loss	elastic	yes, 100's
			msec
Linteractive			yes and no

Internet transport protocols services

TCP service:

- reliable transport between sending and receiving process
- flow control: sender won't overwhelm receiver
- congestion control: throttle sender when network overloaded
- does not provide: timing, minimum throughput guarantee, security
- connection-oriented: setup required between client and server processes




UDP service:

- unreliable data transfer between sending and receiving process
- does not provide: reliability, flow control, congestion control, timing, throughput guarantee, security, or connection setup,

Q: why bother? Why is there a UDP?

packet switching Store & Forward NIL Serth Connection to the server Application Layer 2-10



Internet apps: application, transport protocols

application	application layer protocol	underlying transport protocol
e-mail	SMTP [RFC 2821]	TCP
remote terminal access	Telnet [RFC 854]	TCP
Web	HTTP [RFC 2616]	TCP
file transfer	FTP [RFC 959]	TCP
streaming multimedia	HTTP (e.g., YouTube),	TCP or UDP
	RTP [RFC 1889]	
Internet telephony	SIP, RTP, proprietary	
	(e.g., Skype)	TCP or UDP

Securing TCP

TCP & UDP

- no encryption
- cleartext passwds sent into socket traverse Internet in cleartext

SSL

- provides encrypted TCP connection
- data integrity
- end-point authentication

SSL is at app layer

apps use SSL libraries, that "talk" to TCP

SSL socket API

- cleartext passwords sent into socket traverse Internet encrypted
- see Chapter 8

