- Client-Server applications
- Server (resources/information)
- Client (request for such information)
- Database + server
- Allows this database to be accessed remotely by any of the clients
- Server has the resources
- Asymmetric. Power
- Server goes down / information not available
- Server has access to your private data

- Alternative to client-server model
- Peer to peer (P2P) application
 - All entities act both as client and server
 - Information is distributed across peer devices
 - No single point of failure
 - Privacy related issues are also not as severe
 - Governments/authorities also are not able to control access to information


- File sharing application (torrent protocol)
- Xender, share it
- Dropbox?
- Find a list of different types of p2p application

Pure P2P architecture

- no always-on server
- arbitrary end systems directly communicate
- peers are intermittently connected and change IP addresses

examples:


- file distribution (BitTorrent)
- Streaming (KanKan)
- VolP (Skype)



File distribution: client-server vs P2P

Question: how much time to distribute file (size F) from one server to N peers?


peer upload/download capacity is limited resource



File distribution time: client-server

- server transmission: must sequentially send (upload) N file copies:
 - time to send one copy: F/u_s
 - time to send N copies: NF/u_s
- client: each client must download file copy
 - d_{min} = min client download rate
 - min client download time: F/d_{min}

time to distribute F to N clients using client-server approach




increases linearly in N

 $D_{c-s} \ge max\{NF/u_s, F/d_{min}\}$

File distribution time: P2P

- server transmission: must upload at least one copy
 - time to send one copy: F/u_s
- client: each client must download file copy
 - min client download time: F/d_{min}



- clients: as aggregate must download NF bits
 - max upload rate (limiting max download rate) is $u_s + \Sigma u_i$

time to distribute F to N clients using P2P approach


$$D_{P2P} \ge max\{F/u_s, F/d_{min}, NF/(u_s + \Sigma u_i)\}$$

increases linearly in N ...

... but so does this, as each peer brings service capacity


Client-server vs. P2P: example

client upload rate = u, F/u = 1 hour, $u_s = 10u$, $d_{min} \ge u_s$




P2P file distribution: BitTorrent

- file divided into 256Kb chunks
- peers in torrent send/receive file chunks



P2P file distribution: BitTorrent

- peer joining torrent:
 - has no chunks, but will accumulate them over time from other peers
 - registers with tracker to get list of peers, connects to subset of peers ("neighbors")



- while downloading, peer uploads chunks to other peers
- peer may change peers with whom it exchanges chunks
- churn: peers may come and go
- once peer has entire file, it may (selfishly) leave or (altruistically) remain in torrent

BitTorrent: requesting, sending file chunks

requesting chunks:

- at any given time, different peers have different subsets of file chunks
- periodically, Alice asks each peer for list of chunks that they have
- Alice requests missing chunks from peers, rarest first

sending chunks: tit-for-tat

- Alice sends chunks to those four peers currently sending her chunks at highest rate
 - other peers are choked by Alice (do not receive chunks from her)
 - re-evaluate top 4 every 10 secs
- every 30 secs: randomly select another peer, starts sending chunks
 - "optimistically unchoke" this peer
 - newly chosen peer may join top 4

BitTorrent: tit-for-tat

- (I) Alice "optimistically unchokes" Bob
- (2) Alice becomes one of Bob's top-four providers; Bob reciprocates
- (3) Bob becomes one of Alice's top-four providers

