

LKM API

Customer

Table of Contents

1. Introduction
2. Authentication & Security
3. Endpoints
4. Models
5. Revision

1. Introduction

The **LKA API Loyalty v2** is a RESTful API designed to support loyalty program operations across multiple applications and partner systems. It provides endpoints for authentication, customer account management, loyalty card operations, points, vouchers, prizes, challenges, surveys, stores, and transaction processing.

The API uses JSON for all request and response bodies and relies on JWT tokens and HMAC-based signatures to ensure secure communication between clients and the LKA Loyalty platform.

This document provides a concise overview of the main endpoints, data models, and typical integration flows.

2. Authentication & Security

All API endpoints require a valid authentication token. There are **two types of tokens**, and every request must include **one of them**, depending on the context:

- **Application Token** – used by applications
- **Client Token** – used by authenticated users

These tokens are obtained exclusively through the authentication endpoints:

- GET /api/auth/applicationtoken
- GET /api/auth/clienttoken

No endpoint in the API can be called without one of these tokens.

Mandatory HMAC Signature (X-Signature)

Every request to the API must include the header:

X-Signature: <HMAC signature>

This signature is generated using the partner secret key, and it ensures:

- request integrity
- request authenticity
- protection against tampering

If the signature is missing or invalid, the API rejects the request.

X-Signature Generation Procedure

The signature is generated using the partner's secret key and a combination of dynamic values. The final header sent to the API follows the format:

X-Signature: <timestamp>:<nonce>:<signature>

1. **Retrieve the partner secret key** The partner receives a unique secret key used to sign all requests. This key must remain confidential and must never be exposed in client applications.
2. **Generate a timestamp** A Unix timestamp (in seconds) is generated at the moment the request is created. This prevents replay attacks and ensures the request is time-bound.
3. **Generate a nonce** A nonce is a random hexadecimal string used only once. It guarantees that even identical requests will produce different signatures.
4. **Read the request body** If the request contains a body, its raw content is used. If the body is empty, an empty string is used instead.
5. **Compute the MD5 hash of the body** The request body is hashed using MD5. This ensures that any change to the body will invalidate the signature.

6. **Build the message to be signed** The signature message is constructed by concatenating:

```
<nonce> + <timestamp> + <md5 (body)>
```

7. **Generate the HMAC-SHA256 signature** The message is signed using HMAC-SHA256 with the partner secret key. The result is encoded in hexadecimal.
8. **Assemble the final X-Signature header** The final header value is formatted as:

```
<timestamp>:<nonce>:<signature>
```

Authentication – Endpoints

GET /api/auth/applicationtoken

Headers

Name	Type	Required	Description
X-Signature	string	Yes	HMAC signature of the request
TokenApp	string	Yes	Application Token
StoreExternalId	int	Yes	LKM unit code

Responses

HTTP Code	Description	Schema
200	OK	AuthDto

GET /api/auth/clienttoken

Headers

Name	Type	Required	Description
X-Signature	string	Yes	HMAC signature of the request
TokenApp	string	Yes	Application Token
AccessToken	string	Yes	Client Token
StoreExternalId	int	Yes	LKM unit code

Responses

HTTP Code	Description	Schema
200	OK	AuthDto

3. Controllers

AccountV2

POST /v2/Account/ResetPassword

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	ResetPasswordEmailRequest	Request payload used to trigger a password reset email.

Responses

HTTP Code	Description	Schema
200	Password reset email sent.	No schema defined
400	Invalid request.	No schema defined
401	Unauthorized.	No schema defined
404	No customer was found with the provided email.	No schema defined
500	Internal Error.	No schema defined

POST /v2/Account/ResetPasswordEmail

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UserResetPasswordRequest	Request payload used to trigger a password reset email.

Responses

HTTP Code	Description	Schema
200	Password reset email sent.	No schema defined
400	Invalid request.	No schema defined
401	Unauthorized.	No schema defined
404	No customer found with the provided email.	No schema defined
500	Internal Error.	No schema defined

POST /v2/Account/ResetPasswordSMS

Headers



Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UserResetPasswordRequest	Request payload used to trigger a password reset SMS.

Responses

HTTP Code	Description	Schema
200	Password reset SMS sent.	No schema defined
400	Invalid request.	No schema defined
401	Unauthorized.	No schema defined
404	No customer found with the provided phone.	No schema defined
500	Internal Error.	No schema defined

POST /v2/Account/ResetPasswordCardSMS

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UserResetPasswordSmsRequest	Request payload used to trigger a password reset by card and SMS.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/LookUpAccount

Query Parameters

Name	Type	Required	Description
email	string	Yes	Email address used to look up an account.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/Register

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	RegisterBindingModelLimitCardInput	Request payload used to register a customer account.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/Registerv2

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	RegisterBindingModelLimitCardInput	Request payload used to register a customer account with GDPR-related data.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/UserInfoCard

Query Parameters

Name	Type	Required	Description
card	string	No	Card identifier used to retrieve user information.
password	string	No	Password associated with the card account.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/UserInfoMobile

Query Parameters

Name	Type	Required	Description
mobile	string	No	Mobile number used to retrieve user information.



password	string	No	Password associated with the mobile account.
----------	--------	----	--

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/UserInfo

Query Parameters

Name	Type	Required	Description
facebookAccessToken	string	No	Facebook access token used to retrieve user information.
email	string	No	Email address used to retrieve user information.
password	string	No	Password associated with the account.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

PUT /v2/Account/UserInfo

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UserInfoUpdateBindingModel	Request payload used to update user account information.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/UserInfoNoLogin

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

PUT /v2/Account/UserInfoV2

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Request Body

Name	Type	Description
model	UserInfoUpdateBindingModel	Request payload used to update user account information with GDPR-related data.

Responses

HTTP Code	Description	Schema
200	OK	object

PUT /v2/Account/ChangePassword

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	ChangePasswordBindingModel	Request payload used to change the current password.

Responses

HTTP Code	Description	Schema
200	OK	object

PUT /v2/Account/ChangePasswordWithCode

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	ChangePasswordBindingModel	Request payload used to change the password using a validation code flow.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/SetPassword

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	PasswordString	Request payload used to define a password.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/GetCardInfo

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/GetQuestionsAndAnswers

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/SaveQuestionsAndAnswers

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
saveQuestionsAndAnswersRequest	SaveQuestionsAndAnswersRequest	Request payload used to save questions and answers.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/SecurityValidationCode

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UsersExistEmailRequest	Request payload used to validate email-based security information.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/LookUpAccountPhone

Query Parameters

Name	Type	Required	Description
telemovel	string	No	Phone number used to look up an account.
countrycode	string	No	Country calling code associated with the phone number.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/LookUpAccountEmail

Query Parameters

Name	Type	Required	Description
email	string	No	Email address used to look up an account.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/LookUpUserInfoPhone

Query Parameters

Name	Type	Required	Description
mobile	string	No	Mobile number used to look up user information.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/ChangeAccountEmail

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	ChangeEmailRequest	Request payload used to change the account email address.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/RequestSMSRandomPin

Query Parameters

Name	Type	Required	Description
telemovel	string	No	Phone number that will receive the random PIN.
pinSize	integer (int32)	No	Length of the random PIN to be generated.
countrycode	string	No	Country calling code associated with the phone number.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/SetPasswordWithPin

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
------	------	-------------



model	ChangePasswordBindingModel	Request payload used to define a password using a PIN-based flow.
-------	----------------------------	---

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/UserLogin

Query Parameters

Name	Type	Required	Description
clientUser	string	Yes	User identifier used for login.
password	string	Yes	Password associated with the user account.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/UpdateCardInformation

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	ActivateCardBindingModel	Request payload used to update card information.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Account/GetCardInformation

Query Parameters

Name	Type	Required	Description
codigocartao	string	Yes	Card code used to retrieve card information.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses



HTTP Code	Description	Schema
200	OK	object

POST /v2/Account/GetCardInformation

Query Parameters

Name	Type	Description
codigocartao	string	Card code used to retrieve card information.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

AccountWithPhone

POST /v2/AccountWithPhone/LinkCard

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	LinkCardWithPhoneBindingModel	Request payload used to link a card to a phone-based account.

Responses

HTTP Code	Description	Schema
200	Model	No schema defined
400	Invalid request.	No schema defined
401	Unauthorized.	No schema defined
500	Internal Error.	No schema defined

GET /v2/AccountWithPhone/LookUpAccount

Query Parameters

Name	Type	Required	Description
telemovel	string	No	Phone number used to look up an account.

Headers

Name	Type	Description
------	------	-------------

Authorization	string	Bearer JWT Client token.
---------------	--------	--------------------------

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/AccountWithPhone/Register
Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	RegisterWithPhoneBindingModel	Request payload used to register a phone-based customer account.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/AccountWithPhone/RegisterV2
Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	RegisterWithPhoneBindingModel	Request payload used to register a phone-based customer account with GDPR-related data.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/AccountWithPhone/UserInfo
Query Parameters

Name	Type	Required	Description
facebookAccessToken	string	No	Facebook access token used to retrieve user information.
telemovel	string	No	Phone number used to retrieve user information.
password	string	No	Password associated with the account.

Headers

Name	Type	Description
------	------	-------------



Authorization	string	Bearer JWT Client token.
---------------	--------	--------------------------

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/AccountWithPhone/SecurityValidationCode

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	UsersExistRequest	Request payload used to validate phone-based security information.

Responses

HTTP Code	Description	Schema
200	OK	object

Challenges

GET /v2/Challenges/ClientChallenges

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Challenges/Challenges

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Challenges/ChallengesV2

Query Parameters



Name	Type	Required	Description
forcerefresh	boolean	No	Indicates whether challenge data should be refreshed.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Challenges/GetChallengeByTrophieId

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
Trophies	array of integer (int64)	Collection of trophie identifiers used to retrieve challenge details.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Challenges/ChallengesV2ForClient

Query Parameters

Name	Type	Required	Description
clientcode	integer (int64)	Yes	Client identifier used to retrieve challenge data.
forcerefresh	boolean	No	Indicates whether challenge data should be refreshed.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

CMS

GET /v2/Cms

Query Parameters

Name	Type	Required	Description
------	------	----------	-------------

parentId	integer (int32)	No	Parent content identifier used to filter CMS entries.
drafts	boolean	No	Indicates whether draft content should be included.
menu	boolean	No	Indicates whether only menu content should be returned.
agendados	boolean	No	Indicates whether scheduled content should be included.
expirados	boolean	No	Indicates whether expired content should be included.
marca	integer (int32)	No	Brand identifier used to filter content.
perPage	integer (int32)	No	Maximum number of CMS items to return per page.
page	integer (int32)	No	Page number to retrieve.
idioma	string	No	Language code used to filter localized content.
codCard	string	No	Card code used to contextualize CMS content.
storeCode	string	No	Store code used to filter CMS content.
id	integer (int32)	No	Specific CMS item identifier.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Cms/RegisterViews

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	RegisterViewsInput	Request payload used to register CMS views.

Responses

HTTP Code	Description	Schema
200	OK	object

Vouchers

GET /v2/Vouchers/Voucher

Query Parameters

Name	Type	Required	Description
CodVoucher	integer (int64)	No	Voucher identifier used to retrieve voucher details.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

DELETE /v2/Vouchers/ClientDeleteVale

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	VouchersControllerClientDeleteVoucherInput	Request payload used to delete a client voucher.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/ClientCreateVale

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	VouchersControllerCreateEmployeeValeFromCatalogInput	Request payload used to create a client voucher from catalog.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Vouchers/ClientList

Query Parameters

Name	Type	Required	Description
ValeStateEnum	string	No	Voucher state filter.
perPage	integer (int32)	No	Maximum number of vouchers to return per page.
page	integer (int32)	No	Page number to retrieve.
cod_loja	string	No	Store code used to filter vouchers.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Vouchers/v2/ClientList

Query Parameters

Name	Type	Required	Description
resgatados	boolean	No	Indicates whether redeemed vouchers should be returned.
perPage	integer (int32)	No	Maximum number of vouchers to return per page.
page	integer (int32)	No	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Vouchers/GetCatalog

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/ClientRedeem

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
request	ClientRedeemClientUnredeemRequest	Request payload used to redeem a client voucher.

Responses

HTTP Code	Description	Schema
-----------	-------------	--------



200	OK	object
-----	----	--------

POST /v2/Vouchers/RedeemCatalog

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	VouchersControllerRedeemCatalogV2Input	Request payload used to redeem a voucher from catalog.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/ClientUnredeem

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
request	ClientRedeemClientUnredeemRequest	Request payload used to unredeem a client voucher.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/Create

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	CreateVoucherBindingModel	Request payload used to create a voucher.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/CreateForExternalVoucher

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	VouchersControllerCreateForExternalVoucherInput	Request payload used to create a voucher from an external voucher code.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/CreateForExternalUniqueVoucher

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	VouchersControllerCreateForExternalUniqueVoucherInput	Request payload used to create a voucher from an external unique voucher code.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/ActivePromotionVoucher

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	codValeInput	Request payload used to activate a promotion voucher.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Vouchers/ActiveVoucher

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	codValeInput	Request payload used to activate a voucher.

Responses

HTTP Code	Description	Schema
200	OK	object

Points

GET /v2/Points

Query Parameters

Name	Type	Description
codGrupo	integer (int32)	Group code used to filter points.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	integer (int32)

GET /v2/GetPoints

Query Parameters

Name	Type	Description
codGrupo	integer (int32)	Group code used to filter points.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	integer (int32)

GET /v2/GetConvertedPoints

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Responses

HTTP Code	Description	Schema
200	OK	number (double)

Prizes

GET /v2/Prizes/List

Query Parameters

Name	Type	Description
codLoja	string	Store code used to filter available prizes.
codGrupo	number (double)	Group code used to filter prizes.
perPage	integer (int32)	Maximum number of prizes to return per page.
page	integer (int32)	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Prizes/Redeemed

Name	Type	Description
CodCard	string	Card code used to retrieve redeemed prizes.
CodLoja	string	Store code associated with the redeemed prizes.
perPage	integer (int32)	Maximum number of redeemed prizes to return per page.
page	integer (int32)	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

DELETE /v2/Prizes/Unredeem

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	CardPrizeBindingModel	Request payload used to unredeem a prize associated with a card.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Prizes/ListAll

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

Surveys

GET /v2/Surveys/GetSurveys

Query Parameters

Name	Type	Description
perPage	integer (int32)	Maximum number of surveys to return per page.
page	integer (int32)	Page number to retrieve.
idioma	string	Language code used to filter localized survey content.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Surveys

Query Parameters

Name	Type	Description
id	integer (int32)	Survey identifier to retrieve.

idioma	string	Language code used to filter localized survey content.
--------	--------	--

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Surveys

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	NewSurveyAnswerBindingModel	Request payload used to submit a survey answer.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Surveys/Bulk

Headers

Name	Type	Description
Authorization	string	Bearer JWT Application token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	NewSurveyAnswerBulkBindingModel	Request payload used to submit survey answers in bulk.

Responses

HTTP Code	Description	Schema
200	OK	object

Transactions

GET /v2/Transactions/v2

Query Parameters

Name	Type	Description
contaCartao	boolean	Indicates whether transactions should be grouped or counted by card account context.
perPage	integer (int32)	Maximum number of transactions to return per page.
page	integer (int32)	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	array of TransactionsHistoryResponse

GET /v2/Transactions

Query Parameters

Name	Type	Description
dataInicial	string	Initial date used to filter transactions.
dataFinal	string	Final date used to filter transactions.
valorMinimo	integer (int32)	Minimum transaction value.
valorMaximo	integer (int32)	Maximum transaction value.
perPage	integer (int32)	Maximum number of transactions to return per page.
page	integer (int32)	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Transactions

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
model	IdStringInput	Request payload used to register a transaction by QR code.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Transactions/WithoutSurveySubmissions

Query Parameters

Name	Type	Required	Description
days	integer (int32)	No	Number of recent days to inspect for transactions without survey submissions.
perPage	integer (int32)	No	Maximum number of transactions to return per page.
page	integer (int32)	No	Page number to retrieve.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	array of TransactionsHistoryResponse

GET /v2/Transactions/CardTransactions

Query Parameters

Name	Type	Description
contaCartao	boolean	Indicates whether transactions should be grouped or counted by card account context.
transactionID	integer (int64)	Specific transaction identifier to retrieve.
perPage	integer (int32)	Maximum number of transactions to return per page.
page	integer (int32)	Page number to retrieve.
startDate	string (date-time)	Start date from which transactions should be returned.
Items	boolean	Include transaction items.
ItemsDetails	boolean	Include detailed item data.
BookingInformation	boolean	Include booking-related information.
OptionalInfo	boolean	Include optional information fields.
WithAllRatings	boolean	Include all rating information.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses



HTTP Code	Description	Schema
200	OK	array of TransactionsHistoryResponse

GET /v2/Transactions/CardTransactionsTopDays

Query Parameters

Name	Type	Description
TopDays	integer (int32)	Number of top days to evaluate.
contaCartao	boolean	Indicates whether transactions should be grouped or counted by card account context.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

POST /v2/Transactions/AddInvoicePicture

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.
X-Signature	string	HMAC signature of the request.

Request Body

Name	Type	Description
invoice	InvoicePicture	Request payload used to attach an invoice image to a transaction.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Transactions/GetOptionalInfos

Query Parameters

Name	Type	Description
nomeInfoOpcional	string	Optional information group name.
nomeCampo	string	Field name to retrieve.
dataMinima	string (date-time)	Minimum date for filtering.
dataMaxima	string (date-time)	Maximum date for filtering.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

GET /v2/Transactions/GetTotalExcludingOptionalInfo

Query Parameters

Name	Type	Description
nomeInfoOpcional	string	Optional information group name.
nomeCampo	string	Field name to exclude from the total.
dataMinima	string (date-time)	Minimum date for filtering.
dataMaxima	string (date-time)	Maximum date for filtering.

Headers

Name	Type	Description
Authorization	string	Bearer JWT Client token.

Responses

HTTP Code	Description	Schema
200	OK	object

5. Models

ResetPasswordEmailRequest

Name	Type	Description
email	string	Email address used to request a password reset email.
pinSize	Int	Length of the PIN or reset code to be generated.

UserResetPasswordRequest

Name	Type	Description
phone	string	Phone number associated with the account.
hash	string	Validation hash used during the password reset flow.
ResetLength	Int	Length of the reset code to be generated.

UserResetPasswordSmsRequest

Name	Type	Description
countrycode	string	Country calling code for the phone number.
phone	string	Phone number used in the password reset request.
hash	string	Validation hash used during the password reset flow.
ResetLength	Int	Length of the reset code to be generated.

RegisterBindingModelLimitCardInput

Name	Type	Description
registerBindingModel	RegisterBindingModel	Main registration payload. The referenced type is not defined in the provided excerpt.
loyaltyClient	RegisterBindingModel	Loyalty client registration payload. The referenced type is not defined in the provided excerpt.
lowerLimitCard	string	Lower bound of the eligible card range.
higherLimitCard	string	Upper bound of the eligible card range.

UserInfoUpdateBindingModel

Name	Type	Description
Email	string	User email address.
Password	string	User password.
Dn	string	Birth date or equivalent identifier, as defined by the implementation.

Contribuinte	string	Tax identification number.
BI	string	Identity document number.
Nome	string	Customer full name.
Sexo	string	Stored sex or gender value.
Rua	string	Street name.
Porta	string	Door number.
Andar	string	Floor information.
Letra	string	Apartment or unit suffix.
Localidade	string	Locality.
CP	string	Postal code.
DescPostal	string	Additional postal description.
CPLocal	string	Postal locality description.
Telemovel	string	Mobile phone number.
Telefone	string	Landline or alternate phone number.
IndicativoZona	string	Area calling code.
IndicativoPais	string	Country calling code.
Avatar	string	Avatar or profile image reference.
ACEITA_POLITICA_PRIVACIDADE	boolean	Privacy policy consent flag.
ACEITA_TELEFONE_PRIVACIDADE	boolean	Phone privacy consent flag.
ACEITA_SMS_PRIVACIDADE	boolean	SMS privacy consent flag.
ACEITA_EMAIL_PRIVACIDADE	boolean	Email privacy consent flag.
ACEITA_POSTAL_PRIVACIDADE	boolean	Postal privacy consent flag.
ACEITA_POLITICA_MARKETING	boolean	Marketing policy consent flag.
ACEITA_TELEFONE_MARKETING	boolean	Phone marketing consent flag.
ACEITA_SMS_MARKETING	boolean	SMS marketing consent flag.
ACEITA_POSTAL_MARKETING	boolean	Postal marketing consent flag.
ACEITA_EMAIL_MARKETING	boolean	Email marketing consent flag.
APLICAR_RGPD	boolean	Indicates whether GDPR rules should be applied.
ID_EXTERNO	string	External customer identifier.
MoradaDistrito	string	Address district.
MoradaCidade	string	Address city.
MoradaFreguesia	string	Address parish.
Facebook	string	Facebook profile or identifier.

Instagram	string	Instagram profile or identifier.
Twitter	string	Twitter profile or identifier.
CodLojaAdesao	string	Store code where the customer joined.
List_External_Id	array of string	List of external identifiers linked to the customer.

ChangePasswordBindingModel

Name	Type	Description
currentPassword	string	Current password of the authenticated user.
newPassword	string	New password to be assigned to the account.
codCard	string	Associated card code, when applicable.

PasswordString

Name	Type	Description
password	string	Password value sent in the request body.

SaveQuestionsAndAnswersRequest

Name	Type	Description
Questions	array of Question	Collection of questions. The referenced type is not defined in the provided excerpt.
ChoiceAnswers	array of ChoiceAnswer	Collection of choice-based answers. The referenced type is not defined in the provided excerpt.
FreeTextAnswers	array of FreeTextAnswer	Collection of free-text answers. The referenced type is not defined in the provided excerpt.

UsersExistEmailRequest

Name	Type	Description
email	string	Email address to be validated or checked.
authtype	Int	Authentication type associated with the request.

ChangeEmailRequest

Name	Type	Description
NewEmail	string	New email address to be associated with the account.

ActivateCardBindingModel

Name	Type	Description
CodigoCartao	string	Card code to be activated or updated.
TipoCartao	Int	Card type identifier.

Email	string	User email address.
Password	string	User password.
Dn	string	Birth date or equivalent identifier, as defined by the implementation.
Contribuinte	string	Tax identification number.
BI	string	Identity document number.
Nome	string	Customer full name.
Sexo	string	Stored sex or gender value.
Rua	string	Street name.
Porta	string	Door number.
Andar	string	Floor information.
Letra	string	Apartment or unit suffix.
Localidade	string	Locality.
CP	string	Postal code.
DescPostal	string	Additional postal description.
CPLocal	string	Postal locality description.
Telemovel	string	Mobile phone number.
Telefone	string	Landline or alternate phone number.
IndicativoZona	string	Area calling code.
IndicativoPais	string	Country calling code.
Avatar	string	Avatar or profile image reference.
ACEITA_POLITICA_PRIVACIDADE	boolean	Privacy policy consent flag.
ACEITA_TELEFONE_PRIVACIDADE	boolean	Phone privacy consent flag.
ACEITA_SMS_PRIVACIDADE	boolean	SMS privacy consent flag.
ACEITA_EMAIL_PRIVACIDADE	boolean	Email privacy consent flag.
ACEITA_POSTAL_PRIVACIDADE	boolean	Postal privacy consent flag.
ACEITA_POLITICA_MARKETING	boolean	Marketing policy consent flag.
ACEITA_TELEFONE_MARKETING	boolean	Phone marketing consent flag.
ACEITA_SMS_MARKETING	boolean	SMS marketing consent flag.
ACEITA_POSTAL_MARKETING	boolean	Postal marketing consent flag.
ACEITA_EMAIL_MARKETING	boolean	Email marketing consent flag.
APLICAR_RGPD	boolean	Indicates whether GDPR rules should be applied.
ID_EXTERNO	string	External customer identifier.
MoradaDistrito	string	Address district.
MoradaCidade	string	Address city.

MoradaFreguesia	string	Address parish.
Facebook	string	Facebook profile or identifier.
Instagram	string	Instagram profile or identifier.
Twitter	string	Twitter profile or identifier.
Data_Validade	string (date-time)	Card expiration date.

LinkCardWithPhoneBindingModel

Name	Type	Description
Card	string	Card identifier to be linked.
Password	string	Password associated with the card or account.

RegisterWithPhoneBindingModel

Name	Type	Description
Email	string	User email address.
FacebookAccessToken	string	Facebook access token used during registration.
Password	string	Password to be assigned to the account.
Nome	string	Customer full name.
Dn	string (date-time)	Birth date.
Bi	string	Identity document number.
Contribuinte	string	Tax identification number.
Sexo	string	Stored sex value.
Avatar	string	Avatar or profile image reference.
LocalNascimento	string	Place of birth.
LocalMorada	string	Address location.
Rua	string	Street name.
CP	string	Postal code.
DescPostal	string	Additional postal description.
Localidade	string	Locality.
GrupoDesconto	integer (int32)	Discount group identifier.
Telemovel	string	Mobile phone number.
ACEITA_POLITICA_PRIVACIDADE	boolean	Privacy policy consent flag.
ACEITA_TELEFONE_PRIVACIDADE	boolean	Phone privacy consent flag.
ACEITA_SMS_PRIVACIDADE	boolean	SMS privacy consent flag.
ACEITA_EMAIL_PRIVACIDADE	boolean	Email privacy consent flag.
ACEITA_POSTAL_PRIVACIDADE	boolean	Postal privacy consent flag.

ACEITA_POLITICA_MARKETING	boolean	Marketing policy consent flag.
ACEITA_TELEFONE_MARKETING	boolean	Phone marketing consent flag.
ACEITA_SMS_MARKETING	boolean	SMS marketing consent flag.
ACEITA_POSTAL_MARKETING	boolean	Postal marketing consent flag.
ACEITA_EMAIL_MARKETING	boolean	Email marketing consent flag.
APLICAR_RGPD	boolean	Indicates whether GDPR rules should be applied.
ID_EXTERNO	string	External customer identifier.
IndicativoPais	string	Country calling code.
MoradaDistrito	string	Address district.
MoradaCidade	string	Address city.
MoradaFreguesia	string	Address parish.
LinkEmailAccount	boolean	Indicates whether an email account should be linked.
CodLojaAdesao	string	Store code where the customer joined.
PartnerSource	string	Partner source identifier.

UsersExistRequest

Name	Type	Description
telemovel	string	Phone number to be validated or checked.
authtype	integer (int32)	Authentication type associated with the request.
countrycode	string	Country calling code associated with the phone number.
hash	string	Validation hash used in the security flow.
pinSize	integer (int32)	Length of the PIN to be generated or validated.

RegisterViewsInput

Name	Type	Description
cms_id	integer (int32)	CMS item identifier whose view should be registered.

ClientRedeemClientUnredeemRequest

Name	Type	Description
CodVoucher	integer (int64)	Voucher identifier.
CodLoja	string	Store code associated with the redeem or unredeem operation.

CreateVoucherBindingModel

Name	Type	Description
------	------	-------------

tipo	integer (int32)	Voucher type identifier.
valor	number (double)	Voucher monetary value.
lojaValida	string	Store code where the voucher is valid.
dataValidade	string (date-time)	Voucher expiration date.
observacoes	string	Additional voucher notes.
codGrupo	number (double)	Voucher group code.

VouchersControllerClientDeleteVoucherInput

Name	Type	Description
CodVoucher	integer (int64)	Voucher identifier to be deleted.
CodLoja	string	Store code associated with the voucher.

VouchersControllerCreateEmployeeValeFromCatalogInput

Name	Type	Description
CodCatalog	integer (int32)	Catalog identifier used to create an employee voucher.

VouchersControllerRedeemCatalogV2Input

Name	Type	Description
Voucher	integer (int64)	Voucher identifier to redeem from catalog.
CodLoja	string	Store code associated with the redeem operation.

VouchersControllerCreateForExternalVoucherInput

Name	Type	Description
externalVoucherCode	string	External voucher code to be imported or created.
inativo	boolean	Indicates whether the voucher should be created as inactive.

VouchersControllerCreateForExternalUniqueVoucherInput

Name	Type	Description
externalUniqueVoucherCode	string	External unique voucher code to be imported or created.
inativo	boolean	Indicates whether the voucher should be created as inactive.

codValeInput

Name	Type	Description
------	------	-------------

codVale	integer (int64)	Voucher code used to activate a voucher or promotion voucher.
---------	-----------------	---

PointsControllerPostInput

Name	Type	Description
Valor	integer (int32)	Point value to apply or query.
Quant	integer (int32)	Quantity associated with the operation.
codLoja	string	Store code.
codGrupo	number (double)	Group code associated with points.
perPage	integer (int32)	Maximum number of results to return per page.
page	integer (int32)	Page number to retrieve.

CardPrizeBindingModel

Name	Type	Description
CodCartao	string	Card code associated with the prize operation.
CodLoja	string	Store code associated with the prize action.
CodGrupo	number (double)	Group code associated with the prize.
CodPremio	string	Prize code to redeem or unredeem.
CodResgate	string	Redemption code associated with the prize transaction.

NewSurveyAnswerBindingModel

Name	Type	Description
AccessToken	string	Access token associated with the survey response context.
CodCartao	string	Card code associated with the respondent.
IDPergunta	integer (int32)	Survey question identifier.
IDQuestionarioResposta	array of integer (int32)	Collection of selected answer identifiers.
RespostaLivre	string	Free-text response provided by the user.
Classificacao	integer (int32)	Rating or score associated with the answer.
Imagens	array of string	Collection of image references attached to the answer.
COD_TRANSACAO	integer (int32)	Transaction code associated with the survey answer.

NewSurveyAnswerBulkBindingModel

Name	Type	Description
CodCartao	string	Card code associated with the bulk survey submission.
CodLoja	string	Store code associated with the response context.

Respostas	array of Resposta	Collection of survey answers submitted in bulk.
CodDesafio	integer (int64)	Challenge code associated with the survey batch.

Resposta

Name	Type	Description
Definition pending	object	This model is referenced by NewSurveyAnswerBulkBindingModel.Respostas , but its detailed Swagger definition was not provided in the available specification. Add the field-level structure when the Resposta definition is available.

TransactionsHistoryResponse

Name	Type	Description
COD_TRANSACCAO	number (double)	Transaction identifier.
COD_LOJA	string	Store code associated with the transaction.
LOJA	string	Store name.
DATAHORA	string (date-time)	Date and time of the transaction.
Valor_compra	number (double)	Purchase value.
Valor_pago	number (double)	Amount paid.
Desconto	number (double)	Discount amount applied to the transaction.
Pontos	integer (int64)	Points earned.
Pontos_resgatados	integer (int64)	Points redeemed.
numero_resgates	integer (int64)	Number of redemptions associated with the transaction.
Premios_resgatados	integer (int64)	Number of redeemed prizes.
Vales_resgatados	integer (int64)	Number of redeemed vouchers.
Classificacao	integer (int32)	Rating associated with the transaction.
ValorAcumulado	number (double)	Accumulated value after the transaction.
LOJAMARCAID	integer (int32)	Store brand identifier.
HardLock	string	Transaction lock flag or code.
WINRESTBOOKING_ID	string	Booking identifier associated with the transaction.
WINRESTBOOKING_DELIVERY	integer (int32)	Booking delivery indicator.
WINRESTBOOKING_APP	integer (int64)	Booking application identifier.
Items	array of TransactionHistoryItem	Collection of transaction items.

ItemsDetails	array of TransactionHistoryItemDetail	Collection of detailed transaction items.
OptionalInfos	array of TransactionHistoryOptionalInfo	Collection of optional information records.
AllRatings	array of TransactionHistoryRatings	Collection of all ratings associated with the transaction.
Points_Factor	number (double)	Points conversion factor.
IsCanceled	boolean	Indicates whether the transaction was canceled.

IdStringInput

Name	Type	Description
id	string	Identifier string used by the request.

InvoicePicture

Name	Type	Description
CodTransaction	number (double)	Transaction identifier associated with the invoice image.
ImageBase64	string	Invoice image encoded in Base64.

6. Revision

Version	Date	Description	Author
1.0	01/01/2026	Add endpoints and models	Nelson Roda