Base Paper

1. Paper Details

Title: PlantHealthNet: Transformer-Enhanced Hybrid Models for Disease Diagnosis and Severity Estimation in Agriculture

Author: Abid Iqbal

Affiliation: Department of Computer Engineering, College of Computer Sciences and Information Technology, King Faisal University, Al Ahsa, Saudi Arabia

Journal: IEEE Access, Volume 13, 2025 (pp. 101160-101176)

Published: 5 June 2025 (received 21 May 2025, accepted 1 June 2025)

DOI: 10.1109/ACCESS.2025.3576990

Funding: Deanship of Scientific Research, King Faisal University, Saudi Arabia, Grant KFU250091

2. Problem Addressed

Plant diseases threaten global food security and can cost up to 50% of productivity if detection is delayed. Traditional diagnosis relies on manual visual inspection, which is slow, labor-intensive, and impractical for large-scale farming. Prior deep-learning approaches (CNNs, single transformers) typically handle only one task at a time (classification OR detection OR segmentation) and are validated mainly on clean, lab-style datasets (e.g., PlantVillage), so they generalize poorly to real field conditions with variable lighting, occlusion, and cluttered backgrounds.

The paper targets three gaps:

- No unified, end-to-end pipeline that performs classification, detection, segmentation, AND severity estimation together.
- Existing datasets (e.g., PlantVillage) are lab-captured and lack real-world background/lighting diversity, hurting generalization.
- Pixel-level annotation for segmentation is extremely costly (~38.7 min/image vs. 6.2 min/image for bounding boxes), limiting dataset scale.

3. Contributions

- Proposed PlantHealthNet — a hybrid framework chaining three transformer-based models: Swin Transformer (classification) -> DETR (detection) -> SAM2-UNet (segmentation) -> a final severity-prediction stage (Mild/Moderate/Severe).
- Built and released PlantSeg, a new dataset of 11,458 field images covering 115 diseases across 34 plant hosts, with full pixel-level segmentation annotations (the largest of its kind including wild/field images).
- Achieved state-of-the-art results: 85.6% top-1 / 96.2% top-5 classification accuracy (Swin), 93.3% detection precision (DETR), 94.7% DSC segmentation (SAM2-UNet), and an overall F1-score of 94.46%, ROC AUC 99.97%, PR AUC 98.47%.
- Proposed future architectural optimizations: pruning/quantization for edge deployment, semi-supervised learning to cut annotation cost, few-shot adaptation for emerging diseases, and pipeline parallelization for real-time use.

4. Methodology

4.1 PlantSeg Dataset

- 11,458 images, 115 diseases, 34 plant hosts, grouped into 4 socioeconomic categories: cash crops, major crops, fruits, vegetables (vegetables + fruits dominate with 45 and 39 diseases respectively).
- Curation pipeline: image acquisition (web-scraped via keyword search) -> data cleaning (removing irrelevant/low-quality images) -> annotation (LabelMe tool, expert-reviewed, saved as JSON).
- Preprocessing: Gaussian filtering + median blurring for noise removal; feature scaling/normalization to [0,1] pixel range.
- Field-condition variability explicitly captured: variable lighting in 63% of samples, leaf occlusion in 41% of samples, irregular backgrounds.
- Augmentation pipeline: photometric (brightness ±30%, contrast ±20%, hue ±0.1), geometric (30° rotation, ±15% scaling, flips), and occlusion (random erasure up to 20% of image area).

4.2 Stage 1 — Swin Transformer (Classification)

- Hierarchical vision transformer; splits images into fixed-size patches, computes self-attention within local windows (W-MSA), then shifts windows (SW-MSA) to capture cross-window/global context efficiently.

- Patch-merging layers progressively reduce spatial resolution while increasing channel depth, building a feature hierarchy similar to CNNs.
- Output: disease class label (e.g., "Rice Blast", "Peach Leaf") passed forward to the detection stage.

4.3 Stage 2 — DETR (Detection)

- End-to-end encoder-decoder object detector with a CNN (ResNet) backbone; eliminates hand-crafted anchor boxes/NMS used in older detectors.
- Encoder applies multi-head self-attention over flattened, positionally-encoded feature tokens; Decoder uses learned "object queries" that attend to encoder output to predict bounding boxes + class labels.
- Trained with a Hungarian-algorithm-based set loss for one-to-one matching between predictions and ground truth (combines classification loss + bounding-box loss).

4.4 Stage 3 — SAM2-UNet (Segmentation)

- Hybrid of Segment Anything Model (SAM) and U-Net: Encoder (with Hiera blocks + Receptive Field Blocks for multiscale features) -> Adapter (aligns encoder/decoder dimensions, enables low-memory fine-tuning) -> U-Net-style Decoder (Conv-BN-ReLU blocks + skip connections) producing pixel-level masks.
- Loss = Binary Cross-Entropy + Dice Loss (weighted by λ), balancing pixel-wise accuracy with mask-overlap quality.

4.5 Stage 4 — Severity Prediction

- Computes ratio of diseased (segmented) area to total plant area from the SAM2-UNet output.
- Classifies severity using thresholds: Mild (<20% affected), Moderate (20-50%), Severe (>50%).

4.6 Training Setup

- Platform: Google Colab, NVIDIA Tesla T4 GPU (2560 CUDA cores, 320 Tensor Cores, 32GB RAM).
- Convergence time: ~4.8 hours total (~8.2 min/epoch).
- Optimizer: AdamW with separate learning rates for backbone vs. transformer components.

5. Key Results

5.1 Per-stage performance

Stage	Model	Key Metric	Result
Classification	Swin Transformer	Top-1 / Top-5 Accuracy	85.6% / 96.2%
Detection	DETR (Detection Transformer)	Precision	93.3%
Segmentation	SAM2-UNet	Dice Similarity Coefficient (DSC)	94.7%
Overall framework	Hybrid (Swin+DETR+SAM2-UNet)	F1-score / ROC AUC / PR AUC	94.46% / 99.97% / 98.47%

5.2 Overall model vs. existing classification models

Model	Accuracy	Precision	Recall	F1-Score
SEViT	88.34%	88.33%	87.61%	87.50%
ViT	83.19%	80.47%	80.12%	79.61%
DenseNet121	94.34%	95%	92%	93%
ConvViT	95.1%	92.1%	91.2%	91%
DeiT-small	95.56%	95.65%	95.66%	95.66%
Proposed (PlantHealthNet)	96.20%	93.3%	92.8%	94.46%

The proposed hybrid model achieved the highest accuracy (96.20%) among all compared models, plus a near-perfect average ROC AUC (99.97%) and average Precision-Recall AUC (98.47%), indicating very strong separation between disease classes even where raw accuracy gains over the next-best model (DeiT-small, 95.56%) were modest.

5.3 Confusion patterns (Swin Transformer, Top-1)

- Strongest classes: Healthy (99.0%) and Viral disease (91.5%).
- Weaker/more confused classes: Bacterial (86.7%), Fungal (89.2%), Nutrient deficiency (83.4%) — likely due to visually overlapping symptoms.
- Top-5 accuracy jumps to 96.2% (vs. 85.6% top-1), showing the model usually ranks the correct disease among its top few guesses even when its single best guess is wrong.

5.4 PlantSeg vs. other public datasets

Dataset	Year	#Images	#Classes	#Plants	Segmentation Mask?
PlantVillage	2015	54,309	38	14	No
PlantDoc	2020	2,598	27	13	No
FieldPlant	2023	5,170	27	3	Yes
PlantWild	2024	18,542	89	33	No
PlantSeg (proposed)	2024	11,458	115	34	Yes

Despite having fewer total images than PlantVillage or PlantWild, PlantSeg is the only large dataset in this comparison offering full segmentation masks together with high class diversity (115 classes) and in-the-wild field images — the paper's stated novelty.

6. Limitations (stated by authors)

- High computational burden of the 3-stage hybrid pipeline may limit deployment on resource-constrained/edge agricultural devices.
- Generalization is validated on the annotated dataset's crop/disease set; performance on novel or rare crop diseases not covered by PlantSeg is unproven.
- Sequential (stage-by-stage) processing introduces latency, limiting near-real-time field use.
- Pixel-level annotation of PlantSeg was labor-intensive (5-7× the time cost of bounding-box annotation), a bottleneck for scaling the dataset further.

7. Future Work Proposed by Authors

- Model pruning and quantization to enable edge-device deployment.
- Semi-supervised learning to reduce annotation cost versus full supervision.
- Few-shot learning extension to handle emerging/rare diseases with very limited labeled examples.
- Pipeline parallelization across the classification/detection/segmentation stages to approach real-time performance.
- Possible integration with CLIP (vision-language foundation model) for few-shot classification, zero-shot pseudo-labeling (cutting annotation dependency), and natural-language explainability of predictions.

8. Possible Directions for Your Project (based on stated gaps)

Starting points if you want to extend or critique this paper rather than just replicate it:

- Implement the pruning/quantization step the authors only propose, and actually benchmark PlantHealthNet on an edge device (e.g., Jetson Nano, Raspberry Pi + accelerator).
- Replace the sequential 3-stage pipeline with a more parallel/joint multi-task architecture to reduce inference latency.
- Add the CLIP-based few-shot / zero-shot pseudo-labeling idea the authors only outline, to cut annotation cost on new disease classes.
- Stress-test cross-dataset generalization: train on PlantSeg, test on PlantVillage/PlantDoc/PlantWild (or vice versa) to quantify the domain-shift the authors mention but don't measure numerically.
- Investigate the classes with the most confusion (bacterial vs. fungal vs. nutrient deficiency) with an auxiliary attention or contrastive-learning module to reduce misclassification.
- Compare against the base-paper-1 lightweight PDSNets approach (if relevant to your project) — PlantHealthNet trades heavy transformer compute for higher accuracy, while PDSNets trades some accuracy for 34 FPS on CPU; a project could explore that speed-accuracy frontier directly.

9. Quick Glossary

- DETR — Detection Transformer, an end-to-end encoder-decoder object detector using learned object queries instead of anchor boxes.
- Swin Transformer — hierarchical vision transformer using shifted-window self-attention for efficient local + global feature extraction.
- SAM2-UNet — hybrid of Segment Anything Model 2 and U-Net for pixel-level segmentation with adapter-based low-memory fine-tuning.
- DSC — Dice Similarity Coefficient, overlap measure between predicted and ground-truth segmentation masks (1 = perfect overlap).
- Top-1 / Top-5 Accuracy — whether the single best prediction (Top-1) or any of the model's top five predictions (Top-5) matches the true class.
- ROC AUC / PR AUC — Area under the Receiver Operating Characteristic / Precision-Recall curve; both summarize classification separability across thresholds.
- RFB — Receptive Field Block, a module using multiple parallel convolution kernel sizes to capture multiscale context.