

BLUE TEAMING

Master Guide: Advanced Blue Team Defensive Operations

Class Presentation Study & Slide Documentation

Date: May 2026 | **Author:** [Abdurahman and Abdi]

Target Tool: Obsidian Knowledge Base

Presentation Navigation Map

Step 1 - What is Blue
Teaming?



Step 2 - Log Types and
Structures



Step 3 - The 5 Ws and 1 H
Framework



Step 4 - Operational
Pillars: SOC, IR, CTI



Step 5 - Log Analysis
Methodology



Step 6 - Hands-On
Practice Guide

♦ Q1: What is Blue Teaming?

Important

Core Definition: Blue Teaming is the continuous practice of defending an organization's information systems by actively monitoring, detecting, isolating, and neutralizing cyber threats. It is the architectural shield that opposes the offensive **Red Team** (ethical hackers).

Core Defensive Goals

- **Prevent Breaches:** Hardening systemic defenses so attackers cannot gain a foothold.
- **Detect Intruders:** Shrinking the window of opportunity for an active attacker.
- **Minimize Impact:** Containing malicious lateral movement instantly.
- **Maintain Resilience:** Restoring business operations seamlessly post-incident.

The Three Pillars of Defense (PPT Framework)

1. People (The Roles)

- **Security Analysts (Tier 1/2):** The watchmen. They manage the alert queue, filter out standard background noise, and spot early indicators of an attack.
- **Incident Responders:** The digital firefighters. They contain active threats, evict hostile actors, and patch up entry points.
- **Threat Intelligence Experts:** The strategic scouts. They research external global adversary tactics to predict future targets.
- **Threat Hunters:** The active detectives. They assume the network is *already* compromised and hunt through logs for deeply hidden threats.

2. Process (The Rules)

- **Compliance Policies:** Legal and organizational frameworks ensuring data privacy laws (e.g., GDPR, HIPAA) are legally maintained.

- **Incident Response Playbooks:** Step-by-step technical blueprints providing deterministic actions for explicit attack types (e.g., Ransomware Playbook).
- **Disaster Recovery Steps:** Strategic recovery checklists detailing how to safely restore data and infrastructure if everything goes offline.

3. Technology (The Tools)

- **Firewalls:** Network gatekeepers analyzing traffic flow against explicit security criteria to block hostile connections.
 - **EDR (Endpoint Detection & Response):** Deep behavioral software running directly on endpoints (laptops, servers) to catch and terminate suspicious processes.
 - **SIEM (Security Information & Event Management):** A central intelligence platform collecting and parsing millions of raw event logs from everywhere simultaneously.
 - **Encryption Tools:** Cryptographic software rendering data entirely unreadable to theft unless unlocked with a valid, secure key.
-

◆ Q2: Digital Footprints: Log Types & Formats

Note

Logs are the immutable digital paper trails left behind by hardware and software actions. Blue teams treat logs as physical evidence at a crime scene.

Category 1: Endpoint Logs (Host-Level)

- **Operating System Logs:** Tracks interactive behaviors like logons, account elevation, and service creations (e.g., Windows Event Logs, Linux Syslog).
- **Application Logs:** Tracks internal software logic states, configuration modifications, and runtime errors (e.g., Apache/Nginx web server logs).

- **Process Execution Logs:** High-fidelity records tracking what binaries ran (`cmd.exe` , `powershell.exe`) and who initiated them.

Category 2: Network Infrastructure Logs

- **Firewall Logs:** Access metrics tracking connections permitted or rejected based on ports, IPs, and protocols.
- **DNS Logs:** Chronological records of every domain lookup requested by endpoints. Essential for catching command-and-control communication.

Category 3: Authentication & Identity Logs

- **Identity Provider (IAM) Logs:** Tracks authorization attempts, multi-factor triggers, and account creation/deletion histories.
- **Privilege Escalation Logs:** Flags events where a normal user successfully jumps to `Administrator` or `root` permissions.

Category 4: Cloud & Modern Service Logs

- **SaaS/Cloud Audit Trails:** Tracks configuration drifts, API calls made to infrastructure (e.g., AWS CloudTrail), and direct file modifications inside cloud storage buckets.

Industry Log Formatting Standards

1. JSON (Highly Parsing-Friendly)

Modern, structured key-value arrays easily parsed by database query engines.

```
{  
  "timestamp": "2026-05-30T10:45:00Z",  
  "event_id": "4624",  
  "user": "jdoe",  
  "status": "success",  
}
```

```
"source_ip": "192.168.1.50"
}
```

2. Syslog (Universal Network Format)

Standard string syntax used by infrastructure hardware like routers and Linux systems.

```
<34>1 2026-05-30T10:45:00.123Z my-firewall-01 filter - - - ID=4624 User=jdoe Status=Success
```

3. CSV / TSV (Flat File Format)

Lightweight tabular data separated by commas or tabs.


```
Timestamp,EventID,User,Status,SourceIP
2026-05-30T10:45:00Z,4624,jdoe,success,192.168.1.50
```


4. EVTX (Windows Binary Format)

Proprietary Windows format optimizing system storage. Requires explicit parsers (like Windows Event Viewer or SIEM ingestion agents) to display.

◆ Q3: The Forensic 5 Ws & 1 H Framework

When an alarm triggers, an analyst must map out these exact six coordinates to establish clear context.






Practical Presentation Scenario: "The Stolen Account"

- **WHO:** User credential amiller (Marketing Manager).
- **WHAT:** Massive exfiltration of a production billing database (customer_billing_info.sql).
- **WHEN:** Sunday, May 24, 2026, from 02:14:00 UTC to 02:18:30 UTC (Out-of-office anomaly).
- **WHERE:** Traffic routed anonymously through a TOR exit node (185.220.101.5) targeting an internal cloud environment in AWS.
- **HOW:** Credential harvesting via a phishing attack that occurred 3 days prior. Access was successful because multi-factor authentication (MFA) was missing on this specific application server.
- **WHY:** Financial extortion and selling clean credit card listings on dark web marketplaces.

- ◆ **Q4: Defensive Ecosystem: SOC, IR, and CTI**



1. Security Operations Center (SOC)

- **Role:** The continuous tactical watchtower.
- **Operations:** 24/7 monitoring of the network perimeter, logging metrics, and performing initial triage on daily automated alerts.

2. Incident Response (IR)

- **Role:** The tactical counter-attack forces.
- **Operations:** Isolating infected machines, eradicating malicious persistence, and performing post-incident file forensics.

3. Cyber Threat Intelligence (CTI)

- **Role:** The strategic global scout network.
 - **Operations:** Tracking global hacker movements (APTs), charting known hostile IP infrastructures, and harvesting Indicators of Compromise (IoCs).
-

The 6-Step NIST Incident Response Lifecycle

1. **Preparation:** Building the defense before the storm (playbooks, technical training, solid offline backup models).
 2. **Detection & Analysis:** Triaging incoming alerts to isolate legitimate incidents from false configurations.
 3. **Containment:** Stopping the spread. Disconnecting an infected server immediately from the local segment to prevent lateral movement.
 4. **Eradication:** Removing the root cause. Purging lingering malware binaries and patching the exploited security gaps.
 5. **Recovery:** Reintroducing clean configurations back into production safely while validating system stability.
 6. **Lessons Learned:** Post-incident review. Documentation of mistakes made and upgrading playbooks so the exact same attack fails next time.
-

◆ Q5: How to Analyze Logs

Tip

Log analysis is a systematic sorting methodology, not an exercise in random text skimming.

- **Step 1: Baseline Normal Behavior:** Document typical system resource usages, authorized office locations, and regular working hours. You cannot identify outliers until you define what is standard.
 - **Step 2: Noise Reduction via Queries:** Apply precise filters in your SIEM to exclude massive, expected system actions (like automated daily server checks) to highlight real anomalies.
 - **Step 3: Multi-Source Data Correlation:** Group alerts using matching fields like a specific **Timestamp** or an **IP Address** to follow the attacker's path from a firewall rule block to an endpoint terminal entry.
 - **Step 4: Tracking Core Anomalies:** Spot patterns like impossible travel (logins across different countries minutes apart) or users invoking suspicious system tools (like `PowerShell` scripts sweeping the subnet).
 - **Step 5: Structural Verification:** Match the anomalous log against the internal IT ticketing system. A weird server setting shift might just be a pre-planned, authorized maintenance ticket.
-

Appendix: Where to Practice Real-Time Blue Teaming

Cloud-Based Training Platforms (No Installation Required)

- **LetsDefend.io:** A web interface mimicking a real enterprise SOC queue. Great for managing alert handling workflows.
- **TryHackMe:** Excellent for interactive split-screen browser setups. Search for paths titled "**SOC Level 1**" or rooms covering "**Splunk**" and "**Wireshark**".
- **Blue Team Labs Online (BTLO):** Deep, capture-the-flag forensic rooms focused on breaking apart historic, real-world breach logs.

Local Defensive Applications (Free / Open-Source)

- **Wireshark:** A tool used to capture, open, and analyze raw network traffic packets directly over your local card.

- **Brim (Zui):** A lightweight desktop dashboard application designed to cleanly query massive network security logs.

```
(kali㉿kali)-[~]
$ cat access.log
026-05-30T10:00:01Z IP=192.168.1.15 URL="/index.html" STATUS=200 USER="jdoe"
026-05-30T10:01:14Z IP=192.168.1.22 URL="/login.php" STATUS=200 USER="asmith"
026-05-30T10:02:45Z IP=203.0.113.88 URL="/admin/config.php" STATUS=403 USER="anonymous"
026-05-30T10:05:00Z IP=192.168.1.15 URL="/profile.php" STATUS=200 USER="jdoe"
026-05-30T10:06:12Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:14Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:16Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:18Z IP=203.0.113.88 URL="/login.php" STATUS=200 USER="root"
026-05-30T10:07:22Z IP=203.0.113.88 URL="/admin/db_backup.sql" STATUS=200 USER="root"
026-05-30T10:10:00Z IP=192.168.1.30 URL="/index.html" STATUS=200 USER="mross"

(kali㉿kali)-[~]
$ grep -E "STATUS=401|STATUS=403" access.log
026-05-30T10:02:45Z IP=203.0.113.88 URL="/admin/config.php" STATUS=403 USER="anonymous"
026-05-30T10:06:12Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:14Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:16Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"

(kali㉿kali)-[~]
$ awk '{print $2}' access.log | sort | uniq -c
  2 IP=192.168.1.15
  1 IP=192.168.1.22
  1 IP=192.168.1.30
  6 IP=203.0.113.88

(kali㉿kali)-[~]
$ grep "IP=203.0.113.88" access.log
026-05-30T10:02:45Z IP=203.0.113.88 URL="/admin/config.php" STATUS=403 USER="anonymous"
026-05-30T10:06:12Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:14Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:16Z IP=203.0.113.88 URL="/login.php" STATUS=401 USER="root"
026-05-30T10:06:18Z IP=203.0.113.88 URL="/login.php" STATUS=200 USER="root"
026-05-30T10:07:22Z IP=203.0.113.88 URL="/admin/db_backup.sql" STATUS=200 USER="root"
```