


Zoom integration architecture

Authorization, meeting synchronization and deauthorization boundaries - production at schedra.xyz



Data flow and security controls

Least-privilege scopes, retained fields and lifecycle controls



OAuth and transport controls

Authorization boundary

- TLS 1.2 or newer for production browser and API traffic.
- State-bound OAuth callback; callback URL fixed from SCHEDRA_URL.
- Client secret and integration encryption key remain server-side.
- Access and refresh tokens encrypted with independent random IVs.
- Rotating refresh tokens persisted atomically to prevent stale overwrite.



Webhook controls

Deauthorization boundary

- Exact raw-body HMAC verification using the Zoom Secret Token.
- Constant-time signature comparison.
- Timestamp freshness check rejects requests outside five minutes.
- Zoom client ID checked before any deletion.
- Repeated valid deauthorization events are handled idempotently.

LEAST-PRIVILEGE ZOOM SCOPES

user:read:user	Identify and label the account the user authorized.
meeting:write:meeting	Create one scheduled meeting after booking confirmation.
meeting:update:meeting	Update the same meeting after a reschedule.
meeting:delete:meeting	Remove the meeting after cancellation.
meeting:read:list_meetings	Recover a Schedra-created meeting after interrupted persistence and avoid duplicates.



Stored by Schedra

Zoom user ID and account label; encrypted OAuth credentials and expiry; granted scopes; meeting ID, join URL and synchronization status.



Sent for a meeting

Event title, guest name, start time, duration, public event description, Schedra marker and private booking-management link.



Never requested

Meeting audio or video, recordings, chat, transcripts, participant activity or meeting analytics. Guest emails and private answers are not placed in the Zoom agenda.