Neo-Bank MSME — API Playbook

Complete REST surface of the composed platform: Bank Orchestrator v3.4.0

Generated 2026-10-21 from the merged OpenAPI schema · 112 paths · 127 operations · 147 component schemas

> **How to read this playbook**
>
> - **Base URL** — every path is relative to `http://localhost:8000`. All five services are mounted in one process.
> - **Wire format** — flat JSON everywhere: enums arrive as plain strings (`"TRACK_1_CLASSICAL"`), datetimes as ISO-8601 strings. No internal persistence markers.
> - **Errors** — uniform body `{"detail": "..."}`. Semantics: **404** unknown identifier, **409** prudential veto / state-machine conflict / governance PENDING, **422** validation gate (unconfirmed packet, amounts outside outstanding, out-of-scope product).
> - **Auth** — none (demo deployment; CORS is open).
> - **Reading order for a demo** — create a candidate in **Pillar 1** → submit (Pillar 2 scores it) → approve → disburse; then watch **Pillar 3** facilities/postings/ledger and **Pillar 4** buffer balances / capital snapshot / veto state update.
> - **Veto semantics** — `GET /p4/veto/consult` is the state *Pillar 2* must consult before confirming a packet. Pillar 3 never sees a veto event; it only ever sees a confirmed packet or none.
> - **Per-service docs** — each sub-app also serves its own Swagger at `/p1/docs`, `/p2/docs`, `/p3/docs`, `/p4/docs`, `/governance/docs`.

Prefix	Service	Owns
`/governance`	Orchestrator governance	Canon versions, Master Lexicon, tier table, interface rules, CIS-1 CASS contract stub, SI-1 staging, amendments, veto log, PENDING register
`/p1`	Pillar 1 — intake + demo flow	Candidates, scoring/approval/disbursement demo loop, board state, simulation tick, SSE
`/p2`	Pillar 2 — credit scoring	BRR/PD/LGD/EAD/EL, versioned BRR→PD grid, early-warning signals, override records, CASS feed contract
`/p3`	Pillar 3 — loan execution	Facilities, P2 packets, audit trail, postings, core-banking ledger, reconciliation, lifecycle actions
`/p4`	Pillar 4 — prudential layer	Buffer sub-accounts, guarantee-pool adequacy, capital snapshot, IFRS 9 staging, two-track veto, mode gate, pledge intake/release
`/bilan` + root	Platform	French-PCG balance sheet from the shared store, `/health`, `/ready`

Contents

1. Platform (root app)
2. Orchestrator Governance
3. Pillar 1
4. Pillar 2
5. Pillar 3

6. Pillar 4
7. Appendix A — Component schema catalogue (147 schemas)
8. Appendix B — Endpoints not in the schema (SSE, health probes)

Platform (root app)

bilan

French-PCG balance sheet (Actif/Passif) computed live from the shared Pillar 3/4 store, its invariant checks, memo (hors-bilan) items, and the admin-gated opening config.

`GET` **`/bilan`**

Bilan Actif/Passif

operationId: `get_bilan_bilan_get` · tags: bilan

Compute the balance sheet live from the shared KvStore.

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
`actif`	array of object	yes		
`passif`	array of object	yes		
`totaux`	object	yes		
`ecart`	number	yes		
`balanced`	boolean	yes		
`mouvements`	object	yes		Flow terms read from Pillar 3/4 — the inputs behind every line.
`hors_bilan`	object	yes		Memo items reported alongside the balance, never added to either face.
`sources`	object	yes		
`as_of`	string (date-time)	yes		
`checks`	array of object			
`reliable`	boolean		`true`	
`warnings`	array of string			

GET /bilan/config

Bilan config

operationId: `get_bilan_config_bilan_config_get` · tags: bilan

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
immobilisations	number		`0.0`	
autres_creances	number		`0.0`	
apport_reserve	number		`0.0`	
resultat_anterieur	number		`0.0`	
sid	number		`0.0`	
tier_c	number		`0.0`	
autres_emprunts	number		`0.0`	
depots_clients	number		`0.0`	
autres_dettes	number		`0.0`	
tresorerie_ouverture	number	yes		
tresorerie_ouverture_configured	boolean	yes		

PUT /bilan/config

Update bilan config

operationId: `put_bilan_config_bilan_config_put` · tags: bilan

Merge a partial update into `bilan_config_v1` and return the result. This is the only bilan path that writes — to a brand-new KV key, leaving `p3_state_v1` / `p4_state_v1` (and therefore `/ready`) untouched. Requires `X-Admin-Token` and leaves an append-only audit row behind. The config write and the audit append are two separate KV writes and are **not atomic**: the config is committed first, then the audit row. If the audit append fails the error is logged and the response is still 200, because the caller's change *did* take effect — reporting failure would invite a retry that then records a spurious second change. A failure of the config write itself still propagates (no transaction layer is built here; see `bug_bilan_fix_round_2.md`, R4).

PARAMETERS

Name	In	Type	Required	Default	Description
X-Admin-Token	header	string | null			

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
immobilisations	number | null			
autres_creances	number | null			
apport_reserve	number | null			
resultat_anterieur	number | null			
sid	number | null			
tier_c	number | null			
autres_emprunts	number | null			
depots_clients	number | null			
autres_dettes	number | null			
tresorerie_ouverture	number | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
immobilisations	number		`0.0`	
autres_creances	number		`0.0`	
apport_reserve	number		`0.0`	
resultat_anterieur	number		`0.0`	
sid	number		`0.0`	
tier_c	number		`0.0`	
autres_emprunts	number		`0.0`	
depots_clients	number		`0.0`	
autres_dettes	number		`0.0`	
tresorerie_ouverture	number	yes		

Field	Type	Required	Default	Description
`tresorerie_ouverture_configured`	boolean	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

system

Platform probes: liveness (`/health`) and the restart-ok readiness check (`/ready`) that re-opens fresh Pillar 3/4 runtimes and asserts a byte-identical snapshot round-trip.

GET /health

Health

operationId: `health_health_get` · tags: system

RESPONSES

200 Successful Response

object

GET /ready

Ready

operationId: `ready_ready_get` · tags: system

Restart-ok probe — mirrors rt3/rt4: open a fresh Pillar 3 and Pillar 4 runtime over the same KvStore file and assert the rehydrated snapshot is byte-identical to the persisted blob. 503 when any assertion fails.

RESPONSES

200 Successful Response

object

Orchestrator Governance

canon

Orchestrator governance — canon versions, ratification and lineage.

GET /governance/api/v1/canon/current

Get Current Canon

operationId: `governance_get_current_canon_api_v1_canon_current_get` · tags: canon

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version_number`	string	yes		
`name`	string	yes		
`status`	string	yes		
`ratified_at`	string (date-time) | null	yes		
`ratification_instrument`	string | null	yes		
`is_current`	boolean	yes		
`change_summary`	string | null	yes		
`lineage_notes`	string | null	yes		
`created_at`	string (date-time)	yes		

GET /governance/api/v1/canon/versions

List Versions

operationId: `governance_list_versions_api_v1_canon_versions_get` · tags: canon

RESPONSES

200 Successful Response

array of object

POST /governance/api/v1/canon/versions

Create Version

operationId: `governance_create_version_api_v1_canon_versions_post` · tags: canon

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`version_number`	string	yes		Canon version number, e.g. '3.4'
`name`	string	yes		
`change_summary`	string | null			
`lineage_notes`	string | null			
`status`	string		`"PENDING"`	

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version_number`	string	yes		
`name`	string	yes		
`status`	string	yes		
`ratified_at`	string (date-time) | null	yes		
`ratification_instrument`	string | null	yes		
`is_current`	boolean	yes		
`change_summary`	string | null	yes		
`lineage_notes`	string | null	yes		
`created_at`	string (date-time)	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /governance/api/v1/canon/versions/{version}

Get Version

operationId: `governance_get_version_api_v1_canon_versions__version__get` · tags: canon

PARAMETERS

Name	In	Type	Required	Default	Description
version	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version_number	string	yes		
name	string	yes		
status	string	yes		
ratified_at	string (date-time) | null	yes		
ratification_instrument	string | null	yes		
is_current	boolean	yes		
change_summary	string | null	yes		
lineage_notes	string | null	yes		
created_at	string (date-time)	yes		
ratification_instruments	array of object		`[]`	

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/canon/lineage

Get Lineage

operationId: `governance_get_lineage_api_v1_canon_lineage_get` · tags: canon

RESPONSES

200 Successful Response

array of object

POST /governance/api/v1/canon/versions/{version}/ratify

Ratify Version

operationId: `governance_ratify_version_api_v1_canon_versions__version__ratify_post` · tags: canon

PARAMETERS

Name	In	Type	Required	Default	Description
version	path	string	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
instrument_number	string	yes		e.g. 'RI-4'
resolution_ref	string | null			
description	string | null			
ratified_by	string		`"Governance Committee"`	

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version_number	string	yes		
name	string	yes		
status	string	yes		
ratified_at	string (date-time) | null	yes		
ratification_instrument	string | null	yes		
is_current	boolean	yes		
change_summary	string | null	yes		
lineage_notes	string | null	yes		
created_at	string (date-time)	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/canon/versions/{version}/supersede`

Supersede Version

operationId: `governance_supersede_version_api_v1_canon_versions__version__supersede_post` · tags: canon

PARAMETERS

Name	In	Type	Required	Default	Description
version	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version_number	string	yes		
name	string	yes		
status	string	yes		
ratified_at	string (date-time) | null	yes		
ratification_instrument	string | null	yes		
is_current	boolean	yes		
change_summary	string | null	yes		
lineage_notes	string | null	yes		
created_at	string (date-time)	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

lexicon

Master Lexicon — locked terms and the rename map.

GET `/governance/api/v1/lexicon/categories`

List Categories

operationId: `governance_list_categories_api_v1_lexicon_categories_get` · tags: lexicon

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/lexicon/terms

List Terms

operationId: `governance_list_terms_api_v1_lexicon_terms_get` · tags: lexicon

PARAMETERS

Name	In	Type	Required	Default	Description
category_id	query	string | null			
model_scope	query	string | null			
search	query	string | null			

RESPONSES

200 Successful Response

array of object

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/lexicon/terms

Create Term

operationId: `governance_create_term_api_v1_lexicon_terms_post` · tags: lexicon

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`term`	string	yes		The locked term name
`category_id`	string (uuid)	yes		
`abbreviation`	string | null			
`definition`	string	yes		
`model_scope`	string		`"NEUTRAL"`	
`canon_section_ref`	string | null			
`is_new_in_v34`	boolean		`false`	
`supersedes`	string | null			

RESPONSES

`201` Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`category_id`	string (uuid)	yes		
`term`	string	yes		
`abbreviation`	string | null	yes		
`definition`	string	yes		
`model_scope`	string	yes		
`canon_section_ref`	string | null	yes		
`is_new_in_v34`	boolean	yes		
`supersedes`	string | null	yes		
`created_at`	string (date-time)	yes		
`updated_at`	string (date-time)	yes		

`422` Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /governance/api/v1/lexicon/terms/{term}

Get Term

operationId: `governance_get_term_api_v1_lexicon_terms__term__get` · tags: lexicon

PARAMETERS

Name	In	Type	Required	Default	Description
term	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
category_id	string (uuid)	yes		
term	string	yes		
abbreviation	string | null	yes		
definition	string	yes		
model_scope	string	yes		
canon_section_ref	string | null	yes		
is_new_in_v34	boolean	yes		
supersedes	string | null	yes		
created_at	string (date-time)	yes		
updated_at	string (date-time)	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

PUT /governance/api/v1/lexicon/terms/{term}

Update Term

operationId: `governance_update_term_api_v1_lexicon_terms__term__put` · tags: lexicon

PARAMETERS

Name	In	Type	Required	Default	Description
term	path	string	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
definition	string | null			
model_scope	string | null			
abbreviation	string | null			
is_new_in_v34	boolean | null			
supersedes	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
category_id	string (uuid)	yes		
term	string	yes		
abbreviation	string | null	yes		
definition	string	yes		
model_scope	string	yes		
canon_section_ref	string | null	yes		
is_new_in_v34	boolean	yes		
supersedes	string | null	yes		
created_at	string (date-time)	yes		
updated_at	string (date-time)	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/lexicon/renamed

List Renamed

operationId: `governance_list_renamed_api_v1_lexicon_renamed_get` · tags: lexicon

RESPONSES

200 Successful Response

array of object

POST /governance/api/v1/lexicon/validate

Validate Terms

operationId: `governance_validate_terms_api_v1_lexicon_validate_post` · tags: lexicon

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
terms	array of string	yes		List of terms to validate against the Master Lexicon

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
valid	array of string		`[]`	
invalid	array of string		`[]`	
renamed	object			old term -> new locked term

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

tiers-and-pillars

Canonical tier table (Tier A/B/Senior Debt/C/B-Fees/D), insurance status (sole-locus rule) and pillar boundary/perimeter checks.

GET /governance/api/v1/tiers

List Tiers

operationId: `governance_list_tiers_api_v1_tiers_get` · tags: tiers-and-pillars

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/tiers/protection-rules

List Protection Rules

operationId: `governance_list_protection_rules_api_v1_tiers_protection_rules_get` · tags: tiers-and-pillars

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/tiers/{label}

Get Tier

operationId: `governance_get_tier_api_v1_tiers__label__get` · tags: tiers-and-pillars

PARAMETERS

Name	In	Type	Required	Default	Description
`label`	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`tier_label`	string	yes		
`tier_name`	string	yes		
`model_scope`	string	yes		
`description`	string | null	yes		
`insurance_status`	string | null	yes		
`insurance_status_authority`	string | null	yes		
`sort_order`	integer	yes		
`canon_section_ref`	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /governance/api/v1/tiers/{label}/insurance-status

Get Insurance Status

operationId: `governance_get_insurance_status_api_v1_tiers__label__insurance_status_get` · tags: tiers-and-pillars

PARAMETERS

Name	In	Type	Required	Default	Description
label	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
tier_label	string	yes		
tier_name	string	yes		
model_scope	string	yes		
description	string | null	yes		
insurance_status	string | null	yes		
insurance_status_authority	string | null	yes		
sort_order	integer	yes		
canon_section_ref	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

PUT /governance/api/v1/tiers/{label}/insurance-status

Set Insurance Status

operationId: `governance_set_insurance_status_api_v1_tiers__label__insurance_status_put` · tags: tiers-and-pillars

§4.6 'sole locus' rule: Tier A insurance status resolves ONLY here.

PARAMETERS

Name	In	Type	Required	Default	Description
label	path	string	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
status	string	yes		Tier A insurance status (sole locus rule)

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
tier_label	string	yes		
tier_name	string	yes		
model_scope	string	yes		
description	string | null	yes		
insurance_status	string | null	yes		
insurance_status_authority	string | null	yes		
sort_order	integer	yes		
canon_section_ref	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/pillars

List Pillars

operationId: `governance_list_pillars_api_v1_pillars_get` · tags: tiers-and-pillars

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/pillars/{number}

Get Pillar

operationId: `governance_get_pillar_api_v1_pillars__number__get` · tags: tiers-and-pillars

PARAMETERS

Name	In	Type	Required	Default	Description
number	path	integer	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
pillar_number	integer	yes		
pillar_name	string	yes		
produces	array of object	yes		
consumes	array of object	yes		
decides	array of object	yes		
must_not_do	array of object	yes		
canon_section_ref	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/pillars/{number}/check-perimeter`

Check Perimeter

operationId: `governance_check_perimeter_api_v1_pillars__number__check_perimeter_post` · tags: tiers-and-pillars

Check whether a proposed action is within a pillar's perimeter.

PARAMETERS

Name	In	Type	Required	Default	Description
`number`	path	integer	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`pillar_number`	integer	yes		
`action`	string	yes		A textual description of the proposed action

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`allowed`	boolean	yes		
`reason`	string	yes		
`violated_rule`	string | null			

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

interface-rules

Inter-pillar interface rules (§6) and flow validation.

GET `/governance/api/v1/interfaces`

List Interfaces

operationId: `governance_list_interfaces_api_v1_interfaces_get` · tags: interface-rules

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/interfaces/summary

Interface Summary

operationId: `governance_interface_summary_api_v1_interfaces_summary_get` · tags: interface-rules

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/interfaces/{rule_number}

Get Interface

operationId: `governance_get_interface_api_v1_interfaces__rule_number__get` · tags: interface-rules

PARAMETERS

Name	In	Type	Required	Default	Description
rule_number	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
rule_number	string	yes		
name	string	yes		
description	string | null	yes		
direction	string	yes		
decides_who	string | null	yes		
executes_who	string | null	yes		
bypasses_pillar3	boolean	yes		
canon_section_ref	string | null	yes		
notable_v34_change	string | null	yes		
fields	array of object		`[]`	

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/interfaces/validate-flow`

Validate Flow

operationId: `governance_validate_flow_api_v1_interfaces_validate_flow_post` · tags: interface-rules

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`source`	string	yes		e.g. 'P2'
`destination`	string	yes		e.g. 'P4'

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`rules`	array of object		`[]`	
`bypasses_pillar3`	boolean		`false`	

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

cass-stub

CASS interface stub (CIS-1) — the contract shape only; the full methodology is PENDING and blocks Gate G1.

GET `/governance/api/v1/cass-stub`

Get Stub

operationId: `governance_get_stub_api_v1_cass_stub_get` · tags: cass-stub

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version`	string	yes		
`issued_by`	string	yes		
`scope`	string	yes		
`source_pillar`	string	yes		
`dest_pillar`	string	yes		
`refresh_cadence`	string | null	yes		
`failure_semantics`	string | null	yes		
`fields`	array of object		`[]`	

PUT /governance/api/v1/cass-stub

Update Stub

operationId: `governance_update_stub_api_v1_cass_stub_put` · tags: cass-stub

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
version	string		`"1.0"`	
issued_by	string		`"Orchestrator"`	
scope	string		`"contract shape only \u2014 never signal derivation or consumption logic"`	
source_pillar	string		`"P2"`	
dest_pillar	string		`"P4"`	
refresh_cadence	string | null			
failure_semantics	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version	string	yes		
issued_by	string	yes		
scope	string	yes		
source_pillar	string	yes		
dest_pillar	string	yes		
refresh_cadence	string | null	yes		
failure_semantics	string | null	yes		
fields	array of object		`[]`	

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/cass-stub/fields

Get Stub Fields

operationId: `governance_get_stub_fields_api_v1_cass_stub_fields_get` · tags: cass-stub

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version	string	yes		
issued_by	string	yes		
scope	string	yes		
source_pillar	string	yes		
dest_pillar	string	yes		
refresh_cadence	string | null	yes		
failure_semantics	string | null	yes		
fields	array of object		`[]`	

GET /governance/api/v1/cass-stub/scope

Get Stub Scope

operationId: `governance_get_stub_scope_api_v1_cass_stub_scope_get` · tags: cass-stub

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
version	string	yes		
issued_by	string	yes		
scope	string	yes		
source_pillar	string	yes		
dest_pillar	string	yes		
refresh_cadence	string | null	yes		
failure_semantics	string | null	yes		
fields	array of object		`[]`	

staging-mode

SI-1 staging registry — bank-wide mode (Conventional / Adaptive), build stage, and gate states G0–G3.

GET /governance/api/v1/staging/mode

Get Mode

operationId: `governance_get_mode_api_v1_staging_mode_get` · tags: staging-mode

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
current_mode	string	yes		
fallback_guarantee	string	yes		
changed_at	string (date-time)	yes		
changed_by	string	yes		
change_rationale	string | null	yes		

PUT /governance/api/v1/staging/mode

Set Mode

operationId: `governance_set_mode_api_v1_staging_mode_put` · tags: staging-mode

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
new_mode	string	yes		
changed_by	string		`"Governance Committee"`	
change_rationale	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
current_mode	string	yes		
fallback_guarantee	string	yes		
changed_at	string (date-time)	yes		
changed_by	string	yes		
change_rationale	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/staging/stage

Get Stage

operationId: `governance_get_stage_api_v1_staging_stage_get` · tags: staging-mode

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
current_stage	integer	yes		
changed_at	string (date-time)	yes		
changed_by	string	yes		

PUT /governance/api/v1/staging/stage

Set Stage

operationId: `governance_set_stage_api_v1_staging_stage_put` · tags: staging-mode

PARAMETERS

Name	In	Type	Required	Default	Description
stage	query	integer	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
current_stage	integer	yes		
changed_at	string (date-time)	yes		
changed_by	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/staging/gates

List Gates

operationId: `governance_list_gates_api_v1_staging_gates_get` · tags: staging-mode

RESPONSES

200 Successful Response

array of object

GET /governance/api/v1/staging/gates/{label}

Get Gate

operationId: `governance_get_gate_api_v1_staging_gates__label__get` · tags: staging-mode

PARAMETERS

Name	In	Type	Required	Default	Description
label	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
gate_label	string	yes		
status	string	yes		
criteria	string | null	yes		
cleared_at	string (date-time) | null	yes		
cleared_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/staging/gates/{label}/clear

Clear Gate

operationId: `governance_clear_gate_api_v1_staging_gates__label__clear_post` · tags: staging-mode

PARAMETERS

Name	In	Type	Required	Default	Description
label	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
gate_label	string	yes		
status	string	yes		
criteria	string | null	yes		
cleared_at	string (date-time) | null	yes		
cleared_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/staging/gates/{label}/block

Block Gate

operationId: `governance_block_gate_api_v1_staging_gates__label__block_post` · tags: staging-mode

PARAMETERS

Name	In	Type	Required	Default	Description
label	path	string	yes		
notes	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
gate_label	string	yes		
status	string	yes		
criteria	string | null	yes		
cleared_at	string (date-time) | null	yes		
cleared_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/staging/is-adaptive-active

Is Adaptive Active

operationId: `governance_is_adaptive_active_api_v1_staging_is_adaptive_active_get` · tags: staging-mode

Whether adaptive machinery (ABSF/CASS/ERME) should currently be running.

RESPONSES

200 Successful Response

object

change-control

Amendment proposals, dependency review, ratification and rejection.

GET /governance/api/v1/changes/proposals

List Proposals

operationId: `governance_list_proposals_api_v1_changes_proposals_get` · tags: change-control

PARAMETERS

Name	In	Type	Required	Default	Description
status	query	string | null			
change_type	query	string | null			

RESPONSES

200 Successful Response

array of object

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/changes/proposals

Create Proposal

operationId: `governance_create_proposal_api_v1_changes_proposals_post` · tags: change-control

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`title`	string	yes		
`description`	string | null			
`change_type`	string		`"STRUCTURAL"`	
`proposed_by`	string	yes		
`canon_version_target`	string | null			
`requires_dependency_review`	boolean		`false`	
`requires_g2s_review`	boolean		`false`	

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`proposal_number`	string	yes		
`title`	string	yes		
`description`	string | null	yes		
`change_type`	string	yes		
`proposed_by`	string	yes		
`status`	string	yes		
`canon_version_target`	string | null	yes		
`requires_dependency_review`	boolean	yes		
`requires_g2s_review`	boolean	yes		
`submitted_at`	string (date-time)	yes		
`resolved_at`	string (date-time) | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /governance/api/v1/changes/proposals/{proposal_id}

Get Proposal

operationId: `governance_get_proposal_api_v1_changes_proposals__proposal_id__get` · tags: change-control

PARAMETERS

Name	In	Type	Required	Default	Description
proposal_id	path	string (uuid)	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
proposal_number	string	yes		
title	string	yes		
description	string | null	yes		
change_type	string	yes		
proposed_by	string	yes		
status	string	yes		
canon_version_target	string | null	yes		
requires_dependency_review	boolean	yes		
requires_g2s_review	boolean	yes		
submitted_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
dependency_reviews	array of object		`[]`	
ratification_votes	array of object		`[]`	

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/changes/proposals/{proposal_id}/dependency-review

Submit Dependency Review

operationId: `governance_submit_dependency_review_api_v1_changes_proposals__proposal_id__dependency_review_post` · tags: change-control

PARAMETERS

Name	In	Type	Required	Default	Description
proposal_id	path	string (uuid)	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
pillar_number	integer	yes		
review_status	string		`"PENDING"`	
reviewer_notes	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
proposal_id	string (uuid)	yes		
pillar_number	integer	yes		
review_status	string	yes		
reviewer_notes	string | null	yes		
reviewed_at	string (date-time) | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/changes/proposals/{proposal_id}/ratify

Ratify Proposal

operationId: `governance_ratify_proposal_api_v1_changes_proposals__proposal_id__ratify_post` · tags: change-control

PARAMETERS

Name	In	Type	Required	Default	Description
proposal_id	path	string (uuid)	yes		
instrument_number	query	string | null			
resolution_ref	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
proposal_number	string	yes		
title	string	yes		
description	string | null	yes		
change_type	string	yes		
proposed_by	string	yes		
status	string	yes		
canon_version_target	string | null	yes		
requires_dependency_review	boolean	yes		
requires_g2s_review	boolean	yes		
submitted_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/changes/proposals/{proposal_id}/reject`

Reject Proposal

operationId: `governance_reject_proposal_api_v1_changes_proposals__proposal_id__reject_post` · tags: change-control

PARAMETERS

Name	In	Type	Required	Default	Description
proposal_id	path	string (uuid)	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
proposal_number	string	yes		
title	string	yes		
description	string | null	yes		
change_type	string	yes		
proposed_by	string	yes		
status	string	yes		
canon_version_target	string | null	yes		
requires_dependency_review	boolean	yes		
requires_g2s_review	boolean	yes		
submitted_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

veto-log

Immutable log of veto freeze events and their resolution.

GET /governance/api/v1/vetoes

List Vetoes

operationId: `governance_list_vetoes_api_v1_vetoes_get` · tags: veto-log

PARAMETERS

Name	In	Type	Required	Default	Description
track	query	integer | null			
status	query	string | null			

RESPONSES

200 Successful Response

array of object

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/vetoes

Record Veto

operationId: `governance_record_veto_api_v1_vetoes_post` · tags: veto-log

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
track	integer	yes		
scope	string		"facility"	
facility_id	string | null			
pillar_4_signal	string | null			
p2_packet_action	string	yes		
notes	string | null			

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
event_number	string	yes		
track	integer	yes		
scope	string	yes		
facility_id	string | null	yes		
pillar_4_signal	string | null	yes		
p2_packet_action	string	yes		
orchestrator_notified_at	string (date-time)	yes		
governance_review_status	string	yes		
restart_authorized_at	string (date-time) | null	yes		
restart_authorized_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /governance/api/v1/vetoes/{event_id}

Get Veto

operationId: `governance_get_veto_api_v1_vetoes__event_id__get` · tags: veto-log

PARAMETERS

Name	In	Type	Required	Default	Description
event_id	path	string (uuid)	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
event_number	string	yes		
track	integer	yes		
scope	string	yes		
facility_id	string | null	yes		
pillar_4_signal	string | null	yes		
p2_packet_action	string	yes		
orchestrator_notified_at	string (date-time)	yes		
governance_review_status	string	yes		
restart_authorized_at	string (date-time) | null	yes		
restart_authorized_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/vetoes/{event_id}/resolve`

Resolve Veto

operationId: `governance_resolve_veto_api_v1_vetoes__event_id__resolve_post` · tags: veto-log

PARAMETERS

Name	In	Type	Required	Default	Description
event_id	path	string (uuid)	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
decision	string	yes		
authorized_by	string		`"Governance Committee"`	
notes	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
event_number	string	yes		
track	integer	yes		
scope	string	yes		
facility_id	string | null	yes		
pillar_4_signal	string | null	yes		
p2_packet_action	string	yes		
orchestrator_notified_at	string (date-time)	yes		
governance_review_status	string	yes		
restart_authorized_at	string (date-time) | null	yes		
restart_authorized_by	string | null	yes		
notes	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

pending-register

Governance PENDING items — named stops that must never be silently resolved in code.

GET /governance/api/v1/pending

List Items

operationId: `governance_list_items_api_v1_pending_get` · tags: pending-register

PARAMETERS

Name	In	Type	Required	Default	Description
status	query	string | null			
priority	query	string | null			
category	query	string | null			

RESPONSES

200 Successful Response

array of object

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/pending

Register Item

operationId: `governance_register_item_api_v1_pending_post` · tags: pending-register

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
title	string	yes		
description	string | null			
category	string		"GOVERNANCE"	
registered_in_canon	string | null			
scope_details	string | null			
priority	string		"MEDIUM"	
assigned_to	string | null			

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
item_number	string	yes		
title	string	yes		
description	string | null	yes		
category	string	yes		
registered_in_canon	string | null	yes		
scope_details	string | null	yes		
status	string	yes		
priority	string	yes		
assigned_to	string | null	yes		
registered_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
resolution_notes	string | null	yes		
governance_reference	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET `/governance/api/v1/pending/summary`

Summary

operationId: `governance_summary_api_v1_pending_summary_get` · tags: pending-register

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
total	integer		`0`	
open	integer		`0`	
by_category	object			
by_priority	object			

GET /governance/api/v1/pending/{item_id}

Get Item

operationId: `governance_get_item_api_v1_pending__item_id__get` · tags: pending-register

PARAMETERS

Name	In	Type	Required	Default	Description
item_id	path	string (uuid)	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
item_number	string	yes		
title	string	yes		
description	string | null	yes		
category	string	yes		
registered_in_canon	string | null	yes		
scope_details	string | null	yes		
status	string	yes		
priority	string	yes		
assigned_to	string | null	yes		
registered_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
resolution_notes	string | null	yes		
governance_reference	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

PUT /governance/api/v1/pending/{item_id}

Update Item

operationId: `governance_update_item_api_v1_pending__item_id__put` · tags: pending-register

PARAMETERS

Name	In	Type	Required	Default	Description
item_id	path	string (uuid)	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
title	string | null			
description	string | null			
category	string | null			
scope_details	string | null			
priority	string | null			
assigned_to	string | null			
status	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
item_number	string	yes		
title	string	yes		
description	string | null	yes		
category	string	yes		
registered_in_canon	string | null	yes		
scope_details	string | null	yes		
status	string	yes		
priority	string	yes		
assigned_to	string | null	yes		
registered_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
resolution_notes	string | null	yes		
governance_reference	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /governance/api/v1/pending/{item_id}/resolve

Resolve Item

operationId: governance_resolve_item_api_v1_pending__item_id__resolve_post · tags: pending-register

PARAMETERS

Name	In	Type	Required	Default	Description
item_id	path	string (uuid)	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
resolution_notes	string	yes		Required by do-not-resolve-in-code discipline
governance_reference	string | null			e.g. 'RI-3' or governance ruling reference

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string (uuid)	yes		
item_number	string	yes		
title	string	yes		
description	string | null	yes		
category	string	yes		
registered_in_canon	string | null	yes		
scope_details	string | null	yes		
status	string	yes		
priority	string	yes		
assigned_to	string | null	yes		
registered_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
resolution_notes	string | null	yes		
governance_reference	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/governance/api/v1/pending/{item_id}/strike`

Strike Item

operationId: `governance_strike_item_api_v1_pending__item_id__strike_post` · tags: pending-register

PARAMETERS

Name	In	Type	Required	Default	Description
`item_id`	path	string (uuid)	yes		
`governance_reference`	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`item_number`	string	yes		
`title`	string	yes		
`description`	string | null	yes		
`category`	string	yes		
`registered_in_canon`	string | null	yes		
`scope_details`	string | null	yes		
`status`	string	yes		
`priority`	string	yes		
`assigned_to`	string | null	yes		
`registered_at`	string (date-time)	yes		
`resolved_at`	string (date-time) | null	yes		
`resolution_notes`	string | null	yes		
`governance_reference`	string | null	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

system

Platform probes: liveness (`/health`) and the restart-ok readiness check (`/ready`) that re-opens fresh Pillar 3/4 runtimes and asserts a byte-identical snapshot round-trip.

GET `/governance/health`

Health

operationId: `governance_health_health_get` · tags: system

RESPONSES

200 Successful Response

object

Pillar 1 — Candidates + Demo Flow

p1

Pillar 1 — borrower intake: create/import candidates, run the origination flow (submit → score → approve → disburse), and read candidate state. Demo harness, not a lending authority.

GET /p1/candidates

List candidates

operationId: `p1_list_candidates_candidates_get` · tags: p1

Optionally filter by `status` (new / submitted / approved / disbursed / rejected).

PARAMETERS

Name	In	Type	Required	Default	Description
status	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
candidates	array of object	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p1/candidates

Create a candidate

operationId: `p1_create_candidate_candidates_post` · tags: p1

Borrower intake form. Auto-generates a payment behaviour (or uses the override) and stages the candidate as `new`.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
first_name	string	yes		
last_name	string	yes		
name_ar	string | null			
gender	string — one of: `male`, `female`		`"male"`	
age	integer		`0`	
national_id	string | null			
phone	string | null			
city	string		`"Muscat"`	
employer_name	string | null			
employer_type	string — one of: `government`, `military`, `private`, `self_employed` | null			
employment_years	number		`1.0`	
employer_start_date	string | null			
job_title	string | null			
monthly_salary	number	yes		
product	string		`"auto_loan"`	
requested_amount	number	yes		
requested_tenure_months	integer		`12`	
payment_behavior	object | null			
outcome_override	string — one of: `paid`, `default`, `delinquent_cured` | null			

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
candidate	object	yes		API representation of a candidate row.
payment_behavior	object | null			

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p1/candidates/import

Import a candidate (JSON body)

operationId: `p1_import_candidate_candidates_import_post` · tags: p1

Import a candidate from an exported JSON payload. Payment behaviour is used verbatim when present; otherwise auto-generated. Status is always `new` so the demo pipeline can re-run from scratch. Re-importing an existing borrower returns 409 (never a duplicate row).

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`first_name`	string	yes		
`last_name`	string	yes		
`name_ar`	string | null			
`gender`	string — one of: `male`, `female`		`"male"`	
`age`	integer		`0`	
`national_id`	string | null			
`phone`	string | null			
`city`	string		`"Muscat"`	
`employer_name`	string | null			
`employer_type`	string — one of: `government`, `military`, `private`, `self_employed` | null			
`employment_years`	number		`1.0`	
`employer_start_date`	string | null			
`job_title`	string | null			
`monthly_salary`	number	yes		
`product`	string		`"auto_loan"`	
`requested_amount`	number	yes		
`requested_tenure_months`	integer		`12`	
`payment_behavior`	object | null			
`outcome_override`	string — one of: `paid`, `default`, `delinquent_cured` | null			
`seed_profile`	string | null			
`application_json`	object | null			
`sim_state`	object | null			

RESPONSES

`201` Successful Response

Field	Type	Required	Default	Description
`candidate`	object	yes		API representation of a candidate row.
`payment_behavior`	object | null			

409 Candidate already exists

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p1/candidates/import/file

Import a candidate (file upload)

operationId: `p1_import_candidate_file_candidates_import_file_post` · tags: p1

Import a candidate from a JSON file upload.

REQUEST BODY

multipart/form-data required

Field	Type	Required	Default	Description
file	string	yes		

RESPONSES

201 Successful Response

Field	Type	Required	Default	Description
candidate	object	yes		API representation of a candidate row.
payment_behavior	object | null			

409 Candidate already exists

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /p1/demo/data-files

List exported candidate files

operationId: `p1_list_data_files_demo_data_files_get` · tags: p1

List exported candidate JSON files under `data/candidates/`.

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
files	array of object	yes		

GET `/p1/demo/data-files/{filename}`

Read one exported candidate file

operationId: `p1_get_data_file_demo_data_files__filename__get` · tags: p1

Return the content of a specific exported candidate JSON file.

PARAMETERS

Name	In	Type	Required	Default	Description
filename	path	string	yes		

RESPONSES

200 Successful Response

object

404 File not found

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /p1/candidates/{candidate_id}

Read a candidate

operationId: `p1_get_candidate_candidates__candidate_id__get` · tags: p1

PARAMETERS

Name	In	Type	Required	Default	Description
candidate_id	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
id	string	yes		
seed_profile	string | null	yes		
first_name	string	yes		
last_name	string	yes		
name_ar	string | null	yes		
gender	string	yes		
age	integer	yes		
national_id	string | null	yes		
phone	string | null	yes		
city	string	yes		
employer_name	string | null	yes		
employer_type	string | null	yes		
employment_years	number	yes		
job_title	string | null	yes		
monthly_salary	number	yes		
product	string	yes		
requested_amount	number	yes		
requested_tenure_months	integer	yes		
status	string	yes		
submitted_at	string (date-time) | null	yes		
scored_at	string (date-time) | null	yes		
approved_at	string (date-time) | null	yes		
originated_at	string (date-time) | null	yes		
disbursed_at	string (date-time) | null	yes		
application_id	string | null	yes		
facility_id	string | null	yes		
p2_brr	integer | null	yes		
p2_pd	number | null	yes		

Field	Type	Required	Default	Description
p2_zone	string | null	yes		
p2_packet_status	string | null	yes		
payment_behavior	object | null	yes		
sim_state	object | null	yes		
created_at	string (date-time)	yes		
updated_at	string (date-time)	yes		
approval_note	string | null	yes		
approved_by	string | null	yes		
display_name	string	yes		

404 Unknown candidate

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

DELETE /p1/candidates/{candidate_id}

Delete a candidate

operationId: `p1_delete_candidate_candidates__candidate_id__delete` · tags: p1

Deletes the candidate row; a disbursed facility is mirrored closed in P3/P4 first.

PARAMETERS

Name	In	Type	Required	Default	Description
candidate_id	path	string	yes		

RESPONSES

204 Successful Response

404 Unknown candidate

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p1/candidates/{candidate_id}/submit

Submit for scoring

operationId: `p1_submit_candidate_candidates__candidate_id__submit_post` · tags: p1

Run the origination flow: Pillar 2 scores the candidate (BRR, PD, zone) and a provisional output packet is registered with Pillar 3; Pillar 4's veto state is consulted as the packet is confirmed.

PARAMETERS

Name	In	Type	Required	Default	Description
`candidate_id`	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`status`	string | null			
`candidate_id`	string | null			
`facility_id`	string | null			
`packet_id`	string | null			
`approved`	boolean | null			
`amount`	number | null			
`currency`	string | null			
`brr`	integer | null			
`pd`	number | null			
`zone`	string | null			

404 Unknown candidate

409 Candidate not in a submittable state

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p1/candidates/{candidate_id}/approve

Officer approval decision

operationId: `p1_approve_candidate_candidates__candidate_id__approve_post` · tags: p1

The manual officer gate — ALWAYS required (MANUAL_APPROVAL_ALWAYS). Approval confirms the Pillar 2 packet and opens the facility in Pillar 3.

PARAMETERS

Name	In	Type	Required	Default	Description
candidate_id	path	string	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
approve	boolean		`true`	
officer_id	string		`"OFFICER-1"`	
officer_name	string | null			
note	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
status	string | null			
candidate_id	string | null			
facility_id	string | null			
packet_id	string | null			
approved	boolean | null			
amount	number | null			
currency	string | null			
brr	integer | null			
pd	number | null			
zone	string | null			

404 Unknown candidate

409 Candidate not in an approvable state

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST `/p1/candidates/{candidate_id}/disburse`

Disburse the approved facility

operationId: `p1_disburse_candidate_candidates__candidate_id__disburse_post` · tags: p1

Disburse the facility in Pillar 3, register the opening balance in Pillar 4, and book the origination-fee and risk-premium postings.

PARAMETERS

Name	In	Type	Required	Default	Description
`candidate_id`	path	string	yes		

REQUEST BODY

`application/json`

Field	Type	Required	Default	Description
`amount`	number | null			
`currency`	string		`"USD"`	

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`status`	string | null			
`candidate_id`	string | null			
`facility_id`	string | null			
`packet_id`	string | null			
`approved`	boolean | null			
`amount`	number | null			
`currency`	string | null			
`brr`	integer | null			
`pd`	number | null			
`zone`	string | null			

404 Unknown candidate

409 Candidate not in a disbursable state

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

p1-demo

Pillar 1 demo loop — SSE event stream, board state, simulation tick, seed profiles and factory reset.

GET /p1/demo/state

Demo board state

operationId: `p1_get_state_demo_state_get` · tags: p1-demo

One snapshot for the demo board: candidates by status, facilities, book KPIs, IFRS 9 map, and the live P4 veto/mode state. Pure GET — does not publish to the SSE bus.

RESPONSES

200 Successful Response

object

POST /p1/demo/tick

Advance the simulation one month

operationId: `p1_post_tick_demo_tick_post` · tags: p1-demo

Move every disbursed facility one month along its payment behaviour (repayment / delinquency / default / recovery), then publish the new state on the SSE bus.

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
tick	object	yes		
state	object	yes		

GET /p1/demo/profiles

List seed profiles

operationId: `p1_get_profiles_demo_profiles_get` · tags: p1-demo

The demo seed profiles (data tier, expected outcome, tagline) the board can instantiate.

RESPONSES

200 Successful Response

object

POST /p1/demo/seed

Seed the demo pipeline

operationId: `p1_post_seed_demo_seed_post` · tags: p1-demo

Instantiate every seed profile as a fresh candidate.

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
seeded	integer	yes		

POST `/p1/demo/reset`

Factory reset the demo bank

operationId: `p1_post_reset_demo_reset_post` · tags: p1-demo

Wipe candidates, facilities, postings and ledger in P1/P3/P4, re-seed the governance-approved initial Tier D capital base, and return the board to month 0.

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
`status`	string	yes		
`state`	object	yes		

Pillar 2 — Credit Scoring & Risk Rating

health

Sub-app liveness probes.

GET `/p2/health`

Liveness + grid version

operationId: `p2_health_health_get` · tags: health

RESPONSES

200 Successful Response

object

pillar2

Pillar 2 — credit scoring & risk rating: BRR scoring, PD/LGD/EAD/EL, the versioned BRR→PD grid, early-warning signals, override records, and the CASS feed contract.

POST /p2/v1/score

Score one application

operationId: `p2_score_application_v1_score_post` · tags: pillar2

The full Pillar 2 pipeline for one application (Spec §2): factor scoring, BRR assignment via the versioned BRR→PD grid, PD/LGD/EAD/EL, collateral-track selection, and the output packet Pillar 3 records verbatim. 422 when the product is outside sandbox scope or the selected track is unavailable under the model.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
application_id	string	yes		
segment	`Segment`	yes		MSME segment — size/complexity based, not data-availability based (Canon §2.1). one of: `MICRO`, `SMALL`, `MEDIUM`
operating_model	`OperatingModel`	yes		Which sibling Orchestrator Canon the market runs under. one of: `S`, `G`
facility	object	yes		
maturity_regime	`MaturityRegime` | null			
model_maturity_stage	`ModelMaturityStage`			Model Maturity Stage (Canon §2.0, ratified P-5). one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
financials	object			Minimum financial schema after OCR (Spec §12.1). All fields optional.
cash_flow	object			Bank-feed / POS derived series (Data Matrix L-001..L-006).
business	object			Data Matrix B-001..B-005.
management	object			Data Matrix M-001..M-004.
alternative	object			Data Matrix A-001..A-004.
collateral	array of object			
rails_connected	array of string			
policy_exception_flags	array of string			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
application_id	string	yes		
segment	`Segment`	yes		MSME segment — size/complexity based, not data-availability based (Canon §2.1). one of: `MICRO`, `SMALL`, `MEDIUM`
maturity_regime	`MaturityRegime`	yes		Digital maturity regime — an internal regime inside each segment (Canon §2.2). one of: `LOW`, `INTERMEDIATE`, `HIGH`
data_quality	object	yes		
rating	object	yes		
credit_risk	object	yes		

Field	Type	Required	Default	Description
pricing	object	yes		
zone	DecisioningZone	yes		Three-zone decisioning model (Canon §2.7, ratified P-6). one of: AUTO_APPROVE, AUGMENTED_DECISION, MANUAL_REVIEW
packet	object	yes		P2 -> P3 handoff packet (Canon §2.7 V3.0 addition, §3 P2->P3).

422 Product out of sandbox scope or track unavailable

GET /p2/v1/brr-pd-grid

Versioned BRR→PD grid

operationId: p2_get_brr_pd_grid_v1_brr_pd_grid_get · tags: pillar2

The versioned BRR→PD grid (Canon §2.5.1, ratified P-2).

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
version	string	yes		
grid	object	yes		

GET /p2/v1/category-weights/{segment}

Category weights for a segment

operationId: p2_get_category_weights_v1_category_weights__segment__get · tags: pillar2

Scoring category weights for one borrower segment (Spec §4.3).

PARAMETERS

Name	In	Type	Required	Default	Description
segment	path	string	yes		

RESPONSES

200 Successful Response

object

404 Unknown segment

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p2/v1/ews

Early-Warning Signal

operationId: `p2_ews_v1_ews_post` · tags: pillar2

EWS evaluation from a BRR migration (Canon §2.15, ratified P-7).

PARAMETERS

Name	In	Type	Required	Default	Description
application_id	query	string	yes		
brr_at_origination	query	integer	yes		
brr_current	query	integer	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
application_id	string	yes		
triggered	boolean	yes		
brr_at_origination	integer	yes		
brr_current	integer	yes		
deterioration_notches	integer	yes		
routed_to_officer	boolean	yes		
triggers_p3_action	boolean		`false`	

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p2/v1/cass-feed

CASS feed packet (contract shape)

operationId: `p2_cass_feed_v1_cass_feed_post` · tags: pillar2

Builds the CIS-1-contract-shaped data packet Pillar 4's future ABSF engine will consume (Canon §2.13). The full CASS methodology is PENDING — this is the contract stub, not a live scoring feed.

PARAMETERS

Name	In	Type	Required	Default	Description
application_id	query	string	yes		
brr	query	integer	yes		
pd_pit_adjusted	query	number	yes		
expected_loss	query	number	yes		
days_past_due	query	integer			
significant_credit_risk_increase	query	boolean			
cash_flow_deterioration_indicator	query	number			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
application_id	string	yes		
brr	integer	yes		
pd_pit_adjusted	number	yes		
ifrs9_stage	`IFRS9Stage`	yes		IFRS 9 staging signal fed to P4, PIT-adjusted (Canon §2.11.1, §2.13). one of: `STAGE_1`, `STAGE_2`, `STAGE_3`
cash_flow_deterioration_indicator	number	yes		
expected_loss	number	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p2/v1/pooled-guarantee-level

G-model pooled guarantee level

operationId: `p2_pooled_guarantee_level_v1_pooled_guarantee_level_post` · tags: pillar2

The required pooled-guarantee level under the Guarantee Intermediation Model (Canon §2.12.2) — computed by Pillar 2, monitored against guarantees received by Pillar 4.

PARAMETERS

Name	In	Type	Required	Default	Description
portfolio_ead	query	number	yes		
portfolio_facility_collateral_value	query	number	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
pooled_guarantee_level	number	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p2/v1/override/open

Open an override record

operationId: `p2_override_open_v1_override_open_post` · tags: pillar2

Opens a learning-oriented Override Record (Canon §2.11.2, ratified P-3): an officer's reasoned BRR adjustment, kept as model-recalibration evidence.

PARAMETERS

Name	In	Type	Required	Default	Description
application_id	query	string	yes		
override_type	query	string	yes		
model_brr_before	query	integer	yes		
officer_brr_after	query	integer	yes		
factor_category_overridden	query	`FactorCategory`	yes		
reason_code	query	string	yes		
narrative	query	string	yes		
authority_level	query	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
application_id	string	yes		
override_type	string	yes		
model_output_before	string	yes		
officer_output_after	string	yes		
direction	string	yes		
factor_category_overridden	`FactorCategory`	yes		The six BRR master factor categories (Spec §4.2) — the system backbone. one of: `1`, `2`, `3`, `4`, `5`, `6`
reason_code	string	yes		
narrative	string	yes		
authority_level	string	yes		
approver	string | null			
approver_decision	string | null			
outcome_at_maturity	string | null			
vindicated	string | null			
model_improvement_disposition	string | null			
disposition_notes	string | null			

422 Invalid override parameters

POST /p2/v1/override/close

Close an override record

operationId: `p2_override_close_v1_override_close_post` · tags: pillar2

Closes the loop at facility maturity — the evidence-led recalibration input.

PARAMETERS

Name	In	Type	Required	Default	Description
outcome_at_maturity	query	string	yes		
vindicated	query	string	yes		
model_improvement_disposition	query	string	yes		
disposition_notes	query	string			

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
application_id	string	yes		
override_type	string	yes		
model_output_before	string	yes		
officer_output_after	string	yes		
direction	string	yes		
factor_category_overridden	`FactorCategory`	yes		The six BRR master factor categories (Spec §4.2) — the system backbone. one of: `1`, `2`, `3`, `4`, `5`, `6`
reason_code	string	yes		
narrative	string	yes		
authority_level	string	yes		
approver	string | null			
approver_decision	string | null			
outcome_at_maturity	string | null			
vindicated	string | null			
model_improvement_disposition	string | null			
disposition_notes	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
application_id	string	yes		
override_type	string	yes		
model_output_before	string	yes		
officer_output_after	string	yes		
direction	string	yes		

Field	Type	Required	Default	Description
`factor_category_overridden`	`FactorCategory`	yes		The six BRR master factor categories (Spec §4.2) — the system backbone. one of: `1`, `2`, `3`, `4`, `5`, `6`
`reason_code`	string	yes		
`narrative`	string	yes		
`authority_level`	string	yes		
`approver`	string | null			
`approver_decision`	string | null			
`outcome_at_maturity`	string | null			
`vindicated`	string | null			
`model_improvement_disposition`	string | null			
`disposition_notes`	string | null			

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

Pillar 3 — Loan Lifecycle & Execution

pillar3

Pillar 3 — loan lifecycle & execution: facilities, P2 packets, audit trail, postings, core-banking ledger, reconciliation, and the state-machine actions (originate, disburse, repayment, default, restructure, recovery, close). No allocation logic lives here.

GET `/p3/facilities`

List facilities

operationId: `p3_list_facilities_facilities_get` · tags: pillar3

Every facility P3 executes, with its state-machine status, collateral count, and whether a Pillar 4 veto is currently frozen on it.

RESPONSES

200 Successful Response

array of object

GET /p3/facilities/{facility_id}

Facility detail

operationId: `p3_get_facility_facilities__facility_id__get` · tags: pillar3

Full facility record: lifecycle timestamps, the collateral objects held on the facility, and the collateral-service records recorded against it.

PARAMETERS

Name	In	Type	Required	Default	Description
`facility_id`	path	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`facility_id`	string	yes		
`state`	string	yes		
`origination_packet_id`	string	yes		
`veto_frozen`	boolean	yes		
`created_at`	string	yes		
`updated_at`	string	yes		
`collateral_objects`	array of object			
`collateral_service_recorded`	array of object			

404 Unknown identifier

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /p3/packets

Received Pillar 2 packets

operationId: `p3_list_packets_packets_get` · tags: pillar3

All Pillar 2 output packets P3 has received. These are pass-through records — P3 records every field verbatim and never infers or recomputes a packet field (Canon §8.1).

RESPONSES

200 Successful Response

array of object

GET /p3/audit

Full audit trail

operationId: `p3_list_audit_audit_get` · tags: pillar3

Append-only audit trail carrying the Spec §8 mandatory field list: packet version, Model Maturity Stage, BRR-PD grid version, P4 veto status, and core-banking confirmation for every event.

RESPONSES

200 Successful Response

array of object

GET /p3/audit/{facility_id}

Facility audit trail

operationId: `p3_facility_audit_audit__facility_id__get` · tags: pillar3

Append-only audit records for one facility.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	path	string	yes		

RESPONSES

200 Successful Response

array of object

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /p3/postings

Per-loan posting events

operationId: `p3_list_postings_postings_get` · tags: pillar3

Every posting event P3 captured (disbursements, repayments, fees, losses, recoveries). P3 computes no allocation — events flagged `routes_allocation_question_to_p4` carry the allocation question to Pillar 4, which owns all burden-sharing.

RESPONSES

200 Successful Response

array of object

GET /p3/ledger

Core-banking ledger

operationId: `p3_list_ledger_ledger_get` · tags: pillar3

Core-banking postings — the system of record. Core banking always wins a reconciliation dispute against the P3 event log; P4 governs only the tolerance.

RESPONSES

200 Successful Response

array of object

GET /p3/reconcile

Reconcile postings vs ledger

operationId: `p3_core_banking_reconcile_reconcile_get` · tags: pillar3

Compare total P3 posting amounts against the core-banking ledger within a tolerance (default 0.0 — exact match). Returns the unmatched P3 event ids when they differ.

PARAMETERS

Name	In	Type	Required	Default	Description
`tolerance`	query	number			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`p3_event_total`	number	yes		
`core_banking_total`	number	yes		
`discrepancy`	number	yes		
`tolerance`	number	yes		
`within_tolerance`	boolean	yes		
`unmatched_p3_event_ids`	array of string			

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/originate

Originate a facility

operationId: `p3_originate_originate_post` · tags: pillar3

Open a facility from a confirmed Pillar 2 packet. The packet must pass the confirmation gate (Canon §8.1); a frozen Pillar 4 veto resolves at Pillar 2 and surfaces here as a 409 — P3 never sees a veto event, only a confirmed or withheld packet.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_id	string	yes		
state	string	yes		

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p3/disburse

Disburse a facility

operationId: `p3_disburse_disburse_post` · tags: pillar3

Disburse funds against an originated facility. Emits the PRINCIPAL_MOVEMENT posting event and posts it to core banking.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		
amount	query	number	yes		
currency	query	string	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
event_id	string	yes		
facility_id	string	yes		
event_type	string	yes		
amount	number	yes		
currency	string	yes		
p2_packet_id	string	yes		
occurred_at	string | null			

Field	Type	Required	Default	Description
`routes_allocation_question_to_p4`	boolean		`false`	
`memo`	string | null			

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/pledge-collateral

Pledge facility collateral

operationId: `p3_pledge_collateral_pledge_collateral_post` · tags: pillar3

Record a facility-specific collateral pledge against a facility. Stage 1 is Track 1 (classical) collateral only; this pledge is structurally distinct from the pooled guarantee held by Pillar 4 (Two-Guarantee-Layer Rule).

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		
external_reference	query	string | null			

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
collateral_id	string	yes		
facility_id	string	yes		
kind	string	yes		
track	string	yes		
model_flag	string	yes		
p2_packet_id	string	yes		
recorded_at	string | null			

Field	Type	Required	Default	Description
`external_reference`	string | null			

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/repayment

Record a repayment

operationId: `p3_record_repayment_repayment_post` · tags: pillar3

Record a scheduled repayment. Splits into an interest (income) posting and a principal posting; the risk-premium component of income is routed to Pillar 4's RP Pool.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		
interest_amount	query	number	yes		
principal_amount	query	number	yes		
currency	query	string	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
income_event	object	yes		
principal_event	object	yes		

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/mark-delinquent

Mark facility delinquent

operationId: `p3_mark_delinquent_mark_delinquent_post` · tags: pillar3

Risk-officer delinquency marker. P3 detects and routes only — no allocation, provisioning, or burden-sharing is computed here; those belong to Pillar 4.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_id	string	yes		
status	string	yes		

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/mark-default

Mark facility defaulted

operationId: `p3_mark_default_mark_default_post` · tags: pillar3

Crystallize a default and record the loss amount. The guarantee leg (Pillar 4 computes and settles the guarantee call) runs separately from the collateral leg P3 records here — the two legs never substitute for each other.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		
loss_amount	query	number			
currency	query	string			

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
event_id	string	yes		
facility_id	string	yes		
event_type	string	yes		
amount	number	yes		
currency	string	yes		
p2_packet_id	string	yes		
occurred_at	string | null			

Field	Type	Required	Default	Description
`routes_allocation_question_to_p4`	boolean		`false`	
`memo`	string | null			

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/restructure

Restructure a facility

operationId: `p3_restructure_restructure_post` · tags: pillar3

Restructure a facility. Requires `human_authorised_for_workout` on the packet — origination confirmation and workout authorisation are deliberately separate acts (Canon §8.6).

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		

REQUEST BODY

application/json required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_id	string	yes		
status	string	yes		

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/recovery

Record a recovery

operationId: `p3_initiate_recovery_recovery_post` · tags: pillar3

Record the collateral-leg recovery receipt against a defaulted facility — classical foreclosure proceeds returned to the book. Pillar 4 credits the EL Pool / ULA Buffer separately.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		
recovered_amount	query	number	yes		
currency	query	string	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
event_id	string	yes		
facility_id	string	yes		
event_type	string	yes		
amount	number	yes		
currency	string	yes		
p2_packet_id	string	yes		
occurred_at	string | null			

Field	Type	Required	Default	Description
`routes_allocation_question_to_p4`	boolean		`false`	
`memo`	string | null			

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p3/close

Close a facility

operationId: `p3_close_facility_close_post` · tags: pillar3

Close a facility after final settlement.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_id	query	string	yes		

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
packet_id	string	yes		
facility_id	string	yes		
status	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
maturity_stage	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string	yes		
collateral_track	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
packet_version	string	yes		
officer_confirmed	boolean		`false`	
officer_id	string | null			
human_authorised_for_workout	boolean		`false`	
issued_at	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_id	string	yes		
status	string	yes		

409 Conflict — a prudential veto is frozen at Pillar 2, a governance PENDING item blocks the action, or the state machine forbids the transition

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

Pillar 4 — Prudential Layer

pillar4

Pillar 4 — prudential layer: buffer sub-account balances, guarantee-pool adequacy, capital snapshot (Tier D/RWA, portfolio EL, G/G ratio), IFRS 9 staging, the two-track veto, mode gate, and pledge intake/release. Veto state resolves at Pillar 2 — Pillar 3 never sees a veto event.

GET /p4/buffer/balances

Buffer sub-account balances

operationId: `p4_buffer_balances_buffer_balances_get` · tags: pillar4

Live balances of the four Part II sub-accounts: EL Pool (IFRS 9 ECL provisions), ULA Buffer (loss capacity beyond Budgeted Loss), LR (funding-side liquidity), and RP Pool (risk-premium income).

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
`el_pool`	number		`0.0`	
`ula_buffer`	number		`0.0`	
`liquidity_reserve`	number		`0.0`	
`rp_pool`	number		`0.0`	

GET /p4/pool/adequacy

Guarantee-pool adequacy

operationId: `p4_pool_adequacy_pool_adequacy_get` · tags: pillar4

Guarantees received vs the Pillar 2 required pooled-guarantee level. A shortfall paces origination; a shortfall coinciding with a ratio breach triggers the Track 1 veto. Pillar 4 never re-sizes the required level.

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
`received`	number	yes		
`required`	number	yes		
`status`	string	yes		
`shortfall_amount`	number	yes		

GET /p4/capital/snapshot

Capital & leverage snapshot

operationId: `p4_capital_snapshot_capital_snapshot_get` · tags: pillar4

The three live prudential ratios: Tier D / RWA (floor 12%), portfolio EL vs the Budgeted Loss (2%), and the Guarantees-Granted/Received ratio, plus their raw inputs (RWA by facility, risk weights, guarantee books).

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`tier_d_over_rwa`	number | null			
`portfolio_el`	number | null			
`guarantees_granted_over_received`	number | null			
`tier_d_amount`	number | null			
`rwa`	number | null			
`rwa_by_facility`	object			
`risk_weights`	object			
`budgeted_loss`	number | null			
`el_pool_balance`	number | null			
`given_book`	number | null			
`received_book`	number | null			
`tier_d_floor`	number | null			
`budgeted_loss_ratio`	number | null			

POST /p4/capital/tier-d

Set Tier D capital base

operationId: `p4_set_tier_d_amount_capital_tier_d_post` · tags: pillar4

Set the Tier D (common equity + Perpetual AT1) capital base — the numerator of the Tier D / RWA prudential ratio. Seeded by governance on first boot; this is the explicit runtime adjustment path.

PARAMETERS

Name	In	Type	Required	Default	Description
amount	query	number	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
tier_d_amount	number	yes		
status	string	yes		

422 Validation failed

Field	Type	Required	Default	Description
detail	string	yes		

GET /p4/ifrs9

IFRS 9 staging map

operationId: `p4_ifrs9_facilities_ifrs9_get` · tags: pillar4

Per-facility IFRS 9 stage (1/2/3), ECL, EAD and EL. Fed by Pillar 2's direct staging signal, which bypasses Pillar 3 entirely — a staging migration is a provisioning event, never a covenant or freeze.

RESPONSES

200 Successful Response

object

POST /p4/risk-packet

Register a Pillar 2 risk packet

operationId: `p4_feed_risk_packet_risk_packet_post` · tags: pillar4

Register P2's BRR/PD/LGD/EAD/EL outputs for a facility — the inputs to capital adequacy, EL vs Budgeted Loss, and the required pooled-guarantee comparison.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
facility_ref	string	yes		
brr	number	yes		
pd	number	yes		
lgd	number	yes		
ead	number	yes		
el	number	yes		
model_maturity_stage	`ModelStage`			one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
brr_pd_grid_version	string | null			
packet_ref	string | null			
as_of	string (date-time)			
product_type	string | null			
margin_of_conservatism_applied	boolean		`true`	

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_ref	string	yes		
status	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/staging-signal

Receive an IFRS 9 staging signal

operationId: `p4_feed_staging_signal_staging_signal_post` · tags: pillar4

Pillar 2's direct staging feed (Stage 1/2/3) on significant credit-risk increase. Updates ECL provisioning in the EL Pool; triggers no Pillar 3 covenant or freeze.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
facility_ref	string	yes		
stage	integer	yes		
packet_ref	string | null			
as_of	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_ref	string	yes		
stage	integer	yes		
status	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/required-guarantee-level

Update the required guarantee level

operationId: `p4_feed_required_guarantee_level_required_guarantee_level_post` · tags: pillar4

Pillar 2 sizes the required pooled-guarantee level; Pillar 4 compares it against guarantees received and monitors adequacy. Pillar 4 never re-sizes the required level itself.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`required_amount`	number	yes		
`revision_ref`	string	yes		
`published_at`	string (date-time)			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`revision_ref`	string	yes		
`status`	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /p4/veto/consult

Consult the veto state

operationId: `p4_consult_veto_veto_consult_get` · tags: pillar4

The Track 1 / Track 2 veto state Pillar 2 must consult before confirming any output packet. If frozen, P2 withholds the packet — Pillar 3 never sees a veto event. Supply `facility_ref` for the facility-level (Track 2) view.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_ref	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
any_frozen	boolean	yes		
track1_frozen	boolean	yes		
track1_triggers	array of string			
track2_frozen_for_facility	boolean		`false`	
track2_policy	string | null			

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /p4/veto/confirm

Would a packet be confirmed?

operationId: `p4_confirm_packet_veto_confirm_get` · tags: pillar4

Dry-run of P2's packet-confirmation gate for a facility — True only when no veto blocks the facility and the required guarantee level permits origination.

PARAMETERS

Name	In	Type	Required	Default	Description
`facility_ref`	query	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`confirmed`	boolean	yes		

404 Unknown identifier

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p4/veto/track2

Evaluate a Track 2 (facility) veto

operationId: `p4_evaluate_track2_veto_track2_post` · tags: pillar4

Evaluate one facility against Pillar 4 policy — freezes that facility's action class even when portfolio metrics are clean. Resolution happens at Pillar 2; P3 is never contacted.

PARAMETERS

Name	In	Type	Required	Default	Description
facility_ref	query	string	yes		
violates_policy	query	string | null			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
facility_ref	string	yes		
resolution	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/veto/lift-track1

Lift a Track 1 freeze (governance)

operationId: `p4_lift_track1_veto_lift_track1_post` · tags: pillar4

Governance-only lift of a standing Track 1 freeze, citing its governance reference. Cannot be overridden by Pillar 2 or 3.

PARAMETERS

Name	In	Type	Required	Default	Description
governance_ref	query	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
governance_ref	string	yes		
status	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

GET /p4/events

Intra-Pillar-4 event log

operationId: `p4_intra_events_events_get` · tags: pillar4

Internal Part I/II event stream: staging signals, adequacy shortfalls, guarantee-call settlements, and other intra-pillar transitions.

RESPONSES

200 Successful Response

array of object

POST /p4/events

Route a Pillar 3 event

operationId: `p4_feed_pillar3_event_events_post` · tags: pillar4

Receive a loan-level event from Pillar 3 and route it to the correct buffer sub-account. Pillar 3 moves data; Pillar 4 decides what the data means — no allocation logic lives in P3.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
event_type	`Pillar3EventType`	yes		one of: `scheduled_repayment`, `origination_fee`, `risk_premium_accrual`, `default_or_write_off`, `recovery_collateral_leg`, `guarantee_call_guarantee_leg`
facility_ref	string	yes		
amount	number		`0.0`	
principal_component	number		`0.0`	
interest_component	number		`0.0`	
collateral_leg_amount	number		`0.0`	
occurred_at	string (date-time)			
meta	object			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
event_type	string	yes		
facility_ref	string	yes		
status	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/recompute-track1

Recompute Track 1 triggers

operationId: `p4_recompute_track1_recompute_track1_post` · tags: pillar4

Recompute the capital ratios and evaluate the Track 1 threshold set. `breached_triggers` are live freezes; `unmonitored_triggers` are named-but-PENDING thresholds with no settled number yet (never silently defaulted).

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
tier_d_over_rwa	number | null			
portfolio_el	number | null			
breached_triggers	array of string			
unmonitored_triggers	array of string			
auto_lifted	boolean		`false`	

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

GET /p4/mode

Current operating mode

operationId: `p4_mode_status_mode_get` · tags: pillar4

Bank-wide operating mode from SI-1: Conventional (static tiers, classical foreclosure, no adaptive scoring) or Adaptive (CASS scoring + ABSF, sandbox-gated). A governance switch, not a build phase.

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
mode	string	yes		
adaptive	boolean	yes		
conventional	boolean	yes		

POST /p4/mode/activate

Activate Adaptive Mode (governance)

operationId: `p4_activate_adaptive_mode_activate_post` · tags: pillar4

Governance ruling to enter Adaptive Mode. Requires the Gate G1 criteria; the CASS methodology itself is still PENDING, so this is exercised in the sandbox only.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`ruling_ref`	string	yes		
`rule_type`	string	yes		
`signed_by`	string	yes		
`detail`	string		`""`	

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`mode`	string	yes		
`status`	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p4/mode/fallback

Fall back to Conventional Mode (governance)

operationId: `p4_fallback_conventional_mode_fallback_post` · tags: pillar4

Governance ruling to deactivate Adaptive Mode. Deactivation is not deletion — no rebuild, no book unwind, no contract amendment; Conventional Mode is the permanent floor.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
`ruling_ref`	string	yes		
`rule_type`	string	yes		
`signed_by`	string	yes		
`detail`	string		`""`	

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`mode`	string	yes		
`status`	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p4/pledge/submit

Submit a pledge for admission

operationId: `p4_submit_pledge_pledge_submit_post` · tags: pillar4

Pillar 5 pledge intake, reviewed against Pillar 4's admissibility POLICY (eligible types, haircuts, concentration limits) — a policy-level check, not a case decision; Pillar 2 confirms each individual case.

REQUEST BODY

`application/json` required

Field	Type	Required	Default	Description
submission_ref	string	yes		
pledger_id	string	yes		
tier	`TierPosition`	yes		one of: `TierA`, `TierB`, `SeniorInstitutionalDebt`, `TierC`, `TierBFees`, `TierD`
amount	number	yes		
asset_class	string	yes		
submitted_at	string (date-time)			

RESPONSES

`200` Successful Response

Field	Type	Required	Default	Description
submission_ref	string	yes		
disposition	string	yes		
reason	string | null			
policy_version	string	yes		

`409` Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

`422` Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/pledge/release

Request a pledge release

operationId: `p4_request_release_pledge_release_post` · tags: pillar4

Open the release notice window. Release is a right at/post term (exception with penalty pre-term). Invariant: no release path may ever generate a cash outflow or draw the Liquidity Reserve.

PARAMETERS

Name	In	Type	Required	Default	Description
pledge_ref	query	string	yes		
at_or_post_term	query	boolean			

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
pledge_ref	string	yes		
status	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
detail	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
detail	array of object			

POST /p4/pledge/manage-adequacy

Manage pool adequacy during the release window

operationId: `p4_manage_adequacy_pledge_manage_adequacy_post` · tags: pillar4

Run the adequacy tools while a release is pending: origination pacing, replacement intake, or — if a shortfall coincides with a ratio breach — the Track 1 veto.

PARAMETERS

Name	In	Type	Required	Default	Description
`pledge_ref`	query	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`pledge_ref`	string	yes		
`status`	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

POST /p4/pledge/finalize

Finalize a pledge release

operationId: `p4_finalize_release_pledge_finalize_post` · tags: pillar4

Execute the release after the notice window: lift the security interest, exit the asset from custody, extinguish the contingent cash-equivalent position. No cash moves; guarantees-received drops.

PARAMETERS

Name	In	Type	Required	Default	Description
`pledge_ref`	query	string	yes		

RESPONSES

200 Successful Response

Field	Type	Required	Default	Description
`pledge_ref`	string	yes		
`status`	string	yes		

409 Conflict — mode-gate refusal, an unresolved governance PENDING item, an admissibility-policy violation, or a pledge-release invariant violation

Field	Type	Required	Default	Description
`detail`	string	yes		

422 Validation Error

Field	Type	Required	Default	Description
`detail`	array of object			

GET /p4/veto/notifications

Orchestrator veto notifications

operationId: `p4_veto_notifications_veto_notifications_get` · tags: pillar4

Mandatory freeze notifications sent to the Orchestrator on every Track 1 / Track 2 freeze — governance review opens on each.

RESPONSES

200 Successful Response

array of object

Appendix A — Component schema catalogue

Every named request/response schema referenced by the endpoints above.

`AlternativeData`

Field	Type	Required	Default	Description
`utility_payment_regularity`	number | null			
`telco_regularity`	number | null			
`ecommerce_reputation_score`	number | null			
`supply_chain_centrality`	number | null			

`ApprovalDecision`

Field	Type	Required	Default	Description
`approve`	boolean		`true`	
`officer_id`	string		`"OFFICER-1"`	
`officer_name`	string | null			
`note`	string | null			

`AuditRecordOut`

Field	Type	Required	Default	Description
`record_id`	string	yes		
`facility_id`	string	yes		
`event_type`	string	yes		
`timestamp`	string | null			
`actor_reference`	string	yes		
`p2_packet_version`	string	yes		
`maturity_stage`	string	yes		
`brr_pd_grid_version`	string	yes		
`collateral_track`	string | null			
`p4_veto_status`	string	yes		
`posting_routing_flag`	string | null			
`core_banking_confirmed`	boolean	yes		
`resulting_state`	string	yes		
`collateral_reference`	string | null			
`guarantee_linkage`	string | null			

BilanCheck

Field	Type	Required	Default	Description
id	string	yes		
ok	boolean	yes		
detail	string	yes		

BilanConfigUpdate

Field	Type	Required	Default	Description
immobilisations	number | null			
autres_creances	number | null			
apport_reserve	number | null			
resultat_anterieur	number | null			
sid	number | null			
tier_c	number | null			
autres_emprunts	number | null			
depots_clients	number | null			
autres_dettes	number | null			
tresorerie_ouverture	number | null			

BilanConfigView

Field	Type	Required	Default	Description
immobilisations	number		`0.0`	
autres_creances	number		`0.0`	
apport_reserve	number		`0.0`	
resultat_anterieur	number		`0.0`	
sid	number		`0.0`	
tier_c	number		`0.0`	
autres_emprunts	number		`0.0`	
depots_clients	number		`0.0`	
autres_dettes	number		`0.0`	
tresorerie_ouverture	number	yes		
tresorerie_ouverture_configured	boolean	yes		

BilanFacilite

Field	Type	Required	Default	Description
`dec`	number	yes		
`rem`	number	yes		
`rad`	number	yes		
`rec`	number	yes		
`etat`	string | null			

BilanHorsBilan

Field	Type	Required	Default	Description
`ula_buffer`	number	yes		
`liquidity_reserve`	number	yes		
`rp_pool`	number	yes		
`rwa`	number	yes		
`tier_d_over_rwa`	number | null	yes		
`garanties_consenties`	number	yes		
`garanties_recues`	number	yes		
`niveau_requis_garanties`	number	yes		
`el_pool`	number		`0.0`	

BilanLine

Field	Type	Required	Default	Description
`compte`	string	yes		
`libelle`	string	yes		
`montant`	number	yes		

BilanMouvements

Field	Type	Required	Default	Description
`decaisses`	number	yes		
`remboursements`	number	yes		
`interets`	number	yes		
`frais`	number	yes		
`sinistres`	number	yes		
`ecl_total`	number	yes		
`el_pool`	number	yes		
`ecl_consomme`	number	yes		
`tresorerie_ouverture`	number	yes		
`recouvrements`	number		`0.0`	
`radiations`	number		`0.0`	
`non_classes`	integer		`0`	
`par_facilite`	object			

BilanResponse

Field	Type	Required	Default	Description
`actif`	array of object	yes		
`passif`	array of object	yes		
`totaux`	object	yes		
`ecart`	number	yes		
`balanced`	boolean	yes		
`mouvements`	object	yes		Flow terms read from Pillar 3/4 — the inputs behind every line.
`hors_bilan`	object	yes		Memo items reported alongside the balance, never added to either face.
`sources`	object	yes		
`as_of`	string (date-time)	yes		
`checks`	array of object			
`reliable`	boolean		`true`	
`warnings`	array of string			

BilanSources

Field	Type	Required	Default	Description
`p3_events`	integer	yes		
`p4_facilities`	integer	yes		

BilanTotaux

Field	Type	Required	Default	Description
actif	number	yes		
passif	number	yes		

Body_import_candidate_file_candidates_import_file_post

Field	Type	Required	Default	Description
file	string	yes		

BorrowerApplication

Field	Type	Required	Default	Description
application_id	string	yes		
segment	Segment	yes		MSME segment — size/complexity based, not data-availability based (Canon §2.1). one of: MICRO, SMALL, MEDIUM
operating_model	OperatingModel	yes		Which sibling Orchestrator Canon the market runs under. one of: S, G
facility	object	yes		
maturity_regime	MaturityRegime | null			
model_maturity_stage	ModelMaturityStage			Model Maturity Stage (Canon §2.0, ratified P-5). one of: DESIGN, SANDBOX, PRODUCTION
financials	object			Minimum financial schema after OCR (Spec §12.1). All fields optional.
cash_flow	object			Bank-feed / POS derived series (Data Matrix L-001..L-006).
business	object			Data Matrix B-001..B-005.
management	object			Data Matrix M-001..M-004.
alternative	object			Data Matrix A-001..A-004.
collateral	array of object			
rails_connected	array of string			
policy_exception_flags	array of string			

BrrPdGridOut

Field	Type	Required	Default	Description
version	string	yes		
grid	object	yes		

BufferBalancesOut

Field	Type	Required	Default	Description
`el_pool`	number		`0.0`	
`ula_buffer`	number		`0.0`	
`liquidity_reserve`	number		`0.0`	
`rp_pool`	number		`0.0`	

BusinessProfile

Field	Type	Required	Default	Description
`top5_customer_share`	number | null			
`single_supplier_share`	number | null			
`registration_date`	string (date) | null			
`sector_code`	string | null			
`geography_code`	string | null			
`legal_form`	string | null			

CASSFeedPacket

Field	Type	Required	Default	Description
`application_id`	string	yes		
`brr`	integer	yes		
`pd_pit_adjusted`	number	yes		
`ifrs9_stage`	`IFRS9Stage`	yes		IFRS 9 staging signal fed to P4, PIT-adjusted (Canon §2.11.1, §2.13). one of: `STAGE_1`, `STAGE_2`, `STAGE_3`
`cash_flow_deterioration_indicator`	number	yes		
`expected_loss`	number	yes		

CandidateCreate

Field	Type	Required	Default	Description
`first_name`	string	yes		
`last_name`	string	yes		
`name_ar`	string | null			
`gender`	string — one of: `male`, `female`		`"male"`	
`age`	integer		`0`	
`national_id`	string | null			
`phone`	string | null			
`city`	string		`"Muscat"`	
`employer_name`	string | null			
`employer_type`	string — one of: `government`, `military`, `private`, `self_employed` | null			
`employment_years`	number		`1.0`	
`employer_start_date`	string | null			
`job_title`	string | null			
`monthly_salary`	number	yes		
`product`	string		`"auto_loan"`	
`requested_amount`	number	yes		
`requested_tenure_months`	integer		`12`	
`payment_behavior`	object | null			
`outcome_override`	string — one of: `paid`, `default`, `delinquent_cured` | null			

CandidateEnvelope

Field	Type	Required	Default	Description
`candidate`	object	yes		API representation of a candidate row.
`payment_behavior`	object | null			

CandidateImport

Field	Type	Required	Default	Description
`first_name`	string	yes		
`last_name`	string	yes		
`name_ar`	string | null			
`gender`	string — one of: `male`, `female`		`"male"`	
`age`	integer		`0`	
`national_id`	string | null			
`phone`	string | null			
`city`	string		`"Muscat"`	
`employer_name`	string | null			
`employer_type`	string — one of: `government`, `military`, `private`, `self_employed` | null			
`employment_years`	number		`1.0`	
`employer_start_date`	string | null			
`job_title`	string | null			
`monthly_salary`	number	yes		
`product`	string		`"auto_loan"`	
`requested_amount`	number	yes		
`requested_tenure_months`	integer		`12`	
`payment_behavior`	object | null			
`outcome_override`	string — one of: `paid`, `default`, `delinquent_cured` | null			
`seed_profile`	string | null			
`application_json`	object | null			
`sim_state`	object | null			

CandidateListOut

Field	Type	Required	Default	Description
`candidates`	array of object	yes		

CandidateRead

Field	Type	Required	Default	Description
id	string	yes		
seed_profile	string | null	yes		
first_name	string	yes		
last_name	string	yes		
name_ar	string | null	yes		
gender	string	yes		
age	integer	yes		
national_id	string | null	yes		
phone	string | null	yes		
city	string	yes		
employer_name	string | null	yes		
employer_type	string | null	yes		
employment_years	number	yes		
job_title	string | null	yes		
monthly_salary	number	yes		
product	string	yes		
requested_amount	number	yes		
requested_tenure_months	integer	yes		
status	string	yes		
submitted_at	string (date-time) | null	yes		
scored_at	string (date-time) | null	yes		
approved_at	string (date-time) | null	yes		
originated_at	string (date-time) | null	yes		
disbursed_at	string (date-time) | null	yes		
application_id	string | null	yes		
facility_id	string | null	yes		
p2_brr	integer | null	yes		
p2_pd	number | null	yes		
p2_zone	string | null	yes		
p2_packet_status	string | null	yes		
payment_behavior	object | null	yes		
sim_state	object | null	yes		
created_at	string (date-time)	yes		
updated_at	string (date-time)	yes		
approval_note	string | null	yes		

Field	Type	Required	Default	Description
`approved_by`	string | null	yes		
`display_name`	string	yes		

CanonVersionCreate

Field	Type	Required	Default	Description
`version_number`	string	yes		Canon version number, e.g. '3.4'
`name`	string	yes		
`change_summary`	string | null			
`lineage_notes`	string | null			
`status`	string		`"PENDING"`	

CanonVersionOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version_number`	string	yes		
`name`	string	yes		
`status`	string	yes		
`ratified_at`	string (date-time) | null	yes		
`ratification_instrument`	string | null	yes		
`is_current`	boolean	yes		
`change_summary`	string | null	yes		
`lineage_notes`	string | null	yes		
`created_at`	string (date-time)	yes		

CanonVersionOutDetail

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version_number`	string	yes		
`name`	string	yes		
`status`	string	yes		
`ratified_at`	string (date-time) | null	yes		
`ratification_instrument`	string | null	yes		
`is_current`	boolean	yes		
`change_summary`	string | null	yes		
`lineage_notes`	string | null	yes		
`created_at`	string (date-time)	yes		
`ratification_instruments`	array of object		`[]`	

CanonVersionRatify

Field	Type	Required	Default	Description
`instrument_number`	string	yes		e.g. 'RI-4'
`resolution_ref`	string | null			
`description`	string | null			
`ratified_by`	string		`"Governance Committee"`	

CapitalSnapshotOut

Field	Type	Required	Default	Description
`tier_d_over_rwa`	number | null			
`portfolio_el`	number | null			
`guarantees_granted_over_received`	number | null			
`tier_d_amount`	number | null			
`rwa`	number | null			
`rwa_by_facility`	object			
`risk_weights`	object			
`budgeted_loss`	number | null			
`el_pool_balance`	number | null			
`given_book`	number | null			
`received_book`	number | null			
`tier_d_floor`	number | null			
`budgeted_loss_ratio`	number | null			

CashFlowData

Field	Type	Required	Default	Description
`daily_net_cashflow`	array of number | null			
`avg_daily_inflow`	number | null			
`debt_service_obligation`	number | null			
`receivable_days`	number | null			
`payable_days`	number | null			
`inventory_days`	number | null			
`bounced_items_count`	integer | null			
`months_of_history`	number | null			

CassStubFieldOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`stub_metadata_id`	string (uuid)	yes		
`field_name`	string	yes		
`field_type`	string | null	yes		
`cardinality`	string	yes		
`description`	string | null	yes		
`is_derived`	boolean	yes		
`is_consumed`	boolean	yes		

CassStubMetadataIn

Field	Type	Required	Default	Description
`version`	string		`"1.0"`	
`issued_by`	string		`"Orchestrator"`	
`scope`	string		`"contract shape only \u2014 never signal derivation or consumption logic"`	
`source_pillar`	string		`"P2"`	
`dest_pillar`	string		`"P4"`	
`refresh_cadence`	string | null			
`failure_semantics`	string | null			

CassStubMetadataOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`version`	string	yes		
`issued_by`	string	yes		
`scope`	string	yes		
`source_pillar`	string	yes		
`dest_pillar`	string	yes		
`refresh_cadence`	string | null	yes		
`failure_semantics`	string | null	yes		
`fields`	array of object		`[]`	

CategoryScore

Field	Type	Required	Default	Description
category	FactorCategory	yes		The six BRR master factor categories (Spec §4.2) — the system backbone. one of: 1, 2, 3, 4, 5, 6
raw_score	number	yes		
weight	number	yes		

ChangeProposalCreate

Field	Type	Required	Default	Description
title	string	yes		
description	string | null			
change_type	string		"STRUCTURAL"	
proposed_by	string	yes		
canon_version_target	string | null			
requires_dependency_review	boolean		false	
requires_g2s_review	boolean		false	

ChangeProposalOut

Field	Type	Required	Default	Description
id	string (uuid)	yes		
proposal_number	string	yes		
title	string	yes		
description	string | null	yes		
change_type	string	yes		
proposed_by	string	yes		
status	string	yes		
canon_version_target	string | null	yes		
requires_dependency_review	boolean	yes		
requires_g2s_review	boolean	yes		
submitted_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		

ChangeProposalOutDetail

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`proposal_number`	string	yes		
`title`	string	yes		
`description`	string | null	yes		
`change_type`	string	yes		
`proposed_by`	string	yes		
`status`	string	yes		
`canon_version_target`	string | null	yes		
`requires_dependency_review`	boolean	yes		
`requires_g2s_review`	boolean	yes		
`submitted_at`	string (date-time)	yes		
`resolved_at`	string (date-time) | null	yes		
`dependency_reviews`	array of object		`[]`	
`ratification_votes`	array of object		`[]`	

CollateralClass

string — one of: `RECEIVABLES`, `INVENTORY`, `EQUIPMENT`, `REAL_ESTATE`, `PERSONAL_GUARANTEE`

CollateralOffer

Field	Type	Required	Default	Description
`collateral_class`	`CollateralClass`	yes		one of: `RECEIVABLES`, `INVENTORY`, `EQUIPMENT`, `REAL_ESTATE`, `PERSONAL_GUARANTEE`
`track`	`CollateralTrack`	yes		Three-track collateral model, model-conditional (Canon §2.12.1, ratified P-9). one of: `NONE`, `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
`p4_admitted_value`	number	yes		

CollateralOut

Field	Type	Required	Default	Description
`collateral_id`	string	yes		
`facility_id`	string	yes		
`kind`	string	yes		
`track`	string	yes		
`model_flag`	string	yes		
`p2_packet_id`	string	yes		
`recorded_at`	string | null			
`external_reference`	string | null			

CollateralTrack

string — one of: `NONE`, `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`

ConfirmPacketOut

Field	Type	Required	Default	Description
facility_ref	string	yes		
confirmed	boolean	yes		

CreditRiskResult

Field	Type	Required	Default	Description
ead	number	yes		
lgd	number	yes		
lgd_with_moc	number	yes		
expected_loss	number	yes		
el_vs_budgeted_loss	string	yes		
pooled_guarantee_level	number | null			

DataFileInfo

Field	Type	Required	Default	Description
filename	string	yes		
name	string		`"?"`	
seed_profile	string | null			
status	string		`"new"`	
size_bytes	integer		`0`	

DataFileListOut

Field	Type	Required	Default	Description
files	array of object	yes		

DataQualityResult

Field	Type	Required	Default	Description
completeness	number	yes		
consistency	number	yes		
recency	number	yes		
dqs	number	yes		
is_thin_file	boolean	yes		
moc_pd_uplift	number	yes		
moc_lgd_uplift	number	yes		

DecisioningZone

string — one of: `AUTO_APPROVE`, `AUGMENTED_DECISION`, `MANUAL_REVIEW`

DependencyReviewCreate

Field	Type	Required	Default	Description
`pillar_number`	integer	yes		
`review_status`	string		`"PENDING"`	
`reviewer_notes`	string | null			

DependencyReviewOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`proposal_id`	string (uuid)	yes		
`pillar_number`	integer	yes		
`review_status`	string	yes		
`reviewer_notes`	string | null	yes		
`reviewed_at`	string (date-time) | null	yes		

DisbursementRequest

Field	Type	Required	Default	Description
`amount`	number | null			
`currency`	string		`"USD"`	

EWSResult

Field	Type	Required	Default	Description
`application_id`	string	yes		
`triggered`	boolean	yes		
`brr_at_origination`	integer	yes		
`brr_current`	integer	yes		
`deterioration_notches`	integer	yes		
`routed_to_officer`	boolean	yes		
`triggers_p3_action`	boolean		`false`	

ErrorOut

Field	Type	Required	Default	Description
`detail`	string	yes		

FacilityDetail

Field	Type	Required	Default	Description
`facility_id`	string	yes		
`state`	string	yes		
`origination_packet_id`	string	yes		
`veto_frozen`	boolean	yes		
`created_at`	string	yes		
`updated_at`	string	yes		
`collateral_objects`	array of object			
`collateral_service_recorded`	array of object			

FacilityRefOut

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`status`	string	yes		

FacilityRequest

Field	Type	Required	Default	Description
`product`	`Product`	yes		Facility products — EAD conventions differ by product (Canon §2.5). one of: `INVOICE_DISCOUNTING`, `SUPPLY_CHAIN_FINANCE`, `WORKING_CAPITAL_LINE`, `TERM_LOAN`, `GROWTH_LOAN`
`requested_amount`	number	yes		
`drawn_amount`	number | null			
`undrawn_amount`	number | null			
`tenor_months`	integer | null			
`recourse`	boolean		`true`	

FacilitySummary

Field	Type	Required	Default	Description
`facility_id`	string	yes		
`state`	string	yes		
`origination_packet_id`	string	yes		
`collateral_count`	integer	yes		
`veto_frozen`	boolean	yes		
`updated_at`	string	yes		

FactorCategory

integer — one of: `1`, `2`, `3`, `4`, `5`, `6`

FinancialStatement

Field	Type	Required	Default	Description
`revenue`	number | null			
`cost_of_sales`	number | null			
`operating_expenses`	number | null			
`net_profit`	number | null			
`period_end`	string (date) | null			
`total_assets`	number | null			
`current_assets`	number | null			
`total_liabilities`	number | null			
`current_liabilities`	number | null			
`equity`	number | null			
`prior_period_revenue`	number | null			

FlowResultOut

Field	Type	Required	Default	Description
`status`	string | null			
`candidate_id`	string | null			
`facility_id`	string | null			
`packet_id`	string | null			
`approved`	boolean | null			
`amount`	number | null			
`currency`	string | null			
`brr`	integer | null			
`pd`	number | null			
`zone`	string | null			

GateStateOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`gate_label`	string	yes		
`status`	string	yes		
`criteria`	string | null	yes		
`cleared_at`	string (date-time) | null	yes		
`cleared_by`	string | null	yes		
`notes`	string | null	yes		

GovernanceRuling

Field	Type	Required	Default	Description
`ruling_ref`	string	yes		
`rule_type`	string	yes		
`signed_by`	string	yes		
`detail`	string		`""`	

HTTPValidationError

Field	Type	Required	Default	Description
`detail`	array of object			

IFRS9Stage

string — one of: `STAGE_1`, `STAGE_2`, `STAGE_3`

InsuranceStatusUpdate

Field	Type	Required	Default	Description
`status`	string	yes		Tier A insurance status (sole locus rule)

InterfaceFieldOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`interface_rule_id`	string (uuid)	yes		
`field_name`	string	yes		
`field_type`	string | null	yes		
`cardinality`	string	yes		
`direction`	string	yes		
`description`	string | null	yes		
`is_pending`	boolean	yes		

InterfaceFlowCheck

Field	Type	Required	Default	Description
`source`	string	yes		e.g. 'P2'
`destination`	string	yes		e.g. 'P4'

InterfaceFlowResult

Field	Type	Required	Default	Description
`rules`	array of object		`[]`	
`bypasses_pillar3`	boolean		`false`	

InterfaceRuleOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`rule_number`	string	yes		
`name`	string	yes		
`description`	string | null	yes		
`direction`	string	yes		
`decides_who`	string | null	yes		
`executes_who`	string | null	yes		
`bypasses_pillar3`	boolean	yes		
`canon_section_ref`	string | null	yes		
`notable_v34_change`	string | null	yes		

InterfaceRuleOutDetail

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`rule_number`	string	yes		
`name`	string	yes		
`description`	string | null	yes		
`direction`	string	yes		
`decides_who`	string | null	yes		
`executes_who`	string | null	yes		
`bypasses_pillar3`	boolean	yes		
`canon_section_ref`	string | null	yes		
`notable_v34_change`	string | null	yes		
`fields`	array of object		`[]`	

IntraP4EventOut

Field	Type	Required	Default	Description
`type`	string	yes		
`payload`	object			
`occurred_at`	string | null			

LedgerPostingOut

Field	Type	Required	Default	Description
`posting_id`	string	yes		
`source_event_id`	string	yes		
`facility_id`	string	yes		
`amount`	number	yes		
`currency`	string	yes		
`posted_at`	string | null			

LexiconCategoryOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`name`	string	yes		
`annex_ref`	string	yes		
`description`	string | null	yes		
`sort_order`	integer	yes		

LexiconTermCreate

Field	Type	Required	Default	Description
`term`	string	yes		The locked term name
`category_id`	string (uuid)	yes		
`abbreviation`	string | null			
`definition`	string	yes		
`model_scope`	string		`"NEUTRAL"`	
`canon_section_ref`	string | null			
`is_new_in_v34`	boolean		`false`	
`supersedes`	string | null			

LexiconTermOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`category_id`	string (uuid)	yes		
`term`	string	yes		
`abbreviation`	string | null	yes		
`definition`	string	yes		
`model_scope`	string	yes		
`canon_section_ref`	string | null	yes		
`is_new_in_v34`	boolean	yes		
`supersedes`	string | null	yes		
`created_at`	string (date-time)	yes		
`updated_at`	string (date-time)	yes		

LexiconTermUpdate

Field	Type	Required	Default	Description
`definition`	string | null			
`model_scope`	string | null			
`abbreviation`	string | null			
`is_new_in_v34`	boolean | null			
`supersedes`	string | null			

LexiconValidateRequest

Field	Type	Required	Default	Description
`terms`	array of string	yes		List of terms to validate against the Master Lexicon

LexiconValidateResult

Field	Type	Required	Default	Description
`valid`	array of string		`[]`	
`invalid`	array of string		`[]`	
`renamed`	object			old term -> new locked term

LiftTrack1Out

Field	Type	Required	Default	Description
`governance_ref`	string	yes		
`status`	string	yes		

ManagementProfile

Field	Type	Required	Default	Description
owner_experience_years	number | null			
prior_default_history	boolean | null			
has_governance_plan	boolean | null			
account_conduct_score	number | null			

MaturityRegime

string — one of: `LOW`, `INTERMEDIATE`, `HIGH`

MaturityStage

string — one of: `DESIGN`, `SANDBOX`, `PRODUCTION`

ModeAckOut

Field	Type	Required	Default	Description
mode	string	yes		
status	string	yes		

ModeChangeIn

Field	Type	Required	Default	Description
new_mode	string	yes		
changed_by	string		`"Governance Committee"`	
change_rationale	string | null			

ModeStateOut

Field	Type	Required	Default	Description
id	string (uuid)	yes		
current_mode	string	yes		
fallback_guarantee	string	yes		
changed_at	string (date-time)	yes		
changed_by	string	yes		
change_rationale	string | null	yes		

ModeStatusOut

Field	Type	Required	Default	Description
mode	string	yes		
adaptive	boolean	yes		
conventional	boolean	yes		

ModelMaturityStage

string — one of: `DESIGN`, `SANDBOX`, `PRODUCTION`

ModelStage

string — one of: `DESIGN`, `SANDBOX`, `PRODUCTION`

ModelTier

string — one of: `TIER_1`, `TIER_2`, `TIER_3`

OperatingModel

string — one of: `S`, `G`

OriginationResultOut

Field	Type	Required	Default	Description
facility_id	string	yes		
state	string	yes		

OutputPacket

Field	Type	Required	Default	Description
application_id	string	yes		
status	`PacketStatus`	yes		P2→P3 output packet status (V3.0 addition, Canon §2.7). one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
model_maturity_stage	`ModelMaturityStage`	yes		Model Maturity Stage (Canon §2.0, ratified P-5). one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
pd_grid_version	string	yes		
collateral_track	`CollateralTrack`	yes		Three-track collateral model, model-conditional (Canon §2.12.1, ratified P-9). one of: `NONE`, `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
brr	integer	yes		
pd	number	yes		
lgd	number	yes		
ead	number	yes		
expected_loss	number	yes		
pricing	object	yes		
zone	`DecisioningZone`	yes		Three-zone decisioning model (Canon §2.7, ratified P-6). one of: `AUTO_APPROVE`, `AUGMENTED_DECISION`, `MANUAL_REVIEW`
requires_officer_confirmation	boolean	yes		

OverrideRecord

Field	Type	Required	Default	Description
`application_id`	string	yes		
`override_type`	string	yes		
`model_output_before`	string	yes		
`officer_output_after`	string	yes		
`direction`	string	yes		
`factor_category_overridden`	`FactorCategory`	yes		The six BRR master factor categories (Spec §4.2) — the system backbone. one of: `1`, `2`, `3`, `4`, `5`, `6`
`reason_code`	string	yes		
`narrative`	string	yes		
`authority_level`	string	yes		
`approver`	string | null			
`approver_decision`	string | null			
`outcome_at_maturity`	string | null			
`vindicated`	string | null			
`model_improvement_disposition`	string | null			
`disposition_notes`	string | null			

P2OutputPacket

Field	Type	Required	Default	Description
`packet_id`	string	yes		
`facility_id`	string	yes		
`status`	`P2PacketStatus`	yes		Pillar 2 output packet status — Canon §8.1. one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`
`maturity_stage`	`MaturityStage`	yes		Model Maturity Stage gate — Spec §1, Build Handoff §5. one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
`brr_pd_grid_version`	string	yes		
`collateral_track`	`p3_CollateralTrack`	yes		Three-track collateral model — Spec §4. one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`
`packet_version`	string	yes		
`officer_confirmed`	boolean		`false`	
`officer_id`	string | null			
`human_authorised_for_workout`	boolean		`false`	
`issued_at`	string (date-time)			

P2PacketOut

Field	Type	Required	Default	Description
`packet_id`	string	yes		
`facility_id`	string	yes		
`status`	string	yes		
`maturity_stage`	string	yes		
`brr_pd_grid_version`	string	yes		
`collateral_track`	string	yes		
`packet_version`	string	yes		
`officer_confirmed`	boolean		`false`	
`officer_id`	string | null			
`human_authorised_for_workout`	boolean		`false`	
`issued_at`	string | null			

P2PacketStatus

string — one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`

PacketStatus

string — one of: `APPROVED`, `PROVISIONAL`, `CONDITIONAL`

PaymentBehavior

Field	Type	Required	Default	Description
`outcome`	string — one of: `paid`, `default`, `delinquent_cured`		`"paid"`	
`facility_amount`	number	yes		
`disbursed`	number	yes		
`currency`	string		`"USD"`	
`tenure_months`	integer		`12`	
`repayments`	array of object			
`delinquent_month`	integer | null			
`default_month`	integer | null			
`recovered_amount`	number		`0.0`	
`interest_rate_bps`	integer		`1000`	

PendingItemCreate

Field	Type	Required	Default	Description
title	string	yes		
description	string | null			
category	string		`"GOVERNANCE"`	
registered_in_canon	string | null			
scope_details	string | null			
priority	string		`"MEDIUM"`	
assigned_to	string | null			

PendingItemOut

Field	Type	Required	Default	Description
id	string (uuid)	yes		
item_number	string	yes		
title	string	yes		
description	string | null	yes		
category	string	yes		
registered_in_canon	string | null	yes		
scope_details	string | null	yes		
status	string	yes		
priority	string	yes		
assigned_to	string | null	yes		
registered_at	string (date-time)	yes		
resolved_at	string (date-time) | null	yes		
resolution_notes	string | null	yes		
governance_reference	string | null	yes		

PendingItemResolve

Field	Type	Required	Default	Description
resolution_notes	string	yes		Required by do-not-resolve-in-code discipline
governance_reference	string | null			e.g. 'RI-3' or governance ruling reference

PendingItemUpdate

Field	Type	Required	Default	Description
`title`	string | null			
`description`	string | null			
`category`	string | null			
`scope_details`	string | null			
`priority`	string | null			
`assigned_to`	string | null			
`status`	string | null			

PendingSummary

Field	Type	Required	Default	Description
`total`	integer		`0`	
`open`	integer		`0`	
`by_category`	object			
`by_priority`	object			

Pillar2RiskPacket

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`brr`	number	yes		
`pd`	number	yes		
`lgd`	number	yes		
`ead`	number	yes		
`el`	number	yes		
`model_maturity_stage`	`ModelStage`			one of: `DESIGN`, `SANDBOX`, `PRODUCTION`
`brr_pd_grid_version`	string | null			
`packet_ref`	string | null			
`as_of`	string (date-time)			
`product_type`	string | null			
`margin_of_conservatism_applied`	boolean		`true`	

Pillar3Event

Field	Type	Required	Default	Description
event_type	Pillar3EventType	yes		one of: scheduled_repayment, origination_fee, risk_premium_accrual, default_or_write_off, recovery_collateral_leg, guarantee_call_guarantee_leg
facility_ref	string	yes		
amount	number		0.0	
principal_component	number		0.0	
interest_component	number		0.0	
collateral_leg_amount	number		0.0	
occurred_at	string (date-time)			
meta	object			

Pillar3EventAckOut

Field	Type	Required	Default	Description
event_type	string	yes		
facility_ref	string	yes		
status	string	yes		

Pillar3EventType

string — one of: scheduled_repayment, origination_fee, risk_premium_accrual, default_or_write_off, recovery_collateral_leg, guarantee_call_guarantee_leg

PillarBoundaryOut

Field	Type	Required	Default	Description
id	string (uuid)	yes		
pillar_number	integer	yes		
pillar_name	string	yes		
produces	array of object	yes		
consumes	array of object	yes		
decides	array of object	yes		
must_not_do	array of object	yes		
canon_section_ref	string | null	yes		

PillarPerimeterCheck

Field	Type	Required	Default	Description
pillar_number	integer	yes		
action	string	yes		A textual description of the proposed action

`PillarPerimeterCheckResult`

Field	Type	Required	Default	Description
`allowed`	boolean	yes		
`reason`	string	yes		
`violated_rule`	string | null			

`PledgeAckOut`

Field	Type	Required	Default	Description
`pledge_ref`	string	yes		
`status`	string	yes		

`PledgeSubmission`

Field	Type	Required	Default	Description
`submission_ref`	string	yes		
`pledger_id`	string	yes		
`tier`	`TierPosition`	yes		one of: `TierA`, `TierB`, `SeniorInstitutionalDebt`, `TierC`, `TierBFees`, `TierD`
`amount`	number	yes		
`asset_class`	string	yes		
`submitted_at`	string (date-time)			

`PledgeSubmitOut`

Field	Type	Required	Default	Description
`submission_ref`	string	yes		
`disposition`	string	yes		
`reason`	string | null			
`policy_version`	string	yes		

`PoolAdequacyOut`

Field	Type	Required	Default	Description
`received`	number	yes		
`required`	number	yes		
`status`	string	yes		
`shortfall_amount`	number	yes		

`PooledGuaranteeLevelOut`

Field	Type	Required	Default	Description
`pooled_guarantee_level`	number	yes		

PostingEventOut

Field	Type	Required	Default	Description
`event_id`	string	yes		
`facility_id`	string	yes		
`event_type`	string	yes		
`amount`	number	yes		
`currency`	string	yes		
`p2_packet_id`	string	yes		
`occurred_at`	string | null			
`routes_allocation_question_to_p4`	boolean		`false`	
`memo`	string | null			

PricingResult

Field	Type	Required	Default	Description
`base_rate_bps`	number	yes		
`risk_premium_bps`	number	yes		
`all_in_rate_bps`	number	yes		

Product

string — one of: `INVOICE_DISCOUNTING`, `SUPPLY_CHAIN_FINANCE`, `WORKING_CAPITAL_LINE`, `TERM_LOAN`, `GROWTH_LOAN`

RatificationInstrumentOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`canon_version_id`	string (uuid)	yes		
`instrument_number`	string	yes		
`resolution_ref`	string | null	yes		
`description`	string | null	yes		
`ratified_at`	string (date-time)	yes		

RatificationVoteOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`proposal_id`	string (uuid)	yes		
`instrument_number`	string | null	yes		
`resolution_ref`	string | null	yes		
`vote`	string	yes		
`voted_at`	string (date-time)	yes		
`voted_by`	string	yes		

RatingResult

Field	Type	Required	Default	Description
`category_scores`	array of object	yes		
`sector_geo_adjustment`	number	yes		
`composite_risk_score`	number	yes		
`brr`	integer	yes		
`tier_used`	`ModelTier`	yes		Three-tier modelling stack (Canon §2.3). one of: `TIER_1`, `TIER_2`, `TIER_3`
`thin_file_capped`	boolean	yes		
`pd_grid_version`	string	yes		
`pd_point_estimate`	number	yes		
`pd_range`	array of object	yes		
`pd_with_moc`	number	yes		

RecomputeTrack1Out

Field	Type	Required	Default	Description
`tier_d_over_rwa`	number | null			
`portfolio_el`	number | null			
`breached_triggers`	array of string			
`unmonitored_triggers`	array of string			
`auto_lifted`	boolean		`false`	

ReconcileOut

Field	Type	Required	Default	Description
`p3_event_total`	number	yes		
`core_banking_total`	number	yes		
`discrepancy`	number	yes		
`tolerance`	number	yes		
`within_tolerance`	boolean	yes		
`unmatched_p3_event_ids`	array of string			

RepaymentResultOut

Field	Type	Required	Default	Description
`income_event`	object	yes		
`principal_event`	object	yes		

RepaymentRow

Field	Type	Required	Default	Description
`interest`	number	yes		
`principal`	number	yes		
`month`	integer	yes		

RequiredGuaranteeLevel

Field	Type	Required	Default	Description
`required_amount`	number	yes		
`revision_ref`	string	yes		
`published_at`	string (date-time)			

ResetOut

Field	Type	Required	Default	Description
`status`	string	yes		
`state`	object	yes		

RevisionAckOut

Field	Type	Required	Default	Description
`revision_ref`	string	yes		
`status`	string	yes		

ScoringResult

Field	Type	Required	Default	Description
`application_id`	string	yes		
`segment`	`Segment`	yes		MSME segment — size/complexity based, not data-availability based (Canon §2.1). one of: `MICRO`, `SMALL`, `MEDIUM`
`maturity_regime`	`MaturityRegime`	yes		Digital maturity regime — an internal regime inside each segment (Canon §2.2). one of: `LOW`, `INTERMEDIATE`, `HIGH`
`data_quality`	object	yes		
`rating`	object	yes		
`credit_risk`	object	yes		
`pricing`	object	yes		
`zone`	`DecisioningZone`	yes		Three-zone decisioning model (Canon §2.7, ratified P-6). one of: `AUTO_APPROVE`, `AUGMENTED_DECISION`, `MANUAL_REVIEW`
`packet`	object	yes		P2 -> P3 handoff packet (Canon §2.7 V3.0 addition, §3 P2->P3).

SeedOut

Field	Type	Required	Default	Description
`seeded`	integer	yes		

Segment

string — one of: `MICRO`, `SMALL`, `MEDIUM`

StageStateOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`current_stage`	integer	yes		
`changed_at`	string (date-time)	yes		
`changed_by`	string	yes		

StagingAckOut

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`stage`	integer	yes		
`status`	string	yes		

StagingSignal

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`stage`	integer	yes		
`packet_ref`	string | null			
`as_of`	string (date-time)			

StatusAckOut

Field	Type	Required	Default	Description
`facility_id`	string	yes		
`status`	string	yes		

TickOut

Field	Type	Required	Default	Description
`tick`	object	yes		
`state`	object	yes		

TierDAckOut

Field	Type	Required	Default	Description
`tier_d_amount`	number	yes		
`status`	string	yes		

TierDefinitionOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`tier_label`	string	yes		
`tier_name`	string	yes		
`model_scope`	string	yes		
`description`	string | null	yes		
`insurance_status`	string | null	yes		
`insurance_status_authority`	string | null	yes		
`sort_order`	integer	yes		
`canon_section_ref`	string | null	yes		

TierPosition

string — one of: `TierA`, `TierB`, `SeniorInstitutionalDebt`, `TierC`, `TierBFees`, `TierD`

TierProtectionRuleOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`source_tier_id`	string (uuid)	yes		
`target_tier_id`	string (uuid)	yes		
`direction`	string	yes		
`description`	string | null	yes		

Track2ResultOut

Field	Type	Required	Default	Description
`facility_ref`	string	yes		
`resolution`	string	yes		

ValidationError

Field	Type	Required	Default	Description
`loc`	array of string | integer	yes		
`msg`	string	yes		
`type`	string	yes		
`input`	object			
`ctx`	object			

VetoConsultOut

Field	Type	Required	Default	Description
`any_frozen`	boolean	yes		
`track1_frozen`	boolean	yes		
`track1_triggers`	array of string			
`track2_frozen_for_facility`	boolean		`false`	
`track2_policy`	string | null			

VetoEventCreate

Field	Type	Required	Default	Description
`track`	integer	yes		
`scope`	string		`"facility"`	
`facility_id`	string | null			
`pillar_4_signal`	string | null			
`p2_packet_action`	string	yes		
`notes`	string | null			

VetoEventOut

Field	Type	Required	Default	Description
`id`	string (uuid)	yes		
`event_number`	string	yes		
`track`	integer	yes		
`scope`	string	yes		
`facility_id`	string | null	yes		
`pillar_4_signal`	string | null	yes		
`p2_packet_action`	string	yes		
`orchestrator_notified_at`	string (date-time)	yes		
`governance_review_status`	string	yes		
`restart_authorized_at`	string (date-time) | null	yes		
`restart_authorized_by`	string | null	yes		
`notes`	string | null	yes		

VetoEventResolve

Field	Type	Required	Default	Description
`decision`	string	yes		
`authorized_by`	string		`"Governance Committee"`	
`notes`	string | null			

VetoNotificationOut

Field	Type	Required	Default	Description
event	string	yes		
track	string	yes		
triggers	object | array of object			
governance_ref	string | null			

p3_CollateralTrack

string — one of: `TRACK_1_CLASSICAL`, `TRACK_2_NFT`, `TRACK_3_STABLECOIN`

Appendix B — Endpoints not in the schema

These routes exist but are excluded from the OpenAPI document (`include_in_schema=False`). Frontend still uses them.

Method	Path	Description
GET	`/`	Demo SPA (serves `demo/dist` when built, otherwise the legacy static page).
GET	`/health` (root, /p1, /p3, /p4)	Liveness probe — `{"status": "ok"}` . The root app also exposes `GET /ready` (restart-ok check, 503 on failure) and governance exposes `GET /governance/health` .
GET	`/p1/demo/events/sse`	Server-Sent Events stream for the demo board. Events arrive as `data: {json}` frames: • `state_update` — full board snapshot after create/import/approve/disburse/seed • `tick` — `{"tick": {...}, "state": {...}}` after each simulation month • `reset` — full board snapshot after factory reset • keep-alive: empty `{}` frame every 30s The board also polls `GET /p1/demo/state` ; SSE is reserved for state *changes*.
GET	`/assets/*`	Vite build assets when `demo/dist` exists.

Generated by scripts/export_playbook_pdf.py from docs/openapi.json — regenerate after API changes.