

## NOTES

1. ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED.
2. MATERIAL (ASTM)  
RIB PLATE : A36 or EQUIVALENT
3. CONCRETE FOUNDATION SUPPORT SHALL BE CONSTRUCTED BY CIVIL.
4. EXPANSION ANCHOR BOLT  
1) REFERENCE DWG  
BOLT : L - L24A  
2) THE INSERT DEPTH IS 110MM.  
HOWEVER IT COULD NOT BE LONGER THAN PAVED DEPTH-30MM.
5. DESIGN CALCULATION AND INSTALLATION OF THE EXPANSION ANCHORS SHALL COMPLY BY THE GUIDE-LINES AND PROCEDURES SET BY THE MANUFACTURER.
6. SURFACE OF PAVE, BENEATH THE PEDESTAL SHALL BE ROUGHENED AND CLEANED BEFORE GROUTING.
7. BASE PLATES SHALL BE ANCHORED TO THE CONCRETE PAVING BY HILTI HSA ANCHOR OR EQUIVALENT.
8. REQUIRED HILTI HSA BOLT LENGTH SHALL BE RECONFIRMED BY MANUFACTURER.

MFC PROJECT

**GS Caltex Corporation**  
YEOSU, KOREA

**GS Engineering & Construction**

TITLE: SPECIAL PIPE SUPPORT  
(712-SPS-4562)

DRAWING No. 712-SPS-4562 PAGE 1 OF 1 REV. 0

