

NOTES

- ALL DIMENSIONS ARE IN mm UNLESS OTHERWISE NOTED.
- MATERIAL(ASTM)
 - TRUNNION PIPE/REINFORCING PAD : COMPATIBLE WITH MAIN PIPE.
 - END PLATE : A36
- VENT HOLE IS REQUIRED ONLY FOR TRUNNION WITH ENDPLATE. THE VENT HOLE MUST BE LOCATED AT MIN. DISTANCE FROM THE BOTTOM OF THE PLATE. IN ADDITION, WHERE PLATE IS REQUIRED FOR DUMMY, VENT HOLE MUST BE AT THE BOTTOM OF THE DUMMY TO ALLOW DRAINAGE.
- WELDING OF ATTACHMENT SHOULD BE DONE WITHOUT DAMAGING HEADER PIPE.
- TRUNNION PIPE/REINFORCING PAD THICKNESS SHALL BE AS FOLLOWS.
- ON LINE DESIGN TEMPERATURE OVER 450 °c A "HOT BOX" SHALL BE PROVIDED TO TRUNNION SUPPORT.

MAIN PIPE	TRUNNION/R.PAD
BELOW STD	THE SAME SCH. AS MAIN PIPE
STD & OVER	STD


MFC PROJECT

GS Caltex Corporation
YEOSU , KOREA


GS Engineering & Construction

TITLE: SPECIAL PIPE SUPPORT
(712-SPS-3159)

DRAWING No. 712-SPS-3159 PAGE 1 OF 1 REV. 0



ELEVATION
(LOOKING EAST)



DETAIL "A"