



NOTES

- ALL DIMENSIONS ARE IN mm UNLESS
   OTHERWISE NOTED.
- MATERIAL(ASTM)
- (1) TRUNNION PIPE/REINFORCING PAD : COMPATIBLE WITH MAIN PIPE.
- (2) END PLATE: A36
- 3. VENT HOLE IS REQUIRED ONLY FOR TRUNN-ION WITH ENDPLATE. THE VENT HOLE MUST BE LOCATED AT MIN. DISTANCE FROM THE BOTTOM OF THE PLATE.

  IN ADDITION, WHERE PLATE IS REQUIRED FOR DUMMY, VENT HOLE MUST BE AT THE BOTTOM OF THE DUMMY TO ALLOW DRAINAGE.
- 4. WELDING OF ATTACHMENT SHOULD BE DONE WITHOUT DAMAGING HEADER PIPE.
- 5. TRUNNION PIPE/REINFORCING PAD THICKNESS SHALL BE AS FOLLOWS.

| MAIN PIPE  | TRUNNION/R.PAD                |
|------------|-------------------------------|
| BELOW STD  | THE SAME SCH.<br>AS MAIN PIPE |
| STD & OVER | STD                           |

6. ON LINE DESIGN TEMPERATURE OVER 450 °C A "HOT BOX" SHALL BE PROVIDED TO TRUNNION SUPPORT.

ELEVATION (LOOKING NORTH)

DETAIL "A"

 $\Lambda$ 

|   | Trunnion<br>Material | Plate<br>Material | Plate<br>Thickness | Plate<br>Tack Welding Point |
|---|----------------------|-------------------|--------------------|-----------------------------|
|   | CS                   | CS                | 3t                 | 11/2" ~ 6"                  |
|   | AS                   |                   |                    | *                           |
| _ | SS                   | SS                |                    | 8" ~ Over   🙀               |

MFC PROJECT

**GS** Caltex Corporation YEOSU, KOREA

REV. 1



SPECIAL PIPE SUPPORT (712-SPS-3168)

DRAWING No. 712-SPS-3168 PAGE 1 OF 1