gupshup

API Document for Template Id based API

www.gupshup.io

Sales: sales@gupshup.io | **Marketing:** marketing@gupshup.io | **Support:** enterprise-support@gupshup.io

USA | Brazil | Mexico | Colombia | Mumbai | New Delhi | Bangalore | Chennai

Table of Contents

SendMessage and SendMediamessage API with templateID **3**

Feature Summary 3

Need for this feature 3

Feature description 3

Sendmessage and SendMediamessage API with templateID

Feature Summary

The Enterprise APIs for WhatsApp Business messaging can now be triggered by specifying the **'templateID'** and variable values instead of the entire message string with variable values.

Feature description

For the template_id to be specified:

a) The Sendmessage API request payload will not have the **msg** parameter; instead, it will have the **template_id** and the **hvar1(optional),var1,var2** specified.
b) The SendMediaMessage API will not have the caption parameter; instead, it will have the **template_id** and the **var1,var2** specified.

The API request along with the request parameters is as below

Request:

API endpoint

https://media.smsgupshup.com/GatewayAPI/rest

Request Parameters (for media)

Key	Description	Example
userid **REQUIRED** | string	The userid of your Gupshup account. The number must be in pure numeric format with no special characters.	2000155005
password **REQUIRED** | string	The password of your Gupshup account for authentication of the userid	xxxxxxxx
method **REQUIRED** | string	The API method to perform a specific action i.e. send a message on WhatsApp	SendMediaMessage

	Must be: SendMessage	
auth_scheme **REQUIRED** | string	The authentication scheme of the API.	plain
v **REQUIRED** | string	The API version. Must be: 1.1	1.1
send_to **REQUIRED** | string	The phone number of the recipient to whom the message is being sent. The number must be in E.164 formats.	919898989898
msg_type **REQUIRED** | string	The type of message to be sent to the customer. Must be one of: IMAGE, DOCUMENT, VIDEO	IMAGE
media_url **REQUIRED** | string	The Public URL where the media attachment file is hosted.	https://image.shutterstock.c om/image-illustration/movie-ticket-icon-260nw-663331288.jpg
isHSM OPTIONAL | boolean	This indicates whether the message is a Message Template (HSM) i.e. a pre-approved message template. Here, the API will run a template check and submit the message as an HSM to the WhatsApp server. By default, unless specified, it will be 'false' Must be one of: true, false	true
isTemplate OPTIONAL | boolean	This indicates if this is an Interactive Message template (with CTA or	false

	Quick Reply buttons). This must always be passed as isTemplate=true if it is an Interactive Message Template This must always be passed as isTemplate=true if it is an Interactive Message Template or if it has header and footer components Must be one of: true, false	
buttonUrlParam OPTIONAL | string	This is the dynamic suffix of the button URL for a Call-to-Action Interactive Button template of type "Visit Website" where URL=Dynamic. The static prefix of the button URL must be specified at the time of template creation since WhatsApp does not permit a completely dynamic button URL for the "Visit Website" type of Call-to-Action button. For example: If the static prefix of button URL in the template is "https://www.gupshup.io/" and value of buttonUrlParam="developer/home", then when user clicks on the Call-to-Action button, they are redirected to: https://www.gupshup.io/developer/home Note: If this parameter is passed for a Call-to-Action Interactive Button	developer/home

	template where URL=Static, you will get a Template Mismatch error.	
data_encoding OPTIONAL | string	The encoding type of the message i.e. plain English text or Unicode i.e. message is in another language or contains special characters / emoji . Must be one of: text, Unicode_text	text
format OPTIONAL | string	The API response message format. The default value is text, unless otherwise specified. Must be one of: text, JSON, XML	JSON
filename OPTIONAL | string	This is an optional filename that can be passed in case of msg_type=DOCUMENT.	test1.pdf
msg_id OPTIONAL | string	A Custom message ID that can be specified by the business. This will be attached to Message Status Callbacks and can help you track messages using your internal IDs. 200 characters alphanumeric values are allowed for msg_id and it must be unique for every message sent	122356788
extra OPTIONAL | string	A Custom parameter that can be used as an identifier for reporting purposes. You can input any text in this parameter and the same	qwerty

	value will be forwarded in the Status Callback. 50 alphanumeric Characters are allowed for this parameter.	
footer OPTIONAL | string	A short line of text to the bottom of the message template	Orders will be processed with delay
template_id **REQUIRED** | string	A valid Gupshup template ID for the 'enabled' template. If invalid, the API will throw an error	217
var1 OPTIONAL | string	The corresponding values of the variable placeholder, i.e. {{1}} = var1, {{2}} = var2,.....{{n}} = varn where the value of n <= 50 Please note: The API will throw an error if there is a mismatch in the number of variables specified in API request when compared to that in the template.	Julia
hvar1 OPTIONAL | string	The corresponding values of the header variable placeholder. Please note: The API will throw an error if there is a mismatch in the number of variables specified in API request when compared to that in the template. The template must have header with variable and works only in plain text HSM template.	Sid

	hvar1 is not applicable to media templates (SendMediaMessage).	

Sample request for simple text with template_id and variables

```
curl --location --request GET
'https://media.smsgupshup.com/GatewayAPI/rest?method=SENDMESSAGE&msg_type=TEXT&userid=2000152156&auth_scheme=plain&password=abcd1234&format=text&data_encoding=TEXT&send_to=6006682466&v=1.1&format=Text&isHSM=true&template_id=20372&var1=9&var2=1&hvar1=sid' \
--header 'Content-Type: application/x-www-form-urlencoded'
```

Sample request for media message with template_id and variables

```
curl --location --request GET
'https://media.smsgupshup.com/GatewayAPI/rest?method=SendmediaMessage&msg_type=VIDEO&userid=2000152156&auth_scheme=plain&password=abcd1234&format=text&data_encoding=TEXT&send_to=6006682466&v=1.1&format=text&isHSM=true&template_id=216&var1=9&var2=1&var3=3&media_url=http://clips.vorwaerts-gmbh.de/VfE_html5.mp4' \
--header 'Content-Type: application/x-www-form-urlencoded’
```