

DevOps Report

Group F
(insert names)

May 2024

Contents

List of Figures

Chapter 1

Introduction

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.

Chapter 2

System Perspective

2.1 Choice of technology

2.1.1 Choice of web framework

In our project, we have chosen to work with Microsoft open source web framework .Net, with another opensource database namely Postgres database. Our reason for chosen .Net, was several reason, first it opensource, so it is very cheap to have in production. Second Microsoft continue to development and maintain .Net web solution, third it has a huge community/documentation, so it is easy to get help with any issue. Fourth it does a lot of work for the developer, so developing a web application in this, is very easy and straightforward. Fourth, .Net uses C# as a language, C# is generally known to be a relatively fast and reliable language which also motivates our choice of choosing Microsoft .Net solution. Lastly many medium size/big companies in Denmark are using C# and .Net technology for their solutions, by using .Net in our project, we have gained experience we can use when we graduate.

2.1.2 Arguments for the choice of virtualization techniques and deployment targets??!!

PIRO :D

2.1.3 CD/CI reason

Since we use github for storing our source code, we choose to use github for CD/CI tool, since these two work very well together.

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.

2.2 Design and architecture

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.

2.3 Systems dependencies

The list below, is the technologies we are using in our application, group into categories of technology.

Project Start - choose framework

- Microsoft ASP.NET Core v2: For basis web framework to handle, request, authentication,
- .NET API framework: For handling RESTful API's
- Swagger: For .NET API visualization
- Microsoft Entity Framework Core version 8.x: For general handling dependency injection to a database connection.
- PostgreSQL v.8: Chosen database server for this project.
- Docker / Docker-compose / docker-swarm: For containerized applications
- Gravatar: For provide user profile images.
- Github / Github actions / Github secrets: For storing and deploying source code

- DigitalOcean: Production server for our application

Monitoring

- prometheus/prometheus-net/prometheus-net.AspNetCore: For provide metrics to Grafana.
- Grafana: For Data Visualization of data from prometheus and direct data from Postgress database.

Logging

- Serilog.AspNetCore v.8: For logging.
- Fluentd: For collecting logs from different sources.

Software quality - Testing

- Sonarqube: Static analyzer for code quality and securit issues
- CodeClimate: Another static analyzer also for code quality and securit issues
- Playwright: UI testing
- Cypress: End-2-end testing
- Xunit: For Basic Unit testing

2.4 Systems Interactions

This section the interations flow of request for the system, by user create a new request into the system. The request flow is create by providing sequence diagrams, of demonstration for 4 important task for the system, namely, register a user, user login, user create a new tweet, and user follow another user.




Figure 2.1: Sequence diagram demonstrate the flow of registrations of a user




Figure 2.2: Sequence diagram demonstrate the login procedure for a user




Figure 2.3: Sequence diagram demonstrate the procedure for create a new twit




Figure 2.4: Sequence diagram of the procedure for a user follow another user

Chapter 3

Process Perspective

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.

3.1 CI/CD pipelines

To configure and execute our CI/CD pipeline we use GitHub Actions. We chose to use GH Actions because we were already using GitHub for our repository, and GH Actions provided a seamless integration in our workflow in GitHub. Furthermore, it was easy to set up, and the free plan was more than enough for our needs.

We have configured two different variants of the pipeline: one that is executed when a PR is opened or updated, and one that is triggered on pushes to main, which, in practice, is only triggered on PR merges to main, since we never push directly to main. The tasks performed by the pipeline are as follows:

1. **Build and test the application:** In this step we build the application, run the unit tests, UI test and end-to-end tests. The unit tests are run during the building of the image, while the UI and end-to-end tests are each run by using a specially-crafted `compose.yml` file, which allows us to run the application, the database, and the UI or E2E tests simultaneously. We then instruct docker compose to use the exit code from the container executing the tests, which makes the pipeline fail if

any of the tests has failed. This step is executed both when PR and opened or updated, and when a push is made to main. The tests are made using the following tools:

- Unit tests: XUnit
- UI tests: PlayWright
- E2E tests: Cypress

2. **Linting:** In this step we execute linters for our code and Dockerfiles, with the use of the third-party GH action "super-linter". If problems are detected, this part of the pipeline reports an error. This step is only executed when a PR is opened or updated.
3. **Build and push image:** In this step, a production docker image is build and pushed to our image repository. This image will then be used on the deployment step. This step is only executed when a push is made to main.
4. **Create release:** In this step, a release is created on the GH repository, with the contents of the commit triggering the pipeline. This step is only executed when a push is made to main.
5. **Deployment:** In this step, our image is deployed to our server. To do so in a safe way, we have devised a deployment system which is triggered by a simple SSH login:
 - In our VM we have an user called deploy. When someone logs in as this user, either by SSH or by using su, a script is executed. The person logging in cannot execute any other command other than the script, to prevent security issues should someone obtain the keys to the user. When the script finishes, the user is logged out.
 - This script connects to GitHub and clones our "server-files" repository, and executes the script deploy.sh, which contains the deployment logic.
 - This script then pulls the necessary images, including our image created on a previous step, and deploys them in the server. The script uses other files which are also stored on the same repository, such as a compose.yml, which specifies which images to use, and configuration files for f.e. grafana and prometheus.

- The scripts also use secrets, f.e to clone the repository from GH, pull the image, or to configure the app to properly connect to our database (which is not located on the VM). These variables are stored on text files on the server. In order to maximize security, these files are owned by root, and are only readable by root or by members of the group deployers (of which deploy is a member), which prevents them from being read by unauthorized users. The bash scripts then access these files and export them as environment variables, which then can be used where they are required.

In this step, we simply log to our server via SSH from GH Actions, which triggers the whole deployment procedure on the server. This step is only executed when a push is made to main.

During the execution of the pipeline we need to use some secrets, f.e. to SSH into our server. We use GitHub Secrets to store those.

In figures ?? and ?? the flow of the different steps can be seen, both in the case of a PR-triggered pipeline and in the case of a pipeline triggered by a push to main.




Figure 3.1: Diagram with the different steps executed by the pipeline on a push to main.

We also use the Maintainability and Technical Debt estimation tool Sonar-Cube, which provides us reports of our code quality directly in GitHub. However, this tool is managed in its own website, and it is not configured as part of GH Actions.




Figure 3.2: Diagram with the different steps executed by the pipeline when a PR is opened or updated.

3.1.1 Report compilation

We also have an additional GH Action, which is only triggered by pushes which modify files in the "report" subfolder. This action then compiles the \LaTeX project located in that subfolder and generates a PDF, which then commits to the "report/build" subfolder.

3.2 Monitoring

3.2.1 Prometheus

Decision Log

3.2.2 Grafana

Decision Log

3.3 Logging

3.3.1 fluentd

Decision Log

First we tried to implement our logging with kibana and elastic search, which worked on our local machines. The problem with this was that we only had 1GB RAM on our web server, which wasn't enough to run elastic search. To resolve that issue we looked for other technologies like fluentd.

When facing implementing logging to a system several challenges come up, for example there are disparate log formats of different applications, logs that are scattered across multiple sources (data fragmentation), reliability concerns like network outages and routing different logs to different destinations based on the application or service.

In order to manage these difficulties we decided to use fluentd. Fluentd is an open source data collector which processes the data from various sources, making it easier to manage and analyze. The following aspects show why fluentd is so powerful:

- **Unified Logging Layer:** Fluentd provides a unified platform for collecting, transforming, and routing logs from diverse sources, simplifying the log management process.
- **Data Agnosticism:** Regardless of the data source—be it Prometheus metrics, Grafana dashboards, or application logs—Fluentd seamlessly collects and processes data in a unified format, fostering interoperability and ease of analysis.
- **Configurable Routing:** With Fluentd, we could effortlessly configure log routing based on application or service, directing logs to specific destinations for centralized storage and analysis.
- **Flexibility:** Fluentd's versatility enables us to send data from any source to any destination, empowering us to adapt to evolving logging requirements seamlessly.

Implementation of fluentd

A diagram describing our use and implementation of fluentd can be seen in figure ??.

Fluentd Configuration

Fluentd is configured to listen for incoming log data via the forward input plugin on port 24224. Log data from different sources (minitwit-database, minitwit-service, prometheus, grafana) is matched using the match directive which specifies the destination path and format for the corresponding log data. Log data is buffered using the buffer directive to handle data spikes or network outages, ensuring reliable log collection.




Figure 3.3: Diagram describing our implementation of fluentd

Docker Compose Configuration

A fluentd container is defined using the `fluent/fluentd:v1.12-debian` image. Each service in the Docker Compose file depends on the fluentd service for logging. Logging is configured to use fluentd as the logging driver, with specific options (`fluentd-async-connect`, `fluentd-retry-wait`, `fluentd-max-retries`) to ensure reliable log transmission. Each service specifies a unique tag to route log data to the appropriate destination, which in our case are simple log files, in fluentd based on the matching rules defined in the `fluentd.conf` file.

3.4 Security

3.4.1 Risk Identification

Assets

We have different assets that need to be protected:

- The web application: The web app serves and receives content from users.
- The API: The API allows for software developed by third-parties (f.i. the simulator) to obtain content from our application and sent their own.
- The database: The database stores all user information.
- Development, debugging, and deployment tools:
 - SSH: We use SSH to connect to and configure our Ubuntu Server VM(s).
 - Graphana/Prometheus: We use Graphana and Prometheus to monitor our system.
 - GitHub: We use GitHub to store our code, as well as the deployment logic for our application.
 - GitHub Actions: We use GitHub Actions for our CI/CD pipeline.
 - GitHub Secrets: Secrets needed by the CI/CD pipeline are stored in GitHub Secrets.
 - DigitalOcean: Our VM and database are provided by DigitalOcean and managed via their web interface or API.

Threat sources

Threat sources can be diverse, and attach different layers of our application:

- Vulnerabilities in our code: Vulnerabilities in our code could allow attackers to access user data or send malware to users. Among the vulnerabilities that we **could** have, these are the most relevant ones:
 - SQL injection: SQL injection would allow attackers to access and modify user data.

- Cross Site Scripting (XSS): Cross Site Scripting would allow attackers to potentially access and modify user data, as well as to send malicious information to users.

We need to emphasise that we have checked our code for such vulnerabilities, and we haven't found any. We also follow best practices to avoid such vulnerabilities. However, that does not mean that the vulnerabilities are not present, since it is impossible to prove so.

- Missing HTTPS and firewall: The use of basic HTTP could result on attackers snooping on users and obtaining password, or on man-in-the-middle attacks.
- Misconfigured firewall: A misconfigured firewall could give attackers direct access to, amongst others, the DB.
- Stolen SSH keys for the VM: Stolen SSH keys for the VM would allow attackers to execute arbitrary code in our VM.
- Stolen credentials for Graphana: Stolen credentials for Graphana would allow attackers to obtain access to the monitoring data of our system.
- Public Prometheus metrics: Metrics from the application for Prometheus to scrap are publicly available at */metrics*. Attackers could use this information to gain information about the operations being executed on the system.
- Stolen credentials for GitHub: Stolen credentials or tokens for GitHub would allow attackers to view, modify, and delete our code and/or deployment logic. It would also provide them with access to our secrets and CI/CD pipeline, essentially allowing them to execute arbitrary code in our VM.
- Stolen credentials for DigitalOcean: Stolen credentials or API keys for DigitalOcean would allow attackers to delete and/or access our VM and database.
- Vulnerabilities in the OS or Docker Images used: Vulnerabilities in the OS or Docker images used could allow attackers to take control over our system.
- Supply chain attacks: Supply chain attacks could cause vulnerabilities to be introduced in the dependencies we use.

Risk scenarios

Some possible scenarios of attacks are as follows:

1. Attacker performs SQL injection on web application to download sensitive user data.
2. Attacker performs SQL injection on API to download sensitive user data.
3. Attacker performs XSS on web application to download sensitive user data.
4. Attacker performs XSS on web application to deliver malware.
5. Attacker performs XSS on web application to download sensitive user data.
6. Attacker snoops on user traffic and obtains a user's password, which then uses to impersonate them.
7. Attacker performs a man-in-the-middle attack on a user and provides them with false information.
8. Attacker steals SSH keys, connects to the VM, from there to the DB, and downloads sensitive user data.
9. Attacker steals SSH keys, connects to the VM, and uses it to deliver malware.
10. Attacker steals Graphana credentials, connects to it, and learns more information about the usage of our system.
11. Attacker connects to */metrics* and learns more information about the usage of our system.
12. Attacker steals GitHub credentials and modifies our code to introduce vulnerabilities.
13. Attacker steals GitHub credentials and modifies our CI/CD pipeline to introduce vulnerabilities.
14. Attacker steals GitHub credentials and modifies our code or CI/CD pipeline to execute arbitrary code in our system and download sensitive user data.

15. Attacker steals GitHub credentials and modifies our code or CI/CD pipeline to execute arbitrary code in our system and deliver malware.
16. Attacker steals DigitalOcean credentials and downloads sensitive user data from the DB.
17. Attacker steals DigitalOcean credentials and uses our VM to deliver malware.
18. Attacker steals DB credentials and connects directly to it, due to a firewall misconfiguration.
19. Attacker uses vulnerabilities our the OS or Docker images to connect to the DB and download user data.
20. Attacker uses vulnerabilities our the OS or Docker images to connect to the VM and uses it to deliver malware.

3.4.2 Risk Analysis

Risk Matrix

A risk matrix helps visualize the possible risks in terms of impact and probability. We classified the above scenarios according to their likelihood and probability on the following matrix. Note that the numbers on the matrix correspond to the numbers on the list of risk scenarios above.

	High Impact	Medium Impact	Low Impact
Low Likelihood	8,9,12,13,14,15,16,17,18	-	-
Medium Likelihood	19,20	1,2,3,4,5	10
High Likelihood	-	6,7	11

Steps to take

In order to minimize our risk, we are going to take the following steps:

- Encrypt our SSH key with a passphrase in order to make it more difficult to steal.
- Hide Graphana behind a firewall.
- Limit the access to */metrics*.
- Use two-factor-authentication in all GitHub accounts of the team members.

- Use two-factor-authentication in all DigitalOcean accounts of the team members.
- Continue using best practices when developing, regarding SQL injection and XSS attacks.
- Be aware of the dependencies we are using and their potential vulnerabilities, and keep them updated.

3.4.3 Steps taken

We encrypted our SSH key with a strong passphrase, which teams members keep separate from the key. Most GitHub and DigitalOcean accounts already had 2FA enabled, and we enabled it in all the remaining ones. We decided against hiding Grafana behind a firewall since it needs to be access by third parties, namely the professors.

3.5 AI-Systems used during the project

During the project we have used the AI systems ChatGPT and GitHub Copilot. We have used them mainly to help in debugging, to fix simple errors, like f.i. syntax errors, or to perform menial tasks such as translating from one language to another. This is due to the fact that these AI-assistants do not seem to work very well with bigger tasks, as they lack the view of the "big picture".

3.5.1 Reflection on the use of AI assistants

People would assume that using AI assistants like ChatGPT or GitHub Copilot would make developing software much easier and faster, which we think is only partially true. A positive aspect of using these assistants is for example they assist very well when learning a new programming language. It is much faster to learn the right syntax by asking ChatGPT rather than googling. It is also very good at explaining code, which makes it easier to understand what other people did. Another positive use is for fixing simple errors by just copying the code with the error message. Usually they resolve the mistake pretty good which also saves some time.

The problem is when there are more complex errors, especially when they are between two or more systems. They tend makes a first guess and then try to find solutions within the area of the first suggestion, which can lead

to losing a lot of time because the fix of the problem lies somewhere else completely. An example for this happened when we were implementing our E2E tests with Cypress. When mounting the docker for Cypress we had an error saying that it could not find the test files, which were in the correct directory. ChatGPT suggested that the volume mounting was wrong and kept suggesting fixing this issue within our compose file. However after some quick research on Stack Overflow it became clear that the naming of the test files were wrong, which then we were able to fix quite quickly.

In cases where the error stems from the interaction between several systems, it is also not very helpful to ask AI assistants, as they only see the system you are working currently one, which does not allow them to provide good answers. One can, of course, try to explain them how the systems interact with each other, but this can be quite consuming, and usually it also does not result with the AI assistants providing a satisfactory answer.

As a conclusion, the use of AI-systems can save time and make development efficient, if used in the right places. When ChatGPT or other AI assistants do not give the correct answer within the first tries it is good advice to stop using it and try to resolve the issue by yourself.

Chapter 4

Lessons Learned

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.

Chapter 5

Reflection and conclusion

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Sed efficitur nunc non tempor pulvinar. Quisque congue orci non porta feugiat. Morbi vitae nulla libero. Nulla a sem diam. Pellentesque ullamcorper, est sed posuere eleifend, ante elit imperdiet lorem, ac scelerisque lacus ante id ipsum. Vestibulum ac metus tempor sem mattis ornare at eget massa. Sed ut aliquam lorem.