

Code A:

```
import pandas as pd
import os
import pathlib as pl

script_dir = pl.Path(__file__).parent.absolute()
print(f"Script Directory: {script_dir}")
os.chdir(script_dir)

print("Section A: \n-----\n")
mtcars = pd.read_csv('mtcars.csv')
print(f"Summary Statistics of mtcars dataset:\n{mtcars.describe()}")
print(f"Structure of mtcars dataset:")
mtcars.info()
print(f"Miles Per Gallon Quantile:\n{mtcars['mpg'].quantile([0.25, 0.5, 0.75])}")

print("\nSection B: \n-----\n")
cars = pd.read_csv('cars.csv')
print(f"Summary Statistics of cars dataset:\n{cars.describe()}")
print(f"Structure of cars dataset:")
cars.info()
print(f"Quantile of cars dataset:\n{cars['cty'].quantile([0.25, 0.5, 0.75])}")
```

Code B:

```
import pandas as pd
import os
import pathlib as pl

script_dir = pl.Path(__file__).parent.absolute()
print(f"Script Directory: {script_dir}")
os.chdir(script_dir)

iris = pd.read_csv('iris.csv')
iris_subset = iris[iris['SepalLengthCm'] > 4.6]
print(f"Subset of iris dataset where SepalLengthCm > 4.6:\n{iris_subset}")
print(f"Mean Sepal Length: {iris.groupby('Species')['SepalLengthCm'].mean()}")
```

Output A:

```
PS C:\DevParapalli\Projects\RTMNU-SEM-6> & "C:/Program Files/Python310/python.exe"
"c:/DevParapalli/Projects/RTMNU-SEM-6/PS-II/Practical 01/a.py"
Script Directory: c:\DevParapalli\Projects\RTMNU-SEM-6\PS-II\Practical 01
Section A:
```

Summary Statistics of mtcars dataset:

	mpg	cyl	disp	...	am	gear	carb
count	32.000000	32.000000	32.000000	...	32.000000	32.000000	32.0000
mean	20.090625	6.187500	230.721875	...	0.406250	3.687500	2.8125
std	6.026948	1.785922	123.938694	...	0.498991	0.737804	1.6152
min	10.400000	4.000000	71.100000	...	0.000000	3.000000	1.0000
25%	15.425000	4.000000	120.825000	...	0.000000	3.000000	2.0000
50%	19.200000	6.000000	196.300000	...	0.000000	4.000000	2.0000
75%	22.800000	8.000000	326.000000	...	1.000000	4.000000	4.0000
max	33.900000	8.000000	472.000000	...	1.000000	5.000000	8.0000

[8 rows x 11 columns]

Structure of mtcars dataset:

```
<class 'pandas.core.frame.DataFrame'>
```

RangeIndex: 32 entries, 0 to 31

Data columns (total 12 columns):

#	Column	Non-Null Count	Dtype
0	model	32 non-null	object
1	mpg	32 non-null	float64
2	cyl	32 non-null	int64
3	disp	32 non-null	float64
4	hp	32 non-null	int64
5	drat	32 non-null	float64
6	wt	32 non-null	float64
7	qsec	32 non-null	float64
8	vs	32 non-null	int64
9	am	32 non-null	int64
10	gear	32 non-null	int64
11	carb	32 non-null	int64

dtypes: float64(5), int64(6), object(1)

memory usage: 3.1+ KB

Miles Per Gallon Quantile:

0.25 15.425

0.50 19.200

0.75 22.800

Name: mpg, dtype: float64

Section B:

Summary Statistics of cars dataset:

	displ	year	cyl	cty	hwy
count	234.000000	234.000000	234.000000	234.000000	234.000000
mean	3.471795	2003.500000	5.888889	16.858974	23.440171
std	1.291959	4.509646	1.611534	4.255946	5.954643
min	1.600000	1999.000000	4.000000	9.000000	12.000000
25%	2.400000	1999.000000	4.000000	14.000000	18.000000
50%	3.300000	2003.500000	6.000000	17.000000	24.000000
75%	4.600000	2008.000000	8.000000	19.000000	27.000000
max	7.000000	2008.000000	8.000000	35.000000	44.000000


```

Structure of cars dataset:
<class 'pandas.core.frame.DataFrame'>
RangeIndex: 234 entries, 0 to 233
Data columns (total 11 columns):
#   Column          Non-Null Count  Dtype
---  -
0   manufacturer    234 non-null    object
1   model           234 non-null    object
2   displ           234 non-null    float64
3   year            234 non-null    int64
4   cyl             234 non-null    int64
5   trans           234 non-null    object
6   drv             234 non-null    object
7   cty             234 non-null    int64
8   hwy             234 non-null    int64
9   fl              234 non-null    object
10  class           234 non-null    object
dtypes: float64(1), int64(4), object(6)
memory usage: 20.2+ KB
Quantile of cars dataset:
0.25    14.0
0.50    17.0
0.75    19.0
Name: cty, dtype: float64

```

Output B:

```

PS C:\DevParapalli\Projects\RTMNU-SEM-6> & "C:/Program Files/Python310/python.exe"
"c:/DevParapalli/Projects/RTMNU-SEM-6/PS-II/Practical 01/b.py"
Script Directory: c:\DevParapalli\Projects\RTMNU-SEM-6\PS-II\Practical 01
Subset of iris dataset where SepalLengthCm > 4.6:

```

	Id	SepalLengthCm	SepalWidthCm	PetalLengthCm	PetalWidthCm	Species
0	1	5.1	3.5	1.4	0.2	Iris-setosa
1	2	4.9	3.0	1.4	0.2	Iris-setosa
2	3	4.7	3.2	1.3	0.2	Iris-setosa
4	5	5.0	3.6	1.4	0.2	Iris-setosa
5	6	5.4	3.9	1.7	0.4	Iris-setosa
..
145	146	6.7	3.0	5.2	2.3	Iris-virginica
146	147	6.3	2.5	5.0	1.9	Iris-virginica
147	148	6.5	3.0	5.2	2.0	Iris-virginica
148	149	6.2	3.4	5.4	2.3	Iris-virginica
149	150	5.9	3.0	5.1	1.8	Iris-virginica

```

[141 rows x 6 columns]
Mean Sepal Length: Species
Iris-setosa      5.006
Iris-versicolor  5.936
Iris-virginica   6.588
Name: SepalLengthCm, dtype: float64

```