# Prompting, and output a program can trust

How to ask, how to show examples, and how to get back something your code can use without a person checking.

60 min | Recorded | Class 7 of 15

7





## What this session covers

01
**How to ask**
3 slides

02
**Output a program can trust**
5 slides

03
**What prompting can't fix**
2 slides

04
**Code walkthrough**
3 slides


© 2026 Devansh Parapalli

Section 1 of 4

# How to ask

Roles, examples, and asking it to think.

01

A prompt has parts, and each one does a different job

02

Two good examples beat a paragraph of instructions

03

Asking it to work through the steps helps on reasoning, and costs tokens


© 2026 Devansh Parapalli



## A prompt has parts, and each one does a different job

| | |
|---|---|
| **System message** | Who the model is and the rules it works under. “You triage tickets for LOL. Never invent shipment IDs.” |
| **User message** | The actual job this time: the ticket, the question. |
| **Examples** | Two or three solved cases. The fastest way to show format and tone. |
| **Context** | Documents, data, history. What it needs to know that it wasn’t trained on. |


© 2026 Devansh Parapalli

## Two good examples beat a paragraph of instructions

**Instead of**
“Classify the ticket into the right queue, considering the nature of the issue, the systems mentioned and the department.”

**Show it**
“Scanner not syncing picks at Rotterdam” → warehouse-devices
“Armadillo invoices not in InvoiceHub” → invoice-import

Pick examples that look like the hard cases, not the easy ones. The vague “Account locked” is worth more than another clear password reset.


© 2026 Devansh Parapalli



## Asking it to work through the steps helps on reasoning, and costs tokens

For a payroll variance or an intercompany break, “work through it step by step before answering” gets better answers. The model writes its working, then the conclusion.

For routing a ticket it’s a waste: more tokens, slower, same answer.

**Rule of thumb:** ask for reasoning when a person would need scratch paper. Skip it when they wouldn’t.


© 2026 Devansh Parapalli

Section 2 of 4

# Output a program can trust

The part that matters once this runs without a person watching.

01

A schema says exactly what comes back: fields, types, allowed values

02

For the Nhava Sheva ticket, it returns something the code can act on

03

When the reply doesn't validate, tell the model why and ask again

04

The retry loop is a few lines, and it ends with a person, not a guess


© 2026 Devansh Parapalli



## If code reads the answer, **define its shape.**

A reply that reads well to a person can still break the code that reads it.


© 2026 Devansh Parapalli

## A schema says exactly what comes back: fields, types, allowed values

code/class07/extract_json.py

```python
class Triage(BaseModel):
    queue: Queue                  # one of our 18 queues, or "other"
    shipment_id: str | None       # LOL-SH-1234567, if the ticket names one
    site: str | None              # Hamburg, Rotterdam, Memphis, ...
    blocking: bool                # is someone unable to work right now?
    summary: str                  # one sentence, plain English
```


© 2026 Devansh Parapalli



## For the Nhava Sheva ticket, it returns something the code can act on

**Ticket:** Bill of entry rejected at Nhava Sheva for LOL-SH-4472190, consignee GST number missing on invoice.

Every field is checked before we use it. A queue that isn't on our list fails, and so does a missing field.

```
queue: “shipment-ops”
shipment_id: “LOL-SH-4472190”
site: “Chennai”
blocking: true
summary: “Customs rejected the bill of
entry; the invoice needs the consignee’s
GST number.”
```


© 2026 Devansh Parapalli

## When the reply doesn't validate, tell the model why and ask again

1

Validate the reply against the schema

2

On failure, send back the exact error

3

Ask again, same temperature 0

4

After 3 tries, hand it to a person


© 2026 Devansh Parapalli



## The retry loop is a few lines, and it ends with a person, not a guess

code/class07/extract_json.py

```
def triage(ticket: str, attempts: int = 3) -> Triage:
    prompt = f"{SYSTEM}\n\nTicket:\n{ticket}"
    for _ in range(attempts):
        raw = ask(prompt, temperature=0)
        try: return Triage.model_validate_json(raw)
        except ValidationError as err:
            prompt += f"\n\nYour last reply was invalid:\n{err}\nReply again with valid JSON only."
    raise RuntimeError("no valid reply after retries; send to a person")
```


© 2026 Devansh Parapalli

Section 3 of 4

# What prompting can’t fix

Where people keep rewording the prompt instead of fixing the real problem.

01

No prompt fixes these

02

Ticket text is data, and sometimes it gives orders



© 2026 Devansh Parapalli




## No prompt fixes these

| | |
|---|---|
| **Missing knowledge** | It can’t know our shipment status or runbooks. Give it the data (class 9) or a tool (class 10). |
| **Arithmetic** | It predicts digits. Totals, FX and variances go to code, not the model. |
| **Bad input** | A ticket that says “.” has nothing in it. Ask the person. |
| **Policy** | Whether data may go to the tool at all is decided before the prompt (class 8). |


© 2026 Devansh Parapalli




This is prompt injection. Class 13 goes deeper. For now: the schema helps, because "P1 for the CEO" isn't a field it can fill.



## Run the triage on our 300 handwritten tickets and count the failures, not the wins

- How many replies validated first time, after one retry, after two, never
- Which tickets went to a person, and whether a person would have done better
- How many “other” tickets it forced into a queue anyway


© 2026 Devansh Parapalli

Run it live on 20 tickets to keep the bill small. Put the counts on the board.



## Where today sits on the card

| | |
|---|---|
| **1. A script** | The steps are known and don’t change. |
| **2. A rule** | The decision is known and must be explainable line by line. |
| **3. Classical ML** | Labelled history, and the input is a table or short text. |
| **4. A small trained model** | Lots of text, images or audio, enough labels, cost per call matters. |
| **5. An LLM with a prompt** | **Varied language in and out, few labels, someone checks the output.** |
| **6. An LLM plus retrieval, tools or agents** | Needs private knowledge, has to act, or takes several steps. |
| **7. Not yet** | No ground truth, needs a guarantee, or nobody owns the result. |


© 2026 Devansh Parapalli

# What to do next

1. Run `extract_json.py` on five handwritten tickets and note any retries.
2. Add a `department` field to the schema and see what breaks.
3. Read the class 8 pre-reading: our AI policy, one page.

Questions after class: the course channel.


© 2026 Devansh Parapalli